

ALL ELECTRONICS


C O R P O R A T I O N

NEW AND SURPLUS ELECTRONIC PARTS AND SUPPLIES

SUMMER 2002 CATALOG # 402

INFRARED SENSOR B&W CAMERA

This is a great buy on an inexpensive black and white miniature infrared camera, that is ready to go.



1/3" (8mm) B/W CCD. 320 lines of resolution. 0.1 Lux. Comes complete with a miniature metal enclosure, that measures approximately 2 1/2" X 1 3/4" X 1 1/4" deep including the lens. Includes a mounting bracket. Six infrared LED's mounted in the enclosure, three on each side of the lens, allow the camera to see in low light as well as total darkness. Camera and LED's operate on 12 Vdc between 100ma and 300 ma. 9" leads with RCA jack for video output and 2.1 mm jack for power. Power supply not included. We recommend our CAT# DCTX-122 (\$3.00 each) as a power source.

CAT # VC-303

\$37⁵⁰
each

5MM BLUE LED SPECIAL

High-brightness blue LED. 1000 MCD. Water-clear in off state. Special price.


CAT# LED-86

\$1⁷⁵
each

10 for \$1.50 each
100 for \$1.15 each
1000 for 95¢ each



115 VAC DUAL-SPEED CENTRIFUGAL BLOWER



Fasco # 7062-5301. Two-speed induced draft blower for heating and cooling applications. Thermally protected, ball-bearing, shaded-pole motor. 3000 / 1900 RPM. Rated 115 Vac @ 0.95 Amps. 5 MFD/ 370 Vac capacitor. Steel blower housing and wheel, 9.75" x 8.75" x 3" with 3.75" x 2.75" exhaust port. Overall width, including motor, 7.5". Four mounting flanges on 2.75" x 10.25" centers. 12" pigtail leads. UL, CSA.

CAT # CF-148

\$15⁰⁰
each

10 for \$12.00 each

ORDER TOLL FREE

1-800-826-5432

SHOP ON-LINE **www.allelectronics.com**

FAX (818) 781-2653

24 HOURS A DAY - 7 DAYS A WEEK

Customer Service and Information

(818) 904-0524

WELCOME TO THE WORLD OF SURPLUS ELECTRONICS.

Whether you're a manufacturer, technician, student, hobbyist or inventor - whether your interest is robotics, electric trains, surveillance, remote control models, antique radio restoration or computers, we have something you need. We are your phone-order, mail-order, world-wide web resource for thousands of common and hard-to-find electronic devices.

Continuing our 34 year tradition of great selection, great prices and great service, we bring you "pre-owned" and new electronic parts from around the world. Because much of it is surplus, and because technology is constantly changing, our stock is always changing. Look for many new items in each catalog.

YOUR SATISFACTION IS GUARANTEED

If you are not happy with a product, please return it to us WITHIN 30 DAYS OF RECEIPT in original condition and you will receive a refund or replacement, whichever you prefer.

HAVE YOU VISITED OUR ON-LINE STORE LATELY?

www.allelectronics.com

Place orders on-line 24 hours a day 7 days a week.

Your order will be processed the next business day.

Any item in this catalog can now be ordered on-line using our new EXPRESS ORDER feature. We update our site frequently with new and special items.

DO YOU HAVE MERCHANDISE FOR SALE? We buy excess inventory.

Email lists to: alank@allcorp.com

Fax to 818-781-6847 or call 800-826-5432

115 VAC LED LIGHT BARS SET OF TWO

LED light bars wired to operate on 120 Vac, enable exit fixtures to operate on less than 1.8 Watts per fixture for many years without changing lamps. Kit consists of two 6" long strips of 16 ultra-high brightness LEDs (48000 MilliCandella per strip), 11.75" x 7.25" red plexiglass diffuser, 4 adhesive-backed mylar reflectors and two 0.65" diameter screw-base adaptors. Ultra-high brightness red LEDs, clear in off-state. Great for attention-getting displays of all kinds. UL.

CAT# LBR-16

\$8.50 each • 10 for \$ 7.00 each


ULTRABRIGHT LED KEYCHAIN FLASHLIGHT

Don't get caught in the dark again. Ultrabright, white LED, supplies enough light to let you read in the dark, find keyholes, read maps.

LED with lithium battery are reliable and long-lasting.

Clear weather-resistant plastic case with keychain attachment.

CAT # GL-1 \$7.95 each



LASER POINTER


2.5" long laser pointer with a keychain and snap-clip. Projects an intense solid red dot up to 500 yards. Perfect for sales meetings, lectures. A great gift item.

Includes three LR44 batteries.

CAT # LP-506

\$6.50 each

10 for \$45.00



2" SERIAL THERMAL PRINTER

Panasonic (Matsushita)

EPT-1014LW2

24 character,

144 dot matrix

thermal printer for

2" (50mm) paper.

FPC flexi-connector

with 20 pin (1.25mm pitch)

connector. Mates with Molex


52045-2010 connector.

Removed in good

condition from new

equipment. Includes spec/ hook-up sheet.

CAT # PRNT-4 \$ 6.50 each



SPEED CHUCK FOR DREMEL TOOL

Allows you to quickly and easily change accessory


bits on Dremel and

similar rotary tools

without changing collets. It will

accept all accessory bits with 1/32" to 1/8" shanks.

CAT# CHK-1 \$5.00 each



QUICK INDEX

See pages 92 and 93
for our **COMPLETE INDEX**

AC/DC WALL TRANSFORMERS.....	59
ALARMS & ACCESSORIES.....	20, 21
BATTERIES.....	37 - 39, 90
BOOKS.....	83
BREADBOARDS.....	73
BUZZERS.....	20, 21
CABLE TIES.....	27
CAMERAS, VIDEO.....	40, 41
CAPACITORS.....	66 - 68
CHOKES.....	86
CIRCUIT BREAKERS.....	21, 71
COMPUTER ACCESSORIES.....	50, 61
CONNECTORS.....	43, 48 - 53
CROSSOVERS.....	71
DC-DC CONVERTERS.....	89
DIODES.....	80, 81
DISPLAYS, LED, LCD,.....	2, 3, 5, 41, 89
ENCLOSURES.....	72
FANS.....	16 - 18
FASTENERS.....	26, 27
FILTERS.....	88
FLASHERS.....	5, 61
FUSES.....	22, 23
HEADPHONES.....	23, 24
HEAT SINKS.....	18, 19
INTEGRATED CIRCUITS.....	78 - 79
KITS.....	8, 83 - 85
KNOBS.....	63, 64
LAMPS, INCANDESCENT.....	6 - 8
L.E.D.S.....	4, 5
LCDS.....	3, 41, 89
MAGNETS.....	25, 76
METERS, PANEL.....	50
MICROPHONES.....	24
MOTORS.....	29 - 32
OPTO ELECTRONICS.....	4, 5, 80, 81
PELTIER DEVICES.....	16
PIEZO ELEMENTS.....	20
PLUGS.....	48 - 51
POTENTIOMETERS.....	62, 63
POWER CORDS.....	87
POWER SUPPLIES.....	55 - 57
PRINTED CIRCUIT SUPPLIES.....	74, 75
PROJECT BOXES.....	72
RELAYS.....	33 - 36
RESISTORS.....	68
SEMICONDUCTORS.....	78 - 81
SIRENS.....	21
SOLAR CELLS (Photovoltaics).....	82
SOLDER ACCESSORIES.....	74, 75
SPEAKERS.....	69 - 71
STROBES.....	61
SWITCHES.....	9 - 16
TELEPHONE ACCES.....	46, 47
TERMINALS, CRIMP.....	26
TERMINAL STRIPS.....	60
TEST EQUIPMENT & ACC.....	76, 77
THERMISTORS.....	16
TOOLS.....	26, 43, 47, 73 - 77
TRANSDUCERS.....	21
TRANSFORMERS.....	57 - 60, 71
TRANSISTORS.....	80
VIDEO ACCESSORIES.....	41, 42, 43
VIDEO TAPES.....	41
WALL TRANSFORMERS.....	59
WIRE, CABLE.....	44 - 45

LIQUID CRYSTAL DISPLAYS (LCDs)

16 CHARACTER X 1 LINE LCD

Emerging Display
Technologies
ED16100GR



5 x 7 dot format. Gray characters. 2.58" x 0.63" viewing area. 3.16" x 1.43" module. Includes hook-up sheet.

CAT # LCD-75 \$ 4.50 each

16 CHARACTER X 1 LINE LCD

Samsung # SMC-1611A

5 x 7 dot format.

2.5" x 0.54" viewing area.

3.15" x 1.5" module. Exact specs and data not available at this time. We supply a generic hook-up sheet.

CAT # LCD-55 \$4.50 each




2 X 16 SERIAL LCD

Scott Edwards Electronics

Useful if your BASIC stamp project needs to interact with a human user.

Requires only one I/O line, +5 Volts DC and ground, and are controlled with simple SEROUT instructions from the BASIC stamp.

CAT # 27910 \$49.00 each



20 X 1 LARGE CHARACTER LCD

Samsung # UC-20102-GNAR5

Large 5 x 7 dot characters,

0.46"H x 0.26" W. Blue characters on gray background. 6.1" x 0.64" viewing area. 7.38" x 1.32" module size. Includes hook-up sheet.

CAT # LCD-76 \$ 6.50 each



24 CHARACTER X 2 LINE LCD w/ LED BACKLIGHT


Optrex # DMC24201

0.21" high characters. 5 X 8 dot format.

LED backlight. 0.63" x 3.7"

viewing area. 1.53" x 4.7" module size. Removed in good condition, from new equipment. Prepped with 4" wire leads terminated with 15 pin socket connector (0.075" centers). Includes hook-up diagram.

CAT # LCD-74 \$ 9.50 each



24 CHARACTER X 2 LINE LCD

EDT#

EW24208YLY.


Display size:

3.72" x 0.71".

Module size: 4.62" x 1.42".

LED backlight. New unit, prepped with 9.5" ribbon cable terminated with standard 14 position (7 x 2) female socket connector. Includes hook-up sheet.

CAT# LCD-69 \$12.50 each



256 X 128 LCD PANEL

Hyundai #


HG25504NG-01.

5.8" x 4.58" graphic display module with

SED1330F onboard controller. Viewing area is 5" x 2.75."

STN gray positive type display. 5Vdc logic. 18 Vdc LCD voltage. Includes hook-up diagram.













CAT # LCD-58 \$18.50 each



See 5.5" Video LCD page 41

See LCD Serial Interface ICs page 89

LIGHT EMITTING DIODES (LED)

STANDARD	Color Description		CAT#		100	1000
T-1 3/4 (5mm)	RED - diffused <i>Special Quantity Pricing!</i>		LED-1	10 for \$1.00	.07	.04
	GREEN - diffused		LED-2	10 for \$1.50	.12	.10
	YELLOW - diffused		LED-3	10 for \$1.50	.12	.10
	GREEN - water clear 500 mcd - high brightness		LED-33	4 for \$1.00	.20	.15
ULTRA-BRIGHT T-1 3/4 (5mm)	New, lower prices on these ultra-bright, wide viewing angle 5mm (T 1-3/4) LEDs. Improved brightness and color consistency. Water-clear in off-state.					
	SPECIAL - RED - water clear - 2200 mcd		LED-43	3 for \$1.00	.25	.18
	RED - water clear 3000 mcd		LED-42	2 for \$1.00	.35	.22
	BLUE - water clear 1500 mcd		LED-74	\$2.85	1.95	1.50
	GREEN - water clear 3000 mcd		LED-57	\$3.30	2.55	2.00
	WHITE - water clear 3000 mcd		LED-75	\$2.75	1.85	1.50
	YELLOW - water clear 3000 mcd		LED-72	\$1.35	1.00	.85
	AQUA - water clear 1500+ mcd		LED-77	\$2.85	2.20	1.85
5mm LOW PROFILE	RED - diffused		LED-21	12 for \$1.00	.07	.06
	AMBER - lights RED point source		LED-24	12 for \$1.00	.07	.06
MINIATURE T-1 (3mm)	RED - diffused		MLED-1	10 for \$1.00	.08	.07
	GREEN - diffused		MLED-2	10 for \$1.25	.10	.08
	YELLOW - diffused		MLED-3	10 for \$1.25	.10	.08
	RED - point source		MLED-7	10 for \$1.00	.08	.07
	GREEN - point source		MLED-8	10 for \$1.00	.08	.07
	YELLOW - point source		MLED-9	10 for \$1.25	.10	.08
	BLUE - point source Ultrabright		LED-59	\$3.75	10 for \$30.00	
	WHITE - diffused Ultrabright		LED-83	\$2.85	2.00	1.65
SUB-MINI RED AXIAL LED	Rohm # SLN-210VTT12. Red, 0.07" diameter point-source LED. Water-clear in off-state. Ammo-pack packaging. CAT # LED-81			10 for \$ 1.00 • 100 for \$ 8.00 Ammo-pack box of 2000 pcs \$ 80.00 (\$ 0.04 ea)		
FLASHING LEDS	Built-in flashing unit 3 - 5 Vdc operation					
	T-1 3/4 (5mm) RED - diffused High Brightness		LED-4	2 for .90	.40	.30
	T-1 3/4 (5mm) GREEN - diffused		LED-4G	.50	.45	.40
	T-1 3/4 (5mm) YELLOW - diffused		LED-4Y	.50	.45	.40
	SPECIAL - RED T-1 3/4 - water clear		LED-84	3 for \$1.00	.25	.18
	T-1 (3mm) RED - diffused		LED-72R	.65	.55	.45
	T-1 (3mm) GREEN - diffused		LED-72G	.75	.65	.55
	T-1 (3mm) YELLOW - diffused		LED-72Y	.75	.65	.55
BI-COLOR T-1 3/4 (5mm)	RED / GREEN diffused		CAT# LED-6	1-99 .50	<u>100</u> .45	<u>1000</u> .35
	Two leads. Reverse polarity to change color. Yellow on AC.					
	RED / GREEN diffused		LED-63	.35	.29	.25
	Three leads. Center cathode. Milky-white off-state.					
	GREEN / YELLOW		LED-78	.15	.10	.06
	Three leads. Milky-white off-state.					
BI-COLOR T-1 (3 mm)	RED/GREEN diffused		CAT# LED-67	1-99 .35	<u>100</u> .29	<u>1000</u> .25
	Three leads. Center cathode. Milky-white off-state.					
	YELLOW/GREEN diffused		LED-66	.20	.15	.09
	Two leads. Bent leads.					
INFRARED LEDS	T 1 3/4 EMITTER, clear lens		CAT# ILED-8	3 for \$1.00	.20	.14
	T 1 3/4 EMITTER, Siemens# SFH484-1. Light purple epoxy lens.		ILED-20	3 for \$1.00	.25	.18
	TO-18 EMITTER		TIL-31B	3 for \$1.00	.20	.15
8 mm JUMBO LEDS	8 MM BI-COLOR LED - RED / GREEN Sanyo # SLP-5111A-378. 8 mm diameter, high-brightness LED. Three leads. Two LED elements light for each color, emitting a bright light that can be seen at a distance. Clear in off-state. CAT# LED-23RG 2 for \$1.00 • 10 for \$4.50 • 100 for \$35.00					
3 mm RED LED INDICATOR ASSEMBLY	Dialco # 558-0101. Snap-in mount LED indicator. Black polycarbonate mounting clip fits holes. 0.156" diameter mounting hole. 8" wire leads. Operates on 2 Vdc @ 10 mA. CAT # LED-73 50¢ each • 100 pcs for \$ 35.00					

5MM BLUE LED SPECIAL



High-brightness blue LED. 1000 MCD. Water-clear in off state. Special price.

CAT# LED-86 \$1.75 each • 10 for \$1.50 each


100 for \$1.15 each • 1000 for 95¢ each



5MM RED LED ASSEMBLY W/ 5 FOOT WIRE LEADS

5mm (T 1 3/4) high-brightness red diffused LED in black mounting clip. 5 ft wire leads with 2 conductor socket connector. Mounting clip fits 0.29" diameter hole and has 0.37" dia bezel.

CAT # LED-85 65¢ each • 100 for \$ 40.00



5MM GREEN DUAL LED, RIGHT ANGLE

PC pins on 0.1" centers. Dual T 1 3/4 diffused.

CAT# LED-68 10 for \$1.00 • 100 for 9¢ each • 1000 for 8¢ each



LED MOUNTING HARDWARE

Black plastic clips allow snap-in mounting of standard size LEDs.

CLIPS FOR T 1 3/4 (5 mm) LEDs

2 PIECE HOLDER Mounts in 6.3 mm hole.



CAT#

HLED-4

10 for \$1.20

100

0.09

1000

0.08

1 PIECE HOLDER Mounts in 8 mm hole



HLED-3

2 for .90

0.36

0.30

1 PIECE HOLDER Snap mounts into 6 mm hole



HLED-6

2 for .70

0.25

0.18

CLIPLITE HOLDERS FOR T 1 3/4 LEDs

Colored polycarbonate lens increases brightness and viewing angle with either diffused or non diffused LEDs. Mounts in 0.25" hole in panels of 0.06" to 0.125" thickness.

RED
GREEN
YELLOW
CLEAR



HLDC-L-R

3 for 0.90

.25

.20

HLDC-L-G

3 for 0.90

.25

.20

HLDC-L-Y

3 for 0.90

.25

.20

HLDC-L-C

3 for 0.90

.25

.20

CLIPS FOR T 1 (3 mm) LEDs

1 PIECE HOLDER Mounts in 4.5 mm hole.



HLED-5

10 for \$1.00


.08

.07

LED DISPLAYS

See 7-Segment LED Drivers page 79

7 SEGMENT DISPLAYS



Char Ht.	DIP Socket	Color	Description	CAT #	1-9	10-99	100+
0.3"	14 pin	Red	C.C. Single Digit	SDC-30	0.75	0.60	0.45
0.3"	16 pin	Green	C.A. Single Digit	SDA-19	0.75	0.60	0.45
0.36"	10 pin	Red	C.A. Single Digit	SDA-37	0.75	0.60	0.45
0.36"	10 pin	Red	C.C. Single Digit	SDC-36	0.75	0.60	0.45
0.56"	24 pin	Red	C.A. Dual Digit	TDA-50	0.75	0.65	0.50
0.56"	24 pin	Red	C.C. 3 Digit	TDC-51	1.00	0.90	0.80
0.56"	24 pin	Green	C.A. Dual Digits	TDA-56	0.75	0.65	0.50

BARGRAPH DISPLAYS




DIP Socket	Color	Description	CAT #	1-9	10-99	100+
20	Red	10 segment	BG-10	1.50	1.25	1.00
20	Green	10 segment	BG-10G	1.50	1.25	1.00
20	Yellow	10 segment	BG-10Y	1.50	1.25	1.00

LED TESTER

Pocket-size led tester. Makes it easy to check functionality, color, brightness and uniformity. Plug any leaded LED into one of 12 positions on the socket strip to test at current ratings from 2-50ma. The seven middle positions on the strip are set at 10 mA allowing comparison of LEDs in those spaces. Requires 9 v battery (not included).

CAT# LT-100 \$8.95 each



CHEAP (yet effective) LED FLASHER

The simplest electronic flasher ever.


A red 5mm LED with flasher chip is attached to a battery snap that snaps onto a 2 AA cell battery holder (included). Will flash for months on a set of batteries.

Flash rate, approximately 120 flashes per minute. Batteries not included.

CAT# FSH-10 \$1.00 each

100 for 70¢ each • 500 for 60¢ each

1000 for 50¢ each



LAMPS

T-1 3mm Diameter Lamps

T-1 (3MM) w/ BARE WIRE LEADS

	CAT#		100+
5 Volt 115 ma	LP-715	2/\$1.00	\$40.00
10 Volt 15ma	LP-7218	2/\$1.00	\$40.00
14 Volt 40 ma	LP-23	2/\$1.00	\$40.00

T-1 (3MM) w/ INSULATED WIRE LEADS

1.5v @ 40 ma. 10" leads.

CAT# LP-3 2 for \$1.00 • 100 for 40¢ each
3v @ 55 ma. 10" leads.

CAT# LP-4 2 for \$1.00 • 100 for 40¢ each

14v @ 45 ma. 10" leads.

CAT# LP-6 2 for \$1.00 • 100 for 40¢ each

12v @ 60 mA. 6" leads.

CAT# LP-10 2 for \$1.00

100 for 35¢ each • 1000 for 28¢ each

16v @ 80 ma. 3" leads.

CAT # LP-16 3 for \$ 1.00

100 for 25¢ each • 1000 for 15¢ each

T-1 3/4 5mm Lamp w/ Leads

24 Volts @ 130 mA. 5 mm dia. (T 1 3/4) incandescent lamp. Molded black plastic mounting clip with bayonet-type flange fit 0.31" dia. mounting hole. 6" pigtail leads.

CAT# LP-195 4 for \$1.00 • 100 for \$18.00

3 Volt Lamps w/ 20" Insulated Leads

3 volt 80 ma miniature incandescent lamps. Operate on 3 - 6 volts. Bulb size: 0.15" (4mm) diameter x 0.47"

(12 mm) long. **CAT# LP-60**

4 for \$1.00 • 100 for \$20.00

SPECIAL - 14V 330 MA LAMP with WIRE LEADS

GE # 193. T 3 1/4 size, 0.4" dia. x 1" long lamp with bare 0.7" wire leads.

14 Volts @ 330 mA. Large quantity available.

CAT # LP-193 4 for \$ 1.00

100 for \$ 18.00 • 1000 for \$ 100.00

8V 150 MA LAMP

8 VOLT, 150 MA with insulated wire leads. T 3 1/4 size,

0.4" diameter lamp with 9" leads.

CAT # LP-62 4 for \$ 1.00

100 for 16¢ each • 1000 for 12¢ each

SPECIAL #550 MINI-FLANGE BASE

T-1 (3MM) 5.5 Volts 0.060 Amps

CAT# LP-550 5 for \$1.00

100 for \$15.00 • 1000 for \$100.00

BLUE 5 VOLT PC MOUNT LAMP

T-1, 3 mm lamp with a blue filter.

5 Volts @ 44 mA. Mounted on a plastic base. 0.275" x 0.169" footprint.

0.28" high overall. PC leads on 0.2" centers, crimped for snap-in mounting.

CAT # LP-9 4 for \$ 1.00 • 100 for \$ 15.00

Automotive Wedge-Base Lamps

T 3 1/4, 1" X 0.43" diameter, size.



VOLTS	mA	CAT#	PRICE	100+
14	330	LP-194	2 for \$1.00	.40
14	190	LP-161	2 for \$1.00	.40
14	80	LP-73	3 for \$1.00	.23

500 for 18¢ each • 1,000 for 11¢ each

120V, 15W CANDELABRA BASE LAMP


0.97" dia. x 1.2" high spherical bulb.

0.46" dia. candelabra screw base.

CAT # LP-197 2 for \$1.00


50 for 35¢ each

200 for 30¢ each



MINIATURE BAYONET BASE LAMP


TRADE	VOLTS	AMPS	CAT#	PRICE	100+
47	6.3	.150	LP-47	2 / \$1.00	45¢
1813	14.0	.100	LP-1813	2 / \$1.00	45¢
1815	14.0	.200	LP-1815	2 / \$1.00	45¢
1819	28.0	.040	LP-1819	2 / \$1.00	45¢



T - 1 3/4 5 mm Diameter Lamps

T - 1 3/4 BI-PIN LAMP

VOLTS	AMPS	CAT#	
14.0	.080	LP-7382	2 for \$1.00 100 for \$45.00
28.0	.040	LP-7387	2 for \$1.00 100 for \$45.00



T-1 3/4 MIDGET FLANGE LAMP

VOLTS	AMPS	CAT#	
6.0	.040	LP-345	2 for \$1.00 100 for \$45.00
28.0	.040	LP-327	2 for \$1.00 100 for \$45.00



LARGE BAYONET BASE LAMPS

#67 lamp 13.5 Volts, 0.59 Amps.

Single contact, large bayonet base lamp.

CAT # LP-67 \$1.00 each • 10 for \$8.00



FUSE LAMPS

Popular lamps which are the same size as a 3AG 1/4" X 1 1/4" (AGC) fuse.



6 VOLTS

CAT# LPFS-6 75¢ each 10 for \$7.00

8 VOLTS

CAT# LPFS-8 \$1.00 each 10 for \$8.50

12 VOLTS

CAT# LPFS-12 75¢ each 10 for \$7.00

NEON LAMPS

NEON INDICATOR 120 VOLT

Good looking neon indicator

RATED: 120 volts @ 1/3 watt . Mounts in 5/16" hole. Red lens with chrome ring.

CAT# IND-100 75¢ each

10 for \$7.00 • 100 for \$65.00



NEON LAMP

Ne-2 style neon lamp. Operates on 115 Vac when used with a dropping resistor. 0.23" diameter x 0.72" long.

CAT# NL-2 20¢ each

100 for 15¢ each



NEON LAMP ASSEMBLY

Well-made assembly with NE-2 neon lamp, 100K resistor and 6" long pigtail leads, all connections covered with heat-shrink tubing. Stripped and tinned, ready to operate on 117 Vac.

CAT# LPN-4 5 for \$1.00 • 100 for \$17.00

HALOGEN LAMPS

MR-11, 12 VOLT 35 WATT

General Electric
Q35MR11/ NSP(FTE)

MR-11 quartz halogen lamp.
12 Volt, 35 Watt. 1.38" diameter
Multi-Mirror™ lamp. 0.15" pin spacing.

CAT # HLP-350 \$3.50 each • 10 for \$30.00



MR-16, 12 VOLT 35 WATT

General Electric
Q35MR16/CG

MR-16 quartz halogen
lamp. 12 Volt, 35Watt,
12 degree beam. 1.975" diameter
multi-faceted reflector with cover glass.

CAT # HLP-351 \$3.50 each • 10 for \$30.00



MR-16, 50 WATT FLOOD LAMP

Gilway Technical Lamp # L521
Bi-pin base halogen lamp.

12 Volt, 50 Watt flood lamp.
13 degree beam angle. 4,000 hours.
1.97" dia. x 1.46" deep (excluding pins).
0.2" pin spacing. **CAT # HLP-51**
\$ 3.50 each • 10 for \$ 30.00



MR16, 50 WATT FLOOD LAMP

Bi-pin base halogen lamp.

12 Volt, 50 Watt flood lamp with a
front glass lens. 1.97" dia. x
1.46" deep. 0.2" (5mm) pin spacing.

CAT # HLP-50

\$3.50 each • 10 for \$30.00



MR-16, 12 VOLT 75 WATT

General Electric EYJ/CG
Q75MR16/ NFL/ CG

MR-16 quartz halogen
lamp. 12 Volt, 75 Watt,
25 degree beam. 1.975" dia. Multi-Mirror™
lamp with cover glass. 0.2" pin spacing.

CAT # HLP-751 \$3.50 each • 10 for \$30.00




120 VOLT 300 WATT HALOGEN LAMP



Ushio # TWJ. 0.32" diameter x 4.61" long halogen
lamp. Recessed contacts on both ends of lamp.
Commonly used in square and rectangular flood-
lights. **CAT # HLP-300** \$2.25 each
10 for \$2.00 each • 100 for \$1.50 each

MINI-HALOGEN LAMP WITH WIRE LEADS

14 Volt, 3 Watt halogen lamp 
with wire leads. T 1 3/4,
5mm diameter x 12mm long. 0.8" long wire leads.
CAT # HLP-405 \$1.20 each


LAMP HOLDERS

MINI BAYONET LAMP HOLDERS

For use with #44, 47, 1815 etc...
standard mini-bayonet base lamps.


CAT# LHL-30

2 for \$1.00



CAT# LHL-22

2 for \$1.00




CAT# LHL-21

2 for \$1.00



CAT# LHL-36

2 for \$1.00




LARGE BAYONET LAMP HOLDERS

For single contact 0.6" dia. bayonet base lamps.

4" insulated wire lead.

CAT# LHL-34 2 for \$1.00



SOCKET FOR T 1 1/2 WEDGE BASE LAMP

JKL # 2967-22-120-BLA. Fits 5mm glass
wedge base lamps. Socket has 4.5" flying
leads. **CAT# LS-3** 4 for \$1.00


100 for 20¢ each • 1000 for 15¢ each



LAMP ASSEMBLIES

12 VOLT COURTESY LAMP ASSEMBLY


Ford Motor Co.# D0ZB-13707C. 12 Vdc, 0.66A
cylindrical lamp with wire loop connections
at each end. 1.6" long x 0.36" dia.
Mounted in white plastic holder with
1.37" metal mounting bracket. Nice
bright light. Ideal for control and panel or
display lighting. **CAT# LMP-4** 75¢ each




12V INDICATOR LAMPS

12 Vdc @ 50 mA lamp assemblies. Lens is 0.73"
square x 0.5" high. Threaded bushing mounts in 0.58"
dia. hole up to 0.2" thick. Solder loop terminals.

color	Cat#	each	10+
RED	LMP-12R	\$ 1.00	75¢
GREEN	LMP-12G	\$ 1.00	75¢
AMBER	LMP-12A	\$ 1.00	75¢
BLUE	LMP-12B	\$ 1.00	75¢
CLEAR	LMP-12C	\$ 1.00	75¢




MINIATURE CCFT LAMPS



Removed from new LCD backlights.

9" x 2.6 MM DIAMETER LAMP

In white plastic shade, 9.5" x 0.39" x 0.27." 
Directs light in one direction. Shade is easily remov-
able. With wire leads and two pin connector. Leads
extend 3.5" beyond end of lamp. **CAT # BF-279**
\$2.50 each • 10 for \$2.00 each


DUAL LAMPS 12.5" x 2.6 MM DIA.

Two CCFT lamps in a metal shade. Shade directs
light in one direction. The lamps are parallel to each
other, approximately 2mm apart, with rubber end caps
holding them together. The lamps are easily removable
from the shade assembly, however extreme care must
be used to separate lamps from the rubber caps. For
maximum intensity and to avoid damage to the lamps,
use lamps as mounted. Shade is 13.7" x 0.35" x 0.26".
Wire leads extend 3.5" beyond end of assembly.

CAT# BF-262 \$4.50 ea. • 10 for \$3.75 ea.

JKL MINIATURE FLUORESCENT AND UV FLUORESCENT LAMPS

Miniature CCF (Cold Cathode Fluorescent) lamps in a variety of sizes. Ideal lighting for controls, models, LCD backlighting and experimentation. The narrow spectrum UV lamps (blacklights) are great for mineral display, money verification and other special effects applications. Long life. Low power consumption. Operate on 12 Vdc using appropriate inverter.



WHITE FLUORESCENT LAMPS

Diameter	Length	CAT #	Price
3 mm	100 mm	BF-3100	\$12.50
3 mm	160 mm	BF-3160	\$13.75
5 mm	200 mm	BF-5200	\$15.00
3 mm	228 mm	BF-3228	\$15.00

SPECIAL PURCHASE! MINI-CCF LAMP

3.2 mm diameter X 250 mm long.
White. JKL BF3250-20B

CAT# BF-3250

\$4.95 each • 100 for \$400.00

REDUCED
PRICE!

COLORED FLUORESCENT LAMPS

Lamps have two leads at each end.
Use one or both leads for connection.

6 mm diameter X 165 mm length

Color	CAT #	Price
Orange	BF-6165O	\$5.50
Green	BF-6165G	\$5.50
Blue	BF-6165B	\$5.50

UV Fluorescent Lamps (ultraviolet)


Diameter	Length	CAT #	Price
3 mm	25 mm	UV-325	\$8.25
3 mm	50 mm	UV-350	\$8.50
3 mm	100 mm	UV-3100	\$10.75

12 Vdc INVERTER

1.75" x 0.79" x 0.5" Will drive
one or two lamps.

Includes spec/hook-up sheet.

CAT # BXA-12529 \$9.95 each




MINIATURE 12 Vdc INVERTER

2.2" x 0.25" x 0.2". Will drive one lamp
only. Includes spec/hook-up sheet.

CAT # BXA-12576

\$10.95 each



INVERTER, 5 VDC INPUT

TDK-2090. Inverter for small to
medium CCFT lamps.


Operates on 3-5 Vdc.

No official specs available at
this time. Our tests indicate that it
lights lamps of 250mm length or less.

Module is 2.17" x 1.1" x 0.4" high. PC pins on
2" x 0.84" centers. Large quantity available.

CAT# INV-7 \$3.75 each

10 for \$3.25 each • 100 for \$2.50 each



REDUCED
PRICE!

ELECTROLUMINESCENT EXPERIMENTER KITS

Electroluminescent lamp strips are used for backlighting control panels, computer and pager displays, wristwatches and hundreds of other items. When voltage is applied they glow gently and produce almost no heat. EL strips are thin and easy to cut and bend. Ideal for model builders, safety lighting and other special effects lighting.


EL KIT

This kit
provides
everything
you need to
start using EL strips. Includes one


white 1.7" x 3.75" EL strip with six sets of electrodes, a power supply, battery holder, switch, an assortment of color overlays and instruction book. Requires 2 AAA batteries (not included).

CAT # EL-340 \$22.95 each

5 or more \$21.95 each



JUMBO EL KIT




Includes

a 4" x 6" EL panel

with 14 electrodes. The power supply has 6 sets of
connectors and can power up to 6 panels at the
same time. Requires 3 AA cells (not included).

Includes instructions.

CAT # EL-2504 \$34.95 each



ELECTROLUMINESCENT CHASER KIT

Make
animated
miniature
neon signs
and light
displays using

thin, flexible,

cool electroluminescent

strips. Pre-programmed with 32 different sequen-

tial patterns. Each pattern has five channels,


meaning you can light up to five strips. Comes

with one 3.75" x 1.7" strip with six connectors
which can be cut into smaller pieces to make
shapes and letters. Includes, inverter/chaser mod-

ule, EL strip, color overlays, battery holder for 3

AAA cells and instructions. Batteries not included.

CAT # EL-2502 \$28.95 each



INVERTER FOR EL PANELS AND STRIPS

Input: 12 Vdc. Output: 90 Vac.

Inverter designed to light

larger electroluminescent


(EL) panels and strips up

to 100 sq. in. surface

area. 2.42" x 1.39" x

1.17" high. 1 foot pigtail leads.

CAT# INV-8 \$5.00 each • 10 for \$4.75 ea.



SWITCHES


(brackets) indicate momentary position

SUB MINIATURE TOGGLE

0.2" diameter threaded bushing. 0.4" long bat handle.

S.P.D.T. ON-ON

Rated: 3 amp @ 125 Vac. Solder lug terminals. **CAT# SMTS-4** \$1.35 each
10 for \$12.50 • 100 for \$110.00



D.P.D.T. ON-ON

Rated: 3 amp @ 125 Vac. Solder lug terminals. **CAT# SMTS-8** \$1.75 each
10 for \$15.50 • 100 for \$135.00




MINIATURE TOGGLE

1/4-40 threaded bushing. 0.43" long handle unless otherwise noted


S.P.D.T. ON-ON

RATED: 6 amp @ 120 Vac. Solder lug terminals. **CAT# MTS-4** \$1.00 each
10 for \$9.00 • 100 for \$75.00




S.P.D.T. ON-ON

RATED: 6 amp @ 120 Vac. P.C. terminals. **CAT# MTS-4PC** \$1.00 each
10 for \$9.00 • 100 for \$80.00
1000 for \$700.00



S.P.D.T. ON-OFF-ON

RATED: 3 amp @ 120 Vac
Center off. Solder lug terminals. **CAT# MTS-5** \$1.00 each
10 for \$9.00 • 100 for \$80.00



S.P.D.T. ON-OFF-ON WIRE WRAP PINS

Augat/Alcoswitch # AE103MD1W4B
Center-off position. Contacts rated 5 Amps @ 125 vac. Short toggle handle, 0.282" long. 0.232" diameter non-threaded bushing. Thermoplastic case. Four-level wire wrap pins. **CAT# MTS-50WW** \$1.00 ea. • 25 for \$22.50




S.P.D.T. ON-OFF-ON NON-THREADED BUSHING

P.C. style Center off. RATED: 5 amp @ 120 Vac. **CAT# MTS-50PC** 50¢ each
10 for \$4.00 • 100 for \$30.00




S.P.D.T. ON-OFF-(ON)

NON-THREADED BUSHING
Rated: 5 amp @ 120 Vac. Center-off P.C. style. Momentary one direction only. **CAT# MTS-70PC** 50¢ each
10 for \$4.75 • 100 for \$43.00 • 1000 for \$400.00




S.P.D.T. ON-OFF-(ON)

NON-THREADED BUSHING
RATED: 5 amp @ 120 Vac. Momentary one direction only. Handle measures 1". **CAT# MTS-75PC** 50¢ each
10 for \$4.00 • 100 for \$30.00




D.P.D.T. ON-ON

RATED: 6 amp @ 120 Vac. Solder lugs. **CAT# MTS-8** \$1.25 each
10 for \$10.50 • 100 for \$85.00



S.P.3.T. ON-ON-(ON)


JBT Switch. Single-pole, three position miniature toggle switch. On in all three positions. Momentary in one position. 0.24" plain, non-threaded bushing. Right-angle pc terminals.



CAT# MTS-85RT \$1.75 each


D.P.D.T. ON-ON NON-THREADED BUSHING, CLIP MOUNT

C & K # E201. Contacts rated 0.4VA. Non-threaded 0.24" dia. bushing with flatted sides can be spring-clipped onto panel (spring-clip included). Right angle pc mounting leads. **CAT # MTS-80RT** \$1.00 each • 10 for \$8.50 • 100 for \$70.00




D.P.D.T. ON-ON

RATED: 6 amp @ 120 Vac. PC Mount. **CAT# MTS-8PC** \$1.00 each
10 for \$8.50 • 100 for \$70.00




D.P.D.T. ON-ON NON -THREADED BUSHING

P.C. style. RATED: 5 amp @ 120 Vac. Extra long flat lever. Handle measures 1" long. **CAT# MTS-85PC** 75¢ each
10 for \$7.00 • 100 for \$65.00




S.P.3.T. ON-ON-(ON)

ALCOSWITCH# MTA206TA
Single-pole, 3 position. Momentary in one position. Rated 6 amps @ 125 Vac. Solder lug terminals. Requires external jumper. **CAT# MTS-81** \$2.00 each • 10 for \$18.50




D.P.D.T. ON-OFF-ON

RATED: 3 amp @ 120 Vac
Threaded bushing. Solder lug terminals. **CAT# MTS-12** \$1.60 each
10 for \$13.00 • 100 for \$100.00



D.P.D.T. ON-OFF-ON

NON-THREADED BUSHING. RATED: 5 amp @ 120 Vac. P.C. terminals. Center-off. **CAT# MTS-120PC** \$1.50 each
10 for \$13.00 • 100 for \$100.00



STANDARD TOGGLES

Switches have 15/32" threaded bushings.


S.P.D.T. ON-OFF-ON

S.P.D.T., center-off toggle switch. 10 Amp, 250 Volt contact rating. Standard toggle handle and 15/32" threaded bushing. Solder terminals. **CAT # STS-42** \$ 1.50 each




D.P.D.T. ON-OFF-ON

15 AMP D.P.D.T. toggle. Standard toggle handle. 15/32" threaded bushing. UL listed. **CAT# STS-8** \$2.50 each



DPST TOGGLE SWITCH

Japan Switch # ST206K
Standard D.P.S.T. toggle switch. 6A 125 Vac. 15/32" threaded bushing. Solder terminals. **CAT # STS-811** \$ 1.50 each




LIGHTED ROCKER SWITCHES

120 VAC LIGHTED ROCKER

S.P.S.T. neon-lighted rocker switch. Contacts rated 20 amps @ 125 vac. Black bezel is 1.32" x 0.61" and has a white dot marking on-position. Red rocker. Switch snap-mounts into 1.1" x 0.5" cut out. Solder or qc terminals.


CAT # LRS-17 \$1.25 each • 100 for \$95.00



120 VAC LIGHTED ROCKER

Carling. D.P.S.T. neon-lighted rocker switch. Black bezel and rocker with red rectangular light in top half of rocker. Bezel is 1.16" x 1.25". Contacts rated 10 Amps @ 120 Vac. Snap-mounts in 1" square cut out. QC or solder terminals. UL, CSA.

CAT # LRS-18 \$ 1.75 each




LED LIGHTED ROCKER SWITCH, SPST

SMK # JWZ1120-0203.

S.P.S.T. rocker switch rated 6 Amps @ 125 Vac. Green LED indicator in rocker. LED requires a ballast resistor, dependent on operating voltage. Snap-mounts into 0.5" x 0.75" panel cutout. 0.187" Faston or solder terminals.

CAT# LRS-20 \$1.00 each



ROCKER SWITCHES

S.P.S.T. ROCKER SWITCH

Black rocker switch with 0.83" x 0.6" black bezel. White indicator dash on rocker. S.P.S.T. contacts rated 6 Amps, 125 Volt. Snap-mounts in 0.7" x 0.5" chassis cutout. Solder lugs.


CAT# RS-106 2 for \$1.00 • 100 for 35¢ each



SPDT ROCKER SWITCH, 16 AMP

Eaton # 5121A1E. Black bezel and rocker. Snap-mounts into 1.20" x 0.44" cutout. Rated 0.50 h.p. 16 Amps 125 Vac. 0.25" qc or solder terminals. CSA, UL, VDE.


CAT# RS-107 75¢ each



SPDT ROCKER, MOMENTARY BOTH DIRECTIONS

Arrow England B160611E. S.P.D.T. center-off, momentary both directions. Large matte-black rectangular rocker measures 1.81" x 1". Snap mounts into 1" x 0.5" hole. Rated 10 amp 250 vac. 0.25" qc or solder terminals. UL.

CAT# RS-108 \$1.25 each



S.P.D.T.(ON)-OFF-(ON)

MOMENTARY ROCKER C & K E105

SPDT, center-off, momentary both directions. Rated 0.4 Va. Black rocker is 0.67" X 0.365". Right angle pc pins.

CAT# RS-23 50¢ each




THINLINE ROCKER SWITCH

Arcoelectric # H8800VAWB132W

S.P.S.T. thinline rocker switch. Rated 15 Amps @ 250 Vac, Tested for 75 Amp inrush current. Snap-mounts into 0.27" x 0.69" panel cutout. Black rocker with 0 - I legend in white. Opaque white body and bezel. 0.19" qc or solder terminals. UL, CSA.


CAT# RS-102 2 for \$1.00



DPDT MINI ROCKER SWITCH

C & K T series D.P.D.T. miniature rocker switch. Contacts rated 3 Amps @ 120 Vac. Right-angle, pc mount. Black rocker is 0.58" x 0.3" x 0.25" thick. Body is 0.32" x 0.32" x 0.39."

CAT # RS-104 65¢ each • 10 for \$5.00



S.P.S.T. 16 AMP

Carlingswitch. Black bezel and rocker. Red indicator on rocker is visible in the on-position. Rated 16 Amps @ 125 Vac. Snap-mounts in a 0.5" x 1" chassis cutout. Solder terminals. UL, CSA.


CAT # RS-103 65¢ each • 100 for \$40.00



3PST, 6 and 15 AMPS

Eaton. Three pole, on-off rocker switch. One pole is rated 6 amps and two poles are rated 15 amps. Black bezel and black rocker with "ON" "OFF" in white letters. Snap-mounts into 0.75" X 1.5" rectangular chassis hole. Overall dimensions: 1.44" X 1.33" X 1.57" deep. Quick-connect or solder terminals. UL and CSA listed.

CAT# RS-45 75¢ each



S.P.D.T. - MINI 10 AMP

Miniature S.P.D.T. rocker switch. Contacts rated 10 Amps @ 125/250 Vac. Ivory rocker and bezel. Snap-mounts into 0.8" x 0.53" rectangular cutout. UL, CSA. Solder loop terminals.


CAT# RS-74 2 for \$1.00



S.P.D.T. 16 AMP

CW Switch. Black rocker and bezel. Snap-mounts in 0.5" x 1.125" chassis cutout. 16 Amps @ 125 Vac. 3/4 H.P. Solder or 0.25" qc terminals. UL, CSA.


CAT # RS-101 75¢ each • 10 for \$6.50



D.P.D.T. CENTER-OFF

Russenberger. Flat black rocker and bezel. Rated 10 amps @ 250 Vac. Snap-mount in 1" X 0.88" rectangular hole. 3/16" quick-connect solder terminals.


CAT# RS-67 2 for \$1.00 10 for \$4.50 100 for \$40.00 • 1000 for \$350.00



D.P.D.T. MINI-ROCKERS

Carlingswitch. Rated 8 amps @ 125 Vac. Snap mount in 0.7" X 0.52" rectangular chassis hole. UL and CSA. Black rocker, white bezel, no lettering.

CAT #RS-61 2 for \$1.00 • 100 for 35¢ each



DIP SWITCHES

3 POLE DIP SWITCH

Three - S.P.S.T. switches per unit
CAT# DWS-3 3 for \$1.00

5 POLE DIP SWITCH


5 - S.P.S.T. switches per unit.
CAT# DWS-5 4 for \$1.00

6 POLE DIP SWITCH

6 - S.P.S.T. switches per unit.
CAT# DWS-6 2 for \$1.00

7 POLE DIP SWITCH

7 - S.P.S.T. switches per unit.
CAT# DWS-7 4 for \$1.00




SNAP ACTION SWITCHES

LARGE BODY STYLE

15 AMP, SPST N.O.

Master Switch S.P.S.T., normally-open. Contacts rated 15 Amps @ 125 Vac. Body size, 1.9" x 0.64" x 0.64". Mounting holes on 1" centers. Solder or 0.25" qc terminals. UL, CSA. **CAT # SMS-194** \$ 1.25 each




STANDARD BODY STYLE

BODY SIZE: 3/8" X 5/8" X 1 1/8"

CHERRY D40 W/ SIM ROLLER LEVER

S.P.D.T. Rated 1 Amp @ 125 VAC. Lever with simulated roller tip extends 0.4" beyond end of switch. 0.187" qc or solder terminals. UL, CSA.


CAT # SMS-186 \$1.00 each



CHERRY D40 W/ LEVER

S.P.D.T. Rated 1 Amp @ 125 VAC. Lever extends 0.43" beyond end of switch. 0.187" qc or solder terminals. UL, CSA.

CAT # SMS-185 \$1.00 each




INTERLOCK SWITCH

Omron 1VAP2-2. SPDT switch rated 15A, 1/2hp @ 125/250VAC. Interlock assembly designed to disable equipment when access panels or doors are opened. Overall size: 1.81" x 1.69" x 0.5". Threaded holes on front and side. 0.187" QC terminals. UL/CSA.

CAT # SMS-193


\$ 2.00 each • 100 for \$ 1.25 each



CHERRY D43

S.P.D.T. with roller positioned above switch actuator. Rated 5 amps @ 125/250 vac. Switch body: 1.1" x 0.63" x 0.375". Solder or qc terminals. UL/CSA.


CAT# SMS-150 \$1.25 each • 10 for \$10.00



MICRO# V3L141D94

SPST, normally open. Short lever with roller. Rated 4 amps. 1/4" quick-connect terminals. UL, CSA


CAT# SMS-68 \$1.25 each



S.P.D.T. PREPPED W/ WIRES

Cherry D44. Rated 10 Amps @ 125/250 Vac. New snap-action switch prepped with two wires with quick-connect terminals. QC or solder terminals. UL, CSA.

CAT# SMS-168 85¢ each




S.P.S.T., N.O., 15 AMP

Microswitch # V7-1C27E9

S.P.S.T., normally-open. Rated 15A @ 125/250 Vac. 0.25" qc or solder terminals. UL, CSA. **CAT # SMS-175** \$1.00 each

10 for \$ 8.50 • 100 for \$ 65.00



SMALL SIZE BODY


SUB-MINI SNAP ACTION SWITCH

Microswitch # 21SX39-T. S.P.D.T. sub-miniature switch with button actuator and gold-plated turret terminals. Rated 7 Amps @ 250 Vac. Body size: 0.5" x 0.2" x 0.35" high (excluding plunger and terminals). UL, CSA. **CAT # SMS-192** \$1.25 each



SUBMINIATURE MICRO SWITCH W/ LEVER


Micro # 311SX91-H330. Subminiature S.P.D.T. snap-action switch rated 5 vdc 200 ma. Lever is bent upward and curved, extends approximately 0.30" beyond switch when straightened. Body size: 0.58" long x 0.18" x 0.45" high. Short p.c. pins (0.08"). **CAT# SMS-189** 50¢ each



MICRO # UM10E20E01

S.P.D.T. miniature snap-action switch with lever. Contacts rated 0.1A @ 250 Vac. Switch body is 0.77" x 0.39" x 0.25" thick. Lever with simulated roller tip extends 0.14" beyond end of switch. PC terminals can be wrapped and soldered. UL, CSA.


CAT# SMS-182 \$1.00 each



SWITCH WITH FLEXI-LEAD

Microswitch # SM120S. S.P.D.T. switch rated 3 Amps @ 250 Volts. Body is 0.8" x 0.25" x 0.4". Lever with semi-rolled end extends just past end of switch body. Switch is soldered onto a flexible conductive lead that extends 4" and can be desoldered. UL, CSA.


CAT # SMS-190 50¢ each



DUAL SNAP-ACTION SWITCH ASSEMBLY WITH FLEXI-LEAD

Assembly consists of two Microswitch # SM120S switches, side-by-side, on a metal bracket. Switches are S.P.D.T. rated 3 Amps @ 250 Volts. They have levers with semi-rolled tips that extend just past end of switch body. Both switches are connected to a desolderable flexible conductive lead. Assembly also has a roller lever, unrelated to the switches. Each switch is 0.8" x 0.25" x 0.4" and are UL and CSA.


CAT # SMS-191 \$1.00 per assembly



SUBMINIATURE SNAP-ACTION SWITCH W/ ROLLER LEVER

Omron J-7 or equiv. with JX-222 roller S.P.D.T. subminiature snap-action switch rated 7 Amps @ 125 Vac. Included with each switch, in a separate package, is a lever with a roller tip. The lever extends 0.28" beyond the end of the switch. Switch body without lever is 0.51" x 0.20" x 0.43". Turret terminals. UL, CSA.


CAT # SMS-174 \$1.25 each



S.P.D.T. W/ ROLLER LEVER


Omron # SS-5GL2. S.P.D.T. miniature snap-action switch. Rated 5 Amps @ 125 Vac. Body size: 0.78" x 0.40" x 0.25". Lever with roller tip extends 0.1" beyond end of switch. Solder-loop terminals. UL, CSA.

CAT # SMS-180 \$1.25 each




SNAP-ACTION SWITCH with LEVER

Unimax # LMGHC. S.P.D.T. miniature snap-action switch. Contacts rated 5 Amps @ 250 Vac. Lever extends 0.365" beyond end of switch. Switch body is 0.78" L x 0.25" W x 0.51" high. Solder turret terminals. UL, CSA.
CAT # SMS-181 \$1.00 each • 10 for \$9.00




S.P.S.T., NORMALLY-OPEN SNAP-ACTION SWITCH

Cherry # DB2. SPST switch rated 10.1 A @ 250 V. Body size: 0.78" x 0.25" x 0.37" high. UL, CSA. **CAT# SMS-167** 2 for \$ 1.00




CHERRY DG1C-BJ07

S.P.D.T. Sub-miniature snap-action switch. Body size: 0.51" long X 0.255" high X 0.255" wide. Lever with ridged end simulates roller action. Rated 3 amps @ 125 Vac, 2 amps @ 30 Vdc. PC pins on 0.2" centers. Large quantity available. **CAT# SMS-133**
2 for \$1.00 100 for \$45.00 1000 for \$350.00



WEATHER PROOF SNAP-ACTION


Cherry E-73. S.P.D.T. sealed, watertight snap-action switch rated 0.1 Amp @ 125 Vac. Lever with roller tip extends 0.6" beyond end of switch. Body is 0.91" x 0.89" x 0.38". 10" 16 gauge leads. UL, CSA.
CAT # SMS-179 \$2.00 each



ROTARY SNAP-ACTION SWITCHES


COUNTER-CLOCKWISE ACTION (USED)

Cherry E 53. S.P.D.T. Rated 0.1 Amp @ 125 Vac. Prepped with wire lead on the common terminal. UL and CSA
CAT # CCW-9 \$ 1.25 each



COUNTER-CLOCKWISE

Cherry E51. S.P.D.T. 5 Amp, 125 Vac. Counter clockwise action. Prepped with 24" leads on the common and n.o. terminals. UL, CSA.
CAT # CCW-10 \$2.50 each



SUB-MINIATURE PUSH BUTTONS

S.P.S.T. PC MOUNT

ALPS# SKHHAK409A. 0.25" square X 0.19" high. Leads on 0.15" X 0.25" centers.
CAT# PB-126 4 for \$1.00 • 100 for \$22.50
500 for \$100.00 • 1000 for \$180.00



FSM SERIES TACTILE PUSHBUTTON

Augat/Alcoswitch FSM series 0.24" square miniature pc mount pushbuttons. SPST momentary, normally open. Beryllium copper contacts rated 50 mA @ 12 Vdc. PC lead spacing, 0.256" x 0.177". Plunger height 0.055"
CAT# FSM-4 4 for \$1.00 • 100 for \$22.50
500 for \$100.00 • 1000 for \$180.00



S.P.S.T. PC MOUNT

S.P.S.T. momentary, normally open. 0.48" square x 0.18" body. Plunger stands 0.3" above body. Four PC leads on 0.2" x 0.5" centers.
CAT# MPB-127 4 for \$1.00 • 150 for \$30.00



S.P.S.T MECHANICAL PUSHBUTTON

Omron # B3F-1022. SPST N.O. mechanical push button switch with a positive click action. 0.23" (6m) square x 0.20" (5mm) h. Switching capacity 5-24 vdc, 50 ma (resistive load). PC pins on 0.18" X 0.26" centers.
CAT # MPB-129 4 for \$1.00
100 for \$22.00 • 1000 for \$180.00



MOMENTARY PUSHBUTTON SWITCH, PC MOUNT

Schurter # MTG 1241.1052 S.P.S.T., normally-open, momentary pushbutton switch for pc mounting. 0.5" square x 0.15" high. PC pins on 0.2" centers (diagonal). Positive snap-action feel. Rated 24 Vdc @ 50 mA. Black.
CAT# PB-122 3 for \$ 1.00 • 100 for \$ 25.00



SPST N.O. PUSHBUTTON, PC MOUNT

Omron # B3F-4050. S.P.S.T., N.O. mechanical push-button. Positive click action. 0.48" (12mm) square x 0.3" (7mm) high. Switching capacity 50ma @ 24 Vdc. PC pins on 0.2" x 0.47" centers.
CAT# MPB-130 4 for \$1.00
100 for 22¢ each



PUSHBUTTON SWITCHES

S.P.S.T. MOMENTARY

Normally open switch with 1/4" bushing and plastic button. Ideal for most low current projects.


RED BUTTON CAT# MPB-1
35¢ each • 10 for \$3.25 • 100 for \$30.00



BLACK BUTTON CAT# MPB-1B
35¢ each • 10 for \$3.25 • 100 for \$30.00


S.P.S.T. MOMENTARY RED PUSH-BUTTON WITH 5 FT WIRE LEADS

Terminated with 2-pin female connector (0.1" spacing).
CAT # MPB-16 65¢ each
10 for \$6.00 • 100 for \$50.00



S.P.S.T. MOMENTARY, N.O.

Sub-mini SPST momentary switch. Normally open. Right-angle pc mounting. 0.1" dia. plunger. 0.18" plain bushing. Rated 20 VA.
CAT # PB-82 2 for \$1.00




DPDT, PUSH-ON/ PUSH-OFF

Small, push-on/ push-off pc mount pushbutton switch. 0.31" square x 0.31" high. Gray cap 0.2" X 0.37". Plunger rises 0.5" above switch body. PC pins on 0.1" centers. Contacts, 0.1A @ 30 Vdc.
CAT # PB-94 4 for \$1.00
100 for \$20.00 1000 for \$120.00



S.P.S.T. LED LIGHTED PUSHBUTTON

S.P.S.T., momentary, normally-open pushbutton switch for p.c. mounting. 0.23" square x 0.25" high white cap. Overall height of switch is 0.9". Base is 0.39" square x 0.47" high with PC leads in each corner and two plastic pins for stability. **CAT# PB-125** 3 for \$1.00
100 for 25¢ each • 1000 for 19¢ each
2000 for 15¢ each




MINIATURE ILLUMINATED

Mountain Switch (Miyama Electric)
MS-800 / B2SFC. Good-looking
miniature D.P.S.T. momentary pushbutton
switch with red lens. Contacts rated
0.1 Amp @ 30 VDC. 0.55" square, matte-black
bezel. 0.386" square red lens. Lamp operates on
12 – 28 Volts. Snap-mounts in a 0.5" square cutout.
0.95" behind panel depth. Solder-loop terminals.
CAT # PB-100 \$1.75 each • 10 for \$16.00




PUSHBUTTON SWITCH

Judco model# J-188 SPST, push-on
push-off, plastic pushbutton. Contacts
rated 3 amps @ 125 Vac. Black body,
actuator and panel nut. 3/8-27 threaded
bushing. 4 1/2" stranded wire pigtails.
UL listed. **CAT# PB-21**
75¢ each • 100 for \$60.00




EXCEPTIONAL DEAL ON KEYBOARD TYPE SWITCHES

These inexpensive SPST, pc mount
push-button switches are priced to move.
White plastic body and plunger; 4 pc pins -
two contacts and two supports. Body is
0.59" square. The unit stands 1.15" off of the pc
board. No keycaps available, but they could be
trimmed and used without caps. **CAT# PB-49**
10 for \$1.00 • 100 for \$8.00 • 1000 for \$60.00




SPST, N.O. PUSHBUTTON

McGill switch. SPST, normally-open
momentary pushbutton. Rated
15 Amps @ 125 Vac. Standard 15/32"
threaded bushing. 0.36" dia. pushbutton.
0.25" qc or solder terminals. UL, CSA.
CAT # PB-106 \$1.50 each




S.P.D.T. PUSHBUTTON

Marquardt# 1843. - Push-On Push-Off.
Rated: 6 amp @ 125/250 Vac. UL/CSA.
Handsome 0.31" dia. black plastic push-
button. 0.46" dia. threaded bushing. Chrome
dress nut and standard back-up nut included.
Switch body: 0.92" behind the bushing X 0.94" X
0.65". Solder loop or 0.2" q.c. terms. **CAT# PB-18**
85¢ each • 10 for \$7.50 • 100 for \$65.00




D.P.D.T. PUSH-ON / PUSH-OFF

White nylon plunger, 0.13" square.
Solder or PC pin terminals.
CAT# ISW-10 3 for \$1.00




SPST, ON/OFF PUSH-BUTTON

Arcoelectric 1100 series. Push-on/ push-off
single pole switch. Rectangular plastic
body, 0.5" x 0.39" x 0.85" long, designed
for custom mounting. Plunger extends
0.43" above body. Rated 125 mA @
125 Vac. Solder-loop terminals. UL.
CAT# PB-103 3 for \$1.00 • 100 for \$25.00




PUSH-ON/ PUSH-OFF SWITCH

Kautt u. Bux # T85. S.P.S.T. push-on /
push-off switch. Black. Rated 6 Amp,
250 Vac. Snap-mounts in 0.54" x 0.72"
rectangular cutout. 0.187" quick-
connect / solder terminals. UL, CSA.
CAT # PB-123 75¢ each
10 for 65¢ each • 100 for 50¢ each



PUSH SWITCH ASSEMBLY

Assembly includes POWER and
RESET switches with caps and
clear LED lens from Nintendo
games. Switches are SPST.
One is push-on/ push-off;
the other is momentary, normally-open.
The LED lens fits a T1 3/4 LED. Could be disassembled and used in other applications.




CAT# ISW-4 5 for \$1.00

100 for \$8.00 • 1000 for \$50.00


PUSHBUTTON & LED ASSEMBLY

Black plastic assembly with a S.P.S.T.
momentary, normally open push-
button switch and a T 1 3/4 (5mm)
red led. 0.97" x 0.75" x 0.55" depth,
with flanges extending 0.50" on both sides
of housing. Four 3' wire leads, two for switch and
two for led, terminate to a 4 pin (0.1 center) con-
nector. For low current applications under 1 amp.
CAT# PB-128 \$1.25 each




MINI DPDT MOMENTARY PUSHBUTTON

Alps # SPPJ621528. Miniature D.P.D.T.
momentary push switch for pc board
mounting. When mounted, plunger is
parallel to pc board. Rated 0.2 Amps
@ 12 Vdc. Ideal for signal switching
applications. Switch body is 0.36" x 0.36" x 0.18"
high. Plunger extends 0.38" from body.
CAT # PB-528 5 for \$1.00
100 for \$15.00 • 1000 for \$100.00



SPDT MOMENTARY PUSHBUTTON

NKK # M2B-15. SPDT, pc mount
momentary pushbutton switch.
Rated 0.4VA @ 28 Volts. Good-quality
switch with a crisp, snap-action response.
Gold-plated right-angle pc leads. 0.2" dia.
black pushbutton. 0.12" dia. metal plunger.
Plain bushing, 0.21" x 0.24." **CAT# PB-120**
2 for \$1.00 • 100 for 35¢ each



JUMBO PUSHBUTTONS

Durable plastic S.P.D.T. momentary
pushbutton switch frequently found
in arcade games. Useful in any
application requiring a large, rugged
pushbutton switch. Button operates
a 10 Amp snap-action switch.
Plunger is 0.86" diameter. Bezel is
1.33" diameter. Threaded bushing
is 1.1" diameter and will mount in
panels up to 0.75" thick. Includes large
plastic mounting nut. Available in two colors:



RED SWITCH **CAT# PB-211** \$3.75 each
BLACK SWITCH **CAT# PB-216** \$3.75 each


MANUFACTURERS
We Purchase Excess
Inventories
CALL, WRITE, E-MAIL
or FAX your list

B.C.D. SWITCHES

7 POSITION ROTARY

BCD encoded rotary pushbutton switch. Has digits 0-6. Prepped with a 7" cable terminated with a 6 pin socket connector. Useful for SCSI chains. Snap-mounts into rectangular panel cutout, 0.56" x 0.47".


CAT # RDIP-12 \$1.00 each • 10 for \$7.50



10 POSITION ROTARY

10 position, BCD rotary switch. Screwdriver adjust, slotted shaft. 0.43" x 0.28" x 0.4" high. 6 pc leads.

CAT # RS-109 2 for \$1.00 • 100 for 35¢ ea.




ROTARY SWITCH

1 POLE, 3 POSITION

Electroswitch # 205 9023. This is actually a custom-made two pole, 3 position switch with resistance built into one of the poles. The pole without resistance is normal, however the contact rating is unknown. Brass 0.25" diameter flattened shaft and 3/8" threaded bushing. Body is 0.85" x 0.56" x 0.68" behind the bushing depth. Solder loop terminals.

CAT # RS-95 \$1.00 each



MINIATURE LEVER SWITCH

S.P.D.T. (ON) OFF (ON)

Alps # SSCF2136LX. S.P.D.T., center-off miniature lever switch. Spring-action lever returns to center-off position. 0.49" x 0.43" plastic body. Lever extends 0.375" beyond switch. Mounting flange extends 0.24". Solder-loop terminals. Large quantity available.

CAT # LSW-1 4 for \$1.00 • 100 for \$20.00
1250 for \$150.00 (12¢ each)



SLIDE SWITCHES

DPDT MINIATURE SLIDE SWITCH

Body size: 0.61" x 0.3" x 0.48" deep including solder terminals. Mounting holes on 0.75" centers.

CAT # SSW-33 4 for \$1.00

100 for \$20.00 • 1000 for \$120.00



KEY SWITCHES

S.P.S.T. MOMENTARY-ON

Chicago Lock Spring-loaded key switch. Momentary-on position. Key removable in off position only. 0.75" threaded bushing is 1" long. Below panel depth of switch including terminals is 1.85". 0.87" diameter chrome bezel. Hardware includes 1.07" diameter chrome trim bezel and mounting nut. Screw terminals. **CAT # KSW-16** \$3.50 each



2-POSITION, SPDT KEYSWITCH


C&K Y Series.

2 position, S.P.D.T. keyswitch.

Key removable in both positions. Rated 4 Amps.

Prepped with 23" 3 conductor wire lead. Threaded bushing fits 3/4" hole in panels up to 0.25" thick. Length of body, behind panel is 0.75". Includes two keys and speed-clip for attachment to panel. UL, CSA.

CAT# KSW-24 \$3.00 each




LOW PROFILE KEYSWITCH

C & K # P101133WM03NQ2.

High-reliability, S.P.D.T. keyswitch.

Key removable in one position. Rated 4 Amps @ 125 Vac. Flat-black nylon bezel and body. Bezel dia. 0.875". Approximately 0.6" behind-the-panel clearance. 0.75" diameter threaded bushing with nut. Solder-loop terminals. UL, CSA.


CAT # KSW-22 \$2.75 each



KEY SWITCH / DRAWER LOCK SET

High-quality key switch and drawer lock set manufactured for Hewlett Packard. Both are keyed alike. Both switch and lock have attractive 0.87" diameter, brushed aluminum tapered bezel. Both have threaded bushings that fit 0.75" dia. holes. S.P.S.T. switch, key can be removed in both positions. The key switch will fit up to 0.9" thick panels and comes with a 0.5" high collar that can be used to raise it above the panel. The drawer lock fits panels up to 0.3" thick. Includes 2 keys and mounting clips.

CAT # KSW-19 \$4.00 per set



REED SWITCHES

S.P.S.T. NORMALLY OPEN REED SWITCH

Rated 1 Amp @ 50 Vdc. or 250 Vac. Hermetically sealed glass body is 1.4" long x 0.2" diameter. Lead length is 0.47".

CAT # RSW-14 2 for \$1.00




LEVER-ACTUATED REED SWITCH

Hamlin # 10-59600-054

S.P.S.T. normally-open reed switch with a spring lever. Ideal low-noise, low-operating force sub for rotary snap-action switches and other limit switches. Composite plastic body and lever assembly. Body is 1.24" x 0.655" x 0.69". Two mounting holes approximately, 0.9" apart. Two 2.5" wire leads.

CAT# RSW-21 \$1.50 ea. • 100 for \$1.15 ea.



AUTO PIN SWITCHES


Standard 1.93" long pin switch for auto security and lights. **CAT # PSW-2** 75¢ each • 100 for \$50.00



PIN SWITCH WITH MOUNTING BRACKET

2.55" long pin switch. Includes 3.7" x 1.4" metal mounting bracket and crimp-on bullet connector.

CAT # PSW-8 75¢ each • 100 for \$50.00



**FAX YOUR ORDER 24 HOURS
A DAY 7 DAYS A WEEK.**

(818) 781-2653


**YOUR ORDER WILL SHIP THE
NEXT BUSINESS DAY.**

KEYPADS

TOUCHTONE KEYPAD

Farbell# DU200P (A).
Standard 12 button telephone keypad with touchtone (DTMF) circuitry. Field replacement for some GTE payphones. White plastic buttons with black numerals and letters. 11 color-coded leads, 9" long with spade lugs.

CAT# KP-11 \$3.00 each
25 for \$62.50



12 KEY KEYPAD

12 key keypad with numerals 0-9, * and #. Matrix encoded with one common terminal. Contacts rated 20 mA @ 24 Vdc. 2.01" x 2.24". Black with white buttons. Mounting holes on 1.8" x 2.24" centers. Can be rear-mounted through a 2.25" X 1.81" cutout.

CAT# KP-12 \$ 4.95 each




ALARM SWITCHES

STANDARD MAGNETIC PROXIMITY SWITCH

For closed loop alarm systems. Switch is closed when magnet is near. Cover hides screw terminals. Off-white switch and magnet. UL listed.


CAT# MS-14 \$3.75 ea. • 10 for \$32.50



SPDT

Can be used on normally open or normally closed loop systems. Switch measures 2" long X 3/8".

CAT# MS-7
\$3.50 each • 10 for \$32.50



PRESS-FIT MAGNET SWITCH

Press-fit into 3/8" hole. Ideal for windows and doors. For normally closed systems. 0.75" operating gap. U.L. listed.


CAT# MS-11 \$2.25 per set
10 sets for \$21.00



MECHANICAL ROTARY ENCODERS

Noble # SDE161PUB20F-1-5-32-32PC
Manually operated rotary mechanical encoder. 3/8" threaded bushing. 1/4" flatted shaft x 0.55" long. 32 detents per revolution. 6 pin output.


CAT # MRE-1
\$1.00 each • 100 for \$75.00



4 BIT, 12 POSITION

Noble# SDB161(9x6)-PH20F-1-4-12-12PC
5 output pins. Has metal bracket to accommodate horizontal mounting in pc board.


CAT # MRE-2
\$2.00 each • 10 for \$17.50



MUSICAL "EFFECTS" FOOT PEDAL

Fatar # VFP-1. High-quality, Italian-made foot pedal. S.P.S.T. normally-open switch. Elongated, piano-style pedal, 8.75" x 2.95" x 2.19" high. Quiet-action. Rubberized, non-slip enclosure and base. Metal pedal with removable protective Nylon cover. 7' cord with molded 1/4" phone plug.

CAT # FSW-11 \$16.50 each



INFRARED DEVICES

IR SENDER / RECEIVER

Scottsdale Technologies, Program Master # KC-15S
A hand-held infrared remote control device, probably designed to be upgradeable via the internet. We don't know if they are in current use, but they contain some useful parts and may be the basis for IR remote projects. They operate on two AAA cells (not included). When button is pressed LED lights green, then turns red. Inside are two IR emitter LEDs and one L14C1 IR phototransistor on a PC board with a crystal, ceramic oscillator and other components.

CAT # IR-11 \$ 1.75 each




IR REMOTE

SWITCH MODULE


Add infrared remote control to a project or existing device. Allows device to be switched on or off using any video or audio remote. The single flip-flop type output is triggered by holding down IR remote button for 2 seconds. This prevents accidental triggering of the TV or audio device. On-board LEDs indicate switch status. Must be in an enclosure to prevent actuation by ambient IR radiation. PC board is 3.4" x 0.69." Operates on 6-12 Vdc delivering 75 mA at output. Use relay or solid-state device if higher output is desired. Kit includes a ruby IR filter, hardware and instructions.

CAT # IR-93 \$ 5.00 each



INFRARED EMITTER W/ CORD

Infrared emitting LED in an L-shaped plastic assembly. Molded onto a six foot cord with a 3.5 mm mini-phone plug on opposite end. Probably originally designed to extend the range of an IR control. 5 mm (T 1 3/4) LED. The L-shaped assembly is 0.37" wide x 1.57" long and has peel-off adhesive tape on front & back. **CAT# ILED-12** \$1.50 each
10 for \$ 12.50 • 100 for \$ 85.00




INFRARED RECEIVER / RANGE EXTENDER

Infrared receiver on a 16' cord terminated with a 3.5mm stereo mini-phone plug. Were packaged with audio/video equipment to extend the range of the IR controls. Black plastic, mouse-shaped device at end of cord is 1.9" x 1.4" x 0.9" and has double sided tape for attachment to equipment or wall. Contains a Sharp #GP1U59 IR receiver module which could be removed.

CAT # IRD-8 \$2.50 each • 10 for \$20.00



THERMOELECTRIC COOLERS PELTIER JUNCTIONS



(127 thermocouples per device)

These incredible miniature solid state heat pumps raise or lower temperature in a small area almost instantly. Utilizing the Peltier effect these modules perform the same cooling or heating functions as freon based refrigerators but they do it with no moving parts, and are very reliable. Current applied to the device will produce heat on one side and cold on the other side, up to 68° C difference between the two sides. Modules can be mounted in parallel to increase the heat transfer effect or can be stacked to achieve high differential temperatures. Operate on 3-12 Vdc. Requires a heat sink to prevent overheating. *Two sizes available.*

1.18" (30 mm) square X 0.15"
CAT# PJT-1 \$17.00 • 5 for \$75.00

1.57" (40 mm) square X 0.15"
CAT# PJT-2 \$26.00 • 5 for \$110.00


THERMOELECTRIC COOLER WITH HEATSINK (USED)

Removed from a portable heating/cooling unit. 127 thermocouple device attached to 5" square x 1.22" high heatsink. Overall height: 2.55".

Operates on 12 - 15 Vdc @ 6 Amps.

Includes 180 degree thermal cut-off switch.

CAT # TEC-1 \$26.00 each • 5 for \$100.00



THERMAL FUSES & BREAKERS

PC BOARD THERMOSTAT 80 DEG. C

Airpax # 66F080. PC mount 4 pin DIP package. Normally open. Closes on rise at 75 - 80 degrees C. Resets at 6 degrees C below the close temperature.

Rated 1 amp @ 120 Vac. UL and CSA listed.

CAT# THSW-31 2 for \$1.00 • 10 for \$4.00



THERMAL FUSES

One-time use thermal fuses for upper-limit protection on all kinds of appliances.

Limit Temp	CAT #	Mfg.	Price
91 C	THF-91	Microtemp	2 for \$ 1.00
93 C	THF-93	Microtemp	2 for \$ 1.00
141 C	THF-141	Elmwood	2 for \$ 1.00
152 C	THF-152	Elmwood	2 for \$ 1.00
167 C	THF-167	Microtemp	2 for \$ 1.00
184 C	THF-184	Microtemp	2 for \$ 1.00


BIMETAL DISC THERMOSTATS

Normally closed thermal limit switches. Open on rise at specified temperature. Automatic reset when temperature drops.

74 DEGREES C

Elmwood 3100-3-802 L74C. 0.6" dia. x 0.36" high. Mounting holes on 0.9" centers.


CAT # THSW-74 75¢ each



112 DEGREES C

Klixon # 1NT02L. 0.64" dia. x 0.57". 0.25" quick-connect/ solder terminals.

UL, CSA. **CAT # THSW-112** 75¢ each



30K THERMISTOR

Keystone (Similar to #RL0503-17-56K-96-MS) 30K ohms @ 25 degree C (77 degree F.). Negative temperature coefficient. 0.2" long X 0.09" dia., epoxy insulated bead. 1.13" long teflon insulated AWG#30 wire leads. Prepped with 0.75" long metal tabs.

CAT# THR-19 2 for \$1.00

264 for \$79.20 (30¢ each)

1056 for \$211.20 (20¢ each)



SELCO THERMAL PROTECTORS

110 DEGREE C, NORMALLY CLOSED

Selco # UP61.

Self-resetting

snap-action switch with quick-make/ quick- break, fast sensing action. Rated 4A @ 125 Vac.

Reinforced PBT enclosure, 0.61" x 0.25" x 0.12."

Open on rise at 110 degree C. 2.25" solid, uninsulated leads. **CAT # THSW-110** \$ 1.00 each
10 for \$ 9.00 100 for \$ 75.00




12 VDC HIGH EFFICIENCY FANS w/ INTEGRATED HEAT SINK

Beautifully engineered assemblies designed for high efficiency CPU cooling. Panaflo 12 Vdc fan is built into a heatsink milled from a single block of aluminum with many slots and holes for maximum surface area and heat dissipation.

90 MM DIAMETER



Fan removed
from assembly



Panaflo # FBA06A12H fan embedded in a 3.55" diameter x 1.6" high heatsink. The bottom face of the heatsink has a flat mounting surface, 2.54" x 2.12". The fan/heatsink assembly is mounted in another metal assembly, from which it can be easily removed. **CAT # CF-75** \$ 17.50 each

90 MM DIA. W/ FLAT SIDE

Similar to CAT # CF-75 above except the heatsink is flattened on one side. Also, the exterior metal assembly is not present. Fan diameter is 3.62".

3.21" diameter across the flat side. 1.35" overall height.


CAT # CF-82 \$ 12.00 each



70 MM DIAMETER

Panaflo FBA06A12H fan embedded in a 2.75" dia. X 1.25" high heatsink. Heatsink sits on a 2.6" x 3.08" x 0.2" thick aluminum base with a 2.2" diameter raised mounting surface that adds an additional 0.15" of thickness to the base. Four mounting screws on 2" x 2.5" centers.


CAT # CF-103 \$ 10.00 each



DC FANS


5 Vdc, 60 mm

Mechatronics ® # F6025H05B
2.36" square x 1." 5 Vdc @ 0.41 Amps.
Ball bearings. 7 blades. 8" pigtail
leads prepped with connector.
UL, CSA. **CAT# CF-105**
\$3.50 each • 10 for \$3.00 each




12 Vdc 35 mm

Elina Fan # KDA123510MB
1.38" square x 0.42." 12 Vdc 120 mA.
3" wire leads with two pin socket
connector, 0.1" spacing. UL.
Removed from new equipment.
CAT# CF-133 \$2.00 each • 10 for \$1.75 ea.




12 Vdc 40 mm

Adda # AD0412HB-G76
1.58" square x .4." 12 Vdc, 0.1Amp.
DC brushless fan with ball bearings.
Three leads; one lead is speed
sensor lead, 10" long with 3-pin
(.1" spacing) socket connector.
CAT # CF-143 \$2.50 each




12 Vdc 40 mm

Sunon # KDE1204PFB3-8
1.58" square x 0.42." 12 Vdc
0.5 Watt. 2" wire leads with two pin
socket connector. 0.1" spacing.
UL. Removed from new equipment.
CAT# CF-134 \$1.75 each • 10 for \$1.50 ea.




12 Vdc 40 mm

Adda # AD0412HB-G70
1.58" square x 0.4". 12 Vdc 0.1 Amp.
7 blades. 11" leads with 4 pin Molex
power adapter plug. UL.
CAT # CF-86 \$2.50 each




12 Vdc 50 mm FAN WITH HEATSINK

Iceberg™ by Foxconn ®. 12 Vdc
square mini-fan and heatsink
designed for use with Pentium
series PPGA370, AMD K6
and Cyrix M2 CPUs. Quiet,
reliable design. Includes
easy-on clip. Also good for
other cooling applications.
Heatsink is 1.92" x 2.02" x 0.83" high. Assembly is
1.22" high including fan. Bottom of heatsink has a 1"
square patch of thermal compound. UL, CSA.
CAT # CF-73 \$4.50 each




586 CPU COOLING KIT

12 Vdc fan on a 2.04" x 1.98"
heatsink with easy-install/
release clip. Overall height,
0.83." Compatible with Intel
Pentium 75-150MHz,
IBM6X86-100, Cyrix 6X86
110-133Mhz and AMD K5.
11" leads with male/female molex adapter for
in-line connection. UL, CSA, VDE.
CAT # CF-113 \$4.50 each




12 Vdc, 60 mm

Canon # CF60-T314N1D
2.37" square x 1." 12 Vdc (9 - 13.8V)
70 mA. Ball bearings. 7 blades.
12" pigtail leads. 0.33 m³/min. 23dB.
UL, CSA. **CAT # CF-106** \$4.00 ea.
10 for \$3.50 each • 100 for \$2.75 each



12 Vdc, 80 mm

Jamicon ® # JF0825B
3.15" square x 1." 7 blades.
12 Vdc @ 0.15 Amps. 7" pigtail
leads prepped with 2 pin connector.
CAT # CF-107 \$ 4.50 each




12 Vdc, 80 mm FAN

Panaflo ® Model # FBA08A12L
3.15" square x 1." 12 Vdc, 0.1Amp.
Operates 7 - 13.8 Vdc. 24 CFM.
7 blades. 12" pigtail leads. UL, CSA.
CAT # CF-109 \$ 4.50 each
Case price -100 pcs \$ 3.25 each




12 Vdc 80 mm

Sanyo Denki "Petit Ace 25"
109R0812M401
3.17" x 3.17" x 1."
12 Vdc, 0.09 Amp. 7 blade
impeller. Three leads, one speed
sensor, 10" long. UL, CSA.
CAT # CF-144 \$4.00 each




12 Vdc 92 mm

Nidec Beta SL # DO9T-12PH
3.64" square x 1".
12 Vdc, 0.17 Amp.
7 blades. 11" leads.
CAT # CF-87 \$5.00 each




SPECIAL - 12 Vdc 119 mm

Sanyo Denki "San Ace 25"
109P1212M4011. 4.7" square x 1."
12 Vdc @ 0.14 Amps. Medium speed
fan. Three leads; one is a
pulse (speed) sensor. UL, CSE.
CAT # CF-139 \$6.00 each
Case price - 30 pcs \$4.75 each




12 Vdc 120 mm

Mechatronics ® # E1225H12B1
4.71" square x 1" ball bearing fan.
12 Vdc @ 0.385 Amps. 82 CFM.
12" pigtail leads. Has a third lead,
probably for tach output signal. UL,
CSA. **CAT # CF-114** \$6.75 ea.




12 Vdc, 120 mm

Elina # HDF1225-12HHB
4.7" square x 1".
12 Vdc, 0.56 A.
7 blade fan.
12" pigtail leads.
CAT # CF-101 \$ 6.75 each



24 Vdc, 80 mm

Panaflo® DC Brushless
Model FBA08A24M
3.15" square x 1." 24 Vdc @ 0.1 Amp.
(14-27.6 Vdc) 32 CFM. 7 blade
impeller. 11" pigtail leads. UL, CSA.
CAT # CF-118 \$3.00 each • 10 for \$2.75 ea.
Case of 100 for \$2.00 each




12 Vdc 120 mm COOLING FAN

Adda # AD1212HB-F52
4.72" square x 1.52" high-speed
ball bearing fan. 12 Vdc,
0.50 Amp. Metal frame. 5 blade
thermoplastic impeller.
10" pigtail leads. UL, CSE.
CAT # CF-132 \$ 7.50 each



24 VDC 6.75" DIAMETER "PATRIOT"® FAN

Comair/Rotron "Patriot"®
PQ24B4QDNX. 6.75" dia. x
2" thick. 24 Vdc, 1 Amp. Metal
housing. Seven blade thermo-
plastic impeller with Feathered
Edge (tm) for lower noise. 235 CFM.
Two pin connector fit most fan plugs or
can be soldered. UL, CSA, TUV.
CAT # CF-141 \$ 12.50 each




24 VDC "PATRIOT"® FAN, USED

Same fan as CF-141, above. Removed
from new equipment in good condition.
CAT # CF-135 \$ 9.50 each

24 Vdc, 80 mm


Mechatronics # F8025L24B
3.15" square x 0.98". 24 Vdc @
0.06 Amp. 7 blade, ball bearing fan.
13" pigtail leads. UL, CSA.
CAT # CF-88 \$4.00 each



AC FANS


115 Vac 80 mm

EZ Fan# FP-108A-S-3. 3.13" square X
1.5". 110/120 Vac, 0.5 Amps. 17 CFM.
Zinc housing with seven blade thermo-
plastic impeller. 12" wire leads. UL/CSA.
CAT# CF-117 \$14.00 each




115 Vac 119 mm

EZ Fan # FP-108-1-S3.
4.69" square x 1.5". 110/120 Vac,
0.11 Amps. 54 CFM. Aluminum
housing with 5 blades. Terminals
can be soldered or used with
standard fan plug. UL, CSA.
CAT# CF-120 \$14.00 each



115 VAC 120 MM


Arctic # KEST-470.
4.77" square x 1.54".
115 Vac, 0.24 Amps.
115 CFM. Sleeve bearings. Metal
housing with 5 blade thermoplastic
impeller. Two pin connector for solder
or standard fan cords. UL, CSA.
CAT# CF-146 \$14.00 each



CENTRIFUGAL BLOWERS


115 VAC DUAL-SPEED CENTRIFUGAL BLOWER

Fasco # 7062-5301
Two-speed induced
draft blower for heating
and cooling applications.
Thermally protected,
ball-bearing,
shaded-pole motor.
3000 / 1900 RPM.
Rated 115 Vac @
0.95 Amps. 5 MFD/
370 Vac capacitor.
Steel blower housing and wheel, 9.75" x 8.75" x 3"
with 3.75" x 2.75" exhaust port. Overall width,
including motor, 7.5". Four mounting flanges on 2.75"
x 10.25" centers. 12" pigtail leads. UL, CSA.
CAT # CF-148 \$ 15.00 each
10 for \$ 12.00 each




12 Vdc MINIATURE CENTRIFUGAL BLOWER

Nidec Gamma 26 Model# A33998-55
2.01" x 2.012" x 0.59" miniature blower.
12 Vdc 0.14 amp. Thermoplastic frame.
Ball bearings. Air outlet dimensions:
0.69" x 0.48." UL, CSA.
CAT # CF-138 \$ 4.00 each



12 Vdc 75 mm BLOWER

Delta # BFB0712H
75 mm square x 30 mm miniature
12 Vdc blower. 12 Vdc, 0.36 Amps.
Air outlet is 0.96" x 1.41." UL, CSA.
CAT# CF-145 \$ 6.50 each



METAL FAN GUARDS

GUARD FOR 60 MM SQUARE FANS

CAT# CFG-60 \$1.00 each




GUARD FOR 80 MM SQUARE FANS

CAT# CFG-80 \$1.25 each

CAGE FOR 80 MM SQUARE FAN

Metal fan guard, raised
0.5" from surface of fan.
CAT# CFG-81 \$ 1.35 each




GUARD FOR 118/120 MM SQUARE FANS

CAT# CFG-120 \$1.60 each



GUARD FOR 160 MM FANS


Mounting holes on 6.375" centers.
CAT # CFG-160 \$ 1.75 each



FAN CORDS


36" FAN CORD

With a straight plug. **CAT # CFC-5** 75¢ each



6' 8" FAN CORD W/ AC PLUG


Fits standard
two-prong fan
connectors on many
115 Vac cooling fans.
6' 8" long. Has standard
two-prong AC plug on opposite end.
CAT# CFC-6 \$1.55 each



HEAT SINKS


TO-220 Thermalloy# THM-6045.

Clips onto TO-220 devices.
1" X 0.75" X 0.34". **CAT# HS-6045**
5 for \$1.00 • 100 for \$15.00



0.95" x 0.88" x 0.38"

Aluminum heatsink. 8 cooling fins on
one side. 0.6" X 0.8" flat space on
the other side for mounting a device.
CAT# HS-84 4 for \$1.00



CPU COOLER W/ CLIP

Aavid™ black anodized heatsink, 1.97" x 1.96" x 1.77" high. 1.38" square thermally conductive pad on bottom of heatsink. Stainless steel clip for Zif sockets.

CAT # HS-70 \$1.25 each • 10 for \$10.00




EXTRUDED ALUMINUM

1.58" x 3.7" x 1.75" high.

Weight: 0.5 lbs. Assorted

small, tapped mounting holes along the bottom and side

of the unit. **CAT # HS-77** \$2.50 each




TO-220 / TO-218 HEATSINK

Heavy-duty, extruded aluminum, gold anodized heatsink for TO-220 and TO-218 tab-type semiconductors. 1.64" x 0.98" x 1" high. 0.1" diameter mounting feet on 1" centers. Flat mounting surfaces on two sides will accommodate devices. Large quantity available.

CAT # HS-89 3 for \$1.00


100 for 26¢ each • 1000 for 18¢ each



TO-220 / TO-218 HEATSINK

Heavy-duty, extruded aluminum, gold anodized heatsink for TO-220 and TO-218 tab-type semiconductors. 0.65" x 0.63" x 2" high. 0.1" diameter mounting feet on 0.4" centers.


CAT # HS-90 4 for \$1.00 • 100 for \$18.00



EXTRUDED ALUMINUM HEATSINK

1.58" x 6.5" x 1.75" high. 1.36" wide on one end. 1" length of cooling fin removed on one end. Weight: 0.84 lbs. Assorted small, tapped mounting holes along the bottom and side of the unit.

CAT # HS-78 \$3.50 each



TO-220 SNAP-ON HEATSINK

Thermalloy# THM-6043. TO-220 heatsink. Snaps to any TO-220 device.


CAT# HS-6043 4 for \$1.00



2.95" x 1" x 0.75" HEATSINK

Extruded aluminum heatsink with cooling fins on two sides and a 0.5" square tunnel through the middle. Mounting surface is 2.95" x 1."

CAT # HS-80 \$1.00 ea.




GREEN ANODIZED

2.03" x 2.07" x 1.08" high.

Aluminum heatsink with eight rows of cooling fins, six rows are 1.08" high, the last two are 1" and 0.54" high respectively.


CAT# HS-86 75¢ each



TO-3 and TO-220


Holes punched for one TO-3 device and eight TO-220 devices. 1.82" square X 1.3" high.

CAT# HS-221 \$1.25 each



MICROPROCESSOR HEAT SINK (USED)

Black anodized aluminum, 1.9" square X 0.25" thick. Removed from equipment. Has adhesive residue on one side. **CAT# HS-56** 45¢ each



ROUND HEATSINK WITH COMPOSITE MOUNTING CLIP


1.36" diameter x 0.24" high heatsink with three cooling fins. The lower part of the heatsink is 0.6" diameter and screws into a black composite mounting clip which appears to fit over a device about 0.82" wide. **CAT # HS-59** 50¢ each



EXTRUDED ALUMINUM HEATSINK

6.38" X 3.05" X 1.05" extruded aluminum heatsink. 30 cooling fins. Has some removable spring clips which may have originally been designed for use with CPU or thermoelectric cooler. Four 0.25" holes on 1.85" X 1.35" centers. Weight: 0.75 lb

CAT# HS-47 \$2.50 each




1.8" x 1.76" x 0.28"

Black anodized heatsink. Adhesive thermal compound on bottom.

CAT # HS-81


2 for \$1.00 • 100 for \$35.00



2.35" SQUARE MICROPROCESSOR HEATSINK

Black anodized aluminum. 2.35" x 2.35" x 0.95" high. Thirteen rows of cooling fins. Standard clips for fastening to microprocessor.

CAT# HS-75 \$1.25 each




3" x 3.16" x 1.3"

Wakefield "Penguin Cooler" # 919029. Black anodized aluminum heatsink.

CAT # HS-74


\$1.75 each



8.25" X 0.82" X 1"

Aluminum heatsink with 4 cooling fins on one side and 0.63" wide x 0.35" deep channel on the other side. Has six threaded mounting holes spaced 0.50" apart.


CAT # HS-88 \$1.35 each



5.4" x 1.89" x 1"

Extruded aluminum heatsink. 1" x 1" patch of thermally conductive adhesive on back for attachment to CPU. Four mounting holes on 2.5" x 1.4" centers. Includes CPU clip.


CAT # HS-83 \$1.75 each



BUZZERS, BEEPERS, AUDIO ALARMS

NEW REDUCED PRICES LOUD PIEZO SIREN ASSEMBLY

Complete pc board assembly from a personal alarm system for protecting windows and doors. Makes a piercing, high-pitched sound when connected to a 9 volt battery. Includes a 1.5" diameter encased piezo element, audio transformer and other components. 2.4" x 2" x 0.87". Battery not included. Large quantity available. **CAT # SBZ-10** 75¢ ea. • 10 for \$ 0.65 ea. 100 for 50¢ ea. Case of 270 pcs for 35¢ each




PIEZOELECTRIC BEEPERS

High pitched piezo alarm signals with built-in oscillator circuitry. Low power consumption. Used in alarms, smoke-detectors, electronic games, cameras and telephones.

AMSECO PAL-328 REPLACEMENTS

Operates on 3-28 Vdc. Continuous tone. 103 db sound pressure. 1.14" dia. x 0.93" ABS plastic housing. Can be bulkhead mounted with tabs on 1.31" mounting centers, or can be mounted through a panel hole of 0.7" diameter via threaded bushing and panel nut. 5" wire leads. Black housing **CAT # SBZ-100** \$ 3.75 each
Surplus Special - Projects Unlimited # EXL-450
Gray housing **CAT # SBZ-450** \$ 2.85 each




PIEZO ALERT

Audible piezo alarm emits a solid, high-pitched tone of low to medium loudness. Operates on 3-15 Vdc. 0.54" diameter x 0.3". PC leads on 0.3" centers. **CAT # SBZ-412** \$1.25 each • 100 for 85¢ each
500 for 75¢ each • 1000 for 60¢ each



SONALERT™ REPLACEMENTS

Plastic enclosed piezo sounders which can be mounted through a 1.08" diameter chassis hole and are fastened with a knurled plastic nut. Dimensions of body behind mounting panel, 1.7" diameter x 1.23". Screw terminals or 1/4" quick-connect.



4-28 Vdc Operation

Continuous tone. Loud 95 db sound pressure. **CAT # SBZ-650** \$ 5.50 each

4-28 Vdc, Pulsing Tone

Projects Unlimited # EAI-381KP
Pulse rate, about 1.2 Hz @ 12 Vdc. 2900 Hz signal. 95 db @ 30 cm. Gray ABS plastic housing. **CAT # SBZ-381** \$ 4.75 each

6-12 Vdc Operation

Continuous tone. Exact specs unknown. Medium volume. **CAT # SBZ-9** \$ 3.00 each

30 - 120 VAC/VDC PIEZO SIGNAL

Projects Unlimited, Inc. # EAI-382K. Loud, 95 db, steady tone. Designed to operate on AC or DC voltage, 30 - 120 volts. Will work as low as 6 volts, but not as loud. Gray plastic body. **CAT # SBZ-382** \$5.00 each

6-12 VDC BEEPER

Intervox. Provides a moderately loud, high-pitched tone on 6-12 Vdc. 1.19" dia. x 0.68" black plastic encased piezo beeper. PC leads on 0.6" centers.

CAT # SBZ-221 \$2.00 each



SONALERT MCP320

3 - 20 Vdc, (3 - 20 mA) audible signal device. 0.95" dia. x 0.68" high. 3.15Khz. 55 dB @ 3 VDC, 74 dB @ 20 Vdc. PC leads on 0.6" centers. **CAT# SBZ-321** \$2.50 each



PROJECTS UNLIMITED # AI-256K

3-20 Vdc. Rated voltage 12 Vdc @ 12 mA. 0.92" dia. x 0.38" black ABS plastic case. Resonant frequency, 3100 Hz. 80 dBA @ 30 cm. PC leads on 15mm (0.59") centers. **CAT# SBZ-256** \$ 2.25 each



ENCASED PIEZO ELEMENTS

Plastic encased piezo elements are more resonant and louder than non encased piezo elements. They require external signal to produce sound.

0.9" DIAMETER X 0.17"

Attached to a 28" lead with a small co-ax plug at one end and a 2 pin connector in the middle of the cord. 0.78" dia. element.


CAT # PE-40 75¢ each • 100 for \$ 50.00



0.97" DIAMETER X 0.32"

Murata # PKM25-6A0
Three terminal, self-excited encased piezo element. Prepped with 0.37" wire leads.


CAT # PE-36 2 for \$1.00 • 100 for \$ 40.00



1.18" DIAMETER X 0.32"

Daeyoung. Enclosed piezo element in black case, Two 34" wire leads terminate to 3 pin connector. Mounting holes on 1.35" centers. Requires external signal to produce sound.

CAT# PE-43 75¢ each • 100 for 50¢ each



1.19" DIAMETER X 0.29"

Shigma # SHI-1130. Black case. PC leads on 0.6" centers.


CAT# PE-34 75¢ each
10 for \$6.50 • 100 for \$50.00



1.31" DIAMETER X 0.5"

Kyocera# KBS-30DB-1A-38
Blue case, 4" long wire leads. Mounting holes on 1.5" centers.

CAT# PE-28 75¢ each • 120 pieces \$70.00



1.36" DIAMETER X 0.34"

AVX/ Kyocera # KBT-34SB-1A
Piezo element encased in a black plastic resonant module.

Designed for tone ring in telephones, device requires external signal to produce sound. Mounting holes on 1.57" centers. 6" wire leads.


CAT# PE-35 75¢ each • 100 for \$50.00



1.38" DIA. PIEZO ELEMENT

Kyocera. 35mm brass piezo element with exciter circuit. Three 2" wire leads.

CAT# PE-44 \$1.00 each
10 for \$8.50 • 100 for \$60.00



MINI TONE TRANSDUCERS

Used in paging, warning signals, metal detectors and alarm clocks. Miniature magnetic transducers require external signal source to produce sound.

BUJEON # BBM-01

0.375" diameter x 0.2" miniature transducer. Sound port on one side. PC pins on 0.15" centers. **CAT # PZB-01**
3 for \$1.00 • 100 for \$25.00 • 1000 for \$125.00



0.82" DIAMETER X 0.15"

AVX/Kyocera # PCRT21BGX
Black plastic front, vented metal back.
Solder loop terminals. **CAT # PE-38**
3 for \$1.00 • 100 for \$25.00 • 1000 for \$125.00




150 OHM ENCASED SPEAKER

Keyrin # KR-285. Small 150 ohm mylar speaker encased in a black plastic housing, 1.1" diameter x 0.3" thick. Two mounting ears with holes on 1.4" centers. **CAT # PE-41** 3 for \$ 1.00 • 100 for \$ 25.00




MINIATURE TONE TRANSDUCER

0.47" diameter X 0.33" high. 5" wire leads. **CAT # PZB-25**
50¢ each • 100 for \$25.00



1.65" DIAMETER X 0.63"

Monaco # MPA-3400. White case. 6" leads. Mounting holes on 1.9" centers. **CAT # PE-42** 75¢ each



METAL BUZZERS

1.94" diameter face.
1.68" diameter body.


6 - 9 Vdc **CAT # BZ-2** \$1.00 each
115 Vac **CAT# BZ-9** \$1.00 each



SIRENS

INCREDIBLE PRICE! PIERCING PIEZO MINI-SIREN

This piezo siren emits a piercing 100 db warble tone that is uncomfortable for anyone nearby. Only 2.3" long x 1.7" x 1.5," it has an adjustable metal mounting bracket and comes with 6' of wire. Operates on 9-12 Vdc. Includes a clip for operation with a 9V battery. Ideal for auto or home alarms. Large quantity available. **CAT # ES-12** \$ 3.00 each
10 for \$ 2.50 each • 100 for \$ 1.50 each




MINIATURE SIREN

Shrill, warble tone miniature electronic siren. Operates on 6 - 14 Vdc. Makes a lot of noise for its size. Ideal in a room or automobile. Makes the environment uncomfortable to remain in. 1.86" x 1.55" x 0.9" thick matte black enclosure. Two recessed mounting holes on diagonal corners. Wire leads. **CAT# ES-5** \$5.95 ea.




ELECTRONIC SIREN

Electronic warble tone siren. 4.3" square x 2.2" white plastic enclosure. Operates on 12 Vdc. Mounts on wall or any flat surface via four screw holes in back plate. Wire leads. **CAT # ES-6** \$7.50 each




12 VDC SIREN

Crimestoppers # CS-194C
Ear-piercing warble-tone siren for auto or home use. 3.75" diameter x 3.9" deep impact-resistant plastic horn. Adjustable metal mounting bracket. 3' wire leads. Suitable for outdoor use. Limited quantity. **CAT # ES-1** \$ 9.50 each



4 1/2" X 8" SUPER SIREN


Three wire hook-up allows either steady tone or high/low yelping. 6 - 12 Vdc operation @ 1.25 amps. Made of high impact ABS plastic. **CAT# SS-86** \$19.75 each



CIRCUIT BREAKERS

LITTELFUSE 815 SERIES


120 volt circuit breaker designed for use in TV, audio, machines, etc. 1.81" X 0.59" X 0.9". CSA certified. 1.75A. Tab mount.



CAT# CB-134 4 for \$1.00 • 100 for \$15.00

ETA CIRCUIT BREAKERS

Resettable circuit breakers
1.15" X 0.75" X 0.43" body. UL, CSA.



0.3 AMP NON-THREADED BUSHING


ETA # 41-04-P30
0.3A, 250 vac. 0.275" dia. non-threaded bushing. **CAT # CB-031** \$1.00 each • 10 for \$8.50

1.5 AMP- PC MOUNT

ETA # 41-04-PR. Three pc mounting legs. **CAT # CB-150** \$1.25 each • 10 for \$11.00

Subminiature Circuit Breakers AUGAT/ALCOSWITCH SC SERIES

PC board circuit protectors. Able to withstand high transitory currents often produced by capacitors in a circuit. Since this is a thermal device relying on heat generated by an overload condition, response time is inverse to the degree of overload. Suitable for AC or DC circuits up to 24 volts. 0.7" X 0.2" X 0.44".



Trip rating	mounting	Cat#
500 ma.	right angle	CAT# SC-0.50AR
1 amp	upright	CAT# SC-1.0A
1.5 amp	upright	CAT# SC-1.5A

SC series circuit breakers
4 for \$1.00 • 100 for \$15.00

RESETTABLE CIRCUIT PROTECTOR, 0.65 - 1.3 AMP

Raychem "Polyswitch" # RXE-065S-1
General purpose circuit protectors for power supplies, alarm systems, speakers, motors etc. Unlike traditional fuses, they automatically reset when fault condition is cleared. Can be paralleled for higher ratings. Current: 0.65 Amps. Trip Current: 1.3 Amps. Max Voltage: 60 Volts. 0.33" dia. UL, CSA. **CAT# RXE-065** 3 for \$1.00 • 100 for \$ 20.00
500 for \$85.00 • 1000 for \$150.00



FUSE HOLDERS

AGC (3AG) FUSE HOLDERS

(For fuses 1/4" X 1 1/4")



PANEL MOUNT

Screw style cap. Holder fits 3 AG (AGC) or MDL fuses. Chassis mounting hole 0.59" (15mm) diameter. **CAT# FHPM-31** 75¢ each • 10 for \$7.00 • 100 for \$65.00

Littelfuse # H342058L. Fuse-post with bayonet-type cap. Solder terminals. UL, CSA



CAT# FHPM-46 75¢ each • 100 for 60¢ ea.

HARNESS ASSEMBLY WITH 2 IN-LINE FUSE HOLDERS



Wire harness from auto cellphone kit. Includes two 3AG in-line fuseholders and 12 feet of 18 AWG stranded black, red and green or yellow wire.

CAT # FHP-19 \$1.00 each

IN-LINE AGC (3AG) FUSE HOLDER



For AGC (3AG) fuses. Red wire. Fuse not included. **CAT# FHP-2** 50¢ each • 10 for \$4.00

GMA FUSE HOLDERS

(For fuses 3/16" X 3/4")

PANEL MOUNT HOLDER FOR GMA FUSE



Alco GMA fuse holder for 3/16" x 3/4" fuses. Screw cap. Solder-lug terminals.

Rated 10 Amps 250 Vac. **CAT # FHPM-45**

2 for \$ 1.00 • 100 for 35¢ each


PANEL MOUNT HOLDER FOR GMA FUSES



Buss # BK/HTB-32M. Shock-proof, international style fuse holder for GMA (5mm X 20 mm) cartridge fuses. Screwdriver slot cap. Mounts in 0.5" diameter chassis hole. Straight solder terminals. Extends 1.9" behind panel. UL, CSA, SEMKO and VDE.

CAT# FHPM-33 50¢ each • 10 for \$4.50

HORIZONTAL PCB MOUNT



Schurter # FAU 0031.3571

Shocksafe pc board fuse holder for GMA fuses. Slotted bayonet fuse carrier. Overall length, 1.77" x 0.48" high. PC leads. UL, CSA, VDE. **CAT # FHPM-43** 75¢ each

FUSE CLIPS FOR AGC FUSES

Requires 2 clips per fuse. PC mount with pins on 0.3" mounting centers. Fits 3AG fuse.

CAT# FC-PC 2 for 30¢ • 100 for 7¢ ea.

Mounting pins are on 0.25" centers.

Requires 2 clips per fuse. **CAT# FC-PC2**

2 for 30¢ • 100 for 7¢ each


MINI-BLADE FUSEHOLDER

Water-resistant, in-line fuse holder for Littelfuse 297 series fuses.

Snug protective cover. Black AWG 14 wire leads, 30" and 5."

CAT# FHP-24

85¢ each • 100 for 65¢ each



ATC BLADE FUSE HOLDER

Red, 14 gauge stranded wire. 8" length.



CAT # FHP-22 75¢ each


FUSE BLOCKS FOR AGC FUSES (3AG)

3AG FUSE BLOCK

Littelfuse # 354601GY.

Gray plastic fuse block with single screw mounting. 20A. 0.185" qc or solder terminals. UL, CSA.

CAT # FHBL-3 65¢ each • 100 for 50¢ each




3AG FUSE BLOCK

Littelfuse # 357. Phenolic block.

Single screw mounting. Solder or 0.187" qc terminals.

CAT# FHBL-6 65¢ each • 100 for 50¢ each



DUAL 3AG FUSE BLOCK


Littelfuse # 354802-GY.

Fuse block for two AGC fuses.

Glass-filled polyester. 1.4" x 1.13" footprint. Rated 20 A @ 300 V.

Solder or 0.25" qc terminals. Recessed mounting holes in the middle of each holder. UL, CSA.

CAT # FHBL-42 85¢ each • 100 for \$ 65.00




5 FUSE BLOCK

Black phenolic block,

2.3" x 1.87" x 0.88" high.

Rated 10 amps @ 250 vac.

CAT# FHBL-50 \$2.00 each




ATC AUTOMOTIVE BLADE FUSES

Used in many current model automobiles.

3/4" X 1/8". Fits fuseholder FHP-22.

AMP	COLOR	CAT#	PACK OF 5	100
3	VIOLET	FSA-3	.75	\$12.00
5	TAN	FSA-5	.75	\$12.00
10	RED	FSA-10	.75	\$12.00
15	TEAL	FSA-15	.75	\$12.00
20	YELLOW	FSA-20	.75	\$12.00
25	CLEAR	FSA-25	.75	\$12.00
30	GREEN	FSA-30	.75	\$12.00



FUSES

3 AG (AGC) FUSES

STANDARD FUSES 1/4" X 1 1/4"

AMP	CAT#	PACK OF 5	100
1/2	FS-0.5	1.00	\$15.00
1	FS-1	.75	\$12.00
1.25	FS-1.25	.75	\$12.00
1.5	FS-1.5	.75	\$12.00
2	FS-2	.75	\$12.00
2.5	FS-2.5	.75	\$12.00
3	FS-3	.75	\$12.00
4	FS-4	.75	\$12.00
5	FS-5	.75	\$12.00
6	FS-6	.75	\$12.00
7	FS-7	.75	\$12.00
8	FS-8	.75	\$12.00
10	FS-10	.75	\$12.00
15	FS-15	.75	\$12.00
20	FS-20	.75	\$12.00
25	FS-25	.75	\$12.00
30	FS-30	.75	\$12.00



3 AG (MDL)

1/4" X 1 1/4" SLOW BLOW FUSES

AMP	CAT#	PACK OF 5	100
3/8	FSSB-0.375	2.00	\$32.50
1	FSSB-1	1.75	\$30.00
1.5	FSSB-1.5	1.75	\$30.00
2	FSSB-2	1.75	\$30.00
3	FSSB-3	1.75	\$30.00
4	FSSB-4	1.75	\$30.00
5	FSSB-5	1.75	\$30.00
6	FSSB-6	1.75	\$30.00

GMA SIZE FUSES

MINIATURE FUSES 3/16" X 3/4"

AMP	CAT#	PACK OF 5	100
1/2	GMA-05	1.00	\$15.00
1	GMA-1	.75	\$12.00
1.5	GMA-1.5	.75	\$12.00
1.6 slow blow	GMA-1.6SB	1.00	\$15.00
2	GMA-2	.75	\$12.00
2 slow blow	GMA-2SB	1.00	\$15.00
3	GMA-3	.75	\$12.00
3.15	GMA-3.15	.50	\$9.00
4	GMA-4	.75	\$12.00
5	GMA-5	.75	\$12.00

1AG FUSE, 5 AMP

Littelfuse # H 301005

0.25" diameter x 0.62" long.

CAT# 1AG-5 4 for \$1.00 • 100 for \$15.00

8 AG FUSE, 6 AMP 1/4" X 0.9"

CAT# 8AG-6 3 for \$1.00

MINI-BLADE FUSES, 10 AMP

Red, 10 amp blade fuse. Leads on

0.3" centers. CAT # MF-10

3 for \$ 1.00 • 100 for \$ 25.00

PC MOUNT FUSE, 2 AMP

Wickmann Microfuse TE-6 # 39612000000

2.00 Amp time-lag fuse. Wire leads on

0.2" centers. CAT # FS-102

4 for \$ 1.00 • 100 for 17¢ each

1400 pcs tape & reel 8¢ each

PICOFUSE MINI-AXIAL FUSES

10 AMP

CAT # PFA-10 4 for \$ 1.00

100 for 15¢ each • 1000 for 9¢ each

15 AMP

CAT # PFA-15 4 for \$ 1.00

100 for 15¢ each • 1000 for 9¢ each

GOLD AGU (5AG) FUSES

1.5" long x 0.41" diameter. Gold-plated

fuses for high current applications.

Sold in packages of 5 pieces. 32 Volt max.

40 Amp CAT# AGU-40 \$2.95 per package

50 Amp CAT# AGU-50 \$2.95 per package

60 Amp CAT# AGU-60 \$2.95 per package

IN-LINE FUSEHOLDER FOR AGU FUSES

Waterproof, see-through fuse holder for AGU fuses.

Clear bulkhead mounting bracket with holes on 1.25" centers.

Gold-plated pressure couplings on each end for use with 4-10 AWG wire.

CAT # FHP-79 \$3.50 ea. • 10 for \$3.00 ea.

HEADPHONES

KOSS DIGITAL STEREO HEADSET

Koss MAC-5

Made for Ford Vans.

These lightweight,

adjustable headsets

have great sound

quality with great bass

response for home or studio.

Frequency response:

20-20,000 HZ. 8' rubberized cords are

terminated with a 3.5mm stereo phone plug.

CAT# HP-5 *Blowout Pricing - was \$11.95 ea. now only \$6.95 each • 10 for \$5.75 each*

KOSS "EAR BUDS" FOR PORTABLE STEREOS

Koss # KSC-19.

Unique sportclip

design fits comfortably

over the ear, eliminates the

need for headband. Neodymium,

rare-earth magnet and oxygen-free cable for

impressive sound in a small, ultralight package.

4' cord with 3.5mm mini-plug. 16 ohm impedance.

Frequency response: 20-20,000 Hz.

CAT # HP-11 \$4.75 each

20 for \$4.25 each • 100 for \$3.50 each

LABTEC "BEHIND-HEAD" STEREO HEADPHONE

Labtec # LT-740. New

"Switchback," behind-the-

head design provides

unobtrusive comfort.

Headband sits low on the

back of the head allowing

you to wear a hat or keep

your hair neat. Great sound

quality - neodymium magnets for

deep, powerful bass. 30mm mylar

cone drivers for accurate audio reproduction. Gold-

plated 3.5mm stereo plug fits most portable stere-

os, CD players and digital music devices. In-line

volume control. Freq. Response: 20-20K Hz.

Impedance: 32 Ohms. Retail packaging.

CAT# HP-740 \$6.00 each

ECONOMY HEADPHONES with ADAPTER

Stereo headphones for

portable stereos or computer

applications. Adjustable

headband, padded

earpiece and 3' cord with

3.5mm mini phone plug.

Includes 3.5mm to 1/4" stereo adaptor.

CAT# HP-12 \$2.50 each

10 for \$2.00 each • 100 for \$1.60 each

LIGHTWEIGHT STEREO HEADPHONES

Lightweight stereo headphones

for audio and computer

applications. Adjustable

headband. 3.5mm phone

plug with 4' shielded cord.

CAT# HP-100 \$1.75 each

10 for \$ 1.50 each • 100 for \$ 1.20 each

HEADPHONES W/ MIKE

LABTEC HEADPHONE W/BOOM MIKE

Labtec # LVA-8520. Designed for PC interactive audio applications. Padded stereo headphones with electret boom mike. Adjustable headband.

8' cord terminated with 3.5mm stereo phone plugs for mike and headphones.

CAT# PHN-23 \$7.50 each



MULTIMEDIA HEADSET WITH CONTROLS


Labtec # LVA-8525. Padded stereo headphones with electret boom mike. In-line volume control for headphones and on/off switch for microphone. 6' cord terminated with two 3.5mm stereo phone plugs, one for headphones, one for microphone.

CAT # PHN-22 \$ 9.50 each



"OVER-EAR" HANDS-FREE HEADSET W/ BOOM-MIKE

This "hands-free" headset puts the earpiece outside of your ear and has a boom-mike to get the mike closer to your mouth. Works with Motorola Star-Tac, Samsung and other cell phones as well as FSR radio, some cordless phones and computers. Beige headset and 5' cord with right-angle 2.5mm stereo mini phone plug. **CAT# PHN-21 \$4.95 ea.**



MICROPHONES


600 OHM MIKE

Public address or Karoke microphone. 8.5" long.

Black handle and windscreen.

On-off switch. With 1/4" phone plug.

Ideal for PA use. **CAT# MIKE-340 \$5.00 each**



CARDIOID DYNAMIC MIKE

Well-suited for stage and public address applications. Uni-directional, cardioid polar pattern resists feedback. 600 ohm impedance. On/off switch. Charcoal wind-screen and handle. 2.1" diameter x 6.75" long. Includes carrying case and 16' shielded cable with XLR female connector on mike end and 1/4" phone plug on other end.

CAT # MIKE-800 \$20.50 each



COMMUNICATIONS MICROPHONES

Push-to-talk, hand-held microphones for CB or other communications. Coil cord. 5 pin DIN connector.

CAT# MIKE-43 \$ 3.50 each



ELECTRET MIKE w/ DESK STAND

Electret condenser desk mike. 7.5" boom swivels up and down. Beige mike, stand and cord. 3'6" cord terminated with 3.5mm stereo phone plug.

CAT # MIKE-53 \$2.75 each



ELECTRET MICROPHONES

All of the electret microphones listed below, including those that are part of headphone microphone assemblies, require a low current voltage of 1.5 - 10 Vdc to operate. They will not function in applications that are not specifically wired for electret microphones.

ELECTRET MIKE

Primo # EM-80XH. 0.4" diameter x 0.29"

CAT # MIKE-45 2 for \$ 1.00



MINIATURE ELEMENT

Panasonic # WM-66D501A. Noise cancelling mike. 0.24" diameter x 0.14" high. Operates on 2-10 Vdc.

CAT # MIKE-46 75¢ each
10 for \$6.00 • 100 for \$50.00



ELECTRET MIKE

Primo Microphones. 0.39" dia. x 0.3." 2.25" insulated pigtail leads. **CAT # MIKE-52 2 for \$1.00**



ELECTRET MIKE W/ 2.5MM PLUG

From hands-free cell phone kit. 10' cord terminated with 2.5mm sub-mini phone plug.

Black housing, 1.67" x 0.93" x 0.54" high. Includes a small piece of self-stick Velcro. **CAT # MIKE-55 \$ 1.25 each**



ELECTRET MIKE W/ 3.5MM PLUG

From hands-free cell phone kit. 12" cord terminated with 3.5mm stereo mini-plug. Black housing, 1.25" x 0.64" x 0.7" high. Self-stick Velcro attached. **CAT # MIKE-56 \$1.25 each**



ELECTRET MICROPHONE

Electret mike in a black plastic enclosure with double-stick tape backing. 1.7" x 0.8" x 0.5" thick.

Part of a cell phone hands-free kit. 10' cord terminated with a two pin connector. **CAT # MIKE-49 75¢ each**




REDUCED PRICE!

GOOSENECK ELECTRET MIKE


Electret condenser desk mike with a 12" flexible gooseneck. Beige mike, stand and cord. 4' cord terminated with 3.5mm stereo phone plug.

CAT # MIKE-51 \$ 3.00 each



ELECTRET MIKE w/ CLIP AND HOLDER

Beige electret mike with 8' cord terminated to a 3.5mm phone plug. Has plastic clip on body for attaching to visor or pocket. Includes an adhesive backed holder for attaching to computer. Overall dimensions: 1.19" x 0.53" x 1.92" high. **CAT # MIKE-54 \$1.25 each**




MAGNETS

POWERFUL NEODYMIUM RARE EARTH MAGNETS

Neodymium iron boron (NdFeB), rare-earth magnets have magnetic properties far exceeding those of the Alnico and Ceramic magnets. NdFeB magnets have ratings into the 45MGOe range as compared to the Samarium Cobalt in the 32MGOe range and Alnico or Ceramics in the 8MGOe range. Because of the high strength of Neodymium magnets, and to prevent injury to people or equipment, care must be taken when handling these around other magnets or metal objects. CAUTION! These magnets are fragile and will shatter.

POWERFUL NEODYMIUM

This is the most powerful neodymium magnet we have. 1.74" X 1.43" X 0.24" thick. Slightly curved with an arc of about 20 degrees. Be careful around other magnets and iron. **CAT# MAG-23** \$5.50 each



IRREGULARLY SHAPED NEODYMIUM MAGNET

Aprox. 1.86" X 1.02" X 0.08" thick. **CAT# MAG-26** \$1.50 each
25 for \$31.25 • 100 for \$100.00



BLACK EPOXY-COATED MAGNET

0.95" x 0.42" x 0.13" thick. Flat on one side; slight curvature on one side. **CAT # MAG-67** \$ 1.00 each



SMALL RECTANGULAR BLOCK

0.35" x 0.28" x 0.22" shiny-coated neodymium block. May have some chipped corners. **CAT # MAG-72** 75¢ each • 10 for 50¢ each



SMALL NICKEL-PLATED

Shiny, nickel-plated neodymium magnet. 0.4" x 0.19" x 0.05".

CAT # MAG-58 2 for \$1.00 • 50 for \$ 20.00



SHINY NEO-DISC

For its size, the most powerful magnet we've sold. Shiny, nickel plated neodymium disk, 0.5" dia. x 0.095" thick with a center hole of 0.1" dia. Weighs 2.5 grams and can lift over 1000 times its weight. Rated for up to 150 deg C.

CAT # MAG-71 75¢ each
32 pieces for 50¢ ea. • 512 pieces for 40¢ ea.



CERAMIC MAGNETS

1/2" ROUND CERAMIC MAGNET

0.5" diameter x 0.2" thick ceramic magnet with 0.1" hole in the center.

CAT # MAG-68
10 for \$1.00 • 100 for \$7.50



0.7" ROUND CERAMIC MAGNET

0.7" diameter x 0.2" thick ceramic magnet.

CAT # MAG-70
5 for \$1.00 • 100 for \$15.00



1.75" DIAMETER CERAMIC MAGNET

Powerful 1.75" dia. x 0.2" thick ceramic magnet. Removed from unknown application. Clean.


CAT# MAG-73 75¢ each • 10 for 60¢ each



TIMERS

THE ONE MINUTE TIMER

When the big blue button is pressed the 4 LEDs light and the beeper pulses. As the seconds pass the beeping increases in frequency and the LEDs go out, one at a time until, at the end of 60 seconds, none are lit and the beeper holds a steady tone ending followed by a squelch. The timer can be stopped in the middle of a cycle by pressing the button. Ivory plastic box with blue button. 3.24" square x 2" high. Operates on 9 Volt battery, not included.




CAT # TMR-4 \$ 2.25 each

100+ \$1.50 each • 1000+ \$1.00 each

DIGITAL ON-TIMER


Digital timer from Mr. Coffee™, coffee maker. Ideal for use in any product that needs to be turned on automatically at a specific time. Operates on 120 Vac. Switch loads up to 10 amps. Can be switched manually. White plastic face. 2.48" X 1.77", with four digit LED clock. Overall size: 2.48" X 2.17" X 1.88" deep behind face. 0.25" qc terminals. Easy to connect and operate. Includes instruction sheet.



CAT# MCT-3 \$5.00 each

2 HOUR MECHANICAL TIMER

Timetech # TT-1663. Spring-wound mechanical 2 hour timer shuts off equipment or lights after prescribed interval up to 2 hours. Normally-open contacts. Turn shaft clockwise to activate device. Contacts rated 15 Amps @ 250 Vac. 2.28" x 2" x 1.2" thick plastic housing. 0.25" qc or solder terminals. Metal 6mm diameter half-moon shaft. Brass 8mm threaded bushing. UL, CSA.



CAT # TMR-7 \$ 4.50 each

ELAPSED TIME INDICATOR


Curtis Instruments # 420-LNA
24 Vdc, 0-150 hour elapsed time indicator. Electro-chemically operated meter monitors the actual use time of equipment. Non-resettable. 2.18" x 0.6" x 0.25". Self-sticking adhesive backing. 9" wire leads. **CAT# ETM-420** 75¢ each • 100 for \$60.00



METAL DETECTOR

Comb beaches, sweep hillsides, ghost towns and construction sites with this inexpensive metal detector for beginning prospectors. Also good around the house for locating pipes and studs in walls.

This one is sensitive enough to detect a coin at a depth of up to 6" and much deeper for larger objects. Has controls to adjust volume and sensitivity. A "find" is indicated by a meter and change in speaker volume. Has a 1/4" phone jack for headphone (not included). Adjustable stem. Requires six AA volt batteries (not included). **CAT# MDR- 2** \$37.95 each



FASTENERS

INSULATED CRIMP TERMINALS

QUICK DISCONNECT MALE 1/4"

	CAT#	WIRE SIZE	COLOR	50 PCS	100 PCS	500 PCS	1,000 PCS
	2125	22-18	RED	2.50	4.50	20.00	32.00
	2225	16-14	BLUE	2.50	4.50	20.00	32.00
	2325	12-10	YELLOW	3.00	5.50	26.00	50.00

QUICK DISCONNECT FEMALE 1/4"

	CAT#	WIRE SIZE	COLOR	50 PCS	100 PCS	500 PCS	1,000 PCS
	1125	22-18	RED	2.50	4.50	20.00	32.00
	1225	16-14	BLUE	2.50	4.50	20.00	32.00
	1325	12-10	YELLOW	3.25	6.00	27.50	52.00

QUICK DISCONNECT FEMALE 3/16"

	CAT#	WIRE SIZE	COLOR	50 PCS	100 PCS	500 PCS	1,000 PCS
	1150	22-18	RED	2.50	4.50	20.00	32.00
	1250	16-14	BLUE	2.50	4.50	20.00	32.00

FULLY INSULATED MALE 1/4"

	CAT#	WIRE SIZE	COLOR	50 PCS	100 PCS	500 PCS	1,000 PCS
	4125	22-18	RED	4.50	8.00	35.00	60.00
	4225	16-14	BLUE	4.50	8.00	35.00	60.00

FULLY INSULATED FEMALE 1/4"

	CAT#	WIRE SIZE	COLOR	50 PCS	100 PCS	500 PCS	1,000 PCS
	6125	22-18	RED	4.50	8.00	35.00	60.00
	6225	16-14	BLUE	4.50	8.00	35.00	60.00

PIGGY-BACK 1/4"

	CAT#	WIRE SIZE	COLOR	50 PCS	100 PCS	500 PCS	1,000 PCS
	3125	22-18	RED	2.50	4.50	20.00	32.00
	3225	16-14	BLUE	2.50	4.50	20.00	32.00

BUTT CONNECTORS

	CAT#	WIRE SIZE	COLOR	50 PCS	100 PCS	500 PCS	1,000 PCS
	5100	22-18	RED	2.50	4.50	20.00	32.00
	5200	16-14	BLUE	2.50	4.50	20.00	32.00
	5300	12-10	YELLOW	3.25	6.00	27.50	52.00

END CAPS

	CAT#	WIRE SIZE	COLOR	50 PCS	100 PCS	500 PCS	1,000 PCS
	0100	22-18	NATURAL	2.50	4.50	20.00	32.00
	0200	12-16	NATURAL	2.50	4.50	20.00	32.00
	0300	16-14	NATURAL	2.75	5.00	23.00	40.00


FULLY INSULATED MALE BULLET CONNECTORS

	CAT#	WIRE SIZE	COLOR	50 PCS	100 PCS	500 PCS	1,000 PCS
	5400	22-18	RED	2.50	4.50	20.00	32.00
	5500	16-14	BLUE	2.50	4.50	20.00	32.00


FULLY INSULATED FEMALE BULLET CONNECTORS

	CAT#	WIRE SIZE	COLOR	50 PCS	100 PCS	500 PCS	1,000 PCS
	5600	22-18	RED	3.25	6.00	27.50	52.00
	5700	16-14	BLUE	3.25	6.00	27.50	52.00

SPADE TERMINALS

	CAT#	WIRE SIZE	COLOR	STUD SIZE	50 PCS	100 PCS	500 PCS	1,000 PCS
	9106	22-18	RED	6	2.50	4.50	20.00	32.00
	9108	22-18	RED	8	2.50	4.50	20.00	32.00
	9110	22-18	RED	10	2.50	4.50	20.00	32.00
	9206	16-14	BLUE	6	2.50	4.50	20.00	32.00
	9208	16-14	BLUE	8	2.50	4.50	20.00	32.00
	9210	16-14	BLUE	10	2.50	4.50	20.00	32.00
	9308	12-10	YELLOW	8	3.25	6.00	27.50	52.00
	9310	12-10	YELLOW	10	3.25	6.00	27.50	52.00

RING TERMINALS

	CAT#	WIRE SIZE	COLOR	STUD SIZE	50 PCS	100 PCS	500 PCS	1,000 PCS
	8106	22-18	RED	6	2.50	4.50	20.00	32.00
	8108	22-18	RED	8	2.50	4.50	20.00	32.00
	8110	22-18	RED	10	2.50	4.50	20.00	32.00
	8206	16-14	BLUE	6	2.50	4.50	20.00	32.00
	8208	16-14	BLUE	8	2.50	4.50	20.00	32.00
	8210	16-14	BLUE	10	2.50	4.50	20.00	32.00
	82516	16-14	BLUE	5/16	3.25	6.00	27.50	52.00
	8308	12-10	YELLOW	8	3.25	6.00	27.50	52.00
	8310	12-10	YELLOW	10	3.25	6.00	27.50	52.00
	83516	12-10	YELLOW	5/16	3.75	7.00	30.00	55.00

QUICK SPLICE

	CAT#	WIRE SIZE	COLOR	50 PCS	100 PCS	500 PCS	1,000 PCS
	7100	22-18	RED	5.50	10.00	47.00	75.00
	7200	16-14	BLUE	5.50	10.00	47.00	75.00

130 PIECE CRIMP TERMINAL KIT




This kit contains an assortment of 130 crimp style connectors. Included in the set are push-on type connectors, spade type connectors, in-line connectors and full round connectors. Complete set including a crimp tool and plastic storage box.

CAT# CRPKT-130

\$7.25 per set

CRIMP TOOL



Designed to be used to crimp "D" sub pins, 22-28 AWG, butt connectors and small solderless connectors.

CAT # CT-1 \$7.50 each

TELECOM CONNECTORS

For 19- 26 AWG wire. Simply put wires in place and push button with pliers or crimping tool. Filled with silicone gel to insulate and improve conductance.

2-WIRE BUTT SPLICE - YELLOW

CAT # UYC 10 for \$2.00
50 for \$7.50 100 for \$11.00



3 -WIRE BUTT SPLICE - RED

CAT # URC 10 for \$2.50
50 for \$10.00 100 for \$14.00



TAP CONNECTOR

Allows user to tap directly into an existing wire without cutting.

CAT # UBC 10 for \$2.50
50 for \$10.00 100 for \$14.00



IN-LINE SPLICE

CAT # BSL-2
10 for 75¢
50 for \$3.00 100 for \$5.50




WIRE SADDLES

WIRE SADDLE WITH ADHESIVE BACKING

White nylon wire harness saddle. 1" x 0.56" base with adhesive backing. Holds wires and bundles of wires up to 0.22" diameter.

CAT# WH-9 100 for \$6.00
1000 for \$40.00



CABLE TIES

CAT#	LENGTH	MIN. TENSIL STRENGTH	COLOR	MAX. BNDL DIA.	10	100	1000
TR-400	4"	18 lbs	neutral	15/16"	.30	\$2.50	\$15.00
TR-400B	4"	18 lbs	black	15/16"	.35	\$3.00	\$17.50
TR-600	6"	30 lbs	neutral	1 1/2"	.50	\$4.00	\$30.00
TR-600B	6"	30 lbs	black	1 1/2"	.50	\$4.00	\$30.00
TR-800	8"	50 lbs	neutral	1 3/4"	.60	\$5.00	\$40.00
TR-800B	8"	50 lbs	black	1 3/4"	.70	\$6.00	\$50.00
TR-1100	11"	50 lbs	neutral	3"	.70	\$6.00	\$50.00
TR-1100B	11"	50 lbs	black	3"	.80	\$7.00	\$60.00
TR-1500	15"	50 lbs	neutral	4"	\$1.00	\$8.00	\$70.00

ADHESIVE-BACKED TIE MOUNTS

3/4" square 10 - 40 lbs ties
1" square 18 - 50 lbs ties

These tie mounts are used to hold the above tie wraps to a flat surface.



CAT# TM-1 10 for \$1.20 100 for \$9.50 1000 for \$85.00
CAT# TM-2 10 for \$1.40 100 for \$10.00 1000 for \$95.00

WIRE NUTS




SIZE	COLOR	CAT#	50	100	500	1000
Fits 18-28 ga. wire	Grey	WN-1	\$2.00	\$3.50	\$15.00	\$25.00
Fits 18-24 ga. wire.	Blue	WN-2	\$3.00	\$5.50	\$25.00	\$45.00
Fits 16-22 ga. wire	Orange	WN-3	\$3.75	\$7.00	\$32.50	\$60.00
Fits 18-12 ga. wire	Yellow	WN-4	\$3.75	\$7.00	\$32.50	\$60.00

THREADED HEX STANDOFFS


(Male to Female)

M-F STYLE



(Female to Female)

F-F STYLE



A= Aluminum B=Brass N=Nylon S=Steel

Length	Dia.	Mat.	Style	Thread	CAT #	10	100
0.32"	0.25"	N	F-F	4-40	SP-110	0.90	5.00
0.5"	0.2"	S	F-F	4-40	SP-124	1.00	8.00
3.53"	0.2"	A	F-F	4-40	SP-78	2.50	20.00
0.3"	0.25"	S	F-F	6-32	SP-116	1.00	8.00
0.5"	0.25"	B	F-F	6-32	SP-123	1.00	8.00
0.9"	0.25"	S	M-F	6-32	SP-122	1.50	10.00
1"	0.25"	S	M-F	6-32	SP-8	1.50	10.00
1.75"	0.25"	N	M-F	6-32	SP-95	1.50	10.00
3"	0.25"	B	F-F	6-32	SP-87	2.50	17.50
1.125"	0.25"	A	M-F	8-32	SP-14	1.50	10.00
2.25"	0.30"	A	M-F	10-32	SP-130	2.00	15.00
0.75"	0.25"	A	F-F	3MM	SP-90	1.00	8.00
1"	0.22"	B	M-F	3MM	SP-15	1.50	10.00
0.63"	0.25"	S	M-F	5MM	SP-89	1.00	8.00

SHOULDER STANDOFF, 4-40 THREAD

1/4" x 1/4" hex standoff with 4-40 female thread. 0.2" long shoulder fits 0.2" dia. hole.

CAT# SP-126 10 for \$1.00

100 for 7¢ each • 1000 for 5¢ each




0.75" NYLON HOLE PLUG

Black nylon hole plug for 0.75" dia. chassis hole. CAT# HPL-0.75
10 for \$1.00 • 100 for \$5.50



SPLIT-LOOM TUBING

Dress up auto and home installations with split-loom tubing. Allows exit or entry of wires at any point.



DIA.	COLOR	CAT#	PER FOOT	100 FOOT
1/4"	black	SLT-14	12¢	\$9.00
3/8"	black	SLT-38	15¢	\$10.00
1/2"	black	SLT-12	19¢	\$12.00
5/8"	black	SLT-58	25¢	\$18.00
3/4"	black	SLT-34	29¢	\$18.00

Minimum order 10' of one size.

NON-THREADED SPACERS



A = Aluminum N = Nylon K = Bakelite

Length	Dia.	Mat.	Hole	CAT #	10	100	1000
0.19"	0.5"	N	#10	SP-107	0.80	5.00	35.00
0.25"	0.25"	N	#8	SP-42	0.80	5.00	35.00
0.25"	0.30"	N	#6	SP-96	0.80	5.00	35.00
0.375"	0.375"	K	#8	SP-99	0.50	4.00	25.00
0.38"	0.25"	K	#8	SP-101	0.50	4.00	25.00
0.50"	0.25"	N	#8	SP-58	0.90	5.50	40.00
0.6"	0.13"	N	18awg	SPC-5	0.40	3.00	20.00
0.62"	0.25"	N	#8	SP-66	0.95	5.75	42.50
0.625"	0.31"	K	#10	SP-100	0.65	4.50	30.00
0.625"	0.32"	N	#10	SP-108	1.00	6.00	45.00
0.63"	0.25"	N	#6	SPC-2	0.65	5.00	40.00
0.69"	0.37"	N	#8	SP-106	1.00	6.00	45.00
0.75"	0.25"	N	#8	SP-74	1.00	6.00	45.00
0.75"	0.30"	N	#8	SP-105	1.00	6.00	45.00
0.87"	0.31"	N	#8	SP-118	1.00	6.00	45.00
0.89"	0.38"	K	#8	SP-119	0.75	6.00	45.00
1.5"	0.25"	A	#6	SP-10	1.50	10.00	80.00

CIRCUIT BOARD SUPPORTS

all the circuit board supports below are priced:
20 of one style \$1.00 • 100 of one style \$4.00
1000 of one style \$20.00

0.25" HIGH. Snap mounts in 0.187" diameter hole. CAT# CBS-11



0.31" HIGH. Richco # MSPE-5-01. Snap-mounts into 0.125" dia. holes. White nylon. CAT # CBS-7




0.43" HIGH. Richco # MSPM-7-01. Snap-mounts into 0.125" diameter holes. White nylon CAT # CBS-6

0.5" HIGH. Snaps into 0.125" diameter hole. White nylon. CAT# CBS-12

1.12" HIGH. Richco# DLMSP-18-01. Snap-mounts in 0.156" dia. hole. White nylon. CAT# CBS-9

Nylon circuit board supports snap into 0.187" hole in chassis. 3/4" high.

CAT# CBS-5



0.4" high x 0.2" diameter hex standoff. One end snap-mounts into 0.156" dia. hole. The other end has a 6-32 male thread. CAT # CBS-10



ROTATING PARTS

(GEARS, PULLEYS, BELTS, O-RINGS)

MINIATURE ROLLER CHAIN



25 roller chain.

Works with 1/4" pitch chain sprockets below.

CAT # CHN-25 \$ 2.25 per foot

MASTER LINK for # 25 roller chain

CAT # ML-25 \$1.00 each

1/4" PITCH SPROCKETS

Glass-reinforced nylon sprockets for use with # 25, 1/4" pitch roller chain. Sprockets are designed for press-fit use, but collars have ample room to be tapped for set screws.



TOOTH	BORE	CAT#	PRICE
11	5/16"	GR-23	\$1.25
12	1/4"	GR-18	\$1.25
13	1/4"	GR-19	\$1.25
25	5/16" (flatted)	GR-72	\$ 1.50
42	5/16" (flatted)	GR-73	\$ 1.75

METAL 16 TOOTH CHAIN GEAR

For #25 roller chain. 3/8" flatted bore.

CAT # GR-75 \$ 1.25 each




MATING GEARS

All of the following gears and sets of gears, with the exception of CAT # GR-27, mate with one another

5 GEAR ASSORTMENT


Five matched break-resistant plastic gears ranging from 0.44" dia.(10 teeth) to 2.02" (50 teeth).

Gears are molded with 0.15" (4mm) bores and come with inserts which reduce the bore to 0.065" (2mm) diameter. **CAT# GR-5**
\$2.75 per set - includes 5 gears and 5 inserts
10 sets for \$20.00



Two black composite plastic gears.
64 teeth: 2.6" diameter x 0.4" 0.4" (10mm) bore. 36 teeth: 1.48" diameter x 0.23" 0.32" (8mm) bore.

CAT# GR-68 \$1.65 per set



34 tooth composite gear with 3/8" diameter aluminum bore. 1.4" dia. x 0.5" thick. Collar extends 0.25" beyond gear.

CAT # GR-79 \$ 1.00 each



16 TOOTH GEAR

Black composite gear. 16 teeth. 0.7" diameter. 0.25" bore. **CAT# GR-64** 75¢ each



27 COG IDLER GEAR

Ball bearing idler gear with 6mm (0.24") bore. 27 teeth. 1.14" diameter x 0.48" thick.

CAT # GR-71 \$ 2.00 each



20 TOOTH NYLON GEAR

Nylon gear. 0.85" dia.x 0.32" wide. 0.32" dia.bore. Collar extends 0.3" beyond gear. **CAT# GR-82** 75¢ each



12 COG GEAR

0.58" diameter x 0.48" thick. 0.1" collar. 0.2" dia. flatted bore.

CAT # GR-74 50¢ each



32 COG GEAR

1.34" diameter x 0.48" thick.

0.36" collar. 0.325" dia. bore.

CAT # GR-70 \$ 1.25 each




COMPOUND GEAR

Black plastic compound gear.

The smaller gear is 0.28" wide, has 14 teeth and a diameter of 0.53".

The larger gear is 0.46" wide, has 21 teeth and a diameter of 0.77". 6 mm (0.24") bore.

CAT # GR-78 50¢ each




MATING GEARS W/ SHAFT

32 cog gear is attached to a 5/16" dia. x 1.5" shaft.

The mating 28 cog gear fits the opposite, flatted end of the shaft.

CAT # GR-76 \$ 1.75 per set



BEVELED MATING GEARS

Mating, beveled gears. Black composite. One is a 36 tooth gear, 1.23" diameter x 0.35" wide with flatted 0.32" bore. The other is a compound gear - the larger part has 46 teeth and is 1.56" diameter x 0.47" wide - the smaller part has 26 teeth and is 0.9" dia. x 0.71" wide. It has a brass reinforced 0.31" bore.

CAT # GR-27 \$1.50 per set



METAL COMPOUND GEAR

Metal gear with 0.1" bore. Overall thickness, 0.25". 0.67" dia. outer gear, 32 cogs, 0.5" pitch. 0.27" dia. inner gear, 10 cogs, 0.5" pitch.


CAT # GR-83 \$ 1.00 each



COGBELT AND TWO PULLEYS

21" circumference x 0.25" wide cogbelt with two pulleys. Large plastic pulley has 60 cogs and is 1.45" diameter. The small pulley is metal and has 27 cogs and is 0.66" in diameter. Both have 5/16" flatted bores. The small pulley has a hole for a set screw. Removed from equipment.

CAT # PA-4 \$ 3.00 per set




SYNCHRONOUS DRIVE

"XL" GEARBELT

1/5" PITCH 1/4" WIDE

40 Teeth 80XL025 **CAT # CGB-40** 85¢ each



SPRING WRAPPED SLIP COUPLINGS


Stainless steel spring wrapped couplings for connecting shafts of two different sizes.

0.25" AND 0.375" BORES

Sterling Instr., (SDP/SI)

S9941Y-SWC13A46. 1.43" overall length. Outside diameter: 1.25" 0.62" bore depth. Slip at 48 oz in. 6-32 set screws.


CAT# FC-13 \$3.50 each



0.1875" AND 0.25" BORES

Sterling Inst., (SDP/SI)


S9941Y-SWC10A34. 1.26" overall length. Outside dia.: 1". 0.550" bore depth. Slip at 20 oz in. 4-40 set screws. **CAT # FC-10** \$3.50 each



DC MOTORS

TINY VIBRATING MOTOR

Low voltage, low current miniature vibrating motor. Operates on 1.5 – 3 Vdc. Tiny motor with offset weighted shaft is used in cell phones and pagers for vibrating alert signal. Remove the weight and they're great for many model and robotics applications. A clear silicone boot surrounds the motor and provides a flat, shock-mounting surface. Without the silicone boot the motor measures 0.16" dia. x 0.5" long. The shaft and weight extend another 0.3". Connection is via two gold-plated solder pads. **CAT # DCM-179** \$ 1.75 each
10 for \$ 15.00 100 for \$ 100.00




MINIATURE VIBRATOR

Sanko Electric # 1E120. 0.55" dia. x 0.135" thick miniature enclosed vibrating motor. Used as a signaling device in pagers and cellphones. Operates on 3 Vdc. Solder pad terminals. **CAT # VB-1** \$ 1.25 each




MINIATURE DC MOTOR

Mabuchi # FF-N20PN/ Miniature 1.5 to 3 Volt DC motor. Ideal for models and radio control applications where small size is important. No load rating: 15,800 RPM @ 2.4 V, 96 mA. Length (excluding shaft), 0.654" long x 0.47" x 0.39". 0.039"(1mm) diameter x 0.13" long shaft. Solder-loop terminals. Large quantity available. **CAT # DCM-166**
2 for \$1.50 • 150 for 60¢ each
600 for 50¢ each • 1500 pieces 35¢ each




1 1/2 - 3 VDC MOTOR

Dual shaft motor operates well on 1.5 to 3 Vdc. 3/32" diameter shaft is 0.58" long on one side and 0.4" long on the other. Motor is 1.08" diameter X 1.47" long. Solder loop terminals. **CAT# DCM-75** \$1.35 each • 10 for \$11.50




3 - 6 VDC MOTOR

Johnson Motor. 0.78" x 1" x 1.38" long. 0.08" (2mm) x 0.33" long shaft. Solder terminals. **CAT# DCM-189** 2 for \$ 1.50




3 - 6 VDC MOTOR

Mabuchi RS-550PF. Good-quality motor with internal cooling fan. No-load rating: 9000 RPM @ 6 Vdc, 1.3 Amps. 1.47" diameter x 2.25" long. 0.13" diameter shaft is 0.63" long. **CAT # DCM-104** \$3.50 each




3 – 12 VDC MOTOR

Mabuchi Motor. Small DC motor. Operates between 3 – 12 Vdc. 0.93" dia. x 1.2" long. 0.078" (2 mm) dia. x 0.27" long shaft. Motor is prepped with a 9 volt battery clip on 6" leads. **CAT # DCM-155** 2 for \$ 1.50




6 VDC MOTOR

Mabuchi # RF-510T. Quiet, low-current DC motor typically used in audio equipment, CD, DVD, tape or VCRs. No load specs: 2800 RPM @ 6 Vdc, 10 mA. 1.25" dia. x 1.07". Shaft is 2mm dia. (0.08") x 0.42" long. Solder terminals. **CAT# DCM-176** \$1.50 ea. • 200 for \$200.00



6 VDC MOTOR

Johnson # 63706. Powerful little motor with internal cooling fan. No load rating: 1200 RPM @ 5.8 VDC @ 1.26 Amps. 1.46" dia. x 2.54" long. 0.125" dia. x 0.35" long shaft. Solder or 0.187" qc terminals. **CAT# DCM-165** \$3.50 each




6 VDC MOTOR

Mabuchi# RS540SH. Good-quality reversible DC motor. No load specs: 1100 RPM @ 6 Vdc @ 1 Amp. 1.41" diameter x 2.15" long. 0.125" diameter x 0.3" long knurled shaft. **CAT # DCM-136** \$3.50 each
Case of 90 for \$2.50 each




6-12 VDC VIBRATING MOTOR

Panasonic "Micro-motor" # AKME-BC 0.59" x 0.79" x 1.15" long vibrating motor. 0.31" long x 0.08" (2mm) dia. shaft has a 0.43" 1/2 moon weight. Operates on 6-12 vdc. 1" wire leads. **CAT# DCM-184** \$1.25 each • 10 for \$ 1.00 each
100 for 85¢ each • 500 for 65¢ each



TWO-SPEED VIBRATING MOTOR

3 Vdc (1.5-6 Vdc) motor with a relatively heavy offset weight which vigorously shakes the motor when voltage is applied. Motor is prepped with a 3-position slide switch with positions for off, slow and fast. Also included are elements of a battery holder. Motor is 1.35" long x 0.94" x 0.72". Shaft is 2mm (0.07") dia. x 0.4" long. Weight is removable from motor shaft. **CAT# DCM-185** \$1.25 ea. • 10 for \$1.00 ea.
100 for 85¢ each • 500 for 65¢ each




12 - 24 VDC MOTOR

Johnson Electric. Small permanent magnet DC motor operates on 12 - 24 Vdc. No load speed: 5000 RPM @ 24 vdc, 85 mA. 2500 RPM @ 12 vdc, 14 ma. 0.95" x 0.72" x 1.21" long. 2 mm x 10 mm long shaft. Prepped with black and red 1.8" long leads terminated with 0.125" qc connectors. **CAT # DCM-100** 2 for \$1.50 • 100 for \$60.00




12 - 36 VDC MOTOR

Johnson Motor. Quiet, smooth operation from 12-36 Vdc. No load spec: 3780 RPM @ 24 Vdc @ 32 mA. 0.967" diameter x 1.21" long. Shaft is 0.08"(2mm) diameter x 0.73" long. Solder terminals. **CAT # DCM-141** \$1.25 each



24-36 VDC MOTOR

Mabuchi # RS-775VB. Quiet, powerful, permanent magnet DC motor. Operates smoothly over a range of 12 – 48 VDC. No-load specs: 2400 RPM @ 24 VDC @ 110 mA. Body is 1.75" diameter x 3" long. Shaft is 5 mm (0.12") dia. x 0.5" long. A 0.32" dia. aluminum sleeve press-fit over the end of the shaft. Motor is prepped with 12" long leads with a ferrite bead. **CAT # DCM-138** \$ 3.75 each




2-9 VDC MOTOR

Samhonsa DHBA
Quiet running DC motor.
0.94" dia. x 0.5" body.

0.08" (2mm) dia. x 0.4" long shaft.
2250 RPM @ 2 Vdc, no-load rating.
Has both 1.5" wire leads and solder terminals.


DCM-196 \$1.25 each • 10 for 90¢ each



1.5-9 VDC MOTOR

Mabuchi # RF-500TB-14415
Quiet, low-current motor typically used
in audio equipment, CD, DVD tape or
VCRs. No load specs: 1800 RPM @
3 Vdc, 0.022 Amps / 3700 RPM @
6 Vdc, 0.28 Amps. 1.25" diameter x
0.9" 0.08" (2mm) diameter x
0.34" long shaft. Solder terminals.

CAT # DCM-197 \$1.50 each
10 for \$1.00 each



DC GEAR MOTORS


MINI-RIGHT ANGLE GEARHEAD MOTOR w/ CONTROL CIRCUIT

Omron # R2DG-41. These
unusual little motors have
built-in control circuits that
allow them to be used in a
continuous or a pulsed mode.

In continuous mode the final drive gear turns
at 22-45 RPM (3-6 Vdc). In the pulsed mode the
final drive gear turns one revolution each time the
controller is momentarily pulsed. The motor assembly
is 1.75" x 1.25" x 0.5" overall. The nylon final gear
is 0.62" dia. and has a little nipple slightly off-center to
which a small push-rod could be attached. Motors
are in good condition, removed from equipment.

Hook-up instructions included. Large quantity available.


CAT# DCM-110 \$3.25 each
10 for \$3.00 each • 100 for \$2.25 each




MOTOR W/ WORM GEAR ASSEMBLY

A smooth-running DC motor, fly-
wheel and nylon gear train are
built into this plastic assembly.
The motor operates from 3-12
Vdc and rotates a worm gear which
turns a 1.8" diameter circular gear.

This gear drives a 1.3" nylon rod
back and forth 100 times per minute
at 6 Vdc. Motor is a Mabuchi #
RF-500TB-18280. It is 1.25" in
dia. x 0.9" long. The
motor/gear assembly
is an integral part of the
larger plastic assembly. It
requires some cutting of the
plastic in order to separate the motor/
gear assembly from the rest of the unit for use in
other applications. **CAT # DCM-92** \$3.00 each




CUTAWAY VIEW



24.5 VDC 115 RPM GEAR MOTOR

Crouzet # 82-048-016. Small worm-gear
driven motor operates from
9 - 32 Vdc. No-load rating:
115 RPM @ 24.5 Vdc @ 55 mA.
Black plastic housing, 2.28" x
1.42" x 1.04" 0.25" dia. x
0.35" long flattened shaft. Included is
a 2 pin female connector with 8" pigtail
leads which works with the recessed male
connector on the motor, but is not a perfect match.

CAT# DCM-172 \$6.00 each



6 VDC GEAR MOTOR ASSEMBLY


Motor/gear-box assembly, removed in good condition,
from rideable toy vehicle. Designed to operate on 6
Vdc, the assembly, enclosed in an unbreakable black
plastic case, provides enough torque to move a child
slowly around a room. The Mabuchi drive motor is,
3.5" long x 1.46" diameter with an internal cooling fan.
The motor, itself, is encased in a removable break-
resistant plastic outer cover which extends 3.25"
beyond gearbox. Two styles:

STYLE 1:

Pear-shaped
gearbox,
3.75" x
6.75" x
1.27".

Drive shaft is a
slotted pentagonal
nylon structure,
1.15" on a side, turning on a
2.17" diameter cylinder around a stationary 0.43"
dia. nylon channel. The rotating structure extends
1" beyond the gearbox. The final drive rotates at
60 RPM @ 6 Vdc / 930 mA (no-load rating).

CAT # DCM-192 \$6.50 each




STYLE 2:

Oval-shaped
gearbox,
8.5" x 4.8" x
2.75". Drive
shaft is

1.77" diameter
nylon sleeve with
slots. It rotates around
a 1.3" diameter cylinder.
Rotating structure extends
0.7" beyond gearbox. The final drive rotates at 60
RPM @ 6 Vdc / 1.7 Amps (no-load rating).

CAT # DCM-193 \$6.50 each




12 - 120 VDC WORM GEAR DRIVE MOTOR

CCL Motor # DE-25L.

This very unusual motor
has been prepped with a
full wave bridge rectifier for
use with 120 Vac. If you bypass
the bridge rectifier it works very nicely on any DC
power from 12 volts on up. The final drive is a 0.8"
long worm gear that turns a 0.8" dia. plastic gear
at 120 RPM @ 12 Vdc (no load). Replaceable
brushes. Motor body is 1.41" diameter x 2.75" long.

CAT# DCM-96 \$2.00 each • 10 for \$15.00




24 VDC GEARHEAD MOTOR

Merkle-Korff. Heavy-duty
gearhead motor designed to
drive a prison lockdown
mechanism. Reversible,
continuous duty motor,
operates at 50 RPM @
24 Vdc, 150 mA (no load).

Will operate at lower
voltages and RPMs. Diecast
gear box is 4.7" x 2.75" x 1.5" and
has four 0.2" mounting holes on 2.4" centers.
2" dia. x 3" long drive motor. Output shaft is 0.5"
dia. x 0.9" long and is on the same side of the
gearbox as the motor.

CAT# DCM-175 \$21.50 each




6 RPM GEAR MOTOR

Molon # CHM-1205-5.

Powerful 12 Vdc, 6 RPM gearhead motor. Gearbox is 3" x 2.75" x 0.83". Drive motor and shaft are both on the same side of the gearbox. Shaft is 3.3" long. Top of shaft is 0.37" square. Base is 0.5" diameter. Motor draws 130 mA at 12 Vdc, no load. Motor protected by removable rubber cover.


CAT # DCM-164 \$ 12.00 each



GEARHEAD MOTOR AND TURNTABLE ASSEMBLY

Heavy-duty, precision turntable assembly originally designed for use in a satellite dish positioning device. Powered by a 12 Vdc motor, the final rotational speed is 5 RPM, with quite a bit of torque. For a description of the motor see our CAT # DCM-177 below. The overall size of the turntable assembly, excluding motor, is 5.6" dia. x 1.84" thick. The outer portion of the turntable is stationary while the inner 3.28" disc rotates. The rotating disc is 1.38" thick including the heavy gear to which it is attached and has a rubber outer ring which serves to weatherproof it. It is tapped with four mounting holes.

CAT # DCM-178 \$ 31.95 each



TWO-SPEED WORM GEAR MOTOR



Powerful windshield wiper motor for 2000-2001 Saturn L series automobiles.

Two speeds; high speed is 106 RPM at 12 Vdc, 4 Amps. Low speed is 41 RPM at 12 Vdc, 0.91 Amps. 3/8" threaded drive shaft with nut. A 2.25" lever with a universal joint, attached to the shaft, is easily removable. 7" overall length x 3.5" x 4".

25 RPM GEARHEAD MOTOR WITH BRAKE

Globe Motors # 409A582 Precision gearhead motor equipped with an electric brake and a tach or positioning sensor. Brake must be energized to allow motor to rotate. Use of the brake enables precision starting and stopping. Brake can be easily disconnected if not required. Motor rated at 12 Vdc, brake at 24 Vdc. No load rating: 25 RPM @ 12 Vdc @ 130 mA. Motor functions well up to 24 Vdc. Overall size, excluding shaft, 5.15" long x 1.52" dia. 0.25" diameter x 0.9" long shaft equipped with a press-fit gear. Threaded mounting holes on gearhead face.


CAT# DCM-177 \$15.00 each



ASSEMBLY WITH 12 VDC MOTOR, GEARS AND PULLEYS

New assembly for a motorized magnetic card strip reader. Driven by a Globe gear motor similar to DCM-151 with a speed of 130-140 RPM. A worm gear turns a pair of cog pulleys linked by a cog belt. The rubber covered wheels pull a credit card past a magnetic head and two U-shaped optical sensors. Assembly includes motor, pulleys, belt, magnetic head and opto sensors. Mounted on an aluminum platform 6.25" x 2.75".

CAT # DCM-180 \$ 15.95 each



REDUCED PRICE!

23.5 VDC GEARHEAD MOTOR


Buehler # 1.61.046.037.

No load rating: 16 RPM @ 23.5 Vdc @ 39 mA. Operates at 12 Vdc at slower speed.

Overall dimensions: 2.72" long x 1.4" diameter. 0.2" diameter x 0.83" long flattened shaft. 6" leads.

Used, removed from equipment in good condition.

CAT# DCM-191 \$13.50 each



24VDC, 50 RPM

Barber-Colman


#EYQF-63604-750

No load ratings: 50 RPM @

24 VDC @ 50 mA. Manufacturer specs:

41.7/ 38.8 RPM with 80.5 oz-in load. 0.185" dia. x 0.75" long flattened shaft. Overall dimensions: 1.36" diameter x 2.92" long (not incl. shaft). Three 4-40 threaded mounting holes in face of motor.

CAT # DCM-150 \$14.95 each



24 VDC, 140 RPM

Barber-Colman


#EYQF-63604-740.

No load rating: 140 RPM @

24 Vdc @ 50mA. Manufacturer specs with

21 oz-in load: 129.5/ 85. 0.185" dia. x 0.75" long flattened shaft. Overall dimensions: 1.36" dia. x 2.72" long (not incl. shaft). Three 4-40 threaded mounting holes in face of motor.

CAT # DCM-151 \$11.95 each




LINEAR ACTUATOR FOR AUTO DOOR LOCK

12 Vdc motor-drive actuator for automotive door locks. Nylon plunger moves 0.75". Push or pull, depending on polarity.

Includes mounting hardware and a 10" metal extension rod which fits through the hole in the end of the plunger. Overall dimensions of actuator assembly (retracted): 8.42" x 2.35" x 1.15". Rubber boot protects against moisture and dust. Pigtail leads.

CAT # DLA-1 \$5.50 each



AC MOTORS

115 VAC MOTOR

Small, relatively powerful

115 Vac Johnson motor.

1.5" dia. x 2.50" long, the motor has a 0.157" dia. shaft 0.57" long. 12,000 RPM (no load). Internal cooling fan. Solder terminals.

CAT# ACM-4 \$1.50 each



115 VAC FAN MOTOR W/ SPEED CONTROL

Lasko . 115 Vac 3-speed, shaded-pole fan motor.

Requires moving air for continuous duty.


Internal non-resettable thermal breaker. 3/8" dia. x 1" long

flattened shaft. Motor is 3.77" dia. x 2.3" with

an integral 5" diameter mounting base. 3.5 uF, 250 Vac capacitor mounted on base. 1750 RPM, no-load speed. Includes 4-position

rotary switch and 6' white 2-conductor power cord.

CAT# ACM-11 \$4.00 each




AC GEAR MOTORS

30 RPM, 120 VAC MOTOR

HTI # 111-0057. 120 Vac, 3 Watt timing-style motor. 1.95" diameter x 0.81" thick. 12" long wire leads. Mounting ears on two sides. 0.16" square shaft is 0.27" long. UL recognized.


CAT # ACM-105 \$2.50 each



40 RPM, 115 VAC MOTOR

Cramer Co # 105VA150-E. 40 RPM, 115 Vac gear motor. 1.83" diameter x 1.18" body. Mounting ears on 2.1" centers. 0.25" dia. x 1" long shaft. Prepped with a 1.25" long pin through the hole in the drive shaft. Pin is removable. 4" long pigtail leads. UL, CSA.

CAT # ACM-108 \$2.50 each




25 RPM 115 VAC GEAR MOTOR W/ BRAKE

Nidec 86BG4H4024G

Powerful 25 rpm thermally protected 115 vac reversible gear motor. Built-in brake for precision stopping. Can be disengaged by removing 5 springs. Requires 25-35 mfd capacitor. 5.33" long x 3.52" x 3.52" body not including shaft. 0.48" (12mm) dia. x 1.125" flattened shaft. Has three 4" wire leads.

CAT# ACM-114 \$37.50 each




230 VAC GEAR MOTOR WITH BRAKE

Nidec 86BG4P4022G

Similar to the above motor, but rated at 24 rpm 230 vac. Requires 6 mfd capacitor. 5.33" long x 3.52" x 3.52" body not including shaft.


CAT # ACM-115 \$37.50 ea.



120 VAC GEAR MOTOR

ECM # 5588. Powerful 50 RPM gearhead on a shaded pole, C-frame motor. Intermittent duty cycle. Ideal for short duration tasks. Thermal protection automatically shuts down motor after about 4 minutes. Left alone, it will automatically start up again when it cools (approx. 5 minutes). 5/16" diameter x 0.6" long flattened shaft. Gearbox is 3" x 2.75" x 0.54" and has threaded mounting holes in four corners. Overall depth of motor is 3" excluding shaft.


CAT# ACM-110 \$6.00 each



240 VAC GEAR MOTOR

ECM # 5589. 40 RPM gearhead on a shaded pole, C-frame motor. Same dimensions as motor above. 240 Vac, 50 Hz. Operates at 40 RPM on 120 Vac as well, without the thermal shutdown kicking in.

CAT# ACM-109 \$4.00 each




STEPPER MOTORS

AIRPAX STEPPER MOTOR

Airpax # C82711-M1. Unipolar, two phase stepper motor with 6 leads. 17 Vdc, 23.25 ohm coil. 7.5 degree per step. 2.25" dia. x 1" high. Two hole mounting flange, 2.75" centers. 0.25" dia. shaft is 0.6" long.


CAT # SMT-6 \$ 2.00 each



STEPPER MOTOR W/ PULLEY

Nidec # 44F5098005S. Unipolar, four phase stepper motor. 25 steps, 14.40 degrees/step. 1.95" dia. x 1.28 high". Attached to 0.22" long x 0.15" (4mm) diameter shaft is a 0.58" diameter aluminum pulley. Nine, two inch wire leads.


CAT# SMT-48 \$2.50 each



EPSON # SMM-6C

Unipolar, two-phase, 6 lead stepper motor. 0.98" dia. x 0.60" high body. 0.08" (2mm) dia. x 0.39" long shaft is fitted with 0.31" dia. gear with 12 teeth. 15 degree per step. Oval mounting flange has holes on 1.60" centers. 16" long leads.


CAT# SMT-42 \$1.50 each



EPSON # SMM-20

Unipolar, two-phase, 6 lead stepper motor. 0.98" dia. x 0.60" high body. 0.08" (2mm) dia. x 0.15" long shaft is fitted with 0.22" dia. gear with 8 teeth. 15 degree per step. Oval mounting flange has holes on 1.30" centers. 18" long leads.


CAT# SMT-43 \$1.50 each



1" DIA. STEPPER WITH GEAR

Bipolar, 4-lead stepper motor. 0.1" long shaft fitted with a 0.21" dia. 12 tooth gear. 1" dia. x 0.5" body. Oval mounting flange with holes on 1.25" centers.

CAT # SMT-55 \$ 1.50 each



2.25" DIAMETER STEPPER

2.25" diameter x 0.52" thick stepper motor. Mounting flange with slotted holes on 3.15" centers. 0.4" long x 0.12" diameter shaft with a plastic corkscrew-like attachment. Five 2" leads.


CAT # SMT-53 \$ 2.00 each



1" DIAMETER STEPPER WITH THREADED SHAFT

Unipolar, 6-lead stepper motor. Oval mounting flange with holes on 1.35" centers. 1" diameter x 0.5" 0.14" diameter x 0.6" long threaded shaft. Thread removed from top 0.25" of shaft. 3" leads.

CAT # SMT-54 \$ 1.50 each




STEPPER MOTOR, 400 STEP

Minebea "Astrosyn"

Type 17PY-Q202-03

Small precision bipolar stepper motor. 0.9 degrees/ step. 400 steps / revolution. 12.5 ohm coils. 1.66" x 1.66" x 0.92" body. 0.2" dia. x 0.4" long shaft. Four 2.25" leads w/ four pin socket connector, 0.1" spacing.


CAT # SMT-46 \$6.75 each



HEAD ASSEMBLY W/ STEPPER MOTOR ADJUSTER

1" diameter stepper motor rotates worm gear to raise and lower a magnetic head assembly, probably from an audio or data tape drive. The worm gear part of this device might be useful for other applications. The motor is a 6 wire, unipolar stepper. The travel of the worm gear is about 0.5". Mounted on a metal assembly 3.1" x 3.3".


CAT # EX-82 \$ 3.00 each



RELAYS

KH STYLE (ICE CUBE)

14 PIN (ICE CUBE) relays. All have clear or opaque plastic dust covers. Relay Size: 1.1" X 0.82" X 1.34" high



12 VDC, 4PDT

Omron # MY4 DC12. 12 Vdc, 160 ohm coil. 4PDT contacts rated 5 Amps @ 240 Vac/ 28 Vdc. Solder or socket mount terminals. UL, CSA.

CAT # 4PRLY-12 \$ 4.00 each
10 for \$ 37.50 • 100 for \$ 340.00

12 VDC, 4PDT (USED)

Omron # MY4 DC12. Same specs as 4PRLY-12 above. Removed from working equipment.

CAT # 4PRLY-12U \$ 2.50 each
10 for \$ 22.50 • 100 for \$ 200.00

24 VDC 4PDT

24 Vdc, 650 ohm coil. 4PDT, 3 amp contacts. Solder or socket mount

CAT# 4PRLY-24N \$4.00 each

24 VDC, 4PDT PC MOUNT

Guardian # 1315P-4C-24VDC. KHU style relay.

24 Vdc, 680 ohm coil. 4PDT, 5 Amp contacts.

PC leads. UL, CSA. **CAT# 4PRLY-24PC**

\$2.00 each • 10 for \$17.50

120 VAC, 4PDT

Kest # KR1205N. 120 Vac, 4500 ohm coil. 4P.D.T. contacts rated 5 A @ 240 Vac. Red LED indicator lights when coil is actuated. Solder/ socket mount terminals.

CAT # 4PRLY-120L \$4.00 each

AUTOMOTIVE / POWER RELAYS

SPDT 30 AMP

Orinco # JD191E-1510. 12 Vdc, 88 ohm coil. N.O. contacts rated 30A. N.C. contacts rated 20 amps. Plastic enclosed relay, 1.1" x 1.2" x 1" high. Plastic flange for bulkhead mounting. Mounts in standard automotive relay socket.

CAT # RLY-351 \$ 2.40 each • 10 for \$ 20.00




HALF-SIZE S.P.D.T. AUTOMOTIVE RELAY

Nais # JJM1-12V-H11

Miniature pc mount relay designed for automotive applications. S.P.D.T. contacts designed to switch 20 Amps on the N.O. side and 10 Amps on the N.C. side. Carry current, up to 33 Amps. 12 Vdc, 225 ohm coil. Plastic case sealed for immersion cleaning, 0.6" x 0.47" x 0.55" high.

CAT # RLY-410 \$1.50 each
10 for \$12.50 • 100 for \$90.00




SPDT 20 AMP, SPECIAL

Ford # F57B-14B192-AA

Small, plug-in automotive relay. S.P.D.T. contacts rated 20 Amps. 12 Vdc, 79 ohm coil.

0.89" x 0.59" x 1.05" case.


CAT # RLY-421 \$ 1.50 each



12 VDC 30 AMP S.P.S.T.


American Zettler # AZ971-1A-12DE Miniature 12 Vdc power relay designed for high in-rush, automotive applications.

12 Vdc, 90 ohm coil. S.P.S.T. contacts rated 30 Amps @ 30 Vdc. Vibration and shock resistant. Epoxy sealed polyester case. 1.03" x 0.83" x 0.82" high. PC pins. **CAT # RLY-396**
\$1.50 each • 10 for \$12.50 • 100 for \$90.00



SPECIAL LOW PRICE S.P.D.T 40 AMP RELAY

12 Vdc, 72 ohm coil. S.P.D.T. contacts rated for up to 40 Amps inrush current on the N.O. side. Standard 1.06" x 1.06" x 0.97" high polycarbonate case. 0.25" terminals fit standard automotive relay socket.



Disclaimer - For some unknown reason, the bottoms of these relays were sprayed red. To the best of our knowledge, there is nothing wrong with them. The terminals may require cleaning before use.


CAT# RLY-412 \$1.00 each • 100 for \$70.00

PC MOUNT POWER RELAYS (15 Amps or greater)

6 VDC MINI-POWER RELAY

Hasco # KLT1C12DC6. S.P.D.T. miniature power relay. 6Vdc, 100 ohm coil. Contacts rated 15 Amps, N.O. and 12 Amps, N.C. Sealed pc mount package, 0.75" x 0.6" x 0.62" high. UL, CSA.


CAT# RLY-415 \$1.50 ea. • 10 for \$1.25 ea.



12 VDC, SPDT

Potter & Brumfield# T90N5D12-12-07 12 Vdc, 100 ohm coil. SPDT contacts rated at 15 amps. 1.15" X 0.9" X 0.65". PC mounting. UL and CSA.


CAT# RLY-149 \$1.00 each • 10 for 80¢ each



12 VDC SPDT

ACC/AN Echlin # HR33A63S12 12 VDC, 379 ohm coil. S.P.D.T. contacts rated 15 Amps @ 120 VAC. 0.96" x 0.65" x 0.80" high. PC leads. UL, CSA.


CAT# RLY-163 \$1.50 each
10 for \$12.50 • 100 for \$100.00



12VDC 16A

American Zettler # AZ942-1CT-12DE. Miniature enclosed power relay. 12 Vdc, 416 Ohm coil. P.C. Pins. SPDT contacts rated 12 Amps @ 277 Vac, 16 Amps @ 250 Vac.

Sealed plastic case: 0.86" x 0.63" x 0.65" high. UL. **CAT# RLY-417** \$1.50 ea. • 10 for \$1.25 ea.



24 VDC, 70 AMPS

Potter & Brumfield # VF7-11H12-Z02 Small S.P.S.T., normally-open relay with 70 Amp contacts. 24 Vdc, 280 ohm coil. Black polycarbonate dustcover, 1.01" x 1.01" x 0.98" high. PC leads.


CAT # RLY-383 \$1.85 each • 10 for \$17.00



24 VDC, SPDT


Small, open-frame, pc mount power relay. Similar P&B T90 style relays. 480 ohm coil. Estimated contact current rating: 15 Amps.(min). 0.9" x 0.71" x 0.72" high. PC pins.

CAT # RLY-275 50¢ each • 10 for \$4.50
100 for \$40.00 • 1000 for \$300.00




24 VDC, SPDT

Potter & Brumfield # T90N5D12-24
24 Vdc, 675 ohm coil. SPDT contacts
rated 20 amps (N.O.), 10 amps (N.C.) @
240 Vac. 1.15" X 0.90" X 0.65". PC terminals.
UL and CSA. **CAT# RLY-55** \$1.25 each
10 for \$10.00 • 100 for \$85.00



110 VDC, SPST N.O. 30 AMP

Aromat # JT1A-DC110V. 110 VDC,
12,760 ohm coil. 30 Amp S.P.S.T. normally-
open contacts. 1.12" x 0.92" x 0.62" high.
PC mount. UL, CSA. **CAT # RLY-339**
50¢ each • 10 for 45¢ each • 100 for 40¢ each



**Molded Epoxy
reed relay
STYLE A**

Miniature mechanical and reed relays with pin configurations to fit standard DIP socket configurations (0.1" X 0.3" grid). Some are sealed for PC bath with vents that should be clipped after installation.

DIP RELAYS



**Plastic case
Mechanical Relay
STYLE B**

5 VDC D.P.D.T. DIP RELAY

NAIS # DS2Y-S-5VDC (STYLE B)
5 Vdc, 125 ohm coil. D.P.D.T. contacts rated 2 Amps
(switching), 3 Amps (carry). Small sealed case,
0.787" x 0.390" x 0.366." Fits 16 pin IC socket DIP
pattern. UL, CSA. **CAT# RLY-413** \$1.25 each
10 for \$1.00 each • 100 for 85¢ each

9VDC RELAY, DPDT

Hasco # HS212 DC9. (STYLE B) 9 Vdc,
540 ohm sensitive coil. D.P.D.T. bifurcated
contacts rated 2 Amps. Fully-sealed case,
0.78" x 0.38" x 0.41" high. Fits 16 pin DIP
configuration. UL, CSA. **CAT# RLY-419**
\$1.25 each • 100 for 85¢ each



12VDC DPDT DIP RELAY

Omron # G5V-2 12Vdc. (STYLE B)
12 Vdc, 288 ohm coil. D.P.D.T. bifurcated
contacts rated 0.50 Amps @ 125 Vac /
2 Amps @ 30 Vdc. Fully-sealed case, 0.78" x 0.38" x
0.45" h. Fits 16 pin DIP configuration. UL, CSA.
CAT# RLY-420 \$1.50 ea. • 100 for \$1.00 ea.



12 VDC, S.P.S.T. N.O. (STYLE A) Gordos#
846A-4. 12 vdc, 575 ohm coil. Internal clamping
diode (sealed). **CAT# DRLY-12** \$1.00 each

12 VDC, SPDT, SENSITIVE COIL

Fujitsu # FBR-211NC-D012-M (STYLE B)
Small SPDT relay. Contacts rated 2 Amps continuous
(8 Amp inrush). 12 Vdc, 700 ohm, 0.2W sensitive coil.
0.6" x 0.4" x 0.42" high. PC pins in DIP configuration.
Sealed for immersion cleaning. **CAT# RLY-375S**
\$1.50 ea. • 100 for \$100.00


24 VDC - S.P.D.T. (STYLE B)

Aromat # HB1-DC24V 24 vdc, 1600 ohm coil.
SPDT contacts rated 2 A 30 VDC/ 1 A 125 VAC.
0.787" X 0.433" X 0.642" high. **CAT # RLY-138**
75¢ each • 10 for \$ 6.00 • 100 for \$ 45.00

MISCELLANEOUS RELAYS

3-6 VDC REED RELAY

AT&T # WE 345B. S.P.S.T., normally-open
reed relay. 312 ohm coil. Operates on 3-6 Vdc.
Small, shielded metal-enclosed package, 1" x 0.29" x
0.25" high. PC leads. **CAT# RLY-395** 75¢ each
10 for \$6.50 • 100 for \$50.00




4.5 VDC SUB-MINIATURE RELAY

NEC# UA2-4.5NW. Tiny D.P.D.T. pc mount relay
with contacts rated 1 Amp @ 30 Vdc. 0.224" x
0.417" x 0.354" high. 4.5 Vdc, 145 ohm coil. Pick-up
voltage, 3.38 Vdc. UL, CSA. Large quantity available.
CAT# RLY-405 75¢ each • 10 for 65¢ each
100 for 50¢ each • 1000 for 35¢ each




5 VDC REED RELAY

Hasco # 713-5. S.P.S.T., N.O. reed relay
in an epoxy molded SIP package.
5 Vdc, 500 ohm coil. Contacts designed
to handle up to 600 Vdc. 0.5 Amps max. switching.
2.5 Amps max carry current.
1.12" x 0.3" x 0.42" high. UL, CSA.
CAT # RLY-414 75¢ each
10 for \$ 6.00 • 100 for \$ 45.00



5-6 VDC REED RELAY

Wabash #1149-15-4. S.P.S.T.
normally-open reed relay. 35 ohm coil.
1.13" x 0.39" x 0.34" high epoxy case.
CAT # RLY-406 75¢ each
10 for \$ 6.00 • 100 for \$ 45.00




5VDC SPST N.O. RELAY

Clare # DSS41A05. 5 Vdc,
450 ohm coil. S.P.S.T.,
normally-open. Contacts
rated 0.5A, switching current,
2A carry current. 0.75" x 0.20" x 0.30" high. UL.
CAT# RLY-418 75¢ each • 100 for 50¢ ea.




6 VDC, D.P.D.T. RELAY

Hasco # UJ2CPDC6. 6 Vdc, 40 ohm coil.
D.P.D.T., 10 Amp contacts. Clear
polycarbonate dustcover. 1.1" x 0.85" x
1.36." high. PC terminals. UL, CSA.
CAT # RLY-416 \$ 2.75 each




9 VDC S.P.S.T. N.O. RELAY

OEG # OJ-SS-109TM. 9 Vdc S.P.S.T.
normally open, 182 ohm coil. 3 amp
contacts. 0.39" x 0.71" x 0.57" high.
P.C. leads. UL. **CAT# RLY-409**
75¢ each • Tube of 25 pieces for 60¢ each
100 pieces for 50¢ each
1000 pieces for 40¢ each




9 VDC, S.P.D.T.

Potter & Brumfield # T70L5D-131-09
9 vdc, 225 ohm coil. PC mount, SPDT
contacts rated 3 amps. Case, 0.86" X
0.63" X 0.93" high. UL and CSA.
CAT# RLY-264 \$1.25 each • 10 for \$10.00



12 VDC, SPST N.O.

OEG # SDT-SS-112DM. 12 Vdc,
270 ohm coil. SPST, normally open
contacts. Rated 10A @ 250 Vac/24 Vdc.
Sealed case. Small footprint. 0.95" x 0.4" x
0.98" high. PC pins. UL, CSA.
CAT # RLY-340 \$ 1.25 each
10 for \$10.00 • 100 for \$85.00




12 VDC REED RELAY

E.-T. # R7218-3. S.P.S.T. normally-open
reed relay. 4650 ohm coil. 1.14" long x
0.34" diameter. In-line pc pins. UL, CSA.
CAT # RLY-407 75¢ each
10 for \$ 6.00 • 100 for \$ 45.00




S.P.D.T. 12 VOLT RELAY

American Zettler # AZ4-1CH-12DE
Small pc mount relay. S.P.D.T.,
5 Amp contacts. 400 ohm, 12 Vdc
coil. 0.85" x 0.63" x 0.72" high.
Sealed for immersion cleaning. UL, CSA.
CAT # RLY-370 \$1.50 ea. • 50 for \$ 60.00




24 VDC, S.P.N.O. RELAY

Takamisawa # VE24HM5K
24 Vdc, 1610 ohm coil. S.P.S.T.
N.O. contacts rated 5 Amps @
30 Vdc/ 250 Vac. 0.81" x 0.41" x
0.81" high. PC pins. UL, CSA.
CAT # RLY-411 50¢ each



12 VDC, S.P.D.T.

Hasco# BAS511DC12. Mini sealed
PC mount relay. 12 Vdc, 320 ohm coil.
S.P.D.T. contacts rated 5 Amps.
0.61" x 0.41" x 0.44" high. PC leads.
CAT # RLY-379 \$1.20 each • 100 for \$95.00




24 VDC S.P.D.T. 10 AMP

American Zettler # AZ 692H-1C-24D
24 Vdc, 1200 Ohm coil. S.P.D.T.
contacts rated 10 Amps. Sealed case.
1.13" x 0.5" x 0.98" high. PC board mount.
UL, CSA. **CAT # RLY-334**
50¢ each • 100 for \$ 35.00




24 VDC D.P.D.T. 10 AMP

Kest # KRLY-2024
24 Vdc, 625 ohm coil. D.P.D.T.
10 Amp contacts. KH "Ice cube" style,
clear polycarbonate case. 1.1" x
0.83" x 1.37" high. Solder or
0.187" qc or solder terminals.
CAT # RLY-2024 \$2.75 each




24 V.D.C. - SPDT

Fujitsu # FBR111NUD024-1
24 Vdc, 1,600 ohm coil. 3 amp @
120 Vac / 28 Vdc contacts. Small
sealed, immersion cleanable relay.
0.8" X 0.62" X 0.9" high. PC pins. UL listed.
CAT# RLY-91 \$1.00 each
10 for \$8.50 • 100 for \$65.00




24 VDC S.P.D.T. ALL PURPOSE RELAY

Guardian Electric # IR-645U-C-24D
Open frame 24 vdc 200 ohm coil
S.P.D.T relay. 10 amp contacts.
Solder lug terminals.
Mounting: 8-32 single screw.
1.80" x 1.07" x 1.65".
CAT# RLY-408 \$1.00 each




24 VDC, 10 AMPS

American Zettler # AZ971-1A-24DE
SPDT, 10 Amp contacts.
24 Vdc, 370 ohm coil.
1" x 0.81" x 0.83". PC pins.
CAT # RLY-327 \$1.75 each



24 VDC, 12 AMP SPDT RELAY


Song Chuan # 812H-1C-C-24DC
24 Vdc, 1645 ohm coil. SPDT contacts
rated 12 Amps @ 125 Vac, 7 Amps @
30 Vdc. Flux-tight case, 0.82" x 0.63" x
0.64" high. PC mount. UL, CSA.
CAT # RLY-381 \$1.35 each



24 VDC 10 AMP


SUBMINIATURE RELAY

Cornell Dubilier# CDR701AFEPL-703D
24 Vdc, 1600 ohm coil. SPST, N.O. contacts
rated 10 Amps @ 125 Vac. Small sealed case
with pc terminals. 0.74" x 0.6" x 0.6" high. UL
CAT # RLY-355 \$1.00 ea. • 100 for \$65.00




120 VAC DPDT RELAY

Magnecraft # W78ARPCX-5. 120 Vac,
4400 ohm coil. DPDT, 10 Amp contacts.
1.354" x 0.81" x 1.07" clear polycar-
bonate dust cover. PC leads. UL, CSA.
CAT # RLY-403 \$ 2.25 each
100 for \$ 1.75 each



120 VAC D.P.D.T. 10 AMP

Kest # KRLY-2120. 120 Vac, 5000 ohm
coil. D.P.D.T. 10 Amp contacts.
KH "Ice cube" style, clear polycarbon-
ate case. 1.1" x 0.83" x 1.37" high.
Solder or 0.187" qc or solder terminals.
CAT # RLY-2120 \$2.75 each




SOLID STATE RELAYS

**ALL SOLID STATE RELAYS
MUST BE TESTED UNDER LOAD**


10 AMP

Potter & Brumfield
SSRT-240D10
Input: 3-32 Vdc
Output: 10 Amps @ 120/240 VAC
UL, CSA. 2.25" x 1.75" x 0.88."
CAT # SSRLY-10 \$ 9.50 each




25 AMP (USED)

Crouzet/ Gordos # G280D25-49
Control Voltage: 3 – 8 Vdc
Load: 25 Amps, 24-280 Vac
2.25" x 1.75" x 1" metal-backed
epoxy package. Screw terminals.
Back-to-back (dual) SCR output for severe inductive
loads. False turn-on immunity and positive turn-off at
high dv/dt. Removed from equipment. "Like-new" con-
dition. Although input is marked 3-8 Vdc, will operate
at 12 Vdc. UL, CSA, CE. **CAT# SSRLY-2503U**
\$11.00 each • 10 for \$ 100.00



25 AMP


Potter & Brumfield
SSRT-240D25
Input: 3-32 Vdc
Output: 25 Amps @ 120/240 VAC
UL, CSA. 2.25" x 1.75" x 0.88."
CAT # SSRLY-25 \$ 17.50 each



LATCHING RELAYS


1.5 VDC Takamisawa# RA4L-D1.5W-K

1.5 vdc, 12.5 ohm dual coil latching relay.
4PDT configuration. Bifurcated contacts rated
1 amp (UL rating), 2 amps resistive. Sealed plastic
case, 1.387" x 0.390" x 0.360" high. PC pins.
UL and CSA. **CAT# LRLY-154** \$2.00 each



5 VDC, D.P.D.T. HIGH SENSITIVITY

Aromat # TQ2E-L-5V. 5 vdc, 250 ohm
single coil latching relay. 1 amp
contacts. Ultra-small size. 0.551" X
0.354" X 0.197" high. DIP pin config-
uration. Sealed for immersion. UL, CSA.




CAT# LRLY-56 \$1.75 each 100 for \$125.00

12 VDC, D.P.D.T. LATCHING

Communications Instruments, Inc.
MQP12L DPDT, 1 amp contacts.
12 vdc, 1400 ohm coil.
0.35" X 0.55" X 0.2" high.

CAT # LRLY-126 \$2.00 each



RELAY SOCKETS


KH RELAY SOCKETS

Fits all KH and KHU style, 14 pin relays except PC mount style (most relays starting with CAT# 4PRLY).

Solder lug terminals.


CAT# PRLY-S

75¢ each



PC pins for PC board mount.


CAT# PRLY-SC 75¢ each



Screw terminals for easy connections and changes. Can be surface mounted or snap-mounted to aluminum DIN rail. UL and CSA listed. 1.17" X 2.44" X 0.98".

CAT# MT14-PC


\$5.50 each • 10 for \$50.00



KUP RELAY SOCKET

Socket to fit KU and KUP style relays.

CAT# SRLY-11 \$1.00 each




8 PIN OCTAL SOCKET

Screw terminals for easy connections and changes. Can be surface mounted or used with aluminum DIN rail. UL listed.

CAT# OT08-PC


\$2.50 each • 10 for \$22.50



RELAY HOLD DOWN SPRING

For use with KH style relays, including our CAT #s beginning with 4PRLY or 2PRLY. Holds relay securely in socket.

CAT # RSP-1 3 for \$1.00



AUTO RELAY SOCKETS



Pre-wired sockets for use in automotive alarms, door-locks, starter-interrupt, light circuits and other auto applications. Both have color-coded 12" long leads. Will fit our relay, CAT# RLY-351.

RELAY SOCKET 5 wire socket with two 18 AWG leads and three 14 AWG leads.

CAT # SRLY-2 \$2.00 each • 10 for \$ 15.00

DUAL RELAY SOCKET Dual 5 wire sockets designed for door-lock applications.

CAT # SRLY-4 \$ 3.00 each • 10 for \$ 25.00

ALUMINUM DIN RAIL



For use with screw terminal sockets. An easy way to attach multiple relay sockets. Sockets snap-on and off of rail. DIN rails come in 1 meter (39") lengths with pre-drilled mounting holes every inch. Can be cut to shorter lengths.

CAT# C102P \$4.50 each • 10 for \$42.50

SOLENOIDS

10.5 VDC SOLENOID

PES Ltd. #

PES-TU1939



Tubular solenoid with

5/16" dia. plunger with turret tip and c-clip at end.

10.5 Vdc, 29 ohm coil. Intermittent duty cycle. 0.77"

dia. x 1.93" long body. Non-threaded mounting bushing could be mounted in a 0.45" wide slot in panel or bracket no more than 0.1" thick. 2.75" leads terminated with 2 pin socket connector.

CAT# SOL-57 \$1.25 each • 10 for \$1.00 ea.

SMALL 12 VDC SOLENOID

Shindengen # F92303P. 0.75" dia. x 0.65" body. Plunger has a 0.63" dia. disc at one end and C clip at opposite end.

Plunger travel is 0.07." 250 ohm coil.

12 Vdc continuous duty cycle.

4.5" pigtail leads. **CAT # SOL-70** \$1.50 each



12 VDC D-FRAME SOLENOID

Deltrol # D-70 Part # 50031-81

Powerful 12 Volt DC


solenoid for intermittent

duty cycle. 3 ohm coil. 48 Watts.

0.5" diameter slotted plunger. Body size:

2.625" x 1.828" x 1.562." 8-32 tapped mounting holes in two sides. Weight: 1 lb, 3 oz.

11" pigtail leads. **CAT # SOL-72** \$ 4.50 each



12 VDC POWER SOLENOID

White-Rodgers # 70-111225-5A

80 Amp, continuous duty power

solenoid. Type 70, single pole,

normally open. Case-grounded

type. 1.77" diameter X 2.5" long.

Applications include remote


control of power circuits on

vehicles and battery chargers. Dust-proof enclosure.

Termination 5/16"-24 UNF-2A thread.

Bracket for bulkhead mounting. UL.

CAT # SOL-71 \$ 7.50 each



12 VDC TUBULAR SOLENOID

Lucas (Ledex) # 174419-021

Powerful 12 Vdc solenoid

for intermittent duty cycle.

1.4 ohm coil. 1.25" dia. x

2.25" long body with

mounting plate. 0.5" diameter plunger.

CAT # SOL-74 \$ 4.20 each



24 VDC D-FRAME SOLENOID

KGS # 15H17.

24 Vdc, 47 ohm coil.


2.49" x 1.18" x 1.49"

open-frame solenoid with

0.59" diameter plunger.

Threaded mounting holes in one side of frame.

CAT # SOL-75 \$ 3.65 each



24 VDC TUBULAR SOLENOID

Lucas (Ledex) # 121E792

24 Vdc, 44 ohm coil.

1" diameter x 2" body.

0.75" diameter threaded

mounting bushing. 0.435" diameter

plunger. 21" leads.

CAT # SOL-76 \$ 4.15 each



24 VDC SOLENOID

Guardian# A420-066622-00 / 11-C-24Vdc

24 Vdc continuous duty solenoid.


124 ohm coil. 1.85" x 1.4" x

1.2" body. 0.31" diameter

slotted plunger with pin.

0.25" qc/ solder connectors.

CAT# SOL-73 \$ 2.50 each



24 VDC "CLAPPER" SOLENOID

Solen # 121E14620. 24 Vdc,

147 ohm coil. Top of "clapper"


moves 0.4" when coil is energized.

Solenoid box is 1" x 0.8" x

0.67" thick including mounting

bracket. 8" pigtail leads.

CAT # SOL-65 \$ 1.50 each



24 VDC SOLENOID WITH SPRING PLUNGER

Ledex 121K04970

1" long x 0.4" x 0.45" box

solenoid mounted on

a bracket. 24 Vdc,


390 ohm coil.

Continuous duty.

Spring-return plunger

travels 0.24" when energized. Pigtail leads.

CAT # SOL-68 \$ 1.75 each



24 VDC PULL-TYPE SOLENOID

Comm. Instruments Inc.

Powerful pull-type

solenoid with spring return.

Intermittent duty, max 10%.

3.3-4.2 ohm coil. Designed for


22-26 Vdc use, but it works fairly well on

12 Vdc. Pull force, 3.7 lbs @ 24 Vdc. Body is

0.77" diameter X 1.82" long. 3" long plunger.

3.4" mounting bracket attached to body.

CAT# SOL-58 \$ 1.50 each



PUSH-TYPE SOLENOID

Guardian # A420-067074-01

Small tubular, push-type

solenoid. 44 ohm coil.

Operates on 24 Vdc with

intermittent duty cycle

or on 12 Vdc, continuous duty cycle.

Plunger travel is 0.165". Pushes out when en-


ergized. Brass plunger has a tip, 0.25" in diameter.

Solenoid body is 0.63" diameter x 1.17" long.

0.32" diameter plain bushing extends 0.36" beyond

body. 9.5" pigtail leads.

CAT # SOL-52 \$2.00 each • 10 for \$17.50



MANUFACTURERS

We Purchase Excess Inventories.

CALL, WRITE, E-MAIL

or FAX your list.

BATTERIES

RECHARGEABLE NICKEL-CAD

SALE ON RECHARGEABLE NICKEL-CADMIUM BATTERIES

AAA CELL 1.2 Volt 220 mAh

CAT # NCB-AAA \$1.25 each

10 for \$ 11.00 • 100 for \$ 90.00



AA CELL 1.2 Volt, 650 mAh

CAT # NCB-AA \$1.25 each

10 for \$11.00 • 100 for \$90.00



C CELL 1.2 Volt 1800 mAh

CAT # NCB-C \$1.45 each

10 for \$12.00 • 100 for \$100.00



D CELL 1.2 Volt 1800 mAh

CAT # NCB-D \$1.55 each

10 for \$13.50 • 100 for \$115.00



NICKEL-CAD CELLS w/ Solder Tabs

1.2 Volt cells with solder tabs.

For building or re-building battery packs.

Type	CAT #	Dimensions
Capacity		1-9 10+
AA	NCB-SAA	0.56" x 1.90"
600 mAh		2.50 2.25
Sub-C	NCB-SC	0.90" x 1.69"
1300 mAh		4.00 3.50
2/3 Sub-C	NCB-23SC	0.90" x 1.03"
600 mAh		4.20 4.00
4/5 Sub-C	NCB-45SC	0.90" x 1.30"
1200 mAh		4.50 4.20

NICKEL-CADMIUM PACKS

2/3 AA CELL PACK FOR CORDLESS PHONES

Sanyo # 3N-270AA.

Popular rechargeable

nickel-cadmium battery packs for

cordless phones. Connector fits many phones

made by Cobra, Code-a-phone, General Electric,

GTE and Sanyo. Can be used with other phones if

you save the connector from the old battery pack

and splice it onto this one. 3.6 Volt, 270 mAh. Pack

size, 1.68" x 1.23" x 0.58".

CAT# NCB-23AA \$2.00 each

10 for \$17.50 each



8.4 VOLT 250 mAH PACK

Seven Sanyo AAA nickel

cadmium cells in a single row.

Shrink-wrapped in a sleeve

with internal thermal cutoff and

wire leads. This pack comes

apart easily if you want to

separate and use the batteries

individually or reconfigure into new packs.

Overall size: 2.82" x 1.76" x 0.43."

CAT# NCB-84 \$ 3.00 each (43¢ per cell)




7.2V NI-CAD BATTERY PACK

7.2 Volt, 110 mAh rechargeable nickel cadmium battery pack. Stack of six oval Varta V110R cells. Overall size: 1.56" x 1.04" x 0.6". Wire leads.

CAT# NCB-14 \$1.50 each

REDUCED
PRICE!



RECHARGEABLE NICKEL METAL HYDRIDE

Nickel Metal Hydride batteries have double the capacity of standard nickel cadmium cells and can be charged faster without the "memory problems" associated with nickel cadmium batteries.

AAA CELL

1.2 Volt, 550 mAh. 0.4" dia. X 1.74" long.

CAT# NMH-AAA \$2.50 ea. • 10 for \$21.00



AA CELL - 1200 mAh

CAT# NMH-AA

\$3.00 each • 10 for \$25.00



AA CELL, 1600 mAh HIGH CAPACITY

0.56" diameter x 1.97" long.

1.2 Volt, 1600 mAh. **CAT# NMH-160**

\$3.50 each • 10 for \$30.00

AA "FLAT-TOP" CELLS


Panasonic# HHR-110AAO. 1.2 Volt, 1100 mAh "flat-top" rechargeable AA cells for use in battery packs. 0.55" diameter X 1.95" long. Two styles:

REGULAR FLAT-TOP

CAT# NMH-110

\$1.50 each • 40 pcs \$1.25 each

120 pcs \$1.00 each • 800 pcs 85¢ each




SOLDER-TABBED

CAT# NMH-110T

\$1.75 each • 40 pcs \$1.50 each

120 pcs \$1.25 each • 800 pcs \$1.00 each



RECHARGEABLE BATTERY FOR 9 VOLT APPLICATIONS

Eveready # NH22. Nickel Metal Hydride rechargeable battery. Replaces 9 Volt batteries in many applications. Actual voltage 7.2 Volts. Can be charged in most Nickel-cadmium chargers.

CAT# NMH-9 \$3.50 each



7.2 VOLT STRIP PACKS

Miniature, rechargeable nickel-metal hydride button cell packs made for NEC. Consist of seven cells in a row, in series. Shrink-wrapped. Double-stick tape on one side. Mini-two-pin female connector (1mm spacing). Two sizes available:

7.2 Volt, 40 mAh 1.75" leads

2.65" x 0.47" x 0.23" **CAT # NMH-11** \$1.50 each

7.2 Volt, 70 mAh 2.75" leads


3.65" x 0.64" x 0.27" **CAT # NMH-10** \$2.00 each



4.8 VOLT 180 MAH STRIP PACK

Four rechargeable 1.2 Volt nickel-metal hydride coin cells in series. Shrink-wrapped. 10" leads w/ 2 pin connector. Pack size: 3.5" x 0.93."

CAT # NMH-12 \$2.00 each




NICKEL-METAL HYDRIDE

4.8 VOLT 850 MAH PACK

Phillips # 25733. New, rechargeable pack manufactured for cell phones. Contains four 1.2 Volt, 850 mAh cells. Each cell is 1.8" x 0.65" x 0.3". Relatively easy to remove cells and reconfigure them to suit your needs.

CAT# NMH-53 \$2.00 each • 10 for \$17.50



LITHIUM BATTERIES

Lithium batteries have a very long shelf life, typically ten years or more. Most of the cells in this section are designed for low current applications like memory back-up. They are not normally used as a primary power source. They are not rechargeable.

3 VOLT, 39 mAh

Rayovac # BR1225-T2. 0.5" diameter.

PC pins on 0.4" centers. **CAT # LBAT-15**

\$1.00 each • 10 for \$7.50 • 100 for \$60.00



3 VOLT, 39 mAh

Rayovac # BR1225-T3. Same as LBAT-15 above with three PC leads in a triangular pattern.

CAT # LBAT-30

75¢ each • 10 for \$6.50 • 100 for \$45.00



Special! 3 VOLT, 255 mAh

Panasonic # BR2330-1GU.

3 volt, 255 mAh coin cell with pc leads.

0.9" dia. x 0.12" thick. 0.7" spacing between positive and negative leads. 1996 date code.

CAT # LBAT-16 2 for \$1.00

100 for \$35.00 • 1000 for \$200.00



3 Volt 300 mAh

Rayovac BR2335L3L, coin cell with pc leads.

0.9" dia x 0.13" thick. 0.7" spacing between positive and negative leads. 1998 date code.

CAT# LBAT-34 2 for \$1.25 • 100 for \$40.00



3 VOLT, 75 mAh

Sony# CR2016. 0.787" dia. X 0.06" thick.

CAT# LBAT-21 75¢ each

10 for \$6.50 • 100 for \$45.00



3 VOLT, 180 mAh

Toshiba# CR2032. 3 volt, 180 mAh. 0.787" diameter.

CAT # LBAT-20 \$1.00 each • 10 for \$8.50



3 VOLT 280 mAh

Sony CR2430. 3 volt 280 ma. 0.96" diameter x 0.11" thick.


CAT# LBAT-32 \$1.25 each



3 VOLT 560 mAh

Daitron # CR2450. 3 Volt, 560 mAh. 0.96" diameter x 0.19" thick.

CAT # LBAT-33 \$1.75 each



3 VOLTS 165 mAh

Panasonic #BR-2325-1VC. 0.9" dia. x 0.1" thick. PC pins on 0.4" centers for vertical mounting. Insulated circumference.

CAT # LBAT-26 75¢ each • 10 for \$6.50



3 VOLT, 950 mAh

Renata # CR2477N. 0.96" diameter x 0.31" thick. PC pins on 0.74" centers.

CAT # LBAT-22 \$1.25 each • 10 for \$10.00



3 VOLT LITHIUM BATTERY CR123A

Tekcell CR123A. 3 Volt lithium cell. Special quantity purchase of recent date code cells. Commonly used in photographic equipment.



1.34" long x 0.65" diameter. **CAT# LBAT-123**
\$2.85 each • 10 for \$2.60 each
100 for \$2.35 each • 800 for \$1.90 each

AA SIZE w/ SOLDER TABS

Electrochem Industries# QTC85 / 3B940
3.6 Volt lithium cell with flat solder tabs on both ends. Can be easily made into packs. Standard AA size: 0.55" dia. x 1.97" long. Raised nipple on positive end. 96 date code.



CAT # LBAT-25 \$2.50 each • 10 for \$20.00

3 VOLT "LASER LITHIUM"


Sanyo # CR12600SE. 2.3" long x 0.45" diameter. 1997 date code.



CAT # LBAT-27 \$2.50 each • 10 for \$20.00

SEALED LEAD ACID BATTERIES

Maintenance-free, rechargeable sealed lead-acid batteries. Can be used in any position and can be trickle charged for long periods of time. Excellent for alarms, communications and back-up applications. WILL NOT LEAK.



6 VOLT, 1.2 AH BATTERY

3.8" x 0.93" x 2" high. **CAT# GC-612**
\$5.25 each • 20 for \$ 4.75 each

6 VOLT 4 AH 2.75" x 1.9" x 4" high.

CAT # GC-64 \$ 7.50 each

6 VOLT 10 AH 5.95" x 2" x 3.65" high.

CAT # GC-610 \$ 15.00 each

SPECIAL, 12 VOLT 1.3 AH

3.82" X 1.88" X 1.95" high.
CAT # GC-1213 \$ 8.00 each

SPECIAL 12 VOLT 2 AH

7" x 1.35" x 2.37" high.
Removed from new equipment.
CAT # GC-122 \$9.50 each

12 VOLT 5 AH

Panasonic #LC-R125P1.
3.5" x 2.7" x 4" high.
0.25" quick-connect/ solder terminals.
CAT# GC-125 \$15.00 ea. • 12 for \$ 12.50 ea.



12 Volt 7 AH 6" x 2.5" x 3.71" high.

CAT# GC-1270 \$22.00 each

12 Volt 17 AH 7.12" x 3" x 6.7" high.

CAT# GC-217 \$ 35.00 each

FAX YOUR ORDER 24 HOURS


A DAY 7 DAYS A WEEK.

(818) 781-2653

YOUR ORDER WILL SHIP THE NEXT BUSINESS DAY.

3.6 VOLT 1200 MA RECHARGEABLE LITHIUM-ION CELL

Sony # 18650. Rechargeable lithium-ion cell with solder-tabs. Ideal for high energy battery packs. 0.72" dia. x 2.56" long.



CAT # BTE-1200

\$3.50 each • 50 for \$3.00 each


ALKALINE BATTERIES

DURACELL®

PROCELL®

INDUSTRIAL

ALKALINE BATTERIES



AA CELL, 1.5 VOLT 2100 mAh

CAT # PRC-1500 65¢ each

AAA CELL, 1.5 VOLT 1000 mAh

CAT # PRC-2400 65¢ each

C CELL 1.5 VOLT 7000 mAh

CAT # PRC-1400 \$ 1.25 each

D CELL 1.5 VOLT 14000 mAh

CAT# PRC-1300 \$1.35 each

9 VOLT BATTERY 565 mAh

CAT # PRC-1604 \$ 2.25 each

AAA ALKALINE CELLS Fresh two-pack of

AAA "heavy-duty" alkaline cells. Made for Polaroid.

CAT # BT-25 50¢ per pack (2 cells)

100 packs (200 cells) 40¢ per pack

12 VOLT ALKALINE BATTERY

0.41" diameter x 1.13" long cylindrical cell used in keychain alarm remotes and photo applications.



CAT # BAT-12 \$1.25 each • 10 for \$ 10.00

SILVER OXIDE BUTTON CELL



386S (silver oxide) button cell. 0.45" dia. x 0.15" thick. For watches, calculators, cameras, games etc. **CAT # BAT-8** 75¢ each
10 for \$5.00 • 100 for \$45.00

ALKALINE BUTTON CELL




For laser pointers, games, clocks, cameras etc. 0.45" diameter X 0.21" thick button cell. Replaces all batteries designated AG-13, A-76, LR-44, V13GA and RW-82. **CAT# BAT-7** 75¢ each
10 for \$5.00 • 100 for \$45.00

COIN CELL HOLDERS

PC MOUNT HOLDER FOR BUTTON CELL

Fits CR-2430, 2450 and similar 0.96" diameter coin cells.
CAT # BH-17 50¢ each



SURFACE MOUNT HOLDER FOR BUTTON CELL

For CR1220 and other 12 mm coin cells. Surface mount solder tabs. Overall dimensions, 0.71" diameter x 0.18" high.



CAT # BH-15 4 for \$ 1.00


100 for \$ 20.00 • 1000 for \$100.00

BATTERY CHARGERS

NCD/NMH BATTERY CHARGER with 4 AA CELLS

Tysonic # TY-3969. Charges AA, AAA and 9 Volt nickel metal hydride (NiMH) and nickel cadmium (NiCd) batteries. Built-in charging control charges at optimum rate for safe charging and maximum battery life. Charges NiCd in 4 hours, NiMH in 7 hours. Reverse polarity protection. LED indicators show charging status. Includes 4 NiMH AA 1600 mAh batteries. Don't miss this opportunity to get batteries and a charger at a special low price. Our regular price for batteries, alone, is \$14.00.

CAT# BC-39 \$19.95 each




NCD/NMH BATTERY CHARGER

Similar to charger above, but doesn't include the batteries. **CAT # BC-5** \$12.50 each


GE CHARGER FOR NICKEL-CAD BATTERIES

General Electric charger for up to four AA, AAA, C or D, or one 9 Volt nickel-cadmium cell. Can be left on continuous charge without causing harm. 8.125" x 3.8" x 2.5" case. Can be wall mounted. LED charging indicators. UL, CSA. **CAT # BC-4** \$9.95 each



4.8 VOLT

Matsushita Electric# RE6040. Great for charging four nickel-cadmium or nickel-metal hydride batteries. Originally designed for charging power tool battery packs. Rated 4.8 Volts, 350 mA. Six foot cord with 2.5 mm co-ax plug. CSA. **CAT # DCTX-4848** \$2.00 each



BATTERY HOLDERS

1/2 AA CELL HOLDER

Keystone # 1103. Spring steel, nickel-plated holder for 1/2 AA cell. 1.23" x 0.62" x 0.65" high. Solder lugs.


CAT # BH-13 2 for \$1.00 • 100 for \$30.00



2 C CELL HOLDER

Aluminum holder for two in-line C cells. 4" long x 1" x 0.96". Solder lugs.

CAT # BH-18 75¢ each




2AA CELL BATTERY HOLDER w/ SNAP

Black nylon holder for two AA cells. Terminates with snaps that fit standard 9V battery snaps.

Simplifies removal and replacement of batteries. Fits our snaps, **CAT # BST-3**. 2.27" x 1.23" x 0.6"

CAT # BH-2S 2 for \$1.00


100 for 35¢ each • 1000 for 25¢ each



9V BATTERY HOLDER, PC MOUNT

MPD Inc., # BH-9VPC. Black plastic holder with snaps for standard 9 Volt battery. 2.15" x 1.18" x 0.82" high. PC pins on 0.5" centers.

CAT # BH-9VPC 50¢ each



9 VOLT BATTERY SNAP

Snaps onto standard 9 volt battery.

3" wire leads. **CAT# BST-3**


4 for \$1.00 • 100 for \$15.00



VIDEO CAMERAS, CABLES, CONNECTORS & ACCESSORIES

MINIATURE INFRARED CAMERA


Miniature PC board camera sees in total darkness as well as daylight and low light. Six on-board Infrared LEDs provide invisible "light" seen only by the camera. 3.6 mm fixed lens. Auto-iris. Operates on 8-12 Vdc. 1.74" x 1.55" x 0.97" thick. 18" leads with RCA jack for video output and 2.1 mm co-ax jack power output. Includes wall-mount power supply. **CAT# VC-3000** \$97.00 each



PINHOLE BOARD CAMERAS

BLACK & WHITE

1/3" CCD. 1.2" square x 0.65." 420 TV lines. 0.1 Lux. F2.0, 3.7mm flat pinhole lens. Includes cable with RCA connector video output, and 2.5mm coax connector (C+) for power. Requires 8-15 Vdc power supply. **CAT # VC-360** \$ 49.00 each



COLOR

1/3" DSP color CCD. 1.25" square pc board camera. 0.2 Lux. F2.0, 380 TV lines. Requires 8-15 Vdc power supply.


CAT # VC-320 \$ 125.00 each

COLOR VIDEO CAMERA with AUDIO

Here's one of the best deals we've seen on a "plug-and-play" color video camera with audio. The Corel

CC2000 camera was designed for video conferencing. Its unusual housing was designed to sit on top of a monitor facing the operator. The lens swivels about 30 degrees in any direction and has settings for normal or wide angle viewing. The camera also has a threaded fitting for mounting on a tripod or camera bracket. Beige housing with a built-in lens cover that can slide closed when not in use. Overall dimensions 7" x 3.6" x 3.25." 6' cord with adaptor has RCA plug outputs for video and audio and a coax jack for DC power. Includes 9Vdc 1.5 Amp power supply. Works with any NTSC monitor or video recorder.

CAT# VC-127 \$49.00 each




INFRARED SENSOR B&W CAMERA

This is a great buy on an inexpensive black and white miniature infrared camera, that is ready to go. 1/3" (8mm) B/W CCD. 320 lines of resolution. 0.1 Lux.

Comes complete with a miniature metal enclosure, that measures approximately 2 1/2" X 1 3/4" X 1 1/4" deep including the lens. Includes a mounting bracket. Six infrared LED's mounted in the enclosure, three on each side of the lens, allow the camera to see in low light as well as total darkness. Camera and LED's operate on 12 Vdc between 100ma and 300 ma. 9" leads with RCA jack for video output and 2.1 mm jack for power. Power supply not included. We recommend our CAT# DCTX-122 (\$3.00 each) as a power source.

CAT # VC-303 \$37.50 each




PINHOLE CAMERA IN MINIATURE ENCLOSURE

BLACK & WHITE

1/3" B/W CCD. Miniature metal enclosure is 1.18" square x 0.72". 420 TV lines. 0.05 Lux. F2.0 lens. Operates on 9-12 Vdc. Includes cable with connectors, mounting bracket & power supply.

CAT # VC-40 \$69.00 each




ADJUSTABLE CAMERA MOUNT

Compact metal camera-mount bracket. Ball joint allows vertical or horizontal orientation. Fits all standard camera threaded mounting holes. 1.75" dia. base with three recessed screw holes. Overall height including screw mount, 2.25". Flat black.

CAT # CMB-1 \$4.25 each



VIDEO CAMERA EXTENSION CABLES



Allows placement of video camera up to 50 feet from its power source and video monitor/recorder. Power cable has 2.1mm coax male on one end, female on the other end. Audio and video cables have RCA plugs on both ends. Suitable for all of the cameras on page 40-41.

VIDEO AND POWER CABLE - dual cable


CAT # CB-29 \$10.50 each

AUDIO, VIDEO AND POWER CABLE - triple cable

CAT # CB-27 \$18.95 each

5.5" BLACK AND WHITE MONITOR


Black & white 5.5" monitor, ideal for surveillance, rear-view camera in RVs and campers or recording monitor. NTSC format. Plug-and-play for most video cameras. RCA jacks for input and output. Brightness, Contrast and Vertical hold adjustments. Sloped black case, 8.5" x 5.5" x 5.5" high. Operates on 120 Vac or use with 12 Vdc 800 mA wall adapter (2.1mm, center positive), or auto cigarette lighter cord. Wall adapter or cigarette lighter cord not included. **CAT# MTR-5** \$40.00 each



GREAT PRICE!

VIDEO / RF MODULATOR

Converts audio and video line level signals to RF which can be inputted to any television on channel 3 or 4. Allows you to use your television as a video monitor for use with a video camera, computer or other video device. Output via 1 foot cord with male F connector. Also has an antenna-in female F connector, so that TV can remain connected while modulator is in use. Channel 3-4 selector switch. Video, audio and power inputs are through a 7 foot cable terminated with a mini-DIN plug which generally needs to be cut off so connections can be made directly to conductors in cable. We supply a hook-up diagram. Requires a 4.5 - 6 Vdc, 50 mA power supply or wall adapter (not included). Large quantity available. **CAT# MOD-6** \$5.00 each • 10 for \$4.50 each




ZENITH VIDEO/RF MODULATOR

Zenith # ZEV210.

Use your television as a video monitor for use with video camera or other video device. Converts audio and video line level signals to RF which can be inputted to any television on channel 3 or 4.

Features an on-off switch allowing you to switch between video input and antenna input. RCA jacks for audio and video inputs. F connectors for RF output and antenna input. Originally designed for use with a Zenith video camera system. Has an output jack to power that device. Input power: 15 Vdc @ 150 mA. Requires a DC wall transformer for power (our CAT# DCTX-1252 works fine). Includes a 3' F to F cable and a 6" cable with DC plugs each end.

CAT# MOD-210 \$15.00 each




VIDEO CASSETTES

"HI 8" VIDEO CASSETTE (Used)

SONY T-120 "HI-8" (120 minute) video cassettes. Top-of-the-line, metal particle cassettes, used for a short time, then bulk erased.

Includes plastic storage box. **CAT# VCU-8**

\$3.00 ea. • 10 for \$28.00 • 100 for \$250.00




S-VHS VIDEO TAPES

(USED)

Save a bundle on name-brand S-VHS, T-120 tapes. These tapes were used for a brief period, then bulk erased. The record-protect tabs have been broken out, so you will have to cover the notch with a piece of tape, but they work great.

CAT# S-VHS \$3.00 each

10 for \$28.00 • 100 for \$250.00




DIGITAL VIDEO TAPE

Panasonic DVM60. Miniature digital video cassette. 60 Minutes.

CAT # DVM-60


\$7.50 each • 3 for \$21.00



VIDEO ACCESSORIES


VIDEO BLACK BOX with VARACTOR TUNER

"Black Box," video converter/ processor. Inside is a pc board with a varactor tuner, circuit board with assorted components. Back panel has four video F connectors and a power jack. Led in front panel. Overall dimensions: 8" x 7.5" x 1.5" **CAT # EX-60** \$2.50 ea.




VIDEO A/B SWITCH

Jebsee # SW-78S. Compact, shielded two position co-ax slide switch. Standard F connectors for 75 ohm input and outputs. Good quality assembly with solid switching action. **CAT# ABS-4** \$3.50 each



LOW PROFILE OUTDOOR TV ANTENNA RCA ANT4100X

Breakthrough in digital technology for receiving local UHF and VHF channels. Low profile, omnidirectional antenna. Replaces unsightly rooftop antenna. Can be hidden in the attic, under the eaves or mounted on the roof. Weatherproof. Ideal for marine use. 14.75" x 14.75" x 2.25." Paintable ABS plastic cabinet. 75 ohm input. Effective for up to 30 mile radius in flat area. **CAT # ANT-100** \$18.95 each



VIDEO/AUDIO DUBBING CABLES

Used to connect two VCR's together, or as a line to line connection between two Video devices. RCA style plugs each end.

6 FOOT VIDEO CABLE



CAT# VMC-6

\$1.00 each • 10 for 80¢ ea. • 100 for 60¢ ea.




**6 FOOT MONO
1 video, 1 audio**

CAT# AVM-6 \$2.50 each • 10 for \$20.00

STEREO VIDEO CABLES

75 ohm video 6' cable with two audio cables for stereo dubbing. Gold tipped RCA plugs. Suitable for DSS.



CAT # AVS-61 \$ 3.75 each

S-VHS PATCH CABLES



Miniature 4 pin mini DIN plugs both ends.

6 foot cable CAT# CB-376


\$2.50 ea. • 10 for \$2.30 ea. • 100 for \$1.90 ea.

12 foot cable CAT# CB-365

\$3.50 each • 10 for \$32.50

OPTICAL CABLE WITH TOSLINK CONNECTORS

High quality fiber optic cable with toslink-to-toslink connectors. Provides a precision audio link between DVD, CD players, Mini Disc Recorders and A/V Receivers. Heavy-duty metal shell protects optical connector. A fraction of regular price.



3 Foot Cable **CAT# OCB-3** \$8.50 each

6 Foot Cable **CAT# OCB-6** \$12.50 each

VIDEO HOOK-UP CABLE




SCREW-ON CONNECTORS

Video cables with screw-on F style connectors both ends.

FEET	CAT#	each	10	100
3'	VHU-3	1.00	0.85	0.70
6'	VHU-6	1.25	1.00	0.85
12'	VHU-12	2.00	1.50	1.10
25'	VHU-25	3.00	2.50	2.00

VIDEO PATCH CABLES with PUSH-ON "F" CONNECTORS




	CAT#	each	100	1000
5' BLACK	VHP-5	60¢	30¢	25¢
6' WHITE	VHP-6	60¢	34¢	28¢
12' WHITE	VHP-12	\$1.00	55¢	40¢


F CONNECTORS AND ADAPTERS

	CAT#	price	100
F-59 connector w/ separate crimp ring for RG-59 cable	F-59	5 for \$1.00	\$15.00
F-59 with attached crimp ring for RG-59 cable	F-59R	4 for \$1.00	\$20.00
Twist-on F-59 for RG-59 cable	FTO-59R	4 for \$1.00	\$20.00
F-56 connector with heavy-duty attached ring. For RG-6U cable.	F-56R	4 for \$1.00	\$20.00
Twist-on F-56 for RG-6 cable	FTO-56R	4 for \$1.00	\$15.00
Push-on F-59. Makes threaded F connector into a quick connect	POF-SW	2 for \$1.00	\$40.00
75 ohm terminator	FTER	3 for \$1.00	\$25.00
F-61. Chassis mount female	F-61	3 for \$1.00	\$25.00
Splicer, female. Connects two male connectors	F-81	4 for \$1.00	\$20.00
Splicer, male. Connects two female connectors	F-71	2 for \$1.50	\$55.00


75 OHM CABLE SPLITTERS



2 WAY SPLITTER
5-900 MHZ
CAT# TWS-2 \$1.00 each



3 WAY SPLITTER
5-900 MHZ
CAT# TWS-3 \$1.50 each



4 WAY SPLITTER
5-900 MHZ
CAT# FWS-4 \$2.00 each

BALUNS



PUSH ON MATCHING TRANSFORMER
Quick connect style 75 to 300 ohm.
CAT# POBL 4 for \$1.00 100 for \$20.00



INDOOR MATCHING TRANSFORMER
75/300 ohm mini matching transformer.
CAT# IMT-1 50¢ each • 100 for \$35.00

REMOTES FOR CDs and VCRs



JVC # RM-RK20	VCR	CAT # IR-7	2.00
TEAC # RC-505	CD Changer	CAT # IR-5	2.00
PIONEER #CU-PD063	CD Changer	CAT # IR-8	2.00
PIONEER # CU-PD105	CD Changer	CAT # IR-9	2.00
AMC # RC-CD9	CD Player	CAT # IR-10	2.00

TUBING

20 GAUGE TEFLON TUBING

20 Natural Thin-wall TFE.
200 deg. C. 300 Volt VW1 SW. UL, CSA.
CAT # TFE-20 25¢ per foot
4 foot minimum
500 foot roll \$ 75.00 (15¢ per ft)

IRRADIATED PVC TUBING


Alpha F105 black irradiated PVC tubing.
VW-1 105 deg. C.
3/32" Diameter **CAT# PVC-332** 10¢ per ft.
10 foot minimum 100 feet \$ 8.00
3/16" Diameter **CAT # PVC-316** 15¢ per ft.
10 foot minimum 100 feet \$ 11.00

FEED THROUGH BUSHINGS

Seal wall openings and protect cables.


Fits one RG-6 cable. 0.30" I.D.
CAT# FTH-1 5 for \$1.00

Fits one RG-59 cable.
0.26" I.D. **CAT# FTH-3**
10 for \$1.00 • 100 for \$8.00



18 GAUGE STRANDED, UNINSULATED WIRE


Woods #893. 500' roll of
18 gauge stranded,
uninsulated copper wire
for grounding applications.
CAT# WR-18SU
\$12.00 per roll



HEAT SHRINKABLE TUBING & ACCESSORIES

UNGAR HEAT GUN

Dual temperature heat gun provides flameless heat for applying heat shrink tubing, curing epoxy, loosening adhesives, heating liquids, thawing frozen pipes, stripping paint and many other applications. Rugged design and high and low temperature settings make this gun ideal for use in repair shop or home. Accessory attachments are available for special applications. U.L. listed.



CAT# UHG-1095 \$52.50 each

ATTACHMENTS

Reducer for concentration of heat.

CAT# UHG-1080 \$6.00 each

Reflector for heat shrink tubing.

CAT# UHG-1082 \$6.00 each



HEAT SHRINKABLE TUBING

Polyolefin heat shrinkable tubing shrinks to 50% of its original diameter when heated. It forms a tight mechanical bond even over irregularly shaped materials.

Available in 4 foot sticks or 100 foot rolls.
Size listed is expanded (pre-shrunk) diameter.

4 FOOT PIECE

Dia.	Color	CAT#	Per 4'
3/64"	BLACK	HUG-364B	\$1.15
	RED	HUG-364R	\$1.15
	WHITE	HUG-364W	\$1.15
1/16"	BLACK	HUG-116B	\$1.20
	RED	HUG-116R	\$1.20
	WHITE	HUG-116W	\$1.20
3/32"	BLACK	HUG-332B	\$1.25
	RED	HUG-332R	\$1.25
	WHITE	HUG-332W	\$1.25
1/8"	BLACK	HUG-18B	\$1.35
	RED	HUG-18R	\$1.35
	WHITE	HUG-18W	\$1.35
3/16"	BLACK	HUG-316B	\$1.60
	RED	HUG-316R	\$1.60
	WHITE	HUG-316W	\$1.60
1/4"	BLACK	HUG-14B	\$1.90
	RED	HUG-14R	\$1.90
	WHITE	HUG-14W	\$1.90
3/8"	BLACK	HUG-38B	\$2.15
	RED	HUG-38R	\$2.15
	WHITE	HUG-38W	\$2.15
1/2"	BLACK	HUG-12B	\$2.40
	RED	HUG-12R	\$2.40
	WHITE	HUG-12W	\$2.40
3/4"	BLACK	HUG-34B	\$3.15
1"	BLACK	HUG-1B	\$4.50
1 1/2"	BLACK	HUG-112B	\$5.00
2"	BLACK	HUG-2B	\$4.00


100 FOOT ROLL

dia	color	CAT#	100' roll
1/16"	Black	HSS-116B	\$21.00
3/32"	Black	HSS-332B	\$23.00
1/8"	Black	HSS-18B	\$25.00
3/16"	Black	HSS-316B	\$28.00
1/4"	Black	HSS-14B	\$33.00
3/8"	Black	HSS-38B	\$38.00
1/2"	Black	HSS-12B	\$45.00

WIRE - CABLE - CO-AX

SHIELDED MULTI-CONDUCTOR JACKETED CABLES 100% FOIL SHIELD WITH DRAIN

For data communication, computer hook ups, audio and instrumentation. Stranded color coded conductors. Gray vinyl jacket.



CAT#	COND.	GAUGE	O.D.	10'	50'	100'	500'	1000'
2C/S22	2	22	.170"	1.70	8.00	15.00	65.00	120.00
3C/S22	3	22	.180"	2.00	9.00	16.00	70.00	130.00
5C/S22	5	22	.200"	2.25	10.50	18.00	85.00	160.00
9C/S28	9	28	.22"	1.50	6.00	10.00	42.50	70.00
10C/S22	10	22	.264"	4.00	18.50	34.00	160.00	315.00

MICROPHONE CABLE

2 CONDUCTOR SHIELDED

22 ga. stranded conductor. Braided copper shield. Flexible black PVC outer jacket. 0.23" nominal O.D.

CAT# MC-2 10 feet \$4.50
100 feet \$32.00 • 300 feet \$90.00

TELEPHONE/STATION WIRE

ROUND STATION WIRE

AWG 24, solid wire.



COND.	CAT #	50'	100'	500'	1000'
4	4C/24	\$4.00	\$6.00	\$25.00	\$45.00
6	6C/24	\$5.00	\$9.00	\$40.00	\$70.00

FLAT TELEPHONE WIRE

AWG 28, stranded wire. For use with crimp-on RJ11, RJ12 and RJ45 modular connectors. Color-coded.

COND.	CAT #	50'	100'	1000'
4	4C/F	\$4.00	\$7.50	\$45.00
6	6C/F	\$6.00	\$8.50	\$65.00
8	8C/F	\$8.00	\$11.00	\$95.00

SPECIAL - 4 CONDUCTOR FLAT PHONE CABLE - BLACK

AWG 24 stranded wire. For use with crimp-on RJ11 modular connectors. Sold on 2,000 foot rolls only.

CAT# 4C/FB 2,000 foot roll \$70.00 per roll

CATEGORY 5E CABLE

4 unshielded twisted pairs (UTP). AWG 24 solid conductors. 350 mHz. Western Electric Standard color coding. UL, CSA listed.

CAT # CT-5E 50' for \$7.00 100' - \$12.00
1000' Speedout box \$74.00



STRANDED HOOK-UP WIRE

Available in black (BK), red (RD), white (WH), green (GR), blue (BL), and yellow (YL).

Not necessarily solid colors. May have colored stripe.

You may want to specify a second color choice in case all colors aren't in stock.



Catalog number specifies gauge, length and color.

For example CAT# 22-100BK = 22 gauge, 100', black.

Gauge	CAT#	100'	CAT#	1000'
26	26-100	\$ 3.00	26-1000	\$ 20.00
24	24-100	\$ 3.25	24-1000	\$ 21.75
22	22-100	\$ 3.75	22-1000	\$ 25.00
20	20-100	\$ 4.00	20-1000	\$ 26.75
18	18-100	\$ 4.25	18-1000	\$ 28.00
16	16-100	\$ 5.50	16-1000	\$ 40.00
14	14-100	\$ 7.50	14-1000	\$ 55.00

CO-AXIAL CABLE

RG-6U DOUBLE SHIELD

BLACK. 18 ga solid center. 100% foil shield and 60% aluminum braid. 75 ohm impedance.

CAT# RG-6U 50 ft. \$9.00
100 ft. \$16.00 • 500 ft. \$70.00
1000 ft. \$130.00



RG-58/U COPPER SHIELD

BLACK. 20 ga. solid center, 80% copper braid shield, 50 ohm impedance.

CAT# RG-58U 50 ft. \$7.00 • 100 ft. \$12.00
500 ft. \$55.00 • 1000 ft. \$100.00

RG-59/U COPPER SHIELD

BLACK. 22 ga. solid center, 80% copper braid shield, foam insulator. 75 ohm imp.

CAT# RG-59C 50 ft. \$7.00 • 100 ft. \$12.00
500 ft. \$55.00 • 1000 ft. \$100.00

RG-174 MINI CO-AX


BLACK. 50 ohm impedance. 26 ga. stranded center. Braided copper shield. **CAT# RG-174**

10 ft. \$2.00 • 50 ft. \$8.00 • 100 ft. \$15.00
500 ft. \$70.00 • 1000 ft. \$110.00

COAX CABLE STRIPPER

Rotary coax cable stripper for RG58, RG59, RG62, RG6.

CAT # WS-60
\$ 12.50 each



EXTRA-FLEXIBLE GROUND AND POWER CABLE

AWG 4 cable. High-quality, finely-stranded, extra-flexible cable for ground, power or audio applications. 1050 (7 x 150) tinned copper strands. **Black** PVC insulation. 0.27" nominal O.D.

CAT # AWG-4B \$ 1.25 per foot
10' for \$10.00 100' for \$ 75.00

8 GAUGE POWER CABLE

133 strand cable. Minimum order, 5 feet.
BLACK CAT # WR-8B 5 feet \$2.25
50 feet - 40¢ per foot 100 feet 35¢ per foot

GROUND STRAP

3.75" GROUND STRAP

Braided copper ground strap. 0.5" wide X 0.03" thick. 0.22" dia holes at each end on 3.5" centers.

CAT# GS-11 4 for \$1.00



RED/BLACK POWER CABLE




Automotive grade "GPT" zip cord with red and black conductors. 80 degree C, flame-retardant PVC insulation. 10 foot minimum order.

	CAT#	10 ft.	500 ft.
18 ga.	WRB-18	15¢ per ft.	10¢ per ft.
16 ga.	WRB-16	19¢ per ft.	15¢ per ft.
14 ga.	WRB-14	25¢ per ft.	22¢ per ft.
12 ga.	WRB-12	32¢ per ft.	29¢ per ft.
10 ga.	WRB-10	45¢ per ft.	41¢ per ft.
8 ga.	WRB-8	87¢ per ft.	77¢ per ft.

SPEAKER WIRE / ZIP CORD

Two stranded, parallel conductors. Can be separated or "zipped" at ends for hook-up. Marked for polarity. Used for home, auto speaker installation or any low voltage application.



2 CONDUCTOR 24 GAUGE CLEAR

50 feet	\$2.50	CAT# 2/24C-50
100 feet	\$4.00	CAT# 2/24C-100
500 feet	\$15.00	CAT# 2/24C-500
1000 feet	\$28.00	CAT# 2/24C-1000

2 CONDUCTOR 18 GAUGE CLEAR

50 feet	\$4.50	CAT# 2/18C-50
100 feet	\$8.00	CAT# 2/18C-100
1000 feet	\$45.00	CAT# 2/18C-1000

2 CONDUCTOR 16 GAUGE CLEAR

50 feet	\$9.00	CAT# 2/16C-50
100 feet	\$17.00	CAT# 2/16C-100
500 feet	\$62.00	CAT# 2/16C-500
1000 feet	\$100.00	CAT# 2/16C-1000

2 CONDUCTOR 14 GAUGE CLEAR


50 feet	\$11.00	CAT# 2/14C-50
500 feet	\$91.00	CAT# 2/14C-500
1000 feet	\$150.00	CAT# 2/14C-1000

2 CONDUCTOR 12 GAUGE CLEAR

50 feet	\$18.50	CAT# 2/12C-50
100 feet	\$35.00	CAT# 2/12C-100
500 feet	\$130.00	CAT# 2/12C-500

SPEAKER WIRE SPECIAL

1000' 18 awg clear speaker wire.



CAT # 2/18C-1000 \$ 45.00 for 1000' roll

TINNED COPPER TUBULAR BRAID

Multi-stranded woven copper for high current grounding and shielding applications.



0.185" DIAMETER when rounded. 0.30" x 0.05" when flattened. Approximate current carrying capacity, 30-40 Amps. **CAT # GS-12**
3 feet for \$ 1.00 • 100 feet for \$ 25.00

Belden #8668

Tinned copper-braid cable for shielding and grounding applications.

30 Amps, recommended current capacity.
Nom. O.D. 0.156" Nom. flattened width: 0.22" Nominal I.D. 0.17" 120 x #34 stranding.

CAT # GS-16 \$1.00 for 3' (3' minimum)
100' for 25¢ per foot • 1000' for 15¢ per foot



RIBBON CABLE



28 AWG stranded. Gray cable with a red marker stripe. .050 (1.27) center spacing. Designed to mate with all standard industry flat cable connectors.

COND.	CAT#	10 FEET	100 FEET
10	RCBL-10	\$2.00	\$12.00
16	RCBL-16	\$3.50	\$20.00
20	RCBL-20	\$4.00	\$23.00
26	RCBL-26	\$5.50	\$40.00
34	RCBL-34	\$6.50	\$50.00
36	RCBL-36	\$6.50	\$50.00
40	RCBL-40	\$8.00	\$60.00

NEW

COIL CORDS



TWO CONDUCTOR COIL CORD

Black 18 AWG, SPT-1, two conductor coil cord. 28" retracted. 6 feet extended. **CAT# CC-2**
65¢ each • 10 for \$5.50 • 100 for \$45.00

EIGHT CONDUCTOR COIL CORD

28" black coil cord extends approximately 6 feet. One end is cut-off near the coil. The other end has a 12" uncoiled run that terminates to a molded 9 pin male D-sub connector. 0.23" diameter. Eight, AWG 22 stranded, color-coded wires. No shield. **CAT # CC-81** \$ 1.75 each

INSULATED STAPLES

Heavy duty plastic staples. Unbreakable, no rusting. Will not shatter in cold temperatures.

White Oval staple for 0.125" X 0.200" Ideal for securing telephone, speaker, and other flat cables.

CAT# CSI-1 25 pieces \$1.25
100 for \$3.50 • 1000 for \$24.00



White Round staple for cable. 1/4" dia. Secure RG-59 / 62 co-ax cables.

CAT# CSI-2 25 pieces \$1.25
100 for \$3.50 • 1000 for \$24.00



Black Round staple for 0.30" dia. cable. Fits RG-6/U co-ax cable.

CAT# CSI-3 25 pieces \$1.25
100 for \$3.50 • 1000 for \$24.00




Special! White Staple for 0.30" dia. cable

Round staple for RG-6/U co-ax cable or other round cables up to 0.30" dia.

CAT# CSI-3W 25 for \$1.00
100 for \$2.50 • 1000 for \$15.00



2 CONDUCTOR SHIELDED CABLE



Flexible black PVC jacket, 0.124" O.D..


Two AWG 24 stranded conductors, red and white insulation. Stranded copper shield. **CAT# 2C/S24**
10 feet for \$ 1.20 • 100 feet \$ 10.00
200 meter roll (approx. 650 feet) \$ 40.00



PHONE ACCESSORIES

SURFACE MOUNT MODULAR WALL JACK

For new construction or retrofitting.



4 Conductor, RJ-11 jack Includes mounting screws and double-sided tape.

CAT # MT-103 65¢ each
12 for 50¢ each • 96 pcs for 40¢ each


6 Conductor, RJ-11 jack

CAT# MT-203 \$ 1.00 each
12 for 85¢ each • 100 for 65¢ each

FLUSH MOUNT MODULAR WALL PLATE

Flush wall mount fits standard outlet box.
4 PIN MODULAR JACK

CAT# MT-107 \$1.10 each
10 for \$9.00 • 100 for \$70.00



DUAL FLUSH MOUNT MODULAR WALL PLATE

Two modular jacks on a flush mount plate which fits a standard outlet box.


WHITE 4 PIN MODULAR JACKS

CAT# MT-109W \$1.25 each
10 for \$1.00 ea. • 100 for 75¢ ea.

IVORY 4 PIN MODULAR JACKS

CAT# MT-109 \$1.25 each
10 for \$1.00 each • 100 for 75¢ each


SPECIAL PRICE!



FLUSH MOUNT ROUND MODULAR WALL PLATE

Modular jack on easy to install round plate.


CAT# MT-RWP \$1.30 each
10 for \$11.00 • 100 for \$90.00



T-ADAPTER FOR MODULAR JACK

For connection of two phones or one phone and one answering machine to one jack.


CAT# MT-101 \$1.10 each
10 for \$9.00 • 100 for \$70.00



2 LINE SPLITTER

Splits 2-line jacks into Line 1, Line 2 and Line 1 & 2.


CAT # MT-105 \$1.50 each



TELEPHONE EXTENSION CORD

Male modular plug on one end, female on the other.
4 conductor - 25 feet.

CAT# MT-EX \$2.40 each
10 for \$20.00 100 for \$160.00



MODULAR CORD COUPLER

Couples two items with modular plugs together. **CAT# MT-104**
75¢ each • 10 for \$6.50

100 for \$25.00 • 1000 for \$150.00




EURO PHONE ADAPTERS

PHONE ADAPTER: FRANCE - USA

Allows you to connect a RJ-11 modular cord to a French phone outlet.


CAT # PA-1 \$1.50 each



PHONE ADAPTER: UK - USA

Allows you to connect a RJ-11 modular cord to a United Kingdom phone outlet.


CAT # PA-3 \$1.50 each



PHONE ADAPTER: GERMANY - USA

Allows you to connect a RJ-11 modular cord to a German phone outlet.

CAT # PA-2 \$1.50 each



MODULAR LINE CORDS AND PLUGS

Cross wired for telephone-voice applications

4 WIRE - MOD PLUGS BOTH ENDS (RJ-11)

DESCRIPTION	CAT#	1-9	10+	100+
7 Feet	MT-260	.50	.45	.40
15 Feet	MT-264	1.00	.85	.75
25 Feet	MT-261	1.50	1.25	1.00




SPECIAL!

30 foot, 4 conductor modular phone cord. Straight wired for modem and data use. Also can be used for phones.

CAT# MT-268 \$1.25 ea. • 10 for \$1.00 ea.
100 for 75¢ each • 1000 for 60¢ each

4 PIN MODULAR PLUG TO SPADE LUGS

7 feet CAT# MT-250
\$1.00 each • 10 for \$9.00
100 for \$60.00



CRIMP STYLE MODULAR PLUGS

Crimp on modular plugs. Make or repair your own phone cords. Fits standard flat phone wire listed on page 44.
Use crimp tool below to connect.



SPECIAL - 2 PIN (Center Pins) CRIMP-ON MODULAR PLUGS

CAT# CMP-2 10 for \$1.50
50 for \$7.00 100 for \$12.00 1000 for \$80.00

4 PIN CRIMP-ON MODULAR PLUGS

Not for handsets. **CAT# CMP-4**
10 for \$2.50 • 50 for \$10.00 • 100 for \$18.00

6 PIN CRIMP-ON MODULAR PLUGS

CAT# CMP-6 10 for \$3.00
50 for \$12.50 • 100 for \$20.00

8 PIN CRIMP-ON MODULAR PLUGS


CAT# CMP-8 10 for \$3.50
50 for \$15.00 • 100 for \$22.50

ECONOMY PUNCH-DOWN TOOL



An inexpensive tool for seating AWG 24 solid phone wire into punch-down terminal blocks.

CAT # HT-318 \$ 2.00 each



MODULAR PLUG CRIMP TOOL

Strips flat phone wire
and crimps modular plugs.


For 4 or 6 pin modular plug.
CAT# MPCPT-6 \$14.00 each

For 8 pin modular plug.
CAT# MPCPT-8 \$15.00 each

RJ-11 MODULAR PHONE JACKS


0.48" X 0.48" X 0.83" high including
locator tab on top. 2 plastic support
pins on 0.63" centers.

4 CONDUCTOR **CAT# MT-4J**
50¢ each • 10 for \$4.50




4 PIN Hirose # TM5RA-64 Ivory 4 pin
modular jack. Large quantity available.

CAT # MT-4WT 2 for \$ 1.00
100 for \$ 35.00 • 1000 for \$ 250.00



Gray RJ-11 jack with 3" color-coded leads.
Fits 0.5" wide slot in telephone or chassis.

CAT # MT-61 2 for \$ 1.00
100 for 35¢ ea. • 1000 for 20¢ ea.



FILTERED MODULAR JACK

Corcom # RJ11B-4L-B"SIGNAL SENTRY"TM

4 pin, RJ-11 modular jack with built-in
ferrite block for inductive filtering.

Fits the same space as non-shielded
jacks. 0.52" x 0.8" x 0.59" high.

UL, CSA listed. Large quantity available.


CAT # MT-4F 2 for \$1.00
100 for \$30.00 • 1000 for \$100.00




4 CONDUCTOR HANDSET JACKS

Mate with smaller modular plugs like those
found on handset cords.

0.81" x 0.44" x 0.59" high
CAT # MT-4H 2 for \$ 1.00
10 for \$ 4.50 • 100 for \$ 40.00



0.48" x 0.48" x 0.83" high
CAT # MT-7 2 for \$ 1.00
10 for \$ 4.50 • 100 for \$ 40.00




PHONE LINE PRIVACY PROTECTOR

Prevents eavesdropping of phone
conversations. Protects modem, fax and
voice transmissions from interruption.

The first device to answer or access
a line secures the line. All of the
others are denied access until the
first device hangs-up. Easy to use. Installs in sec-
onds between phone line and wall jack. **Note:** You
need one unit for each instrument sharing a line.


CAT# TLM-20 2 for \$1.50 • 10 for \$6.50
100 for \$45.00



A/B PHONE SWITCH

Manual A/B switch for
telephone or data use.
Accepts six-conductor
RJ-11 phone plugs.


CAT# FNS-2
\$5.50 each



DSL / PHONE FILTER

Excelsus Technologies, Inc. # Z-200SM
Z-Blocker® filter effectively
filters single-line phone
devices (standard or
cordless phones, fax
machines, answering
machines, etc.) Isolates DSL and home phone line
networking signals from voice signal for peak data
performance. Ideal for blocking RF interference
from cordless phones for uninterrupted video/audio
streaming. Easy installation. UL, CSA listed.
Complies with FCC part 68 regulations.


CAT# FTR-200 \$ 4.25 each



PHONE PICK-UP


Universal telephone pick-up
cup. This device has a suction
cup which attaches to the
earpiece side of a telephone
handset and will pick up both sides of the phone
conversation. Terminates to a 3.5 mm plug.

CAT# TPX-1 \$1.50 each



FOUR NUMBER PHONE DIALER


AT&T # 1800 A3A. AT&T automatic
phone dialer has four large
color-coded, numbered buttons
that make it easy to select the
desired number. Simple
to connect and program,
this dialer is ideal for
children, the elderly, baby-
sitters, or sight-impaired for
emergency services, or any
frequently used phone number. Standard 12 but-
ton keypad can also be used with rotary-style
phones. The touch-tone keypad, alone is well
worth the price. 4.22" X 4.22" X 1.7" beige case.
CAT# FND-1 \$6.00 ea. • Case of 36 - \$4.00 ea.



EXTRA TOUCH-TONE PHONE

Sturdily constructed telephone
that can be used as an
extension phone in your
garage, studio or office.
Designed to hang up
when placed face
down on any flat
surface. However, the
pushbutton that is supposed to disconnect the call
may require a small extension tab glued to it in
order to hang up the call properly. May have been
a promotional item, as it has a logo printed on its
back. Beige plastic housing with large white push-
buttons and black numerals. Other features
include: redial button, low/high volume switch,
lighted keypad and 12" coil cord that extends to 5'.
Plugs into standard wall jack.

CAT# PHN-24 \$2.00 each





















PHONE HANDSET COIL CORD










9' ivory telephone handset coil cord.
21" when contracted. Small modular 4 pin handset
plugs each end. **CAT # MCT-5** \$ 1.50 each

Co-Ax Connectors and Cables









BNC CONNECTORS

CAT#	#1-9	10-99	100+
	TWIST-ON UG-260 (Fits RG-59 or RG-62 cables)		
UG-260TW	1.00	.85	.70
	CRIMP MALE 3 piece style (fits RG-59/62 cable)		
BNC-59	.85	.70	.55
	CRIMP MALE 3 piece style (RG-58 cable)		
BNC-58	.85	.70	.55
	TWIST ON UG-88 (RG-58 cable)		
UG-88TW	1.00	.85	.70
	CHASSIS MNT FEMALE (SOLDER CUP)		
BNC-1094	1.00	.85	.70
	PC MOUNT FEMALE Four stabilizing/ ground pins on 0.25" centers. NEW		
BNC-9	.75	.65	.50
	BULKHEAD MOUNT All metal body and threaded mounting bushing.		
BNC-8	1.25	1.10	.85
	BULKHEAD MOUNT RIGHT ANGLE All metal body and threaded mounting bushing.		
BNC-8R	1.25	1.10	.85
	PC or CHASSIS Mount BNC FEMALE Plastic body with 2 pins on 0.5" (diagonal) centers. Plastic threaded bushing (no hardware). NEW		
BNC-10	1.25	1.10	.85
	UG-914 MALE COUPLER Female both ends		
UG-914	.90	.75	.60
	BNC COUPLER thru chassis Female both ends		
UG-492	2.10	1.75	1.40
	UG-491A/U FEMALE COUPLER Males both ends		
BNC-BNC	1.80	1.50	1.20
	UG-306 RIGHT ANGLE ADAPTOR		
UG-306	2.40	2.00	1.60
	UG-274 BNC SPLITTER		
BNC-T	1.50	1.25	1.00
	BNC-T ADAPTOR (3 female fittings)		
BNC-T2	2.10	1.75	1.40
	IN-LINE BNC FEMALE Amphenol# 31- 3321 MS39012/17-010 (RG-122/RG-180)		
BNC-1	1.00	.85	.70
	50 OHM BNC TERMINATOR		
BNC-50	1.20	1.00	.80
	75 OHM BNC TERMINATOR		
BNC-75	1.20	1.00	.80

UHF CONNECTORS

CAT#	1-9	10-99	100+
	PL-259 PLUG		
PL-259	1.00	.90	.80
	REDUCER FOR RG-58 CABLE (Fits PL-259)		
UG-175	.30	.25	.20
	REDUCER FOR RG-59 CABLE (Fits PL-259)		
UG-176	.30	.25	.20
	CRIMP STYLE PL-259 (Fits RG-59/ RG-62)		
PL-259C	1.00	.90	.80
	RT ANGLE PL259 PLUG (Fits RG-59/RG-62)		
PL-259RT	1.00	.90	.80
	MALE COUPLER PL-258 UHF-UHF		
UHF-UHF	1.00	.80	.65
	SO-239 CHASSIS MOUNT		
SO-239	1.00	.90	.80

ADAPTORS


CAT#	1-9	10-99	100+
	F FEMALE to RCA MALE		
F-RCA	.75	.65	.50
	F FEMALE to BNC MALE		
F-BNC	1.30	1.10	.90
	RCA FEMALE to F MALE		
RCA-F	1.00	.80	.60
	RCA FEMALE to BNC MALE		
RCA-BNC	.80	.70	.55
	UHF FEMALE to BNC MALE		
UHF-BNC	1.80	1.50	1.20
	BNC FEMALE to F MALE		
BNC-F	1.50	1.25	1.00
	BNC FEMALE to RCA MALE		
BNC-RCA	1.00	.80	.60
	BNC FEMALE to UHF MALE		
BNC-UHF	2.00	1.75	1.40

IDC SOCKET CONNECTORS

Mates with double row posts on .100" centers.
Press mount on standard flat ribbon cable.

DESCRIPTION	CAT#	1-9	10+
10 pin (2 X 5)	RCSC-10	.55	.35
14 pin (2 X 7)	RCSC-14	.60	.50
16 pin (2 X 8)	RCSC-16	.65	.45
20 pin (2 X 10)	RCSC-20	.65	.45
26 pin (2 X 13)	RCSC-26	.75	.55
34 pin (2 X 17)	RCSC-34	.65	.45


NEW



D-SUBMINIATURE CONNECTORS

I.D.C. D-SUB CONNECTOR

Insulation Displacement Connector
Press fit on flat ribbon cable.



DESCRIPTION	CAT#	1-9	10-99	100+
9 pin PLUG	IDC-9P	\$1.39	\$1.19	.95
9 pin SOCKET	IDC-9S	\$1.45	\$1.25	.99


DB-25S w/ THREADED STANDOFFS

DB-25S, female connector with
built-in 1/8" long threaded
standoffs. Solder-cup terminals.



CAT # DB-25SC 75¢ each

10-99 for 55¢ each • 100+ for 40¢ each



SOLDER STYLE D-SUB CONNECTORS

SOCKET (female)

DESCRIPTION	CAT#	1-9	10-99	100+
9 pin PLUG	DB-9P	.45	.35	.27
9 pin SOCKET	DB-9S	.49	.39	.29
Hood for DB-9	DB-9H	.39	.29	.22
Right Angle METAL Hood for DB-9	DB-9HRM	1.00	.85	.65
15 pin PLUG	DB-15P	.59	.45	.35
15 pin SOCKET	DB-15S	.69	.49	.38
Hood for DB-15	DB-15H	.39	.29	.22
25 pin PLUG	DB-25P	.69	.50	.35
25 pin SOCKET	DB-25S	.75	.55	.40
Hood for DB-25	DB-25H	.39	.29	.25
Hood for DB-50	DB-50H	.75	.65	.55


PLUG (male)

Right angle PC mount D-sub-miniature socket connector

DB-25SRT 75¢ each

10 for 65¢ each

100 for 55¢ each




MULTI-CONNECTION CONNECTORS



Male / female ends connected with 10" wires

# of Cond.	CAT#	1-9	10-99	100
2	CON-20	1.20	1.00	.80
3	CON-30	1.75	1.50	1.20
4	CON-40	1.90	1.60	1.30
6	CON-60	2.25	1.85	1.50
9	CON-90	3.00	2.75	2.20

2 CONDUCTOR, RC BATTERY CONNECTORS



plug

socket

15 Amp, two-conductor locking nylon connectors. Industry standard for remote control cars. 5.5" silicon-rubber-insulated leads (18 AWG) are very flexible and heat-resistant.

PLUG **CAT# CON-210P** 75¢ each

10 for 70¢ each • 100 for 60¢ each

SOCKET **CAT# CON-210S** 75¢ each

10 for 70¢ each • 100 for 60¢ each

PRE-WIRED CONNECTORS WITH MATING HEADERS

Nylon connectors and mating pc mount, snap-lock headers.

Pins on 0.156" centers.

Female socket connector is pre-wired with 11" long color-coded 18 AWG stranded wire.

CAT# CON-232	2 PIN	75¢ per set
CAT# CON-234	4 PIN	\$ 1.50 per set
CAT# CON-236	6 PIN	\$ 2.25 per set
CAT# CON-238	8 PIN	\$ 3.00 per set




3 INCH JUMPER w/ MATING HEADERS

8 conductor jumper with matching pc mount, snap-lock headers on both ends. 0.1" pin spacing. Color-coded leads.

CAT # CON-88


\$1.75 per set



.1" SNAPPABLE HEADERS

.025" square header pins on 0.1" centers

DOUBLE ROW



DESCRIPTION	CAT#	1-9	10-99	100+
2 X 13 right angle	DHR-13	20¢	15¢	10¢
2 X 16 right angle	DHR-16	30¢	25¢	20¢
2 X 7 straight	DHS-14	20¢	15¢	10¢
2 X 32 right angle	DHR-32	60¢	50¢	40¢
2 X 40 straight	DHS-40	\$1.25	\$1.00	85¢
2 X 40 right angle	DHR-40	\$2.00	\$1.80	\$1.50

HEADER WITH 3 SHORTING JUMPERS

12 pin (2 X 6 pins) double row snappable header prepped with three shorting jumpers, like CAT # SJ-1 below. **CAT # SJ-3** 4 for \$1.00



SINGLE ROW



DESCRIPTION	CAT#	1-9	10-99	100+
40 pin straight	SHS-40	.50	.40	.30

8 pin right angle single row header

CAT# SHR-8 25¢ each

10 for 20¢ each • 100 for 15¢ each



12 PIN EXTRA HIGH HEADER

This snappable header has two insulators in the center. Header leads extend 0.125" above the insulators on top and bottom. **CAT# SHS-12** 40¢ each

10 for \$3.50 • 100 for \$30.00



SHORTING JUMPERS FOR HEADERS

Designed for use with above double and single row headers. Used to short out adjoining posts on headers.

CAT#	1-9	10-99	100+
SJ-1	.10	.08	.07



NON-SNAPPABLE SOCKETS, 0.1" SPACING


SPECIAL - 16 PIN SOCKET

ST0016TBB Non-snappable, 16 pin sip socket. Standard 0.1" spacing.

Dual-wipe contacts.

CAT # SIP-16 10 for \$1.25

100 for \$8.00 • 1000 for \$50.00




20 PIN

0.20" high. Non-snappable.

Pins on 0.1" centers.

CAT# SIP-207 2 for \$1.00



SNAPPABLE SIP SOCKETS

11 MACHINED PINS

0.1" centers.

CAT# SIP-11 4 for \$1.00



30 PIN. 0.1" centers.

CAT# SIP-30 \$1.00 each



2 PIN POLARIZED CONNECTOR

Mating two-pin, polarized connector. Female connector has threaded bushing which mounts in 0.58" diameter hole. Solder lug terminals.

CAT # CON-220


75¢ per set (1Male, 1 Female)



METERS

PM89 SERIES PANEL METERS

3.15" x 2.5" x 2" depth.
2.5% accuracy. Large clear
scale, black lettering on white
background. Available in a variety of ranges.



DC MICROAMMETERS

	CAT #	EACH	10+
0 - 100 uA DC	PMD-100UA	\$12.00	\$10.00

DC MILLIAMMETERS

	CAT #	EACH	10+
0 - 1 mA	PMD-1MA	\$12.00	\$10.00
0 - 25 mA	PMD-25MA	\$12.00	\$10.00
0 - 50 mA	PMD-50MA	\$12.00	\$10.00
0 - 100 mA	PMD-100MA	\$12.00	\$10.00

DC AMMETERS

	CAT #	EACH	10+
0 - 1 A	PMD-1A	\$12.00	\$10.00
0 - 5 A	PMD-5A	\$12.00	\$10.00
0 - 15 A	PMD-15A	\$12.00	\$10.00
0 - 30 A*	PMD-30A	\$12.00	\$10.00

*SHUNT REQUIRED FOR 30A DC AMMETER

Shunt	FL-30A	\$7.50	\$7.00
-------	--------	--------	--------

DC VOLTMETERS

0 - 10 V	PMD-10V	\$12.00	\$10.00
0 - 15 V	PMD-15V	\$12.00	\$10.00
0 - 30 V	PMD-30V	\$12.00	\$10.00
0 - 50 V	PMD-50V	\$12.00	\$10.00
0 - 100 V	PMD-100V	\$12.00	\$10.00

AC AMMETERS

0 - 5A	PMA-5A	\$12.00	\$10.00
0 - 15A	PMA-15A	\$12.00	\$10.00


AC VOLTMETERS

0 - 150V	PMA-150V	\$12.00	\$10.00
0 - 300V	PMA-300V	\$12.00	\$10.00


AC VOLT METER

Small 0-200 Vac meter for monitoring
AC line voltage. Scale is partitioned
into three sections with 0-90V in black,
95-120V in green and above 120V in
red. White face, black lettering, red
indicator line. Clear plastic housing is 1.56" square x
0.87" deep. Display portion of meter is 1.41" x 0.82".

CAT # MET-53 \$1.75 each



BNC CABLES




50 OHM, RG-58 MALE-MALE

length	cat#	each	10	100
3 foot	CBL-27	\$2.50	2.00	1.75
6 foot	CBL-28	\$3.25	2.75	2.25
15 foot	CBL-29	\$4.25	3.75	3.25

Special!

25 foot	CBL-25	\$3.50	3.00	2.50
---------	--------	--------	------	------

75 OHM, RG-59 MALE-MALE




length	cat#	each	10	100
6 foot	CBL-30	\$3.25	2.75	2.25
25 foot	CBL-35	\$5.50	5.00	4.25

DIGITAL PANEL METERS

FEATURES:

- *200.0 mV full scale sensitivity
- *Single 9-12 Vdc operation
- *Decimal point selectable
- *Automatic polarity indication
- *High input impedance (>100 M ohm)
- *Zero reading for 0 volts input 2.66" x 1.71"



Display size 1.77" x 0.8".

Black plastic case and removable bezel.

Except for PM-102B, digital panel meters must have
an isolated power source.

3 1/2 DIGIT LCD DISPLAY

0.5" figure height. Operates on 9-12 Vdc.

CAT # PM-128 \$ 11.95 each

3 1/2 DIGIT LED DISPLAY

SELF-MONITORING Common ground enables
meter to monitor its own voltage source. Operates
on 5 Vdc. 0.56" figure height. To measure voltages
above 200 mV, use add-on board, below.

CAT # PM-102B \$ 14.95 each

Add-on Board for PM-102B Small PC
board with precision divider resistors simplifies volt-
age & decimal point settings on PM-102B. Allows
measurement of voltages to 1000 V. Instructions
included. CAT # AB-102 \$ 6.50 each

LOW COST 3 1/2 DIGIT LCD DISPLAY


Snap mounts into 2.1" X 1.5" chassis cutout.
2.65" X 1.59". **No bezel.** 1.84" x 0.78" display.
0.5" figure height. Operates on 9-12 Vdc.

CAT # PM-200 \$ 7.00 each

Category 5 Patch Cables

Modular data patch cables.

RJ45, 8 conductor,
100MHz, UL.




	CAT#	Ea	10	100
7' Gray	CB-57G	3.90	3.40	2.90
7' Black	CB-57BK	3.90	3.40	2.90

COMPUTER CABLES

USB CABLE

5' USB, Universal Serial
Bus, A-B, cable. For all
standard USB peripherals.


CAT # CB-383 \$3.50 each • 10 for \$25.00




USB CABLE

2' USB, Universal Serial Bus,
A-A, cable.

CAT # CB-384 \$2.00 each



PARALLEL PRINTER CABLES



DB25 TO 36 PIN MALE - 6 FT.

CAT# PCB-1 \$3.95 each • 10 for \$32.50

DB25P TO DB25P - 6 FT.






CAT# PCB-3 \$4.50 each • 10 for \$40.00

DB25P TO DB25S - 6 FT. EXT. CABLE




CAT# PCB-5 \$4.95 each • 10 for \$45.00

AUDIO / POWER / SIGNAL PLUGS & JACKS

RCA PLUGS


	CAT#	1-9	10-99	100+
	RED PLASTIC HANDLE PPRP-R	.30	.25	.20
	BLACK PLASTIC HANDLE PPRP-B	.30	.25	.20
	SHIELDED, METAL MPRP	.50	.45	.35
	CRIMP STYLE RCA FOR RG-59 RCA-59	.50	.45	.35
	Uninsulated, metal RCA RPP-3	.20	.15	.10

RCA JACKS

	SINGLE HOLE CHASSIS MT. (threads from back) RCMJ	.40	.35	.25
	IN-LINE RED PLASTIC PIRP-R	.30	.25	.20
	IN-LINE BLACK PLASTIC PIRP-B	.30	.25	.20
	IN-LINE METAL MIRJ	.45	.40	.30

NEW

RIGHT ANGLE PC MOUNT


	white insulator RCJ-5W	5/\$1.00	.15	.08
	green insulator RCJ-5G	5/\$1.00	.15	.08
	yellow insulator RCJ-5Y	5/\$1.00	.15	.08
	red insulator RCJ-5R	5/\$1.00	.15	.08

FOUR GOLD-PLATED RCA JACKS on 0.5" centers. Each pair has 3 pins, with a common pin for the outer connection of the pair. PC pins for upright mounting. 1.05" x 1.07" x 0.5" thick excluding jacks.
CAT# RCJ-41 2 assemblies for \$1.00

2.5mm PLUG





	MONO, PLASTIC PMMP	.40	.35	.30
---	-----------------------	-----	-----	-----

2.5mm JACK


	MONO W/ SWITCH SMJW-2	.12	.10	.08
---	--------------------------	-----	-----	-----

Thin solder terminals could be pc mounted. No hardware available.

3.5mm PLUGS







	MONO, PLASTIC PMP	.40	.35	.25
	MONO, METAL MMP	.45	.40	.30
	STEREO, PLASTIC SMP	.50	.40	.33
	STEREO, METAL SMPM	.65	.60	.55

3.5mm JACKS

	MONO w. N.C. SWITCH Enclosed jack with 3.5mm threaded bushing. Solder terminals. Large quantity available. MJW-7	.45	.40	.30
---	---	-----	-----	-----




500 for 25¢ each • 1000 for 19¢ each

3.5mm JACKS (cont.)


NEW 	CAT# MONO JACK MJW-8	1-9 .35	10-99 .30	100+ .20
	MONO JACK w/ n.c. switch MJW	.50	.45	.40
	MONO JACK w/ N.C. SWITCH 5.5" wire leads to tip and ring. ESJW-P	.35	.30	.20
	STEREO w/ N.O. SWITCH 6mm threaded bushing. PC pins. MJW-3	.25	.20	.12
		1000 for \$90.00		
	STEREO Jack w/ n.c. switch 6 mm threaded bushing SJW-2	.35	.30	.20
	MONO PLASTIC, IN-LINE MJI	.45	.35	.25
	STEREO PLASTIC, IN-LINE SJI	.60	.50	.40

1/4" JACKS





MONO, W/ N.C. SWITCH

	PHJ-S	.60	.50	.40
	Enclosed, Plastic bushing PHJ-3	.75	.70	.60
	Enclosed, Metal bushing PHJ-1	.75	.70	.60


MONO, INLINE

	Shielded metal jack with plastic outer cover and strain relief. MQJ	.75	.70	.60
--	--	-----	-----	-----


STEREO, W/ N.C. SWITCH















	SPHJ-S	.75	.70	.60
	Enclosed, plastic bushing SPHJ-1	.75	.70	.60
	2 Pole, PC or Panel Mount. N.C. switch. SPJ-12	.55	.50	.40
	3 Pole, PC or Panel Mount. N.C. switch. SPJ-13	.55	.50	.40




















STEREO, UNSWITCHED

	Enclosed SPHJ-2	1.00	.85	.65
---	--------------------	------	-----	-----

1/4" PLUGS


	MONO, PLASTIC SPH	.50	.40	.35
	MONO, METAL MPHM	.85	.75	.60
	HEAVY DUTY metal plug with plastic insulated grip. Built in spring strain-relief. Gold-plated plug and strain-relief. MPH-2	1.75	1.50	1.35
	STEREO, RIGHT ANGLE PLASTIC RAPS	.45	.35	.25
	STEREO, PLASTIC PHPS	.75	.65	.55
	STEREO, METAL MPHS	1.25	1.05	.80


BANANA PLUGS				
CAT#	1-9	10-99	100+	
 RED PLASTIC BPL-R	.40	.35	.25	
BLACK PLASTIC BPL-B	.40	.35	.25	
BANANA JACKS				
 RED PLASTIC CHASSIS MOUNT BJL-R	.40	.35	.25	
BLACK PLASTIC CHASSIS MOUNT BJL-B	.40	.35	.25	
BINDING POSTS				
 5-WAY BLACK PLASTIC 5-BP-B	.65	.50	.40	
5-WAY RED PLASTIC 5-BP-R	.65	.50	.40	
DUAL BANANA PLUG				
CAT#	1-9	10-99	100+	
 BLACK OR RED PLASTIC 0.75" spacing. Color Subject to Availability. BP-2	1.20	1.00	.85	
MINI DIN PLUG				
 MINI DIN IN-LINE 6 PIN MALE PLUG MDN-6	1.00	.90	.80	
DIN PLUGS				
 3 PIN IN-LINE MALE DIN-3	.40	.35	.20	
5 PIN IN-LINE MALE 180° DIN-5	.75	.65	.55	
DIN JACKS				
 3 PIN CHASSIS MOUNT DIN-3C	.40	.35	.25	
 4 PIN FEMALE PC MOUNT DIN-4JC	.40	.35	.25	
 5 PIN CHASSIS MOUNT 180° DIN-5C	.80	.75	.60	
 8 PIN CHASSIS MOUNT 0.7" dia. threaded bushing w/ nut. Will function as 5 pin, 180 degree jack. DIN-8F	1.00	.75	.65	
3 PIN XLR CONNECTORS				
CHASSIS MOUNT FEMALE				
 Metal 1.42" x 1.05" mounting flange. Mounts in 0.94" diameter hole. Solder lugs. MIKE-3CF	2.00	1.75	1.50	
 Plastic 1.27" x 1.03" mounting flange. Mounts in 0.86" diameter hole. Black, break-resistant plastic. PC pins which can be hard wired and soldered. XLF-3	1.00	.85	.65	
CHASSIS MOUNT MALE				
 Metal 1.41" x 0.86" mounting flange. Mounts in 0.75" dia. hole. Solder lugs. MIKE-3CM	1.75	1.50	1.25	
 Plastic 1.27" x 1.03" mounting flange. Mounts in 0.77" diameter hole. Black, break-resistant plastic. PC pins can be hard wired and soldered. XLM-3	1.00	.85	.65	

3 PIN XLR CONNECTORS (cont.)				
CAT#	1-9	10-99	100+	
 IN-LINE FEMALE MIKE-3F	2.00	1.75	1.50	
 IN-LINE MALE MIKE-3M	2.00	1.75	1.50	
XLR ADAPTORS				
 XLR Coupler Male to Male CAT# XLR-320	\$3.75			
 XLR Coupler Female to Female CAT# XLR-310	\$4.50			
 XLR Male To 1/4 Plug CAT# XLR-340	\$3.75			
 XLR Female To 1/4 Plug CAT# XLR-330	\$4.25			
RCA / PHONE PLUG ADAPTORS				
RCA jack to RCA jack 	CAT# AD-3	75¢ each		
RCA jack to 3.5mm mono 	CAT# RCA-3.5	\$1.00 each		
1/4" mono jack to RCA plug 	CAT# 54-421	\$1.00 each		
3.5 mm mono jack to RCA plug 	CAT# AD-12	\$1.00 each		
1/4" mono to RCA jack 	CAT# AD-5	\$1.00 each		
1/4" stereo to 3.5 mm stereo 	CAT# ADMP-1	\$1.00 each		
3.5 mm stereo to 1/4" stereo 	CAT# ADMP-2	\$1.00 each		
3.5 mm mono to 3.5 mm stereo 	CAT # ADMP-4	\$1.00 each		
3.5mm stereo plug to two 3.5mm stereo jacks 	CAT ADMP-5	\$1.50 each		
RCA plug to two RCA jacks 	CAT# AD-4	\$1.00 each		
RCA jack to two RCA plugs 	CAT# AD-4M	\$1.00 each		
For wall transformers with 3.5 mm mini-phone plugs: Converts 3.5 mm mono phone plug to 2.1 mm co-ax power plug. CAT# AD-13 				
CO-AX POWER PLUGS				
CAT#	1-9	10-99	100+	
 1.3 mm CO-AX PLUG DCESID	.50	.40	.30	
2.1 mm (.08") CO-AX PLUG DCSID	.50	.40	.30	
2.5 mm (0.1") CO-AX PLUG DCLID	.50	.40	.30	


D.C. "CO-AX" POWER JACKS


Normally closed shunt opens when plug is inserted.


CAT#	1-9	10-99	100+
1.3 mm Mates with CAT# DCSID			
 1.3mm pin pc pins. DCJ-9	.50	.45	.35

 1.3mm pin solder lugs DCJ-13	.50	.45	.35
--	-----	-----	-----


2.1 mm Mates with CAT# DCSID


 2.1mm pin solder lugs DCJ-1	.35	.30	.27
---	-----	-----	-----


 2.1mm pin solder lugs with mounting ears. DCJ-12	.35	.30	.17
--	-----	-----	-----


 Mouser # 16PJ093 2.1 mm D.C. co-ax power jack with p.c. pins. Normally closed shunt opens when plug is inserted. DCJ-15	.45	.40	.30
--	-----	-----	-----


2.5 mm Mates with CAT# DCLID

 2.5mm pin DCJ-11	.25	.20	.15
--	-----	-----	-----

 2.5mm pin. Molded DC power jack. P.C. mount DCJ-4	.10	.08	.05
	1000 for \$45.00		

 2.5 mm pin Solder-lugs. DCJ-14	.40	.35	.20
--	-----	-----	-----

 2.5 mm pin. N.C. shunt. Mounts in 0.26" X 0.33" slot. Solder lugs. DCJ-16	.25	.20	.15
	1000 for 10¢ each		

 2.5 mm. N.C. Shunt. PC mount. Large quantity available. DCJ-17	.25	.20	.15
	1000 for 10¢ each		

CABLES W/ CO-AX PLUG / JACKS

DC Co-Ax Power Plugs are commonly used with wall transformers and battery packs.



10' cord with 2.5mm co-ax plugs each end. Grey 18/2 SPT-1 zip cord.
CAT# CB-110 \$1.25 each • 10 for \$10.00


15" CABLE WITH FERRITE BEAD



15" cable. 2.5 mm id coax plugs each end. Ferrite bead for RFI/EMI noise suppression molded 1" from one plug.

CAT # CB-111 85¢ each

1' CABLE W/ 2.5MM COAX PLUGS EACH END



CAT# CB-114 85¢ each

1' CABLE W/ 2.5MM COAX PLUG AND 3.5MM MINI PHONE PLUG



CAT# CB-115 85¢ each

SHIELDED AUDIO CABLES

Single RCA Cables



Shielded one conductor audio cable with RCA style phone plug both ends.

	CAT#	1-9	10-99	100+
6 feet	ACB-6	.85	.75	.70
10 feet	ACB-10	1.00	.90	.85
25 feet	ACB-25	1.50	1.40	1.30

Dual Shielded RCA Cables



Shielded cables with molded color coded RCA pin plugs both ends. Used for stereo/audio hook-up.

	CAT#	1-9	10
36 inch (3 feet)	DCB-36	1.00	85¢

9 Foot Dual Audio Cable

Black cable. Red and yellow RCA plugs both ends. Special! Large Quantity Available

CAT # DCB-108 \$1.00 each • 10 for \$8.50
100 for \$75.00 • 1000 for \$500.00

144 inch (12 feet)	DCB-144	2.50	2.00
---------------------------	----------------	------	------


300 inch (25 feet)	DCB-300	3.50	3.00
---------------------------	----------------	------	------

DUAL SHIELDED CABLE

48" with 2 RCA style plugs one end bare wire the other end.

CAT# DCB-4 75¢ each 10 for \$6.50

3.5mm Stereo Plug to two RCA plugs



Commonly used to connect portable audio players to home stereos and to connect speakers to computers.

Length	CAT#	1-9	10	100
5 feet	CB-42	1.50	1.25	1.00

5 PIN DIN TO 4 RCA PLUGS



3' cable. Male 5 pin DIN plug to 4 RCA plugs.

CAT # CB-64 \$1.75 each

10 for \$1.50 each • 100 for \$1.00 each

CABLES WITH 3.5MM MONO PLUGS

3.5 mm Mono Plug One End

	CAT#	1-9	10	100
1 foot cable unshielded	CB-112	50¢	40¢	30¢
6 foot cable shielded	CB-361	75¢	65¢	55¢
7 foot cable unshielded	CB-61	60¢	55¢	45¢

3.5 mm Mono Plug Both Ends

	CAT#	1-9	10	100
6 foot cable	CB-3561	1.25	1.00	.80
16 ft cable	CB-3582	1.25	1.00	.80

DUAL 3.5MM MINI-PLUGS

Shielded cables with two, two conductor (mono) mini phone plugs at each end.



6' DUAL CABLE CAT # CB-372

\$1.50 each • 10 for \$12.50 • 100 for \$100.00

3.5 mm Mono Plug to RCA



	CAT#	1-9	10	100
6 foot	CB-364	\$1.25	\$1.10	90¢


3.5mm Mono Plug to F (Video) Connector



	CAT#	1-9	10	100
2.5 foot	CAT # VHA-1	\$1.00	85¢	65¢

CABLES WITH 3.5MM STEREO PLUGS AND JACKS

3.5mm Stereo Plugs Both Ends



	CAT#	1-9	10	100
6 inch	CB-362	50¢	40¢	30¢
12 inch	NEW CB-118	75¢	60¢	40¢
6 foot	NEW CB-121	\$1.50	\$1.25	\$1.05

6 foot cable -- Special


Beige cable with 3.5mm stereo plugs each end with red plugs **CB-388** \$1.00 90¢ 70¢
with beige plugs **CB-387** \$1.00 90¢ 70¢



Coil-cord with 3.5mm stereo plugs each end. 0.19" dia. black cable. 12 inches retracted. 26" expanded.

NEW **CB-120** \$1.50 \$1.25 \$1.00

4' DUAL CABLE WITH FERRITE BEAD



Dual cable with 3.5 mm stereo plugs, right-angle on one end, straight on the other. A ferrite bead for EMI shielding is molded onto the cable 4 inches from the straight plugs.

Note: Even though both cables have stereo plugs, only one is wired for stereo. The other is mono, wired with only two wires. **CAT # CB-382**

\$1.00 each • 10 for \$8.50 • 100 for \$65.00


3.5 mm Stereo Jack to 3.5 mm Stereo Plug



	CAT#	1-9	10-99	100+
10 foot cable	CB-371	2.00	1.80	1.60

ADAPTOR CABLES with 1/4" PLUGS


1/4" Phone Plug to 1/4" Phone Plug



12" shielded cable. Mono phone plugs.

CAT # CB-66 \$ 1.00 each


1/4" Mono Phone Plug to RCA Plug



12" shielded zip cord

CAT # CB-67 \$ 1.00 each


1/4" Stereo Phone Plug to Two 1/4" Mono Phone Plugs



12" shielded zip cord

CAT # CB-69 \$ 1.00 each


1/4" Stereo Phone Plug to Two RCA Plugs



12.5" shielded zip cord

CAT # CB-70 \$ 1.00 each

1/4" Stereo Phone Plug to Two RCA Plugs



36" shielded zip cord

CAT # CB-68 \$ 2.00 each


AUTOMOTIVE POWER CORDS WITH CIGARETTE LIGHTER PLUGS/JACKS

Good quality 6' coil cord.


Fused plug with LED indicator.

Non-standard coax power plug, needs to be removed for your application.

CAT # CLP-48 \$2.00 each



15' CORD WITH 3.5 MM PLUG



Molded 3.5mm mini phone plug on 15 foot

22/2 zip cord. **CAT # CLP-52** \$ 1.75 each

3 OUTLET LIGHTER CORD

Two foot cord, fused, 10 Amp plug at one end and three outlet jacks at other end.

CAT # CLP-46


\$ 3.75 each



Light-duty 5' cigarette lighter cord. Fused cigarette plug one end. Non-standard coax plug other end.

CAT # CLP-55 \$1.25 each

100 for 85¢ each



Good-quality cigarette lighter coil cord.


Fused plug with LED indicator.

Cord extends 6 feet.

Terminates to stripped ends.

CAT# CLP-56

\$3.00 each • 10 for \$2.50 each



CIGARETTE LIGHTER POWER CORD W/3A BLADE FUSE


Black 6' 18/2 SPT-2 cord with ATC blade type fuse holder

6" from plug.

Includes 3 amp fuse.

CAT# CLP-58 \$1.25 each

10 for \$1.00 each



POWER SUPPLIES

**SWITCHING POWER SUPPLIES MUST
BE TESTED UNDER LOAD!**

GREAT PRICE! 60 WATT SWITCHING SUPPLY

Autec # UPS61-1004-T

Input: 115/230 Vac

Outputs: 3.3V @ 4A,

5 V @ 2A, 12V @ 3A,

32V @ 5 mA. New, open-frame

switching supply. 5" x 3.46" x 1.68."

"Panasonic-type" two conductor receptacle


for AC input, can be hardwired if desired. Fused

input. 10 conductor molex-type plug output. Ferrite

bead for EMI suppression on output wires. Large

quantity available. **CAT # PS-70** \$4.50 each

Case of 48 pieces for \$3.50 each



50 WATT POWER SUPPLY

Autec # UPS50-2002

Input: 115/ 230 Vac


Outputs: 5 Vdc @

3 Amps, 12 Vdc @

3 Amps. Open-frame

switching supply. 5" x 3" x 1.8"

CAT # PS-532 \$ 6.50 each



5VDC/4A & 12VDC/3A POWER SUPPLY

Autec # UPS51-2002

Input: 115/ 230 VAC.


Outputs: 5 Vdc,

4 Amp / 12 Vdc,

3 Amp. 5" x 3" x 1.18"

open frame switching supply.

CAT# PS-235 \$7.00 each



110 WATT POWER SUPPLY

LiteOn Type 32292

Input: 100 - 240 Vac

Outputs: 3 Vdc @ 25 Amps,

5 Vdc @ 15 Amps,

12 Vdc @ 1 Amp.

Open-frame switching

power supply made for

3 Com (Part# 10013058).

EMI filtered input accepts

standard IEC power cord. Outputs through 4.5"


long wire leads terminated with a special 15 pin

connector. Also has a D-sub type connector for

outputs. 8.5" x 3.5" x 2" high. I/O end of board is

4.5" wide. UL, CSA.

CAT # PS-322 \$8.50 each



150 WATT POWER SUPPLY

Cherokee International # MQT154A1

Input: 100 - 240 Vac, 47 - 63 Hz, 3 Amp

Outputs: +5 Vdc @ 26 A, 3.3 Vdc @ 8 A, -12 Vdc @

1 A, +12 Vdc @ 6 A.

Switching power supply

with 0.14" thick

aluminum enclosure

on three sides.

8" x 4.25" x 1.5."

Line and load

regulation. Current


limiting. Voltage adjustment.

Overvoltage setting. Remote sensing.

UL, CSA. Hook-up/spec sheet included.

Large quantity available. **CAT # PS-155**

\$10.50 each • 10 for \$9.00 each



222 WATT POWER SUPPLY

Teapo Model # TP511B-4

Input: 100-240 Vac

Outputs: 5.1VDC @

32A, 12VDC @

6A, -5VDC @

0.3A, -12 Vdc @

0.3A, 3.3VDC @ 24A.

Enclosed, fan-cooled

computer power supply. Push on/off


power switch on 12" cord. Has special power harness

in addition to the common Molex-type power connec-

tors. IEC power inlet. UL, CSA. 5.9" x 5.5" x 3.4."

CAT # PS-511 \$ 16.50 each

Case of 8 for \$12.00 each



New
Item

INCREDIBLY CHEAP! ENCLOSED SWITCHING SUPPLY

Voltek Corp # SPEC7188B

Input: 100 - 240 Vac

Outputs: + 5 Vdc @ 3.70 A,

+12 Vdc @ 0.60 A,

-5 Vdc @ 0.05 A,

+5 Vdc Trickle @ 0.1 A


Metal encased switching

supply. Standard three-prong IEC socket power input.

7 conductor, Molex-type connector output. 9" x 2.1" x

1.36". UL recognized. Removed from new equipment.

CAT # PS-27 \$ 3.50 each



25 WATT POWER SUPPLY

Autec # UPS25-1002T

Input: 115v/1.5A 230V/0.75A

Output: 5V @ 1.9A,

12V @ 1.6A.

25 Watt switching supply

mounted on an L-bracket,


9" x 2.27" x 2.25" overall.

Standard three prong IEC

socket power input. On-Off rocker switch.

Molex-type connector output. UL, CSA recognized.

CAT# PS-251 \$4.25 ea. • 10 for \$3.50 ea.



New
Item

POWER SUPPLY, 5V/3A & 12V/3A

Martec # PV150-21TA.

Input: 100-240 Vac.


Output: 5 Vdc @

3 Amps, 12 Vdc @

3 Amps. 5" x 3" x 1.75" high

open frame supply.

CAT# PS-21 \$6.50 each



New
Item

SWITCHING POWER SUPPLY

Y.K. Systems # KM624LC-6

Input: 115 Vac

Outputs: 3.3V, 5V, 12V,

15V, 22V, 32V, -12V

Current rating unknown.


Open-frame switching supply,

7.38" x 3.5" x 1.46." Output

through 12 pin Molex-type socket

connector on 11" leads.

CAT # PS-104 \$ 3.50 each



New
Item


MANUFACTURERS

We Purchase Excess Inventories.

**CALL, WRITE, E-MAIL
or FAX your list.**

19 WATT POWER SUPPLY

Skyнет # ARC-2133
Input: 115 / 230 Vac
Outputs: 5 Vdc @ 0.7A
and 12 Vdc @ 1.3A
6.75" x 3.75" x 1.1."
9" wire leads with
Molex-type connectors for output.
115/230 V selector slide switch. UL, CSA.
CAT # PS-2133 \$3.50 each




SINGLE OUTPUT SWITCHING POWER SUPPLIES

Ideal for scanners, cameras and sensitive equipment requiring a constant, regulated output. All of the following operate on 120 Vac. UL, CSA.

SPECIAL PURCHASE! 5 VDC 1.9 AMP


Autec # DT25-1004. Input 100-240 Vac
Output: 5 V @ 1.9 Amp, 8 V @ 1.1 Amp, 15 V @ 0.36 Amp, -15V @ 0.09 Amp. 3.25" x 6.39" x 2.35" h.
7' 6" output cord is terminated with custom connector. Requires detachable IEC power cord like our CAT# LCAC-60. UL, CSA listed. **CAT# PS-531**
\$5.00 each • 10 for \$4.50 ea.



50 for \$4.00 each
100 for \$3.50 each

5 VDC 2 AMP

Sceptre #LPS-001
Regulated linear power supply.
Table-top style case with grounded
6' power cord and
6' output cord with 2.5mm ID coax plug, center negative.
Case size: 5.12" x 3.65" x 2.72." UL, CSA.
CAT # PS-52 \$ 9.00 each



5 VDC 2 AMP Uniq Technologies, Inc.
SYS1089-1005L-W2. Plug-in style.
6' cord terminated with 2.1mm coax power plug, center positive. UL, CSA.
CAT# PS-522 \$6.50 each
10 for \$5.50 each




5 VDC 2.4 AMP

GLOBTEK # SA-0524AF-11
Input: 100-250 Vac.
Output 5 Vdc @ 2.4 Amps.
6' cord with 2.1mm coax power plug. Center positive. Includes detachable IEC power cord for 120 Vac.
CAT# PS-524 \$7.75 each




5.7 VOLT 840 MA

Philips Type 10PS206/17.
6' cord terminated with 1.3 mm i.d. coax power plug, center positive. Ideal for scanners, cameras and sensitive equipment requiring a constant, regulated output. Operates on 120 Vac. UL, CSA. **CAT# PS-578**
\$5.50 each • 20 for \$5.00 each




6.5 VOLT 700 MA

Phillips Type FW 7221
6 foot cord terminated with a 1mm I.D., 3mm O.D. coax power plug. Tip positive. Fused.
CAT # PS-657 \$5.50 each




6.5 VDC 5 AMP

Elpac # 8B5047
Input: 95-250 Vac
Output: 6.5 Vdc @ 5 Amps
Enclosed switching power supply. Table-top style case, 6.38" x 3.80" x 2.70". 6' output cord is terminated with an odd mini-din plug which will need to be cut off. Requires a detachable IEC power cord like our LCAC-60. CSA approved. **CAT# PS-655** \$11.75 each




12 VDC 1.25 AMP

DVE # DSA-0151-12
2.1mm I.D. coax power plug.
Center positive. UL, CSA.
CAT # PS-1215
\$7.25 each
10 for \$ 6.95 each • 100 for \$ 6.50 each



12 VDC 3.5 A SWITCHING POWER SUPPLY

Elpac # WR14212.
Input: 95-250 Vac.
Output: 12 Vdc @ 3.5 Amps. Fully enclosed switching power supply. Table-top style plastic case, 6.38" x 3.75" x 2.7." Line and load regulation. Overvoltage and overcurrent protection. Short circuit protection. IEC input with level B EMI filter. Detachable IEC power cord included. 6' output cord terminated with a 5 pin DIN plug. UL, CSA.
CAT # PS-1242 \$18.00 each




12 VDC 6 AMP SWITCHING POWER SUPPLY

Elpac #W7212.
Input: 95-250 Vac.
Output: 12 Vdc @ 6 Amps. Fully enclosed switching power supply. Table-top style plastic case, 6.38" x 3.75" x 2.7." Overvoltage and overcurrent protection. Short circuit protection. IEC input with level B EMI filter. Detachable IEC power cord included. 6' output cord terminated with a 5 pin DIN plug. UL, CSA.
CAT# PS-1244 \$26.00 each




13 VDC 1 AMP

Qualcomm # TAACA0035
DC coax power plug,
2.1mm I.D., 5.5mm O.D., center positive. Wall plug style.
CAT # PS-131
\$6.50 each



1 AMP SWITCHING POWER SUPPLY with SELECTABLE OUTPUT 3 - 4.5 - 6 - 7.5 - 9 - 12V


The perfect power supply for audio / video / telephone / communication / small appliances / any device that normally uses a wall transformer. Provides all of the popular voltages between 3 and 12 Vdc, and it's regulated, so the voltage doesn't fluctuate when the load varies. A good multi-voltage lab supply for breadboard projects up to 1 Amp. Includes a set of seven of the most popular power connectors.
CAT # PS-10 \$12.95 each



ADJUSTABLE POWER SUPPLY


0 - 15 VOLTS DC 30 AMP

Zurich # DS-304M
0 - 15 Vdc fully adjustable bench supply. 25 Amps continuous. 30 Amps peak. 1% line load regulation. Short circuit and overload protection. Switchable meter for volts and amps. Lighted power switch. Binding-posts, spring level terminals, and cigarette lighter socket outputs. 6.5" H x 6" W x 8.38" D. Wt 19 lbs.
CAT # PS-2512 \$165.00 each



ADJUSTABLE LAB POWER SUPPLY 90 WATT

30 Vdc @ 3 Amp. Constant voltage and current. Coarse and fine adjustments for voltage and current. Overload protection. Dual displays for voltage and current. Color-coded terminals for positive, negative and ground connections. Can be used in series or parallel with other power supplies. Operates on 110 or 220 Vac. 11.75" x 5" x 6" H. Available with digital or analog meters. 1 year warranty.




w/ Digital Meters

CAT # PS-303 \$145.00 each

w/ Analog Meters

CAT # PS-304 \$135.00 each

TRANSFORMERS



POWER TRANSFORMERS

All power transformers have 115 vac 50/60 hz primaries unless otherwise noted.

12 V.C.T. @ 2 AMP

1.625" high X 2" X 1.5". CASE STYLE H
CAT# TX-122 \$5.00 each

12 V.C.T. @ 3 AMP

STYLE H 2 1/3" h. X 2 3/4" X 2 1/4".
CAT# TX-123 \$6.00 each

12 V.C.T. @ 4 AMP 2" high X 2 11/32" x 2".
STYLE H **CAT# TX-124** \$7.50 each

12 V.C.T. @ 5 AMP

2 1/4" h. X 2 3/4" X 2 1/4" STYLE H
CAT# TX-125 \$9.50 each

12.6 V.C.T. @ 1 AMP

1.71" h. X 1.55" X 1.36". CASE STYLE H
CAT# TX-121 \$4.25 each • 10 for \$40.00

12.6 VOLT @ 25 AMP STYLE H

Primary: 100 Vac or 115 Vac. Secondary: 12.6 Volts @ 25 Amps. 3.5" X 3.75" X 4.25" high. 6" wire leads for input. 0.25" qc tabs for output.
CAT# TX-12625 \$20.00 each

24 V.C.T. @ 1 AMP 1 5/8" high X 1 5/8" X 2". CASE STYLE H **CAT# TX-241** \$5.00 each

24 V.C.T. @ 2 AMP 2" high X 2 3/8" X 2". CASE STYLE H **CAT# TX-242** \$7.50 each


24 V.C.T. @ 2.4 AMP

Signal Transformers # 241-7-24
2.7" X 1.81" X 2.25" high. CASE STYLE H. UL.
CAT# TX-2424 \$9.50 each

24 V.C.T. @ 3 AMP 2 1/4" X 2 3/4" X 2 1/4". CASE STYLE H **CAT# TX-243** \$12.50 each

24 V.C.T. @ 3.3A or 12V @ 6.6A SPLIT BOBBIN TRANSFORMER

MCI # 4-49-6024. Dual primary: 110/220 Vac input. Secondaries: 24 Vct @ 3.3A - series or 12 Volts @ 6.6 A - parallel 2 1/2" x 2 3/8" x 3" high. 3/16" quick-connect or solder lug terminals. UL, CSA, VDE.



CAT# TX-2433 \$13.75 each

24 V.C.T. @ 4 AMP

2.60" high x 3.10" x 2.12". Case style H (Mounting holes 3.50" centers)
CAT # TX-244 \$13.50 each



24 V.C.T. @ 5 AMP 3 1/2 high X 3" X 3". CASE STYLE H **CAT# TX-245** \$16.00 each

25 VOLT CT, 2 AMP

CASE STYLE H. Magnetek Triad # F41X. 25.2 VCT @ 2 A continuous rating. 3" x 2.2" x 2.6" high. Mounting holes on 3.5" centers. 6" wire leads.
CAT # TX-252 \$8.50 each

28 VOLT, 1.5 AMP CASE STYLE H
2" high x 2.37" x 2.45". with wire leads.
CAT # TX-2815 \$3.50 each

40 VCT @ .25 AMPS TRANSFORMER

CASE STYLE H.
1.95" x 1.8" x 1.66" high. Mounting holes on 2.35" centers.
CAT# TX-4025 \$2.25 each
80 for \$ 1.75 each



50 V.C.T. @ 2 AMPS

ATC-Frost # M1210 Rev 1. CASE STYLE H. 3.1" x 2.3" x 2.6" high. 6" wire leads.
CAT # TX-502 \$ 11.00 each

60 V.C.T. @ 2 AMPS

VFT, LLC # M1128. CASE STYLE H. 3.1" x 2.5" x 2.6" high. Solder terminal inputs. 11" wire leads outputs. **CAT# TX-602** \$ 11.00 each

70 V.C.T. @ 1.5 AMPS

ATC-Frost # M1211. CASE STYLE H
3" x 2.5" x 2.5" high. 6" wire leads.
CAT # TX-7015 \$ 11.50 each

P.C. MOUNT TRANSFORMERS

All PC Mount Transformers CASE STYLE I

10 VCT @ 1.2A or 5V @ 2.5A

Tranex - Dual Primary: 115/230 Vac 2.51" X 2" X 1.04" high. CAT# PCTX-1012 \$4.00 each

12VCT @ 0.35A or 6V @ 0.7A

Dual Primary: 115/ 230 Vac.
1.89" x 1.5" x 0.84" high.

CAT# PCTX-1225 \$2.50 each



16 VCT @ .8A or 8V @ 1.6A

Stancor # DSW-516
Dual Primary: 115/230 Vac.
1.9" x 1.59" x 1.5" high.

CAT # PCTX-168 \$4.00 each

20 VCT @ 0.2A or 10V @ 0.4A

Dual Primary: 115/ 230 Vac.
1.89" x 1.5" x 0.84" high.

CAT# PCTX-2035 \$2.50 each



20 VCT @ 0.6A or 10 V @ 1.2A

Stancor # SW-520 115 Vac primary
1.44" x 1.56" x 1.88".

CAT # PCTX-2061 \$ 4.00 each

20 VCT @ 1.2A or 10 V @ 2.4A

Signal # DPC20-1200
Dual Primary: 115/230 Vac.
1.62" x 2.25" x 1.37" high.

CAT # PCTX-2012 \$ 5.00 each

115 VAC TRANSFORMERS WITH MULTIPLE SECONDARIES

6.3 V @ 3A AND 24 VCT @ 0.6A


STYLE H 2.2" x 2" x 1.9" high. Wire leads.

CAT # TX-624 \$ 3.50 each

12V @ 1A AND 50V @ 0.5A

Dual primary: 115/230 Vac.
Two secondaries, approximate ratings:
12V @ 1 Amp, 50V @ 0.5A. Split
bobbin transformer. 2.64" x 2.19" x
2.25." Mounting holes on 1.75" x 2.2" centers.

CAT # TX-1250 \$ 3.50 each



100 VA ISOLATION TRANSFORMER

Powertec USA# 02-0010

Primary: 120 V, 60 Hz


Secondary: 120 V, 100 VA

3.1" x 2.6" x 2.7" high.

Solder-lug terminals.

Mounting holes on 3.5" centers.

CAT # ITX-4 \$ 9.75 each



600 OHM PHONE/DATA COUPLING TRANSFORMER


Prem Magnetics # SPT115.

600 Ohms primary/secondary
impedance. 1:1 turns ratio.

Resistance, primary/secondary: 6
3 Ohm/88 Ohm. Frequency
response: 300-3500 Hz +-0.5dB.
1.02" x 0.91" x 0.78" high.

CAT# TCX-115 50¢ each

10 for 35¢ each • 100 for 27¢ each




TOROIDAL POWER TRANSFORMERS

26 VCT @ 2 AMPS (SERIES) OR 13 VOLTS @ 4 AMPS (PARALLEL) AND 7 VOLTS @ 0.6 AMPS

117 Vac primary. Three secondary
windings. One 7 Volt,
0.6 Amp and two 13 Volt,
2 Amp secondaries which
can be hooked in series or
parallel for 13 or 26 volts. 3.9" dia. x 1.12".


CAT # TTX-37038 \$9.50 each



36 VCT @ 0.65 Amps

Primary: 115 / 230 Vac
Secondaries: 36 Vct @
0.65 Amps and 48 Vac @
0.1 Amps. 3" diameter x 1.33."


CAT # TTX-3660 \$ 5.00 each



36 VCT @ 2 Amps

Primary: 100 - 120 Vac
Secondaries: 36 Vct @
2 Amps and 48 Vac @
0.15 Amps. 3.64" diameter x 1.6."


CAT # TTX-362 \$ 14.50 each



8.5 Volts @ 1.1 Amps

Primary: 115 / 220 Vac
Secondaries: 8.5 Volts @
1.1 Amps and 14.9 Volts @
0.53 Amps. 2.8" dia. x 1.13."
Includes mounting hardware.

CAT # TTX-0032 \$ 4.00 each




VARIACS

Input: 110 vac

Output: 0 - 130 vac

Fully enclosed variable transformers
in ventilated steel cases with 6'
power cord, 3 prong grounded
receptacle, output voltage meter,
on/off switch, fuse and power cord.

Portable or mountable. Useful in a
variety of applications where adjustment of AC line
voltage is desirable. Available in 4 sizes.



3 AMP VARIABLE TRANSFORMER

5.35" X 4" X 5.5" high. Weight: 6.5 lbs.

CAT # SC-3M \$45.00 each

5 AMP VARIABLE TRANSFORMER

4.75" X 7" X 6" high. Weight: 8 lbs.

CAT # SC-5M \$95.00 each

10 AMP VARIABLE TRANSFORMER

6.5" x 9" x 6" high. Weight: 20 lbs.

CAT # SC-10M \$135.00 each

20 AMP VARIABLE TRANSFORMER

6.5" x 9" x 7.5" high. Weight: 22 lbs.

CAT # SC-20M \$165.00 each

7.5 TO 9 VDC WALL TRANSFORMER


Stancor AC Adaptor # STA-4175A.

Standard wall transformer with dual
output rating. Voltage depends on load
(This is actually the case with all wall
transformers). Rated 7.5 Vdc @
500 mA or 9 Vdc @ 300 mA. Power cord
is terminated with a 2.1mm i.d. coax power
plug, center negative. New, individually
boxed. UL, CSA. CAT# DCTX-4175
\$4.50 each • 100 for \$3.50 each



WALL TRANSFORMERS


STYLE A
Table
Top



STYLE C
Wall Type



STYLE D
Screw
Terminals




A.C. WALL TRANSFORMERS

	VOLTS	AMPS	TERMINATION	STYLE	CAT#	PRICE	100 +
	9 Vac	450 ma.	2.1mm co-ax	C	ACTX-945	\$2.50	\$1.75
	10 Vac	1.7 amp	2.5mm co-ax	C	ACTX-1017	\$2.50	\$1.75
	10 Vac	2.4 amp	2.5mm co-ax	C	ACTX-1024	\$3.85	\$3.00
	11 Vac	2.4 amp	2.1mm co-ax	C	ACTX-1124	\$3.85	\$3.00
NEW	12 Vac	2.08 amp (25VA)	Screw terminals	D	ACTX-1225	\$4.00	\$3.00
	15 Vac	400 amp	3.5mm phone plug	C	ACTX-154	\$2.25	\$1.50
	15 Vac	2.4 amp	2.5mm co-ax	C	ACTX-152	\$4.25	\$3.25
	16 Vac	1.1 amp	2.1mm co-ax	C	ACTX-161	\$3.50	\$2.50
	16.1 Vac	1.86 amp (30VA)	Screw terminals	D	ACTX-163	\$3.00	\$2.50
	18 Vac	3.33 amp (60VA)	Bare wire	A	ACTX-186	\$3.50	\$2.50
	19 Vac	1.26 amp	3.5mm phone plug	C	ACTX-192	\$3.00	\$2.25
	24 Vac	830 ma. (20VA)	Screw terminals	D	ACTX-2420	\$5.50	\$4.50
NEW	24 Vac	1.6 amp (40VA)	Screw terminals	D	ACTX-2440	\$6.00	\$5.00


D.C. WALL TRANSFORMERS

	VOLTS	AMPS	TERMINATION	CENTER	STYLE	CAT#	PRICE	100+
*	3 Vdc	100 ma	2.5 mm phone plug	positive	C	DCTX-31	\$1.35	\$1.00
	3 Vdc	200 ma	unknown co-ax	positive	C	DCTX-321	\$1.50	\$1.10
	4.5 Vdc	500 ma	1.6 mm co-ax	positive	C	DCTX-455	\$3.00	\$2.00
	6 Vdc	300 ma	3.5 mm phone plug	negative	C	DCTX-630	\$3.00	\$2.50
	6 Vdc	1.5 amp	2.5 mm co-ax	positive	C	DCTX-615	\$5.00	\$3.75
	7.5 Vdc	1.2 amp	2.1 mm co-ax	positive	C	DCTX-7512	\$5.00	\$3.75
	7.5 - 9	500-300ma	2.1 mm co-ax	negative	C	DCTX-4175	\$4.50	\$3.50
	8.5 Vdc	1.2 amp	2.1 mm co-ax	negative	C	DCTX-8512	\$5.00	\$3.75
	9 Vdc	100 ma.	2.1 mm co-ax	negative	C	DCTX-918	\$2.50	\$1.75
	9 Vdc	150 ma.	2.1 mm co-ax	negative	C	DCTX-9151	\$2.50	\$1.75
	9 Vdc	170 ma.	2.1 mm co-ax	negative	C	DCTX-917	\$2.50	\$1.75
	9 Vdc	200 ma.	2.1mm co-ax	positive	C	DCTX-920	\$2.75	\$2.00
	9 Vdc	500 ma.	2.1 mm co-ax	negative	C	DCTX-958	\$4.50	\$3.50
	9 Vdc	1 amp	2.1 mm co-ax	positive	C	DCTX-914	\$4.00	\$3.00
	9 Vdc	1 amp	2.5 mm co-ax	negative	C	DCTX-919	\$4.00	\$3.00
	10.5 Vdc	730 ma	2.1 mm co-ax	negative	A	DCTX-107	\$4.00	\$3.00
	12 Vdc	200 ma.	2.1 mm co-ax	positive	C	DCTX-122	\$3.00	\$2.25
	12 Vdc	200 ma	2.1 mm co-ax	negative	C	DCTX-1222	\$3.00	\$2.50
	12 Vdc	300 ma	1.7 mm co-ax	positive	C	DCTX-1234	\$3.50	\$2.50
NEW	12 Vdc	400 ma	cigar plug		C	DCTX-1242	\$3.75	\$2.75
	12 Vdc	500 ma	2.5 mm co-ax	positive	C	DCTX-1252	\$4.50	\$3.50
	12 Vdc	800 ma	2.1 mm co-ax	positive	C	DCTX-1284	\$4.75	\$3.50
	12 Vdc	800 ma	2.5 mm co-ax	positive	C	DCTX-1282	\$4.75	\$3.50
	12 Vdc	1 amp	2.1 mm co-ax	positive	C	DCTX-1216	\$5.00	\$3.85
	13 Vdc	800 ma	2.5 mm co-ax	positive	C	DCTX-1310	\$4.75	
	14 Vdc	360 ma	2.5 mm co-ax	positive	C	DCTX-1436	\$3.50	\$2.75
	15 Vdc	900 ma	2.1 mm co-ax	positive	C	DCTX-1590	\$4.25	\$3.25
	24 Vdc	600 ma.	2.1mm co-ax	positive	C	DCTX-246	\$4.50	\$3.50

co-ax plug



phone plug




cigar plug



For regulated plug-in-wall switching power supplies see pages 55 and 56

UNIVERSAL DC POWER ADAPTER

Power cassette players, CD players, radios, games and "handy-talkies" with one universal wall transformer. Six voltage settings from 3 to 12 Vdc. Universal power plugs that fit almost every product including "Walkman" style devices. Polarity switch and LED indicator. UL and CSA listed. 500 mA. **CAT # MOA-500** \$7.50 each




* 3VDC 100 mA WALL TRANSFORMER

Excellent for LEDs and low current applications. 3 Vdc, 100 mA wall transformer. 6' cord. 2.5mm mini-phone plug, tip positive. Large quantity available. UL.

CAT# DCTX-31 \$1.35 each • 10 to 95 for \$1.25 each

96 to 575 \$1.00 ea. • 576 to 1055 75¢ ea. • 1056 or more 65¢ ea.




Order Toll Free 1-800-826-5432

Page 59

AUDIO LINE MATCHING TRANSFORMERS

25 / 70 VOLT Inputs for 25 or 70 Volt line. Output for 8 ohm, 10 Watt speaker. 1.67" x 1.97" X 1.50"
CAT # LMT-2 \$2.00 each • 10 for \$17.50



TERMINAL STRIPS


SINGLE ROW BARRIER STRIP

TYPE A Open



TYPE B

Feed-Thru with mounting holes




TYPE D

Closed Back



TYPE E

Closed back with mounting holes



No. of screws	Term. centers	Amps	Type	CAT#	Price	50+
2	.43"	20	B	TER-29	2/\$1.00	.30
3	.43"	30	A	TER-30	4/\$1.00	.18
4	.43"	20	A	TER-400	3/\$1.00	.20
5	.375"	20	B	TER-52	3/\$1.00	.20
6	.43	20	A	TER-600	2/\$1.00	.30
8	.375"	15	A	TER-800	2/\$1.00	.30

numbered 1-9, left-to-right

9 .375" 20 A **TER-901** 2/\$1.00 .30

numbered 1-9, right-to-left

9 .375" 20 A **TER-902** 2/\$1.00 .30

10 .375" 20 E **TER-102** 2/\$1.00 .30

12 .375 20 D **TER-125** 2/\$1.20 .50


PC STRIPS W/ HEAVY TERMINALS

2 SCREW - Beau 1200 series.

Dark green thermoplastic. 1.41" x 0.56" x 0.45" high. Screws on 3/8" centers. Mounting holes on 1.08" centers. 0.1" diameter PC terminals for heavier current applications.

CAT # TER-200 5 for \$ 1.00

100 for \$ 12.00 • 1000 for \$ 80.00



DUAL ROW TERMINAL STRIPS

2 POSITION FEED-THROUGH

Kulka 601. Space-saving 2 position feed-through strip with mounting holes between the two terminals. 20 Amps. 1.19" x 1.13" x 0.52" high.


CAT # TS-220Y 50¢ each



2 POSITION, 40 AMP STRIP

TRW Cinch # 2-150. 2.5" x 1.18" x 0.75" high. 10-32 screws accept up to # 10 wire. Terminals on 11/16" centers.

CAT # TS-250 \$1.50 each




3 POSITION

TRW/Cinch.

3 position 20 amp double row barrier strip. 0.43" terminal centers. 2.06" x 1.37" x 0.68" high. Mounting holes on 1.75" centers.


CAT# TS-314 75¢ each



4 POSITION, 50 AMP

Beau 28004. New barrier strip prepped with one jumper, one quick-connect terminal and two solder terminals. These items can be easily removed or relocated on the strip. 11/16" terminal centers. 10-32 screws. 3.9" x 1.8" x 0.75." UL, CSA.


CAT # TS-6034 \$1.75 ea. • 10 for \$1.50 ea.




5 POSITION 30 AMP

Cinch 5-142. 3.77" x 1.31" x 0.62" high. 8-32 screws accept up to #10 wire. Terminals on 0.563" center spacing.

CAT# TS-542 \$2.50 each



70AMP EUROSTYLE TERMINAL STRIPS



For connecting stripped wires from 8 – 22 AWG depending on the block size. Flexible white (natural) Nylon 66 body, 94V2 rated for 105 C degrees. 400 Volts. All metal parts are completely recessed in the housing to prevent shorts. Each strip has 12 circuits, with a mounting hole between each circuit. Can be easily shortened with a knife or saw.

7 AMP

For 22-18 wire. 3.78" x 0.67" x 0.57" high. 0.32"(8mm) terminal centers. UL, CSA, VDE. **CAT # TB-7** \$2.00 each
 10 for \$1.80 each • 100 for \$1.60 each

20 AMP

For 18-14 wire. 4.6" x 0.80" x 0.67" high. 0.39"(10mm) terminal centers. UL, CSA, VDE. **CAT # TB-20** \$2.25 each
 10 for \$2.10 each • 100 for \$1.80 each

35 AMP For 14-10 wire. 5.51" x 0.93" x 0.74" high. 0.47"(12.2mm) terminal centers. UL.

CAT # TB-35 \$2.70 each

10 for \$2.45 each • 100 for \$2.15 each

50 AMP For 20-8 wire. 6.25" x 1.00" x 0.99" high. 0.53"(13.5mm) terminal centers. UL.

CAT # TB-50 \$3.25 each

10 for \$2.95 each • 100 for \$2.60 each

70 AMPS @ 500 VOLTS

6.75" x 1.18" x 1" high. **CAT # TER-12**


\$3.75 each • 10 for \$3.25 each

SCREW-CLAMP STRIPS

16 POSITION

Weco # 960-DS/16. 5.08 mm (0.2") terminal centers. Fits 26-12 AWG wire. 3.24" x 0.35" x 0.51" high. Rated 20 Amps @ 300 Volts. UL, CSA.

CAT # TER-160 \$ 1.75 each



PRESS-FIT® TEFLON TERMINALS

Sealectro # FTMM9SL. Teflon-insulated solder posts. Press fit into 1/16" dia. hole. Sold in bags of 500 only.

CAT #TT-3 \$10.00 per 500 pc bag.




FLASHING LIGHTS

For alarm systems, discos, personal use, warning in case of danger, etc. Long-life xenon tube. Protected against polarity reversal. Fully sealed and waterproof. Power supply: 12 Vdc, 150 mA.

Flash rate: 120/min.
2.75" diameter X 1.70".

Acrylic cover with black ABS base. Threaded mounting studs on 1.7" centers. Hardware included.


color	CAT#	price
red	STROBE-3R	\$8.95 each
green	STROBE-3G	\$8.95 each
blue	STROBE-3B	\$8.95 each
amber	STROBE-3A	\$8.95 each
clear	STROBE-3C	\$8.95 each



MINI STROBE



20 Watt miniature strobe unit with a 2.32" x 1.28" polished reflector. Flash rate is adjustable from 2 to 10 flashes per second. Flash tube rated to 100 million flashes. 5" x 3.3" x 2" case with mounting bracket. Operates on 115 vac.

CAT # STROBE-2 \$ 19.95 each



FLASHERS

BICYCLE HALOGEN HEADLAMP AND LED FLASHER




For riding or walking at night this headlamp and tail lamp set is just the thing. Comes with mounting clamps for handlebars and seat post. Rear LED flasher has 5 ultra-bright LEDs which can be set on one of 7 eye-catching flashing patterns. LED flasher has belt clip for walking at night. Lamp requires 2 C cells. LED flasher requires 2 AA cells. Batteries not included.

CAT # FL-14 \$ 7.50 per set

Variable LED FLASHER Safety Light

5 ultra-bright LEDs in a red reflector case. This versatile safety device can be seen over long distances at night. Includes clip for belt or bag, strap for armband and hardware for attachment to bicycle. Can be set for one of six different chaser or flashing patterns. Water resistant. Requires 2 AA batteries (not included).

CAT # FSH-6 \$ 4.95 each




#552 AUTOMOTIVE FLASHER

Heavy-duty 2 terminal 12 Vdc flasher cars, truck and trailers.
1.34" diameter x 1.05" metal can.

CAT # FSH-552

\$ 3.75 each 10 for \$ 3.50 each




STROBE LIGHT

30 candela xenon strobe.

Mounted on a 4.58" square plastic wall plate, there is probably another part of plastic rim to cover the plate. Flash rate is 1 flash per second at 24 Vdc (20 - 31 Vdc). The strobe, itself, is enclosed in a plastic housing in the middle of the wall plate, 4.04" x 1.19" x 2.6" high with a clear polycarbonate dome over the lamp. Will operate at 12 Vdc with a flash rate of 30 flashes per minute.

CAT# STROBE-4 \$12.75 each
10 for \$11.50 each




UV BLACKLIGHT

New black-light lamps designed by

Avon Cosmetics to highlight dry skin. They have a built-in timer that shuts off the lamp after approximately one minute. Ideal for lighting fluorescence in black-light posters, gemstones, hand stamps and US currency. 5" lamp, F4T5BLB, is housed in a lightweight plastic case. 7" x 3.25" x 2.3" high. Operates on 12 Vdc. Power input is through a 2.5mm coax power jack, center positive.

CAT# UVL-2 \$5.00 each



RECOMMENDED POWER SUPPLY FOR UVL-2
12V 500ma. **CAT# DCTX-1252** \$4.50 each

COMPUTER ACCESSORIES

THREE BUTTON SERIAL


MOUSE Windows compatible

three button serial mouse.

Includes 3.5" floppy disk

with drivers. **CAT# MSE-3**

\$3.50 each 10 for \$30.00



WINDOWS COMPATIBLE KEYBOARD

Genica "Soft-touch"

keyboard. 107 key

keyboard for

Windows


98/2000/NT/ME.

Standard PS/2 Interface

Keyboard. Large Enter, Spacebar and Backspace

Keys. Adjustable cursor speed. Four color-coded keys for Soft Power-on, Sleep-mode, Wake-up and

Function. **CAT# KBD-8** \$7.50 each



3 BUTTON MOUSE


Attractive, ergonomically designed, 3-button mouse.

PS/2, mini-DIN interface.

Plug & play with Windows 95,

98, NT. **CAT # MSE-4**

\$3.25 each • 10 for \$30.00



COPY HOLDER FOR LAPTOP


Curtis "Copy Clip." Holds paper

up next to your screen for easy referral or transcription.

Mountable on right or left

side of computer. Slides away when not in use.

CAT# CH-6 \$1.50 each






POTENTIOMETERS

POTS W/ 6mm SHAFT

All of the following pots have 6mm diameter shafts and 7mm diameter bushings unless otherwise noted.

Resistance	Taper	Description
500	Audio	0.45 knurled shaft
1K	Linear	0.6" half-moon shaft
5K	Linear	0.75" half-moon shaft
5K	Linear	0.32" round shaft. 8mm bushing
5K	Audio	0.7" flatted shaft. 8mm bushing.
10K	Audio	0.4" knurled shaft. Detents.
10K	Linear	0.35" round shaft. SPST switch
10K	Linear	0.6" knurled shaft
10K	Audio	0.5" flatted shaft. 8mm bushing.
20K	Linear	0.32" round shaft
20K	Linear	0.32" flatted shaft. Dual Pot
25K	Linear	0.32" knurled shaft
25K	Audio	0.35" round shaft
50K	Linear	0.35" knurled shaft
50K	Linear	0.35" flatted shaft
50K	Linear	0.32" knurled shaft. Dual Pot
100K	Audio	0.32" knurled shaft
100K	Linear	0.35" round shaft
250K	Linear	0.35" round shaft
500K	Audio	0.35" round shaft
1M	Audio	0.35" round shaft



CAT #	Price each	100
NATP-500	5/\$1.00	\$0.15
NLTP-1K	5/\$1.00	\$0.15
NLTP-5K	2/\$1.00	\$0.40
NLTP-5K4	2/\$1.00	\$0.40
AP-5K	2/\$1.00	\$0.40
NATP-10K	2/\$1.00	\$0.40
NSLP-10K	2/\$1.00	\$0.40
NLTP-10K	2/\$1.00	\$0.40
AP-10K	2/\$1.00	\$0.40
NLTP-20K	2/\$1.00	\$0.40
DLP-20K	2/\$1.00	\$0.40
NLTP-25K	2/\$1.00	\$0.40
NATP-25K	2/\$1.00	\$0.40
NLTP-50K	3/\$1.00	\$0.25
NTP-50K	2/\$1.00	\$0.40
DLP-50K	2/\$1.00	\$0.40
NATP-100K	2/\$1.00	\$0.40
NLTP-100K	2/\$1.00	\$0.40
NLTP-250K	2/\$1.00	\$0.40
NATP-500K	2/\$1.00	\$0.40
NATP-1M	2/\$1.00	\$0.40

SLIDE POTS




Resistance	Taper	Length	Travel	Desc.
1K	Audio	3.5"	2.5"	Dual pot
2K	Audio	3.5"	2.75"	
9K	Linear	2"	1.25"	Center detent
10K	Audio			See below***
10K	Linear	1.2"	0.8"	Dual pot
10K	Linear	2.38"	2"	Dual pot
20K	Linear	1.78"	1.35"	Dual pot
50K	Linear	2.9"	2"	
50K	Linear	2.38"	2"	
100K	Linear	2.38"	2"	

CAT #	Price each	100
ASP-1KD	2/\$1.00	\$0.40
ASP-2K	2/\$1.00	\$0.40
LSP-9K	4/\$1.00	\$0.15
ASP-10K	\$1.75	\$1.20
LSP-10KD	3/\$1.00	\$0.25
LSP-10K	3/\$1.00	\$0.25
LSP-20KD	3/\$1.00	\$0.25
LSP-50KL	2/\$1.00	\$0.40
LSP-50K	2/\$1.00	\$0.40
LSP-100K	3/\$1.00	\$0.25

*** DUAL 10K AUDIO TAPER SLIDE POT


A/D Electronics # SL1009G A10K. 100 mm travel master slide pot. Low-profile, 8mm high body. Dual 10K audio taper. 5.05" x 0.64." Threaded mounting holes on 4.72" (120mm) centers. PC pins. Lever is 0.32" wide x 0.48" high. Ideal for faders and mixers.

CAT# ASP-10K \$1.75 each • 10 for \$1.50 each • 100 for \$1.20 each



PC MOUNT POTS

6mm diameter shafts, 0.5" long minimum. No Threaded bushing.



Resistance	Taper	Other desc	CAT #
5K	Linear	Center detent	LPB-5K
10K	Linear	Horizontal mount	LPBR-10K
10K	Linear		LPB-10K
10K	Audio		APT-10K
10K	Linear	Center detent	LPC-10K
10K	Linear	Dual pot	NDLP-10K
50K	Linear		LPB-50K
50K	Linear		LPP-50K
50K	Linear	Dual pot	DLPC-50K
100K	Audio		APT-100K

All pots above are 4 pcs of one CAT# for \$1.00
100 pcs of one CAT# \$ 15.00 (no mixing)

100K AUDIO TAPER MINIATURE THUMBWHEEL POT W/ SWITCH


Mouser # 31TV501 or equivalent. 16 mm mini-pot with 0.98" dia. black thumbwheel. SPST, on/off switch rated 1 amp @ 12 vdc.

CAT# TTP-100K 5 for \$1.00 • 100 for \$10.00



POTS WITH 1/4" DIA. SHAFT

All of the following pots have 1/4" dia. shafts and 3/8" dia.(3/8-32) threaded bushings. Unless otherwise specified, shafts may be full-round, half-round or knurled.



LINEAR POTS

Values: 15K, 2.5 Meg, 10 Meg.

CAT# LTP-xxx 50¢ each (xxx = value)

10K AUDIO TAPER POT

CAT# ATP-10K 50¢ each


2 MEG AUDIO TAPER

1/4" full round shaft, 3/8" long. ATP-2MS

3 for \$1.00 • 100 for \$25.00

BOURNS MODULAR CERMET POTS

Linear taper cermet pot. 0.5" square plastic body. Metal 3/8" bushing and 1/4" dia. x 0.27" long flatted shaft. PC pin-type leads can be wrapped and soldered.



500 ohm	CAT # PTB-500	\$ 1.00 each
5K ohm	CAT # PTB-5K	\$ 1.00 each
50K ohm	CAT # PTB-50K	\$ 1.00 each

POTS WITH 1/8" DIA. SHAFT

10K LINEAR


Bourns # 51CADE24A15. 0.5" square x 0.35" body. 0.125" dia. x 0.2" long shaft. 1/4-32 threaded bushing. **CAT# LPOT-10KB** \$1.00 each

2.5 MEG LINEAR

Clarostat # CM46945. 0.52" diameter x 0.47" long body. 0.125" diameter x 0.34" long shaft. 1/4-32 threaded bushing. **CAT# LPOT-2.5M** \$1.00 each

AB POTS WITH SWITCH

Series 70 Allen Bradley linear taper modular pots with S.P.D.T. on/off switch. 1/8" dia. x 0.25" long shaft. 1/4" (0.25") threaded bushing. Switch detent operative when pot is fully clockwise. Switch is removable. Two values available.




1K LINEAR CAT # LPS-1K
\$1.00 each • 10 for \$8.50

50K LINEAR CAT # LPS-50K
\$1.00 each • 10 for \$8.50

2 OHM 50 WATT RHEOSTAT


Ohmite Model J. 2.28" dia. x 1.25". 0.25" dia. shaft. 3/8-32 threaded bushing. These are new rheostats, but the ceramic on some is chipped due to improper storage. They are guaranteed functional. **CAT# RHE-25** \$5.50 each



MOTORIZED POTS


MOTORIZED 10K SLIDE POT

Panasonic # EVANMKP08B14
10K linear taper power fader. 100mm travel. 5 Vdc driving motor. Operates on 2 Vdc to 5 Vdc. 0.2 seconds travel time at 5 Vdc. Overall dimensions: 7.32" long x 0.6" wide. Motor, 0.95" diameter x 0.72". Threaded mounting holes on 5.27" centers. **CAT # MSP-10K** \$7.00 each
10 for \$6.75 each • 100 for \$6.00 each




DUAL 10K LINEAR TAPER

Alps Electric# 726T-10KBX2. Dual 10K linear pot powered by a small reversible DC gearhead motor. At 6 Vdc the pot varies from 0 to 10K ohms or vice versa in about 8 seconds. Pot and motor assembly are 1" square x 1.7" long excluding shaft & bushing. 6 mm flattened shaft is 0.5" long. 9mm threaded bushing. PC pins and mounting tabs for pc board mounting. Pins can be wrapped and soldered. **CAT # MPOT-10K** \$4.00 ea. • 10 for \$35.00



DUAL 20K LINEAR TAPER


Shokai # WHE1604A 2 X 20KB
Dual 20K linear pot. Powered by a small reversible DC gearhead motor. At 6 Vdc the pot varies from minimum to maximum resistance, or vice versa in about 8 seconds. Pot and motor assembly are approximately 1.7" deep, behind mounting plane. 6mm flattened shaft is 0.7" long. 9 mm threaded bushing. These are new pots, prepped with 2.5" wires and a connector. **CAT# MPOT-20K** \$4.00 ea. • 10 for \$35.00



PRECISION MULTI-TURN TRIMMERS

RECTANGULAR TRIMMER

0.75" X 0.19" high. 3/4 watt. Comparable to Bourns 3006P, Beckman 89PR, Weston 830P. 5K, 20K **CAT# RTP-xxx**
\$1.00 each (xxx = resistance)



SINGLE TURN TRIMMERS

VERTICAL THUMBWHEEL

3/16" spacing between outer leads. 1K, 20K, 25K **CAT# VTP-xxx**
(xxx = resistance) 10 of one value \$1.00
5/16" spacing between outer leads. 100, 250, 2K, 4K, 50K, 500K **CAT# TPK-xxx** 10 of one value \$1.00



SPECIAL !!! 500K trimmer
CAT# TPK-500K 200 for \$10.00 (5¢ each)

HORIZONTAL THUMBWHEEL

200, 1K, 50K, 200K, 250K, **CAT# HTP-xxx** 10 of one value \$1.00
(xxx = resistance)



47K TOP SCREW ADJUST

CAT# HMTP-47K 10 for \$1.00



SIDE ADJUST 3/8" square X 3/16" thick. 1K, 5K, 50K, **CAT# TTP-xxx** 2 for \$1.00



TOP ADJUST

3/8" square X 3/16" high. 1/2 watt. Comparable to Bourns 3386P, Beckman 72PR and Spectrol 63P. 100, 500, 2K, 50K **CAT# STP-xxx** 2 for \$1.00



500K OHM TOP ADJUST

CAT # TP-500K
4 for \$ 1.00



KNOBS

FITS 6mm Full Round Shaft

0.63" DIAMETER SKIRTED KNOBS

For pots with 6 mm diameter shaft. 0.6" high tapered knob with 0.63" dia. skirt. Raised grey or yellow pointer lines:



GRAY LINE **CAT # KNB-110G** 2 for \$ 1.00
YELLOW LINE **CAT # KNB-110Y** 2 for \$ 1.00

KNOB FOR 6 MM SHAFT

Daka-ware # 27. Black fluted knob with white pointer line on skirt. 1.13" skirt diameter. Knob is 0.84" diameter x 0.65" high. Press-on to 6mm dia. shafts. **CAT # KNB-107** 75¢ each
10 for \$ 6.50 • 100 for \$ 50.00



SKIRTED POINTER KNOB

Black fluted knob with 0.79" skirt, 0.67" high. Brushed aluminum face. White pointer line on one side. Brass insert with set screw. **CAT # KNB-118** 85¢ each
10 for 70¢ each • 100 for 60¢ each




For pots with 6 mm diameter shaft.
0.92" diameter x 0.85" high, black plastic
serrated knob. Face is black with white
pointer line and chrome circumference.
CAT# KNB-10 2 for \$ 1.00



KNOB FOR 1/4" FLATTED SHAFT

White plastic knob with serrated
rim. 1.25" diameter x 0.6" high.
Fits flattened 1/4" dia. shaft.



CAT # KNB-110 2 for \$1.00

KNOBES FOR 6MM HALF-MOON SHAFT

1" diameter, skirted black phenolic knob
with white pointer line and dot on skirt.
0.6" high. Press-on to 6mm and
1/4" diameter half-moon shafts.



CAT # KNB-109 2 for \$ 1.00
10 for \$ 4.00 100 for \$ 30.00

0.5" diameter x 0.57" high fluted black plastic
knob. Skirt is 0.6" diameter and has a 2mm
notch corresponding to the white pointer line
at the top of the knob.




CAT# KNB-34 3 for \$1.00 • 100 for \$25.00

HARDWARE

MOUNTING BRACKETS


GOOSENECK MOUNTING BRACKET (USED)

Versatile 10" long metal gooseneck bracket.
Ideal for automotive audio or communications
equipment. Matte black color. Bottom mounting
plate is 2.6" diameter with four mounting holes.
Top plate is 2" x 2.5" and has multiple holes to
accommodate various mounting configurations.
Top and bottom plates unscrew for convenient
attachment. Removed from automotive
application in good condition. May have minor
scratches. **CAT# FMB-10** \$5.00 each



"CLAM SHELL" MOUNTING BRACKET

A heavy-gauge steel bracket
designed for mounting communications
equipment in a vehicle. Adjustable
over 90 degrees. Pre-drilled holes in
top and bottom plates. Includes screws.



CAT # CMT-2 \$ 1.50 each

TILT AND SWIVEL BRACKET

Heavy plastic mounting bracket ideal for
mobile communications or audio
accessories. Top and bottom mounting
plates are 1.97" x 1.65" with holes in the
corners on 1.2" x 1.5" centers. 2" overall
height. Wide range of tilt and swivel
settings. **CAT# AMB-4** \$3.25 each



SPRING-RETURN CABLE REEL

Spring-driven reel keeps a constant
tension on plastic coated steel cable.
The cable is terminated with a metal
eyelet, and its extended length is 32".
The pull of the unit is approximately
1 3/4 lbs. The reel is housed in a sturdy
plastic case that is open on the back side
and is intended for mounting on a flat surface.
Overall dimensions are 2.38" x 2" x 0.7" thick.
Two mounting holes on 2.4" centers.
Removed from equipment.



CAT # RL-1 \$ 3.50 each

SPRINGS



COMP = compression spring

EXT = extension spring.

Length: coil length/overall length with loops

Dia.	Length	Type	CAT #	Price	100
0.2"	0.3"/0.7"	EXT	SPR-5	10 for \$1.00	\$6.00
0.48"	1.25"	COM	SPR-4	5 for \$1.00	\$10.00
0.4"	3.72"/4.45"	EXT	SPR-3	4 for \$1.00	\$15.00
0.37"	3.64"/5.4"	EXT	SPR-2	4 for \$1.00	\$15.00
0.35"	4"/6"	EXT	SPR-6	4 for \$1.00	\$15.00

WEBBED NYLON STRAP WITH BUCKLE

12" X 3/4" wide black
webbed nylon strap with plastic,
self-clinching buckle. Ideal for bundling wires, fishing
poles or skis. Great for fastening anything where
quick-lock and quick release is desirable. Takes the
place of Velcro™ straps in many applications.



CAT # WS-2 75¢ each • 20 for \$ 10.00

2" WEBBED NYLON STRAP & BUCKLE




Heavy-duty 2" wide black nylon webbed straps
(2 pcs), and nylon buckle. Buckle is designed for
quick fasten, release and easy adjustment of strap
length. Both straps are 23" long with hem on one
end. Great for quick, easy load fastening.

CAT# WS-3 \$1.75 each • 10 for \$15.00

CABINET LOCK

Two position lock with two "Ace"
style keys. Key removable in both positions.
Fits 0.75" dia. holes, flattened on one side.
Fastens with spring-clip. Fits doors up
to 1/8" thick. 0.85" diameter chrome bezel.




CAT # CL-4 \$1.50 each • 10 for \$ 12.50

VELCRO™

"WRAPPERS" REUSABLE VELCRO CABLE TIES


12.5" long x 0.5" wide "Velcro"(tm)
strap ideal for bundling wire or for strapping
together fishing poles, skis and other items.



CAT # WR-1 \$1.00 each • 10 for \$8.50

1.2" WIDE VELCRO STRIPS

- 1 8" loop strip,
nylon backed
- 1 1" loop strip,
adhesive backed
- 3 hook strips, adhesive backed, 4", 2.35", 2.35"



CAT # VCO-5 85¢ each • 10 for 75¢ each

BLACK CLAMP KNOB


1.25" diameter x 1" high. Shiny black
finish with knurled circumference.
Some scuffs and blemishes,
removed from equipment. Brass
insert tapped for 12-24 screw.



CAT# KNB-106 4 for \$1.00 • 100 for \$15.00

BOBBIN

Ho Sung International. EI-2820 nylon
bobbin. Core is 10 mm x 13 mm x 10 mm
high. Top is 18.5 mm x 21.5 mm. Base is
22 mm x 26 mm. Four leads, 15 mm and 20 mm spacing.
CAT# BN-1 10 for \$1.00 • 250 pieces 7¢ each
1000 pieces (5¢ ea.) • 5000 pieces 4¢ each



RUBBER FEET / BUMPERS

ADHESIVE BACKED

Remove from strip  and push onto chassis or whatever. SIZE: 7/16" dia. X 1/4".

CAT# RF-716 8 rubber feet \$1.00
40 rubber feet \$4.00

0.75" DIAMETER

0.75" dia. x 0.28" high black rubber foot. 0.36" dia. recessed hole accepts up to #8 screw.

CAT # RF-16 20¢ each • 100 for \$ 15.00

JUMBO RUBBER FEET

Good quality, high-density gray rubber feet with adhesive backing. Designed to support a computer monitor. 1.14" square top.

0.75" square at base. 0.88" high.

CAT# RF-10 4 for \$1.00 • 100 for 20¢ each

PHENOLIC CABINET FEET

Sturdy phenolic cabinet feet. Dark brown color. 0.87" high. 0.88" diameter at top. Tapers to 0.78" diameter at base.

Recessed mounting hole for #10 screw.

CAT # RF-17 20¢ each

100 for 15¢ each • 1000 for 10¢ each

WHEELS

4.6" DIAMETER WHEEL

A fairly rugged, light-duty wheel, similar to those found on baby strollers. 4.6" dia. x 1" wide. White rubber tire mounted on a dark blue unbreakable plastic rim. 0.25" bore.

CAT # WH-10 \$1.50 each

CASTERS

LIGHT-DUTY SWIVEL CASTER

1.25" diameter x 0.53" wide wheel on a ball bearing swivel. Ideal for light-duty loads, probably not exceeding 35 lbs per wheel.

CAT# CST-4 \$1.00 per caster
20 casters \$15.00

DUAL SWIVEL CASTERS

Light-duty, dual swivel casters.

1.53" diameter wheels.

1.96" x 1.19" metal mounting plate.

CAT # CST-5 \$1.00 each

10 for \$7.50 100 for \$60.00

COPPER STRIP

0.937" wide x 0.0162" thick solid copper strip for shielding, protection or decorative applications.

CAT# CT-8 75¢ per foot • 10' for 65¢ per ft.

GAS SPRING

Heavy-duty spring damper used to aid the opening and closing of doors and hatches. 6.75" extended, 5" compressed. Requires about 60 lbs. of pressure to compress. 0.7" diameter canister. Mounting ends are 0.14" thick and accept 0.25" screw or pin.

CAT# GS-3 \$1.50 each


10 for \$12.50 • 100 for \$100.00

RACK & CABINET HANDLES

RECESSED FLIP HANDLE

Heavy-duty black steel "flip" handle. Spring-loaded handle remains flat when not in use. 6.37" x 4.25." Recessed 0.25".


CAT # HDL-16 \$3.50 each



STEEL CABINET HANDLE

Heavy-duty black steel recessed handle for PA cabinets and other large cabinets and equipment. 8.63" x 6.32" x 2.28" deep.

CAT # HDL-17 \$4.50 each



1.7" HANDLE

0.75" high. 0.187" diameter aluminum stock. Threaded for 4-40 screws on 1.5" centers.

CAT # HDL-25 50¢ each



2.2" HANDLE

0.87" high. 0.187" diameter aluminum stock. Threaded for 4-40 screws on 2" centers

CAT # HDL-12 50¢ each



2.5" RACK HANDLE

1.15" high. 0.31" dia. brass handle with shiny nickel plated finish. Threaded for 8-32 screws on 2.50" centers.


CAT# HDL-23 \$1.00 each



3.2" HANDLE

0.75" high. 0.187" diameter steel stock. Shiny dark gunmetal enamel finish. Threaded for 4-40 screws on 3" centers.


CAT # HDL-13 \$1.00 each



3.2" HANDLE

0.985" high. 0.187" diameter aluminum handle. Threaded for 4-40 screws on 3" centers.


CAT # HDL-27 \$ 1.25 each



4" HANDLE

4.10" X 1.20" high shiny nickel-plated brass rack handle. Threaded for 8-32 screws on 3.75" centers.

CAT# HDL-24 \$1.25 each



4.29" RACK HANDLE

HH Smith # 1624. 1.5" high. 0.25" round, chrome plated brass handle. 8-32 mounting holes on 4" centers.

CAT# HDL-26 \$1.25 each



STEEL CABINET CORNER

Heavy-duty black steel corner. Protects and supports cabinets and equipment. Three hole mounting.

CAT # COR-303
65¢ each



CAPACITORS

RADIAL ELECTROLYTIC

Greatly reduced prices on most radial electrolytic capacitors

UF	Volts	1+	10+	100+
.22	50	.10	.06	.04
.47	50	.15	.13	.10
1	50	.15	.10	.06
2.2	50	.15	.10	.06
3.3	50	.12	.08	.05
4.7	50	.10	.08	.05
10	16	.10	.06	.04
10	35	.10	.08	.05
10	50	.12	.10	.06
22	25	.16	.14	.11
22	50	.10	.08	.05
33	25	.18	.14	.10
33	50	.22	.20	.18
47	10	.08	.04	.035
47	16	.15	.10	.07
47	35	.17	.15	.13
47	50	.10	.08	.05
100	16	.15	.12	.09
100	25	.20	.18	.15
100	50	.30	.25	.20
220	10	.10	.08	.05
220	35	.25	.22	.21
220	50	.25	.14	.12
220	100	.75	.65	.45
330	50	.28	.23	.15
470	16	.33	.25	.20
470	25	.30	.25	.15
470	50	.45	.40	.18
600	50	.30	.25	.20
1000	16	.40	.30	.25
1000	25	.45	.35	.30
1000	35	.48	.45	.40
1000	50	.80	.70	.25
1500	10	.40	.35	.20
2200	10	.20	.15	.08
2200	16	.60	.55	.45
2200	50	1.25	1.00	.85
3300	16	.75	.65	.45
3300	25	1.00	.80	.70
3300	50	1.50	1.20	1.00
4700	25	1.25	1.10	.95

100 VOLT NON-POLARIZED CAPS

MFD	CAT#	1-9	10+
1	NC-1	.50	.45
2.2	NC-2.2	.50	.45
3.3	NC-3.3	.50	.45
4.7	NC-4.7	.60	.50
6	NC-6	.65	.55
8	NC-8	.65	.55
12	NC-12	.80	.70
22	NC-22	.85	.75
33	NC-33	.90	.75
47	NC-47	1.30	1.10
50	NC-50	1.35	1.15
65	NC-65	1.70	1.50
80	NC-80	1.80	1.55
100	NC-100	1.80	1.55
125	NC-125	2.15	1.90
150	NC-150	2.50	2.20

HIGH VOLTAGE CAPS

22 UF 450 VDC

0.63" diameter X 1.6" long axial electrolytic capacitor.

CAT# 22/450VA \$1.25 each
10 for \$10.00 • 100 for \$80.00

33 UF 400 VDC

0.64" dia. x 1.05" long radial electrolytic.

CAT # 33/400VR \$1.15 ea.
10 for \$9.50 • 100 for \$85.00

47 UF @ 200 VDC

105° C 0.52" dia. x 1" long radial electrolytic. 0.2" lead spacing.

CAT# 47/200VR 2 for 90¢
100 for \$30.00 • 1000 for \$150.00

180 UF 400 VDC

Nichicon VZ(M). 105° C.
0.8" dia. x 1.63" long radial electrolytic. 0.4" lead spacing.

CAT# 180/400VR \$2.00 each
10 for \$17.50 each
100 for \$150.00

AXIAL SPECIALS

100 uf @ 16 Vdc Axial Cut and Bent leads

1" lead spacing., 0.32" dia. X 0.63"
CAT# 100/16VAS
100-499 9¢ ea. 500-999 7¢ ea.
1,000 + 5¢ each

3.3 UF @ 50 VDC AXIAL

0.2" diameter x 0.5" long.

CAT # 3.3/50VA
5 for 50¢ • 100 for \$5.00
500 for \$15.00 • 1000 for \$20.00

PHOTOFLASH CAPS

150 UF, 360 VOLT

Samwha # FDA
0.59" diameter x 1.59" long.

CAT # PPC-1536
75¢ each

200 UF, 360 VOLT

Rubycon# CE0.
0.64" diameter x 1.8" long.
CAT # PPC-2036 \$1.25 ea.

410 UF, 300 VOLT

Rubycon # 1A2304A. 0.7" dia. X 1.7" long. Right angle PC or solder leads on 0.25" centers.
CAT# PPC-410 \$2.00 each
10 / \$18.50 • 200 / \$320.00

RADIAL SPECIAL

470 UF 50 VOLT RADIAL CAT# 470/50VR

100 for 18¢ each
1000 for 15¢ each

1000 UF 100 VOLT

0.72" dia. x 1.61" Radial leads on 0.3" centers.

CAT # 1000/100VR
\$1.00 each 10 for 85¢ each
100 for 65¢ each

SNAP-IN CAPACITORS

39 UF 400 VDC

Nichicon CEGJ
105° C.
0.875" diameter x 0.643" high. 0.4" pin spacing.
CAT # EC-3940 85¢ each

180 UF 400 VDC

Nippon Chemi-Con SMM.
85° C. 1.19" diameter x 1.03" high. 0.4" pin spacing.
CAT # EC-1840 \$2.00 ea.

330 UF 400 Vdc

BHC Aerovox #
ALC10D1001DF
-10 +30%. 1.4" diameter x 2" high. 0.4" pin spacing.
CAT # EC-3341
\$2.50 each

330 UF 450 VDC

Nichicon. 85° C
1.18" dia. x 2.03" high.
CAT # EC-3345
\$2.75 each

560 UF 400 Vdc

NICHICON CE 85° C LQ (M)
1.39" diameter X 1.83" h.
0.4" lead spacing.
CAT# EC-5640 \$4.00 each
10 for \$3.75 each
100 for \$3.00 each

1000 UF 200 VDC

Nippon Chemi-con SMH.
85° C. 1.19" dia. x 1.61" high.
0.4" lead spacing.
CAT # EC-1020
\$2.00 each

1800 UF 200 Vdc

Marcom # DUF-M.
105° C. 1.4" dia. x 2" high.
0.4" pin spacing.
CAT # EC-1820
\$3.25 each

3300 UF 50 Vdc

Nippon Chemicon SME

85° C. 1.2" dia. X 1.03" h.

CAT# EC-3500 \$1.00 each

6800 UF 25 Vdc

TSNH CE. 1" dia. X

1.59" high. 105° C

CAT# EC-6825 \$1.25 each

10,000 UF 16 Vdc

TSNH CE. 1" dia. X

1.59" high. 105° C

CAT# EC-1016 \$1.50 each

680 UF 40 VDC CAPACITOR SWITCHING POWER GRADE


Cornell Dubilier
#300681M040JE8

Long life, ultra-low ESR capacitor designed for switching power supplies and UPS battery stiffening applications. 20% tolerance. 105° C. 1" diameter x 1.23" high.

Three leads for stability and reverse-proof mounting.

CAT # EC-684 65¢ each

100 for 40¢ each



1 FARAD 2.5 VOLT AERO- GEL SUPERCAPACITOR

PowerStor (tm) # B0810-2R5105

In addition to battery back-up applications, these capacitors can be used to provide short, high-current pulses for electronic and electro-mechanical applications.

Features include: Extremely low ESR. Ultra low leakage current - can hold a charge for several weeks. Very high charge-discharge cycle life. High usable capacity - high energy that can be discharge quickly.

0.33" diameter x 0.47" high.

0.16" (4mm) cut & bent pc leads.

CAT # CBC-125 \$1.00 each

10 for 85¢ each • 100 for 70¢ each



1 FARAD 5.5 VOLT MEMORY BACK-UP CAPACITORS

Super high capacitance capacitors, excellent for memory back-up in CMOS type RAM. Two styles:

0.8" dia. x 0.29" high.

PC leads on 0.2" centers.

CAT # CBC-11 \$ 3.75 each

10 for \$ 3.50 each

100 for \$ 3.00 each



Vertical Mount. 0.18" thick x 0.74" diameter. PC leads on 0.2" centers. **CAT# CBC-12**

\$3.75 each • 10 for \$3.50 each

100 for \$ 3.00 each



Special Pricing - Monolithic Ceramic Capacitors

CAPACITORS LISTED BELOW MAY HAVE LONG LEADS OR PC CUT LEADS. WE CANNOT GUARANTEE LONG LEADS. CUT LEADS ARE ADEQUATE FOR PC BOARD INSERTION OR BREADBOARDING.

ALL ARE 50 VOLTS OR MORE

RADIAL MONOLITHICS

220 pf **CAT # RM-221**

680 pf **CAT # RM-681**

1000 pf **CAT # RM-102**

0.01 uf **CAT # RM-103**

0.022 uf **CAT # RM-223**



AXIAL MONOLITHICS

18 pf **CAT # AM-180**

680 pf **CAT # AM-681**

4700 pf **CAT # AM-472**

1000 pf **CAT # AM-102**



Any of the above - single value, no mixing for quantity pricing.

20 for \$1.00 • 100 for \$4.00

500 for \$15.00 • 1000 for \$20.00

0.1 mfd 25 Volt Axial

Monolithic

0.15" dia. X 0.39" long.

CAT# MCB-104

10 for \$1.00 • 100 for \$7.00

CERAMIC DISC CAPS

25 VOLT

CERAMIC DISC



0.1 UFD **CAT# DC-104**

10 for \$1.00

100 for \$8.00 • 1000 for \$35.00

50 VOLT CERAMIC DISC

When ordering

use **CAT# DISC**

Followed by value desired.

Prices for disc caps

(except 0.1 mfd) are:

10 PCS. ONE VALUE 60¢

100 PCS. ONE VALUE \$5.00

1000 PCS. ONE VALUE \$35.00

10pf	15pf	47pf	100pf	150pf
220pf	270pf	300pf	330pf	470pf
560 pf	820pf	3300pf	.001	.0015
.0018	.002	.0047	.005	.01
.015	.047			



.1 MFD 50 VOLT DISC

CAT# DISC.1 10 for \$1.00

100 for \$8.00 • 1000 for \$65.00

1,000 VOLT CERAMIC DISC

When ordering use **CAT# HVDC**

followed by value desired.

Prices for 1000 volt disc

capacitors (except .01) are:

10 Pieces of ONE VALUE \$1.00

5pf	10pf	15pf	100pf
200pf	220pf	680pf	

.01 uf 5 for \$1.00

5pf 3KVdc **CAT# HVD-5**

10 for \$1.00 100 for \$8.00

.001 UF 10 KV AXIAL CERAMIC DISC CAPACITOR



Matsushita

ECK-D4A102MDA

0.78" diameter x 0.25" thick

CAT # HVD-102 \$1.00 ea.

10 for \$8.50 • 100 for \$70.00

MOTOR STARTER/ RUN CAPACITORS

2 UF 400 VAC

AEG Telefunken

METALIZED PAPER

AB MP 2/400 Aluminum

case with screw and nut on

top. 1" dia. x 2.93" high.

0.25" qc or solder terminals.

CAT# MPC-240 2 for \$1.00



TRIMMER CAPACITORS

0 - 3 PF TRIM CAP

CTC-05RA

PC leads on 0.2" centers.

CAT# VCAP-16 2 for \$1.00



2 - 18 PF

0.25" square x 0.35" high.

PC leads on 0.2" centers.

CAT # VCAP-18 2 for \$1.00

100 for \$40.00 (40¢ each)

700 for \$210.00 (30¢ each)



5 - 65 PF PC MOUNT

0.38" diameter x 0.42".

Three pc leads.

CAT # VCAP-15

\$1.00 each




10-62 pf

Screw adjust.

1" X 0.47"

CAT# VCAP-12

\$1.25 each



METALIZED POLYPROPYLENE CAPACITORS

5 UF - 280 VAC

ASC# BP103

1.2" X 0.85" X 1.75" long.

CAT # MKP-500

\$1.50 each

7 UF - 250 VAC

Aerovox # W43B2507E

1.05" diameter x 1.91" long.

CAT # MKP-700

\$2.00 each

10 uf - 175 VAC

Aerovox Type ARPM

0.94" diameter x 1.74" long.


CAT# MKP-1001

\$2.50 each

100 VOLT POLYESTER




(RADIAL)



MFD	CAT#	1+	10+	100+	1000+
.001	RMC-102	.10	.08	.06	.05
.0015	RMC-152	.10	.08	.06	.05
.0047	RMC-472	.10	.08	.06	.05
.01	RMC-103	.12	.09	.07	.06
.022	RMC-223	.12	.09	.07	.06
.027	RMC-273	.15	.11	.08	.07
.047	RMC-473	.15	.11	.08	.07
.068	RMC-683	.17	.12	.09	.08
.082	RMC-823	.17	.12	.09	.08
.1	RMC-104	.17	.12	.09	.08
.15	RMC-154	.20	.13	.10	.09
.22	RMC-224	.25	.19	.17	.15
.47	RMC-474	.40	.32	.29	.25

MYLAR CAPACITORS

(AXIAL STYLE)



MFD	VOLT	TOL	CAT#	PRICE
.0015	100	20%	AMC-3	4 for \$1.00
.0022	100	10%	AMC-5	4 for \$1.00
.0047	200	20%	AMC-8	4 for \$1.00
.0068	200		AMC-10	4 for \$1.00
.022	100	1%	AMC-17	4 for \$1.00
.033	100		AMC-77	4 for \$1.00
.033	200		AMC-19	3 for \$1.00
.047	100	10%	AMC-20	4 for \$1.00
.04	100		AMC-191	4 for \$1.00
.056	100	3%	AMC-22	4 for \$1.00
.082	100	5%	AMC-25	4 for \$1.00
.1	100	10%	AMC-27	3 for \$1.00
.18	160	10%	AMC-49	3 for \$1.00
.22	50	5%	AMC-33	4 for \$1.00
.22	100	5%	AMC-71	3 for \$1.00
.47	200	10%	AMC-38	3 for \$1.00
.56	800		AMC-568	\$1.00
.65	200	5%	AMC-42	3 for \$1.00
.68	50	5%	AMC-72	3 for \$1.00
.68	100	10%	AMC-43	3 for \$1.00
1.33MF.	250		AMC-46	2 for \$1.00

RADIAL MYLAR

**NEW LOWER PRICING ON
MOST RADIAL MYLARs!**

MFD	VOLT	CAT#	PRICE
68pf	50	RMC-1	7/\$1.00
.0043	1500	RMC-43	5/\$1.00
.022	630	RMC-51	5/\$1.00
.0299	50	RMC-315	6/\$1.00
.039	50	RMC-100	6/\$1.00
.082	400	RMC-30	6/\$1.00
.2	50	RMC-19	6/\$1.00
.47	250	RMC-85	6/\$1.00
.47	400	RMC-50	4/\$1.00
.82	150	RMC-82	4/\$1.00

DIPPED TANTALUM

Value MFD	Voltage VDC	CAT#	PRICE
0.1	35	DT-1	4 for \$1.00
1	35	DT-25	3 for \$1.00
3.3	10	DT-35	5 for \$1.00
3.3	25	DT-3325	3 for \$1.00
15	25	DT-1525	2 for \$1.00
22	16	DT-2216	2 for \$1.00
22	25	DT-2225	2 for \$1.50
33	16	DT-3316	2 for \$1.35
47	16	DT-4716	2 for \$1.35
47	25	DT-4725	2 for \$1.75

2 UF, 200 VOLT METALIZED POLYESTER

TRW # M446.

1.1" lead spacing.

0.4" long leads.

Body size: 1.27" x

0.54" x 0.4". Large

quantity available.

CAT # RMC-220

10 for \$1.50


100 for \$10.00

500 for \$40.00

1000 for \$70.00

5000 for \$250.00

500 PIECE 1/4 WATT RESISTOR ASSORTMENT



4.7 ohms to 10 Meg ohm, 5% resistors. 54 of the most popular values. 20 pieces each of the most popular values, 1K, 2.2K, 4.7K, 10K, 22K, 47K, 100K. 5, 10 or 15 pieces of other values depending on popularity.

CAT # RES-54

\$ 8.95 per 500 pc assortment

1/4 & 1/2 WATT RESISTORS 5% CARBON FILM

1/4 WATT RESISTORS

Minimum order is

10 PIECES OF

ONE VALUE.

10 PIECES of ONE
VALUE 50¢

100 PIECES of ONE
VALUE \$3.00

200 PIECES of ONE
VALUE \$4.00

1,000 PIECES of
ONE VALUE \$10.00

1/2 WATT RESISTORS

Minimum order is

10 PIECES OF

ONE VALUE.

10 PIECES of ONE
VALUE 50¢

100 PIECES of ONE
VALUE \$3.50

200 PIECES of ONE
VALUE \$4.50

1,000 PIECES of ONE
VALUE \$12.00

1.0	20	300	3.9 K	51 K	680 K
1.5	24	330	4.3 K	56 K	750 K
1.8	27	360	4.7 K	62 K	820 K
2.0	30	390	5.1 K	68 K	910 K
2.2	33	430	5.6 K	75 K	1.0M
2.4	36	470	6.2 K	82 K	1.1 M
2.7	39	510	6.8 K	91 K	1.2 M
3.0	43	560	7.5 K	100 K	1.3 M
3.3	47	620	8.2 K	110 K	1.5 M
3.6	51	680	9.1 K	120 K	1.6 M
3.9	56	750	10 K	130 K	1.8 M
4.3	62	820	11 K	150 K	2.0 M
4.7	68	910	12 K	160 K	2.2 M
5.1	75	1.0 K	13 K	180 K	2.4 M
5.6	82	1.1 K	15 K	200 K	2.7 M
6.2	91	1.2 K	16 K	220 K	3.0 M
6.8	100	1.3 K	18 K	240 K	3.3 M
7.5	110	1.5 K	20 K	270 K	4.7 M
8.2	120	1.6 K	22 K	300 K	5.1 M
9.1	130	1.8 K	24 K	330 K	5.6 M
10	150	2.0 K	27 K	360 K	6.2 M
11	160	2.2 K	30 K	390 K	6.8 M
12	180	2.4 K	33 K	430 K	7.5 M
13	200	2.7 K	36 K	470 K	8.2 M
15	220	3.0 K	39 K	510 K	9.1 M
16	240	3.3 K	43 K	560 K	10 M
18	270	3.6 K	47 K	620 K	

POWER RESISTORS

POWER RESISTOR PRICING

1 - 5 watts

3 for \$1.00

6 - 10 watts

2 for \$1.00

11 - 25 watts


\$1.00 each

50 watts


\$2.00 each

100 watts

\$3.00 each




flat ceramic



ceramic



axial



sand

ohms	watts	style	ohms	watts	style
.05	5	sand	2	5	axial
.1	10	axial	2	10	axial
.1	10	sand	2.5	50	sand
.12	7	axial	7.5	5	sand
.2	5	sand	10	100	ceramic
.22	3	sand	12	3	sand
.47	2	sand	20	7	sand
.47	5	sand	30	5	axial
.5	3	axial	35	10	ceramic
.5	4	axial	40	10	sand
.5	5	axial	60	5	sand
.51	5	axial	80	10	ceramic
.75	5	axial	82	5	sand
.75	5	sand	165	5	sand
.75	10	sand	180	5	sand
1	5	sand	200	5	axial
1.2	4	axial	220	3	axial
1.3	5	axial	240	5	sand
1.5	2	axial	300	5	sand
1.5	5	sand	390	7	sand
1.8	2	sand	680	3	axial
			2.7K	5	sand

SPEAKERS

3/4" 30 OHM SPEAKER

3/4" speaker with polypropylene cone. Cone is covered with a metal plate with four holes. Prepped for use in cell phones with foam gasket on perimeter of face and double-side sticky tape on back. 30 ohm coil. 1" pigtail leads.

CAT # SK-17 75¢ each • 100 for \$ 50.00
1000 for \$ 350.00



1" SPEAKER WITH POLYPROPYLENE CONE

8 ohm, 0.1 watt speaker with clear polypropylene cone. Only 0.15" thick. Good sound quality for its size. Large quantity available.

CAT # SK-218 \$1.00 each • 10 for \$8.50
100 for \$70.00 • 1000 for \$500.00



1" ENCASED SPEAKER

Hakuto # HSM30A-81. 8 ohm, 0.15 Watt speaker in black plastic enclosure. Frequency response 600-5000 Hz. 1.16" diameter x 0.47" high. PC leads on 0.6" centers. In addition to protecting the speaker, the enclosure enhances the speaker's resonance. Large quantity available.

CAT # SK-94 \$ 1.25 each
10 for \$ 1.10 each 100 for 85¢ each



1 3/16" (30 mm) SPEAKER

M&G # AZ-30S
Very thin 8 ohm, 0.4 watt speaker. 1.19" square x 0.21" thick.

CAT# SK-14 \$1.00 each • 100 for \$70.00



1.5" 8 OHM SPEAKER


ICC # S150-RMF. Low-profile 8 ohm speaker. 1.5" clear poly cone. 1.57" dia. x 0.37" thick overall. **CAT # SK-158** \$1.25 each



2" 8 OHM SPEAKER

Mouser # 25SP003.
2" square frame x 0.75" depth. 8 ohm coil. 0.2 watt. Alnico magnet. Prepped with 7" leads.

CAT # SK-96 \$ 1.50 each



2 1/4" SPEAKER, 8 OHM

CAT# SK-214
\$1.25 each



THIN 2.25" SPEAKER, 8 OHM

Thin 2.25" 8 ohm 0.2 Watt speaker. Prepped with 6" leads with 2 pin socket connector (0.1" spacing). 0.37" overall thickness.

CAT # SK-97 \$ 1.00 each
10 for 80¢ each • 100 for 60¢ each



2 1/4" SPEAKER, 32 OHM

0.38" thick. **CAT# SK-232**
75¢ each • 100 for 55¢ each
1000 for 25¢ each



2 1/2" 4 OHM

2 1/2" cone, 0.5 watt 4 ohm imp. 7 1/2" leads. **CAT# SK-254**
75¢ each 100 for \$55.00
Case of 360 - \$162.00 (45¢ each)




2 1/2" 8 OHM

Panasonic# EAS65P76A3
8 ohm 0.4 watt speaker with soft-edge paper cone for improved sound quality. 0.93" overall depth. 2.25" wire leads with 2 prong (0.1" spacing) socket connector. Large quantity available. **CAT # SK-255** \$1.00 each
10 for \$6.00 • 100 for \$40.00

SHIELDED 2.75" FULL RANGE SPEAKER

Made for Bose for use in one of their systems. 2.75" full range speaker. Shielded magnet. Crisp, clean output. Ideal for surround sound applications. 8 ohm 8 oz speaker. 2.75" square x 1.65" deep. Mounting holes on 2.15" centers. **CAT # SK-95** \$6.95 each




1.5" X 3.5" OVAL SPEAKER

12 ohm 6 watt speaker with shielded magnet. 1.8" overall thickness. Mounting holes on 4.4" centers. New speaker, but the gasket on the mounting surface is imperfect.

CAT# SK-89 \$1.00 each


REDUCED PRICE!



3" 8 OHM SPEAKER

8 Ohm, 3.5 Watt full range speaker. Paper cone with a flexible edge for low range response. Metallized dome for improved highs. 1.75" dia. magnet.

CAT # SK-92 \$1.50 each




MID RANGE SPEAKERS

5.25" 50 WATT MIDRANGE SPEAKER

5.25" dia. closed back midrange speaker. 8 ohms. 0.75" voice coil. 10 oz magnet. Rolled foam edge. 50 Watts RMS. 550 - 15 KHz. 92 dB @ 1W/ 1m.


CAT# GM-658 \$5.50 each



5.25" 60 WATT MIDRANGE SPEAKER

5.25" dia. closed back midrange speaker. 8 ohms. 1" voice coil. 12 oz magnet. Poly-mica cone with rolled foam edge. 60 Watts RMS. 500 - 15 KHz. 96 dB @ 1W/ 1m.

CAT# GM-858 \$6.95 each



WOOFERS

4" 40W SHIELDED WOOFER, 8 OHM

8 ohm impedance. Rolled foam edge with poly laminated cone. Shielded for use with computers or video. 11 oz magnet. 1" voice coil. 40 Watts / 70 Watts max. 70 - 10 KHz frequency response. 83 dB @ 1W/ 1m.


CAT# GW-2048 \$7.50 each



PEERLESS 5" SPEAKER

High-quality 5" 4 ohm full range speaker made by Peerless Speaker Company of Denmark. Clear, crisp sound reproduction. Features a polymer cone with rolled rubber edge surround, 1" voice coil and a cloth spider. Dual field-canceling magnets for use with video equipment. No specs available - approximately 50W power. Outer dimensions: 5" x 5" x 2.75" deep.


CAT # SK-405 \$12.00 each



5.25" 70W SHIELDED WOOFER, 8 OHM

8 ohm impedance. Rolled foam edge with poly laminated cone. Shielded for use with computers or video. 16 oz magnet. 1" voice coil. 70 Watts / 130 Watts max. 62 - 9 KHz frequency response. 84 dB @ 1W/ 1m.


CAT# GW-2058 \$8.50 each



6.5" 90 WATT WOOFER, 8 OHM

Poly-mica cone with rolled rubber edge. 20 oz magnet. 1.5" diameter hi-temp voice coil. 90 Watts / 170 Watts max. 41 - 8 KHz frequency response. 85 dB @ 1W/1m.


CAT # GW-6028 \$ 16.50 each



6.5" 90 WATT WOOFER, 8 OHM

Polymer laminated cone with rolled foam edge. 20 oz magnet. 1.5" diameter voice coil. 90 Watts / 180 Watts max. 56 - 8 KHz frequency response. 88 dB @ 1W/ 1m.

CAT # GW-2068 \$ 11.95 each



8" 100W WOOFER, 8 OHM

8 ohm impedance. Rolled foam edge with poly laminated cone. 20 oz magnet with vent and bumper plate. 1.5" voice coil. 100 Watts / 200 Watts max. 45 - 6 KHz freq. response. 87 dB @ 1W/ 1m.


CAT# GW-2088 \$12.95 each



8" 100W WOOFER, 8 OHM

8 ohm impedance. Rolled rubber edge with poly-mica cone. 20 oz magnet with vent and bumper plate. 1.5" voice coil. 100 Watts / 190 Watts max. 35 - 8 KHz freq. response. 84 dB @ 1W/ 1m.


CAT# GW-8028 \$17.50 each



10" 110W WOOFER, 8 OHM

8 ohm impedance. Rolled foam edge with poly-laminated cone. 20 oz magnet with vent and bumper plate. 1.5" voice coil. 110 Watts / 220 Watts max. 40 - 5 KHz freq. response. 90 dB @ 1W/ 1m.


CAT# GW-2108 \$15.95 each



10" 130W WOOFER, 8 OHM

8 ohm impedance. Rolled rubber edge with poly-mica cone. 30 oz magnet with vent and bumper plate. 1.5" voice coil. 130 Watts / 250 Watts max. 29 - 7 KHz freq. response. 86 dB @ 1W/ 1m.


CAT# GW-1038 \$31.75 each



12" 120W WOOFER, 8 OHM

8 ohm impedance. Rolled foam edge with poly laminated cone. 20 oz magnet with vent and bumper plate. 1.5" voice coil. 120 Watts / 240 Watts max. 34 - 2 KHz freq. response. 88 dB @ 1W/ 1m.


CAT# GW-2128 \$18.95 each



12" 150W WOOFER, 8 OHM

8 ohm impedance. Rolled rubber edge with poly-mica cone. 40 oz magnet with vent and bumper plate. 2" voice coil. 150 Watts / 290 Watts max. 18 - 5 KHz freq. response. 87 dB @ 1W/1m.

CAT# GW-1248 \$36.95 each



TWEETERS

1.83" DIA. TWEETER

on a 3.08" x 4.42" flat black mounting plate. Mounting holes 2.5" x 2.82" centers.

CAT # SK-19 \$1.50 each



1 3/4" TWEETER W/CROSSOVER

Ford # F6DF-18808-AB Automotive tweeter with 24 uF in-line crossover capacitor. Covered with a black metal grill. Mounting holes on 2.35" centers.


CAT # SK-47 \$ 1.50 each



3.75" SQUARE DOME TWEETER

3.75" square tweeter. 8 ohm. Pure titanium dome. 8 oz magnet. 1" voice coil. 60 Watts @ 5KHz. 3.5 - 25 KHz. 94 dB @ 1W/ 1m.


CAT# GT-322 \$7.50 each



3 5/8" ROUND DOME TWEETER

3 5/8" diameter tweeter. 8 ohm. Pure titanium dome. 8 oz magnet. 1" voice coil. 60 Watts @ 5KHz. Frequency response, 3.5K - 25 KHz. 94 dB @ 1W / 1m.


CAT# GT-324 \$7.50 each



3.25" SQUARE PIEZO

3.25" square, wide dispersion tweeter. 50 Watts RMS. Frequency response, 3.5K - 27 KHz. 94 dB @ 1W/ 1m.


CAT# GT-1005 \$3.75 each



3.5" ROUND PIEZO

3.5" diameter, wide dispersion piezo tweeter. 60 Watts RMS @ 5 KHz. Frequency response, 3.5 - 30 KHz. 96 db @ 1W/ 1m.

CAT# GT-1056 \$3.50 each




3" X 7" PIEZO

TWEETER HORN

3" X 7" wide dispersion horn tweeter. 60 Watts RMS. Frequency response, 1.8K - 30 KHz. 90 dB @ 1W/ 1m.

CAT# GT-1025 \$4.25 each




INEXPENSIVE 2 WAY CROSSOVERS

2.75" x 2.75" x 0.65".

Specs unknown.

CAT # LX-156 75¢ each

10 for 60¢ each • 100 for 40¢ ea.




WEATHERIZED SPEAKERS

Weatherized stereo speakers for indoor or outdoor use.

Ideal as rear channel home theater speakers.

4" poly-propylene woofer, 2" mylar midrange and 3/4"

dome tweeter in a cast aluminum cabinet. 6 ohm impedance. Includes mounting bracket. Cabinet size 7.38" x 4.63" x 4.13". 50 Watts per speaker.



Black Cabinet.

CAT# DPI-60B \$49.00 per pair

White Cabinet.

CAT# DPI-60W \$49.00 per pair

SPEAKER TERMINALS

Red and black spring loaded terminals, marked - and +, generally used to connect speaker wires to speaker. Mounts in 1.85" dia. hole. Solder or quick connect terminals.

CAT# SLT-2 75¢ ea. 10 for \$6.50



SPEAKER TERMINAL, GOLD BANANA JACKS

3" round recessed assembly.

Knurled, gold plated knobs and

jacks. Knobs have color stripe for

polarity. Can be used with dual banana

plugs or up to AWG 12 wire. Fits 1.94" diameter

cut out. Four screw mounting. Foam gasket.

CAT# SWT-500 \$2.25 each



COMMUNICATIONS SPEAKERS

Extension speaker for Ham, CB, marine radio or business communications improves

clarity in noisy environ-


ments. 4 ohms. Black

case grill and adjustable

mounting bracket. 5.5' cord with 3.5 mm

mini plug. 3.18" x 2.72" x 1.8" deep.

CAT# SK-664 \$6.00 each



Nokia #HFS-12

8 Ohm extension

speaker with 5' cord


terminated with 3.5mm

mini-phone plug. Adjustable

mounting bracket. Speaker

dimensions: 4.2" x 2.14" x 2.34."

CAT # SK-308 \$ 6.50 each



4 Ohm extension speaker.


3.15" x 3.15" x 2.37" deep.

Adjustable mounting bracket.

6' cord with 3.5mm

mini-phone plug.

CAT# SK-906 \$6.50 each



SPEAKER CIRCUIT BREAKERS

Auto reset breakers interrupt circuit when overloaded, then reset when temperature drops back to normal. Leads can be soldered or pc mounted.

CAT # CBR-1 1 AMP 2 for \$ 1.00

CAT # CBR-1.25 1.25 AMP 2 for \$ 1.00



TRIPOD SPEAKER STAND

Folding, adjustable-height tripod

stand. Sturdy polished aluminum

construction. 1" diameter upright.

No assembly required.

Extends to a maximum height 72."

CAT # SKS-1 \$30.00 each




120 VAC - 220 VAC - 110 VAC STEP-UP/STEP-DOWN TRANSFORMERS

AUTOFORMER --CAN BE USED EITHER WAY Convert 110 Vac to 220 Vac, or 220 Vac to 110 Vac. Three styles:

All three styles include adaptors and/or switches to allow use either way. For use in Britain and the UK, CAT # CP-3 adaptor required.


Style A -Primarily for American use. Has a standard American 3-prong plug.

max. wattage	weight	size	CAT#	Price
100 WATT	4 lbs.	5.30" X 3.25" X 5"	TC-100A	\$ 25.00
200 WATT	5 lbs.	5.25" X 3.25" X 5"	TC-200A	\$ 30.00
300 WATT	8 lbs.	6.25" X 3.82" X 4.47"	TC-300A	\$ 40.00
500 WATT	9 lbs.	7" X 3.82" X 4.47"	TC-500A	\$ 54.00
1000 WATT	18 lbs	9" X 4.8" X 6.15"	TC-1000A	\$ 80.00



Style E - Primarily for Europe and 220 Volt countries. Has a 2-prong (round pin) plug.


max. wattage	weight	size	CAT#	Price
100 WATT	5 lbs.	5.5" X 3.5" X 4"	TC-100E	\$ 25.00
200 WATT	6 lbs.	6" X 3.5" X 4.05"	TC-200E	\$ 30.00
300 WATT	8 lbs.	6.25" X 3.82" X 4.44"	TC-300E	\$ 40.00
500 WATT	9 lbs	7" X 3.82" X 4.47"	TC-500E	\$ 54.00



Style Universal - Cord with 2-prong plugs. Includes adaptors for 110 Volt use.

Has mounting feet for internal use in equipment.

max. wattage	weight	size	CAT#	Price
100 WATTS	3 lbs.	2 3/4" X 3 1/2" X 3 1/4" high	TC-100	\$20.00
200 WATTS	4 lbs.	2 3/4" X 4" X 3 1/4" high	TC-200	\$27.00
300 WATTS	5 1/2 lbs.	3" X 4" X 3 1/2" high	TC-300	\$37.50
500 WATTS	8 1/2 lbs.	3 1/4" X 5 1/2" X 4" high	TC-500	\$50.00
1300 WATTS	16 1/2 lbs.	4 3/4" X 7" X 5 1/2" high	TC-1300	\$85.00
2000 WATTS	29 lbs.	4 3/4" X 9" X 5 1/2" high	TC-2000	\$105.00
3000 WATTS	45 lbs.	8" X 13" X 7 1/4" high	TC-3000	\$175.00



No Hassle Return Policy


Page 71

PROJECT ENCLOSURES



MINI-ABS CASES

Black or gray ABS plastic with interlocking lid. Integral standoffs for pc board mounting. Lid held in place with self-tapping #4 screws (included).



1.97" x 1.38" x 0.8"

CAT # 1551-GGY Gray \$ 1.00 each

CAT # 1551-GBK Black \$ 1.00 each

2.36" x 1.38" x 0.8"

CAT # 1551-HGY Gray \$ 1.20 each

CAT # 1551-HBK Black \$ 1.20 each

3.15" x 1.57" x 0.8"

CAT # 1551-KGY Gray \$ 1.30 each

CAT # 1551-KBK Black \$ 1.30 each


HAND-HELD CASES with BATTERY COMPARTMENTS

Hammond Mfg. 1593 series. Black ABS plastic cases with removable front panels and panel for battery compartment. Integral pc board standoffs. Includes self-tapping screws. Five sizes available:



CAT #	Dimensions	1-9	10+
1593-PBK	2.6" x 3.54" x 1.1"	3.00	2.80
1593-QBK	2.6" x 4.4" x 1.1"	3.40	3.05
1593-SBK	2.6" x 3.6" x 0.83"	2.80	2.60
1593-TBK	2.6" x 4.35" x 0.83"	3.25	3.00
1593-YBK	2.6" x 5.45" x 1.1"	3.90	3.55

6.7" x 3.33" x 1.35" light-gray polystyrene case. Designed as a hand-held instrument enclosure. Built-in pc card standoffs and vertical card guides. Recessed top panel for membrane display or keypad. Lap joint construction. Self-tapping screws included.




CAT # 1599-ESGY

\$3.50 each • 10 for \$ 30.00

GENERAL PURPOSE CASES


Black ABS cases with countersunk lid secured with self-tapping screws. Slots for mounting pc boards.



CAT #	Dimensions	1-9	10+
1591-MSBK	3.3" x 2.2" x 1.4"	2.80	2.45
1591-ASBK	3.9" x 2.0" x 0.8"	3.10	2.80
1591-BSBK	4.4" x 2.4" x 1.2"	3.35	3.00
1591-CSBK	4.7" x 2.6" x 1.55"	3.55	3.20

INSTRUMENT CASES


Gray ABS plastic. Two piece tongue and groove construction. 0.064" brushed aluminum front and rear panels. Integral pc standoffs. Front and rear vertical pc board guides.



CAT #	Dimensions	1-9	10+
1598-ASGY	6.1" x 3.65" x 1.36"	7.25	6.50
1598-BSGY	5.26" x 5.3" x 2"	8.00	7.20

BULKHEAD MOUNT CHASSIS BOXES


Black, break-resistant plastic chassis box, originally designed for an auto alarm. 5.18" X 3.36" X 1.25". Box has a matte black finish with a ribbed top and mounting flanges with holes on 5.5" centers. 0.5" X 2.25" slot in one end of box is handy for power cord or wiring harness. Two halves of box screw together with sheet metal screws (screws not provided).



CAT# MB-31 \$1.35 each

WALL-MOUNT BOX


Black, wall-mount chassis box. 6.375" x 3.75" x 2.28". 0.14" thick break-resistant plastic. Back panel has six holes for terminals along bottom edge which are not visible when box is wall-mounted. Back panel interlocks with front cover of box. A real solid, good-looking box. Maybe slightly blemished.



CAT # MB-80 \$2.50 each • 10 for \$20.00

PROJECT ENCLOSURES

Heavy-duty 3/32" molded plastic boxes with aluminum covers. Boxes have built in stand-offs for P.C. or perf boards. Each case has brushed aluminum cover and screws.




FOUR SIZES TO CHOOSE FROM:

CAT#	1-9	10-99	100+
	2 11/16" X 1 11/16" X 1 3/16"		
TB-1	\$1.75	\$1.60	\$1.50
	3 5/16" X 2 1/8" X 1 3/8"		
TB-2	\$1.95	\$1.75	\$1.65
	4 1/8" X 2 3/4" X 1 9/16"		
TB-3	\$2.50	\$2.25	\$2.10
	5 1/4" X 3 1/4" X 1 9/16"		
TB-4	\$3.30	\$3.00	\$2.80

PERF BOARDS ON PAGE 73 FIT ABOVE CASES.

PACTEC CASE


Pactec 6024-1 and 60255-1. Tan plastic project enclosure, 5.75" x 3.6" x 1.13". Crinkle finish on bottom and sides. Smooth finish on top surface. Interlocking top and bottom. Four holes for self-tapping screws (not included).



CAT# MB-84 \$3.00 each

ENCLOSURE W/ 5V 2A POWER SUPPLY

Good-looking metal enclosure ideal for backup drive or project. Includes a 5 Volt, 2 Amp switching power supply. Back panel has input and output IEC power receptacles, an on/off rocker switch and cutouts for D-sub or other connectors. Front panel has a beige plastic face with rectangular 3.94" x 0.94" cutout. Power supply is attached to a removable metal L-bracket. Remaining interior space is 5.5" x 7" x 1.75". Overall size: 8.06" x 7.13" x 1.96. Rubber feet.



CAT # MB-85 \$ 9.50 each

PERF BOARDS

SOLDERABLE PERF BOARDS

Perf board with mounting holes designed to fit our product enclosures TB-1,2,3 and 4. Boards have holes on 0.1" matrix to fit most standard components and have copper solder rings on one side.

1 1/2" X 1 3/4". Fits TB-1 enclosure.

CAT# PC-1 75¢ each

1 7/8" X 2 1/4". Fits TB-2 enclosure.


CAT# PC-2 \$1.00 each

2 1/2" X 3 1/8". Fits TB-3 enclosure.

CAT# PC-3 \$1.50 each

3" X 4 1/4". Fits TB-4 enclosure.

CAT# PC-4 \$2.00 each




SOLDERABLE PERF BOARDS WITH SOLDER PADS AND BUSS STRIPS

6.3" x 3.94" multilayer epoxy boards with tinned copper pattern on one side. Five useful patterns for SIP and DIP components. Holes on 0.1" centers.

SINGLE HOLE PADS

CAT # ECS-1 \$5.50 each



TWO HOLE PADS

CAT # ECS-2 \$5.50 each



THREE HOLE PADS

CAT # ECS-3 \$5.50 each




SOLID LINE PATTERN

CAT # ECS-4 \$5.50 each



IC PATTERN WITH PADS AND BUSS STRIPS

CAT # ECS-5 \$5.50 each



HALL EFFECT SWITCHES

BIPOLAR HALL EFFECT LATCH SURFACE MOUNT PACKAGE

Sprague# UGN3075LT (Allegro UGN3175LT). Operates on 4.5 V to 24 V. Open collector output. Activate with small, commercially available permanent magnets. Will not switch on removal of magnet field. Can sink 10 mA. With suitable output pull up, they can be used directly with bipolar or MOS logic circuits. Tiny SOT 89, surface-mount package, 0.175" x 0.09" x 0.06" thick. Tape and reel packaging.

CAT# UGN-3075LT 4 for \$ 1.00

100 or more 17¢ ea. • 1000 or more 12¢ ea.



BIPOLAR HALL EFFECT SWITCH

Sprague # UGN3030T (Allegro UGN3130T). Operates on 4.5 V to 24 V. Open collector output. Can cleanly track rotation of multipole ring magnets in counter and control circuits. Can sink up to 20 mA at 100 kHz. Can be used directly with bipolar or MOS logic circuits. Three-lead TO-92 package.

CAT # UGN-3030T 2 for \$ 1.20

100 or more 35¢ ea • 1000 or more 25¢ ea.




BREADBOARDS

Design and change circuits quickly and cleanly. Breadboards accommodate all sizes of dips and discrete components with lead diameters up to 0.32". Interconnect with solid hook-up wire (#22 AWG recommended). Wires and components can be used and re-used many times without damage to board or components.


400 tie points, perfect for smaller circuits. 300 contacts on main board and 50 contacts on each of two power distribution strips. Distribution strips are removable. Fits all DIP components. Suitable for 19-29 gauge solid wire.

CAT # PB-400 \$3.50 each




Inexpensive model. Large enough to design most experimental circuits. Contains main board and two power buss strips. 2 5/8" X 6 7/8" X 3/8" high

CAT# PB-840 \$7.50 each




2 terminal strips, 4 distribution strips, 3 binding posts mounted on an aluminum back plate 5 1/8" X 6 7/8" X 3/8" high.

CAT# PB-1680 \$15.00 each



4 terminal strips, 7 distribution strips, 4 binding posts mounted on an aluminum back plate 7 7/8" X 8 3/4" X 3/8" high.


CAT# PB-3260 \$35.00 each




JUMPER WIRE SET

Pre-formed jumper wires for use with solderless breadboards. 10 pieces each of 14 different lengths from 0.14" to 4.92". Assorted colors, solid conductor wire. In a transparent box for quick and easy use.

CAT # WJ-70 \$6.25 each



ELECTRONIC CALIPERS



Precision steel caliper with thumbwheel adjustment for measurements to 6" (150mm). Easy to read LCD digital display, inch/mm conversion, zero at either position, auto-off, slide lock to hold position, hard-shell storage case. Operates on SR-44 button cell (included). Resolution 0.01mm / 0.0005" Accuracy 0.03mm/ 0.001"


CAT # CAL-784 \$ 45.00 each

PC MATERIALS

MAKE PC BOARDS IN MINUTES
From **PHOTOCOPIER** or **LASER PRINTER**

Thousands of people have discovered the easiest and quickest way to transfer pc board patterns to copper-clad board is

PRESS-N-PEEL by Techniks. Works great with CAD and PCB layouts as well as artwork from magazines and books.



No need for photochemicals or darkroom; use a photocopier or laser printer to transfer your design to the special **PRESS-N-PEEL** film. Then, simply iron the design onto a clean copper-clad board with a household iron. Peel off the film, and the board is ready for etching (etchant solution not included). Trace widths of 5 mil and less are possible with this method. We've seen excellent results with this system.

PRESS-N-PEEL consist of five 8 1/2" X 11" sheets of transfer film and complete instructions.


CAT# TEK-5 \$11.95

2 packs (10 sheets) \$17.50

5 packs (25 sheets) \$37.50

DIRECT ETCH™ P.C. KIT

Design your own pc boards. Etch in ferric chloride solution and in a few minutes board is ready to be drilled and loaded with components. Kit includes etch-resist patterns, copper-clad boards, ferric chloride and instructions.



CAT# ER-1 \$15.00 each

DRY CONCENTRATED ETCHANT

1/4 lb. of anhydrous ferric chloride. Makes one pint of etch solution, enough to etch 200 square inches of copper-clad board. Can be used with ER-1 or TEK-5.

CAT# ER-3 \$4.00 each

TINNIT™ ELECTROLESS BRIGHT TIN PLATE

Designed to plate bare copper circuit boards to enhance solderability. The material is supplied as a dry mixture with an indefinite shelf life. When mixed with water, it has a shelf life of approx. two months. No electricity required. Will plate up to 600 square inches. Makes 1 pint.

CAT# ER-18 \$5.50 each

COPPER CLAD BOARD

SINGLE-SIDED PC BOARDS

4" X 6" X 0.062" thick.


CAT# PCB-46

\$2.00 each

6" X 12" X 0.062" thick.


CAT# PCB-612

\$5.00 each



SOLDERING ACCESSORIES


30 WATT SOLDERING IRON



U.L. listed. 30 watt soldering iron. Ideal for P.C. work. **CAT# IR-30 \$4.50 each**

WELLER SOLDER IRONS

These Weller soldering irons combine economy with performance for all types of soldering jobs. Tips are replaceable. UL listed



25 Watt 700 degree F.

Comes with PL-111 pencil tip.

CAT # USI-3125 \$19.00

40 Watt 900 degree F.

Comes with long taper chisel tip.

CAT # USI-3140 \$24.00



REPLACEMENT TIPS FOR WELLER IRONS

Chisel

CAT # PL-113 \$6.00



Pencil

CAT # PL-111 \$6.00



Micro Spade


CAT # PL-114 \$6.00



SOLDER STAND

Spring steel soldering iron holder. Includes replaceable pad for cleaning iron tip.

CAT# 50B-205 \$4.00 each



SOLDER SUCKER



High performance cleaning tool which offers excellent suction for solder removal.

CAT# 50B-410 \$5.00 each

60/40 SOLDER



18 ga. 60/40 rosin core.

Solder in a convenient tube. 110".

CAT# TS-110 \$1.25 each

60/40 SOLDER ROLLS

1/2 pound Roll .032 dia.

CAT# SOL-532 \$4.50 / roll



1 pound Roll .032 diameter

CAT# SOL-032 \$7.50 / roll



ROSIN SOLDERING PASTE/FLUX

PHILMORE # S1207

Soldering paste flux. 2 oz. can.

CAT# SP-44 \$2.00 each






DE-SOLDERING WICK

For easy removal of parts from P.C. boards. Top quality solder wick. 5 feet per spool. 1/16" wide.
CAT# SWK \$1.00 per spool

HELPING HAND with MAGNIFIER

Will hold P.C. board or other small items and allow both your hands freedom to work. Magnifying lens makes work easy to see.


CAT# HELPH-M
 \$4.50 each



TOOLS


6 PIECE PRECISION SCREWDRIVER SET

Long screwdrivers with small blades; great for small screws in hard to reach areas. Three Phillips and three straight blade drivers, 2.4 mm, 3.0 mm, 3.8 mm tips on each type. **CAT# PSS-61** \$2.75 per set



20 PIECE SET - PRECISION BITS FOR ELECTRONICS

Popular miniature bits for electronics with a specially designed handle with a swivel cap. Chrome-vanadium steel. Hard-shell plastic storage case. Includes: 2 Phillips (PH0-0, PH0), 4 Flat (2.0, 2.5, 3.0, 4.0), 5 Torx (T6, T7, T8, T9, T10), 3 Hex (1.5, 2.0, 2.5), 3 Ball (T1.5, T2.0, T2.5), 2 Cross (PZ0-0, PZ0).
CAT # PSS-20 \$19.95 each



MINI PLASTIC SCREWDRIVER


1 3/4" long plastic screwdriver. Ideal for adjusting trimmer pots and caps. **CAT# PSS-1**
 4 for \$1.00 • 100 for \$15.00



INSULATED SCREWDRIVER SET

Right-Tech # E104. 8 assorted Phillips and straight-blade screw-drivers, including one ac/dc 80-250V screwdriver-probe / voltage tester. Range in length from 9.75" to 6". Chrome-vanadium steel blades. Magnetic tips to hold screws. Fully-insulated to the last 1/2" of blade. Complies with ASTM standards.

CAT# PSS-11 \$6.95 each



HEMOSTATS


Hemostats are great for clamping onto small components while soldering or desoldering. Stainless steel.

5" STRAIGHT TIP

CAT# HM-1 \$1.25 each

5" CURVED TIP

CAT# HM-2 \$1.25 each



WIRE STRIPPER

Stripper and cutting tool. Stripper adjusts from 24 to 12 ga wire. Spring-loaded to open after each usage. Plastic grips
CAT# WS-150 \$2.50 each


9 PIECE ASSORTMENT (USED)

CARBIDE DRILL BITS

9 carbide bits varying in size from # 71 to 1/16".

All bits have 1/8"


shanks with collars. The assortment is random and may include more than one of a particular size. **CAT# DRB-9** \$4.50 Per Set



PLASTIC 20 CC SYRINGE

Gainor Medical. Large, individually wrapped plastic syringe ideal for accurate dispensing of liquids. Calibration markings in ounces and CCs or mls. 0.83" dia. x 4.33" long body. Tip is 0.45" long with a 1.5 mm opening.

CAT# SRG-2 \$1.75 each



10 PIECE NEEDLE FILE SET

Assortment of 10, 5 1/2" long needle files including round, flat, triangular and half-round files. Ideal for precision work on models and proto-types. Includes handy pocket-size storage pouch.

CAT# FSET-2 \$4.00 per set



5 PIECE TWEEZER SET

Five piece assortment of 4 1/2" long stainless steel tweezers. Includes 2 fine-point tweezers, curved-tip fine-point tweezers, spade-tip and flat-tip tweezers. Includes storage pouch.

CAT# TW-5 \$5.00 per set




PLASTIC CLAMP-TYPE TWEEZERS

Plastic tweezer with serrated jaws for holding items up to 0.25" diameter.

CAT # TW-8

3 for \$1.00



PLASTIC FLAT-NOSED TWEEZERS

Ideal for holding small, thin or flat items.

Good for static-sensitive applications.


CAT # TW-7 3 for \$1.00



NIBBLER / CUTTER

Cuts up to 18 ga. steel or 1/16" copper and other unhardened metals. Gives you the ability to make square holes for fuse holders, special connectors, displays, etc. Easy to use, simply drill 3/8" hole, insert cutting head and compress handle.

CAT# NCT \$10.00 each




4 1/2" FLUSH CUTTER

Trim leads on PC boards.

Thin cutting edge for hard to reach areas. Useful for jewelry, fishing and electronics.

Insulated handle. Spring return.

CAT # FC-12 \$3.00 each



7" LONG WIRE BRUSHES

Set of three industrial cleaning brushes. One each of brass, stainless steel and nylon bristle.

CAT # WB-772 \$1.75 per set



PRECISION DUSTER



6" brush with natural bristles on one side, stiffer PVC bristles on other side for hard to clean areas. Ideal for automobile consoles, air vents, any device with slots or holes. **CAT # BSH-8** \$1.25 each

TELESCOPING MAGNET



Facilitates retrieval of small metal parts. Adjustable. Extends to 23" overall length.

CAT # MAG-31 \$3.00 each

NYLON SPRING CLAMPS

Hold down your work-in-progress with these rugged nylon spring clamps. Swivel jaws stay parallel on materials of varying thickness. Available in 3 sizes:



3.75" long **CAT # SCL-20** 2 for \$1.00

4.75" long **CAT # SCL-40** \$1.00 each

6.5" long **CAT # SCL-60** \$1.50 each

WIRING TOOL



Harris-Dracon Plastic tool with hook on one end and bent wire on other end.

CAT# WT-1 50¢ each • 10 for \$4.00

4 PIECE PICK SET

4 top quality dental style picks. Ideal for removing material from hard to reach places.



CAT# PSET \$3.50 per set


DIP IC EXTRACTOR

CAT# EX-1 \$1.75 each




INSPECTION MIRROR

Non-conductive plastic handle. Individually wrapped dental-type mirror. Ideal for inspecting hard-to-reach places. **CAT# MIR-7** 2 for \$1.00



3 PIECE CARBON STEEL MINI PLIERS SET

3" spring-action carbon steel pliers with insulated handles. Ideal for soldering wiring and working on models and small projects. Needle-nose, bent needle-nose and end nippers.



CAT # CP-33 \$5.95 per set

ELECTRICAL TAPE

3/4" WIDE

Black PVC - 60' **CAT# PET-1**
65¢ each • 10 for \$6.00



2" EXTRA-WIDE

Black PVC - 60 yards
CAT# PET-4 \$2.50 per roll



TEST EQUIPMENT AND ACCESSORIES

PORTABLE OSCILLOSCOPE

Velleman # HPS5 Personal Scope™.

5 MHz maximum sample rate.

Input impedance: 1M ohm/20pF

(standard scope probe).

Maximum input voltage

100 V peak (AC or DC).

Timebase range: 2us to

20s/div. Input sensitivity:

5mV to 20V/div. High-contrast

64 x 128 pixel LCD graphic

display. True RMS and dB

measurements. Screen hold

function. Operates on 5 AA


batteries (not included). Use alkaline,

or rechargeable NiCad or NiMH.

Recommend 9 Vdc power supply,

our **CAT # DCTX-935**.

CAT# HPS-5 \$189.95 each



SCOPE PROBE SETS

Scope probe with BNC

connector to match most

equipment. Comes with

ground lead, retractable

hook tip, pin tip with IC lead

cover and standard cover.



60 MHz **CAT # PR-60** \$19.50 each

100 MHz **CAT # PR-100** \$29.50 each

CHECK THIS OUT! 3 1/2 DIGIT LCD MULTIMETER WITH BACKLIGHT

Velleman # DVM850BL

For features,

accuracy and

ruggedness, this is

the best inexpensive

multimeter we've ever

seen. DC current

(10 A), DC and AC


voltage (600 V),

resistance (2 M ohm), diode, transistor tester,

audible continuity and hold button. Protective

rubber shell and test leads included.

CAT # DVM-850BL \$17.95 each



3 1/2 DIGIT LCD MULTI-FUNCTION LCD METER

Velleman # DVM890

An incredible array

of features at a

great price.

20A DC current,

1000 DC Volts.

20A AC current,

700 AC volts.

Resistance to 20 M.

Capacitance from

2000pF to 20uF.

Frequency

measurement to 20kHz.

Temperature measurement: -50 deg C to +1000


deg C with K-type thermocouple. Low battery indi-

cation, overload protection and auto power off

function. Protective rubber shell, test leads and

thermocouple included.

CAT # DVM-890 \$45.00 each




POCKET MULTIMETER

Right-Tech # 53311.

An inexpensive general-purpose tester for working on simple projects around the home or office.

18 ranges. Measures AC, DC voltage to 500V. DC Amps to 250 mA. Resistance to 500K ohm. Checks AAA, AA, C, D button and 9 V batteries. Fuse and diode protected circuitry. Built-in self-storing leads. Instructions included. Requires one AAA battery (not included). UL listed.


CAT# VOM-1 \$7.95 each



TEST LEADS

Replace broken or intermittent test leads. Red and black lead set with banana plug on one end and pin probe on other end. 3 ft. long.


CAT# TL-100 \$2.00 per set



5 1/2" HOOK TEST PROBES

5 1/2" long spring-loaded hook test probes can reach further and hook onto slightly larger items than the mini-hooks above. These have a thumbscrew terminal which can easily be connected to a banana plug, pin plug or a piece of wire. Sold in sets of two, one red, one black.

CAT# MTC-21 set of 2 for \$3.00




ALLIGATOR CLIPS

3" INSULATED CLIPS

30 amp alligator clips.

One Red One Black

CAT# ALG-3 \$1.00 per set




FOUR INSULATED ALLIGATOR CLIPS

Two-inch clips with insulating boots. 2 black, 2 red per package.

CAT # ALG-10

\$1.50 per package of 4 clips




30 AMP INSULATED ALLIGATOR CLIP


Heavy-duty, 30 Amp clip with insulating boot. 2.5" long x 0.6" wide. Available

with red insulating boot only.

CAT # ALG-13 2 for \$ 1.30



COIL CORD WITH ALLIGATOR CLIP



Light-gray coil cord with insulated 1" alligator clip on one end. Good-quality, very durable, very flexible cord. Single conductor 20 gauge stranded wire, stripped and tinned on one end. Cord extends 6 feet. Retracts to 2 feet.

CAT# ALG-12 \$1.25 each

100 for 95¢ each • 500 for 75¢ each


MINI-HOOKS AND JUMPERS

Mini-hooks are great for connection to parts in high-density areas. They give a firm, insulated connection

1 1/2" MINI-HOOK JUMPERS

Two 18" long mini-hook patch cords. One black, one red, with 1.5" long mini-hooks on each end.

CAT# MTC-2 set of 2 for \$2.75




2" MINI-HOOK JUMPERS

Five 18" long mini-hook patch cords. Black, red, white, green and yellow.

CAT# MTC-5

set of 5 for \$6.00



JUMPER TEST LEADS


MINI JUMPERS

10 TEST LEADS- 1" CLIPS

2 each of 5 colors.

CAT# MTL-10

\$2.50 per set




REGULAR JUMPERS

5 TEST LEADS

2" CLIPS

CAT# HDTL-5

\$2.50 per set



HOT-MELT GLUE GUN

Ideal for quick repairs


and assembly.

Uses standard glue sticks.

Includes two 2.9" sticks. UL.

CAT # GN-1

\$4.75 each



EPOXY RESIN - SINGLE USE PACKETS

Great for bonding, sealing and repairing, concrete, wood, stone, metal and most plastics. Clear resin and hardener in separated foil packet.

Simply tear off the end, squeeze out equal amounts of resin and hardener, mix and use.

Each packet contains 0.14 oz (4 grams). General Purpose. Quick setting - sets in 3-5 minutes at 75 degrees F. **CAT# EPOX-1**

2 for \$1.00 • 10 for \$4.00 • 100 for \$30.00




ALUMINUM FOIL TAPE 2" X 20'

3M #49. 2" wide aluminum foil tape.

Designed for use as a moisture vapor barrier in communication cable splices and as a splicing shield to reduce cross talk and high frequency radiation interference. Approved for use in REA Cable Splicing Specifications. 2" x 20 FOOT ROLL.

CAT# ALT-2 \$3.00 each



SILICONE SPRAY

UniSport #070307 Silicone Spray
Aerosol spray lubricant for bicycle cables
and chains, rifles, fishing gear, exercise
equipment. 2 oz spray bottle.

CAT # SSS-1 \$1.75 each



LOCTITE® THREADLOCKER

Loctite 290. For use on preassembled parts. Ideal for adjustment screws, set screws or maintenance threadlocking. High strength. 10 ml bottle.

CAT # LT-290 \$5.75 each



PURETRONICS CLEANERS & SPECIALTY PRODUCTS

CONTACT CLEANER

Quick penetrating, zero residue contact cleaner removes oils, greases, grime, dirt silicones, fluxes and other contaminants. Evaporates quickly. Safe on plastics and metal materials. Ozone friendly containing no CFCs or HCFCs.

CAT # PTR-3000

5.5 oz aerosol can \$ 3.79 each

12 cans \$42.00 (\$3.50 each)

CAT # PTR-3500

12.25 oz aerosol can \$ 5.79 each

12 cans \$63.00 (\$5.25 each)



CONTACT CLEANER AND LUBRICANT, 13 OZ

Removes oils, dirt and other contaminants and leaves a thin coating of silicone to lubricate and protect. Safe on plastics.

Ozone friendly. 13 oz aerosol can.

CAT# PTR-5000 \$6.50 each



VALUE DUSTER

Moisture free, zero residue dusting gas.

Removes dust, dirt, lint and other contaminants. Up to 70 psi.

10 oz trigger-control aerosol can.

CAT # PTR-7000 \$ 5.75 each



PRECISION DUSTER, 10 OZ

Helps remove microscopic particles like dust, lint, dirt, oxides and other dry contaminants. Excellent preventative maintenance tool for electronics, optical and mechanical components. Also assists the evaporation of slow drying solvents. Exceptionally pure 134A HFC. 10 oz trigger-control spray can.

CAT# PTR-7200 \$6.50 each



CIRCUIT FREEZE

Helps locate thermal intermittent defective resistors, capacitors and semiconductors. Helps locate cold solder joints and pc board cracks. 10 oz trigger-control spray can.

CAT # PTR-7400 \$ 6.95 each



FLUX REMOVER, 13 OZ CAN

Removes most types of flux including rosin and rosin based no-clean flux. Dissolves and flushes away fluxes, oils, grease, grime, dirt, silicones and other contaminants. Evaporates quickly. Safe on plastic and metal surfaces.

13 oz aerosol can.

CAT# PTR-6000 \$6.35 each



INTEGRATED CIRCUITS

VOLTAGE REGULATORS

POSITIVE REGULATORS

CAT#	DESCRIPTION	CASE	each
7805T	+5 VOLT 1 AMP (LM340T-5)	TO-220	.50
78M05	+5 VOLT 500 MA (1/2 A)	TO-220	.50
7806T	+6 VOLT 1 AMP (LM340T-6)	TO-220	.50
7808T	+8 VOLT 1 AMP (LM340T-8)	TO-220	.50
7812T	+12 VOLT 1 AMP (LM340T-12)	TO-220	.50
78M12	+12 VOLT	TO-202	.35
7815T	+15 VOLT 1 AMP (LM340T-15)	TO-220	.50
78L05	+5 VOLT 100MA	TO-92	.40
78L12	+12 VOLT 100MA	TO-92	.40

NEGATIVE REGULATORS

7905K	-5 VOLT 1 AMP (LM320K-5)	TO-3	1.75
7905T	-5 VOLT 1 AMP (LM320T-5)	TO-220	.50
7912T	-12 VOLT 1 AMP (LM320T-12)	TO-220	.50

ADJUSTABLE REGULATORS

LM317T	ADJ. POSITIVE (1.2-37V)	TO-220	.50
LM317LZ	ADJ. POSITIVE (1.2-37V)	TO-92	.40
LM337T	ADJ. NEGATIVE (1.2-37V)	TO-220	1.50
LM350T	ADJ. POSITIVE 3 AMP	TO-220	3.50

OTHER ICS

CAT#	DESCRIPTION	# of pins	each
74ACT14	HEX SCHMITT TRIGGER INV	(14)	.35
74HCU04E	HEX INVERTER, CMOS	(14)	.35
74HC00	2 IN NAND GATE	(14)	.30
74HC05	HEX INVERTER	(14)	.40
74HC123	DUAL MONO MULTIVIBRATOR	(16)	.30
74HC139	DUAL 2:4 DECODE/DEMUX	(16)	.35
74HC244	OCTAL BUFFER LINE DRIVER	(20)	.58
74HC32	QUAD 2 IN OR GATE	(14)	.35
74HC373	OCTAL D LATCH	(20)	.45
74HC74	DUAL D-TYPE FLIP FLOP	(14)	.29
74HCT244	OCTAL BUFFER LINE DRIVER	(20)	.60
74LS47	BCD TO 7-SEG DEC/DRIVER (OC)	(16)	.90
4001	QUAD NOR GATE	(14)	.25
4017	DECADE COUNTER / DIVIDER	(16)	.40
4077	QUAD NOR GATE	(14)	.50
MC14078	8-INPUT NOR GATE	(14)	.15
MC14099	8 BIT ADDRESSABLE LATCH	(16)	.39
MC145027	REMOTE CONTROL DEC (5 BIT)	(16)	.69
MC14528	DUAL MONO. MULTIVIBRATOR	(16)	.55

LINEAR SERIES

CAT#	DESCRIPTION	# of pins	each
ADM202EAN	Line driver receiver	(16)	.75
TL082	J-FET IN DUAL OP AMP	(8)	.70
LM311	COMPARATOR	(8)	.50
LM324	QUAD OP AMP	(14)	.50
LM339	QUAD COMP	(14)	.60
LF353	DUAL BI-FET OP AMP	(8)	.50
LF355N	OP AMP	(8)	.45
LM358	DUAL OP AMP	(8)	.40
LM380	2 WATT AUDIO AMP	(14)	1.80
LM386N-1	AUDIO AMP .25 W.	(8)	.40
LM555	TIMER	(8)	.75
ICM7555	CMOS TIMER "555"	(8)	1.00
LM556	DUAL (555) TIMER	(14)	.45
LM567	TONE DECODER	(8)	.90
LM741	OP AMP (MC1741)	(8)	.55
AD841J	OP AMP	(14)	.75
MC1458	DUAL OP AMP (MC4558)	(8)	.50
MC1489	QUAD LINE RECEIVER	(14)	.60
LM1496	BALANCED MOD/DEMOM	(14)	.69
MC33078P	DUAL OP AMP	(8)	.40
MC3401	QUAD OPAMP EQUIV 3900	(14)	.45
LM3914	BARGRAPH DISPLAY DRIVER	(18)	1.75
LM3915	3DB STEPS BG DISPLAY DR	(18)	2.75
NE5534	LOW NOISE OP AMP	(8)	1.25
ULN2003	DARLINGTON ARRAY	(16)	.75
LM6321N	BUFFER AMP	(8)	1.85

NE556 - DUAL TIMER

14 PIN DIP package.

CAT # LM556 45¢ each • 25 for \$10.00 (40¢ ea)

100 for \$35.00 (35¢ ea) • 500 for \$150.00 (30¢ ea.)



LOW POWER AUDIO AMPLIFIER

50 pieces - \$20.00 • 500 pieces - \$150.00
1000 pieces - \$250.00

FAHRENHEIT TEMPERATURE SENSOR

CAT# LM34DZ \$2.50 each

KEYPAD ENCODER IC

E-Lab# EDE1144. Designed to interface a matrix-type 4 row x 4 column (16 key or less) keypad with a microcontroller or other host processor. Provides enhanced keypad features such as contact debouncing and key auto-repeat and keybeep feedback to operator. Electrically quiet (reduced EMI) keypad scanning. Serial/ parallel outputs available. 18 pin DIP package. Includes full documentation.

CAT # EDE-1144 \$ 7.50 each

SERIAL LCD INTERFACE IC

E-Lab # EDE702. Allows nearly any text-based LCD module to be controlled via a simple one-wire data link. A cost-effective LCD control solution for a wide variety of embedded designs. RS232 and TTL level compatible. 18 pin DIP package. Includes full documentation. **CAT# EDE-702 \$ 8.95 each**

7 SEGMENT LED CONTROLLER IC

E-Lab # EDE707. Handles up to eight 7-segment LED displays, tremendously reducing I/O demand on your host microcontroller as well as eliminating display refresh/scan software overheads. Features include leading zero blanking, counter functionality, an overflow flag and a full 0-9, A-F Hex character set. 28 pin dip package. Includes full documentation.

CAT # EDE-707 \$ 9.95 each

STEPPER MOTOR CONTROLLER IC

(6 wire motors) **CAT # EDE-1200** \$ 8.30 each

(4 wire motors) **CAT # EDE-1204** \$ 8.30 each

MEMORY

CAT#	DESCRIPTION	# of pins	each
628512ALP-7	512 x 8 SRAM	(32)	\$11.00
AT29C040A	Flash Memory	(32)	\$11.00

CMOS PIC MICROCONTROLLER

CAT#	DESCRIPTION	# of pins	each
PIC16C711-04	MCU w/ A-D 1K 4 mHz	(18)	\$2.25

OPTOISOLATORS



CAT#	Description	1	10	100
IL2 <small>NEW</small>	NPN transistor output	.35	.30	.25
4N25	NPN transistor output	.35	.30	.20
4N26	NPN transistor output	.35	.30	.20
4N27	NPN transistor output	.35	.30	.20
4N33	NPN darlington output	.45	.40	.30
4N35	NPN transistor output	.50	.45	.35
MCT9001	Dual NPN transistor	.60	.55	.45

VOLTAGE TO FREQUENCY CONVERTER

CAT# XR4151P 80¢ each • 100 for 65¢ ea.

IC SOCKETS

SOLDERTAIL				
PINS	CAT#	1-49	50-99	100+
8	ICS-8	.20	.15	.10
14	ICS-14	.20	.15	.10
16	ICS-16	.25	.20	.15
18	ICS-18	.30	.25	.20
20	ICS-20	.40	.35	.30

SOLDERTAIL

		<i>Special Reduced Price!</i>		
24	ICS-24	.15	.12	.10
		1000 for \$50.00 (5¢ each)		
28	ICS-28	.45	.40	.35

HIGH RELIABILITY (MACHINED PINS) SOLDERTAIL

PINS	CAT#	1-99	100+
8	HRICS-8	.60	.55
14	HRICS-14	.50	.40
16	HRICS-16	.75	.45
22	HRICS-22	.90	.80
28	HRICS-28	.50	.25
64	HRICS-64	\$2.00	\$1.50

WIRE WRAP SOCKETS

PINS	CAT#	1-99	100+
8	WWICS-8	1.00	.85
14	WWICS-14	1.25	1.00
16	WWICS-16	1.25	1.00
18	WWICS-18	1.25	1.00
24	WWICS-24	\$1.20	\$1.10
36	WWICS-36	\$1.25	\$1.05

CERAMIC RESONATORS


4 Mhz	CAT# CER-4	\$1.00 each
16 MHZ	CAT# CER-16	\$1.00 each
20 Mhz	CAT# CER-20	\$1.00 each

METAL OXIDE VARISTORS

47 volts nominal. 8.8 Joules. Peak pulse current 1000 amps. 14mm diameter.

CAT# MOV-47 2 for \$1.00 • 100 for \$20.00

TRANSISTORS



CAT#	CROSS TO NTE/ECG	TYPE	CASE	1-99	100+	1000+
D45H5	378	PNP	TO-220	75¢	.65	.50
PN2222A	123AP	NPN	TO-92	5 for 80¢	.15	.13
2N2222A	123A	NPN	TO-18	2 for 1.00	.40	.35
PN2905	159	PNP	TO-92	5 for 50¢	.08	.06
PN2907	159	PNP	TO-92	5 for .75	.10	.08
2N3055	130	NPN	TO-3	1.00	.85	.75

Heavy-duty 2N3055 16A 120 V						
2N3055HV	NPN	TO-3	1.25	1.00	.85	
PN3646	123AP	NPN	TO-92	5 for .75	.08	.06
2N3904	123AP	NPN	TO-92	5 for .75	.13	.10
2N3906	159	PNP	TO-92	5 for .75	.13	.10
2N4124	123AP	NPN	TO-92	5 for 75¢	.13	.10
2N4400	123AP	NPN	TO-92	5 for 50¢	.08	.06
2N4401	123AP	NPN	TO-92	5 for .75	.13	.10
2N4403	159	PNP	TO-92	5 for 50¢	.08	.06
2N5657	157	NPN	TO-126	1.00	.75	-
2N5772	108/123AP	NPN	TO-92	5 for 50¢	.08	.06
2SC2352	69	NPN	TO-92	3 for 1.00	.29	.25
AR-24	125/184	NPN	TO-220	.50	.40	.30
MJ15015	ECG 388	NPN	TO-3	1.50	1.00	.75
MPS2369	107/123AP	NPN	TO-92	5 for 50¢	.08	.06
MPS3638A	159	PNP	TO-92	5 for 50¢	.08	.06
MPS3704	123AP	NPN	TO-92	5 for 50¢	.08	.06
MPS6534	159	PNP	TO-92	5 for 50¢	.08	.06
MPS8093	159	PNP	TO-92	5 for 50¢	.08	.06
MPS8599	159	PNP	TO-92	5 for 50¢	.08	.06
MPSA20	123AP	NPN	TO-92	5 for 50¢	.08	.06
MPSA92	288	PNP	TO-92	3 for \$1.00	.28	.24
TIP30	292	PNP	TO-220	.75	.65	.50
TIP31C	291	NPN	TO-220	.50	.40	.30
TIP32C	292	PNP	TO-220	.65	.40	.35
TIP2955	393	PNP	TO-218	.65	.40	.35
TIP3055		NPN	TO-218	.65	.40	.35

DARLINGTON TRANSISTORS

CAT#	CROSS TO NTE/ECG	TYPE	CASE	1-99	100+
D40K1	268	NPN	TO-202	.75	.65
GES-5307	46	NPN	TO-92	5 for 50¢	.08
MJ10009	98	NPN	TO-3	3.50	2.25
MPSA13	46	NPN	TO-92	5 for 50¢	.08
TIP120	261	NPN	TO-220	.75	.65
TIP142	270	NPN	TO-218	1.00	.75
TIP147	271	PNP	TO-218	1.25	.85

TOSHIBA TO-3 POWER TRANSISTORS

Complementary pair, NPN and PNP, audio amplifier output transistors.

2SB554 PNP NTE/ECG 285
2SD424 NPN NTE/ECG 284

Specs: V_{ceo} 160V I_c 15A
V_{ceo} 160V P_c 150W

PNP CAT # 2SB554 \$3.75 each
10 for \$3.25 each • 100 for \$2.50 each

NPN CAT # 2SD424 \$2.75 each
10 for \$2.25 each • 100 for \$1.65 each

S.C.R.s

CAT#	AMP	VOLT	CASE	PRICE	10
2N5064	0.8	200	TO-92	3 / \$1.00	3.00
IS08S	8	50	TO-202	2 / \$1.50	7.00

TRIACs

CAT#	AMP	VOLT	CASE	PRICE	10
SC141D	6	400	TO-220	\$1.00	9.00
BTA12-600C	12	600	TO-220	\$1.50	12.00

BILATERAL TRIGGER (DIAC)

CAT # DB-3 28-36 volt 3 for \$1.00 100/\$27.00

MOSFETS

IRF522 N-Channel MOSFET.
100 Volt, 8 Amp, 60 W. TO-220 case.
CAT # IRF522 65¢ each
10 for 55¢ each • 100 for 40¢ each

#IRF840 N-Channel MOSFET
500 V, 8 Amp, TO-220 CASE,
crimped leads. CAT# IRF840
85¢ each • 100 for 70¢ each

IRF9Z30 P CHANNEL HEXFET

Samsung P-channel MOSFET.
50 Volts, 18 Amps. TO-220 case.
CAT # IRF9Z30 \$1.25 ea. • 50 for \$1.00 ea.
500 for 65¢ each • 1000 for 50¢ each

HARRIS IRFD110 HEXFET, DIP

N channel Power Mosfet. 100 Volts,
0.54 Ohms, 1 Amp, 1.3 Watts. 4 pin DIP package.
CAT # IRFD110 50¢ each • 100 for \$35.00

PROGRAMMABLE UNIUNCTION

2N6028 (PUT) TO-92 plastic case.
CAT# 2N6028 3 for \$1.00 • 100 for \$25.00

J FETS

J176 P-CHANNEL TO-92
CAT# J176 5 for \$1.00

PHOTO-TRANSISTOR



Ledtech # LT9593-91-0125
Water-clear T 1 3/4 w/ flat face.
CAT # PTR-1 2 for \$1.30 • 50 for \$25.00

TRANSISTOR HARDWARE

TO-3 SOCKET CAT # STR-3
2 for \$ 1.00 • 100 for \$ 35.00

TO-92 SOCKET CAT# STR-92
4 for \$1.00 • 100 for \$20.00

SHOULDER WASHER

For insulating the mounting holes on
TO-3 transistors. Fits 0.15" diameter holes.
CAT# WS-4 100 for \$2.50 • 1000 for \$15.00

DIODES

40 AMP 600 VOLT RECTIFIERS

D0-5 case,
stud-mount rectifier.



1N1190A Cathode case \$ 3.50 each
1N1190AR Anode case \$ 3.50 each

HIGH VOLTAGE RECTIFIER

CAT#	VOLT	AMP	PRICE	100	1000
R6000	6000	0.2	.50	40.00	300.00

FAST RECOVERY RECTIFIER

GI 822. 5 Amp 200 Volt fast
recovery rectifier. T6L axial package.

CAT # GI822 3 for \$1.00
100 for \$25.00 • 1000 for \$150.00

RECTIFIER DIODES

CAT#	VOLT	AMP	PRICE	100	1000
1N4001	50	1	15/\$1.00	5.00	40.00
1N4002	100	1	12/\$1.00	6.00	50.00
1N4003	200	1	10/\$1.00	8.00	70.00
1N4004	400	1	9/\$1.00	9.00	75.00
1N4005	600	1	8/\$1.00	10.00	85.00
1N4007	1000	1	6/\$1.00	12.00	100.00
1N5400	50	3	3/ 60¢	12.50	100.00
1N5402	200	3	3/ 70¢	15.00	110.00
1N5404	400	3	3/ 80¢	17.00	130.00
1N5408	1000	3	3/\$1.00	30.00	250.00
D620	200	6	2/ 90¢	40.00	350.00
D660	600	6	2/\$1.00	45.00	400.00

SCHOTTKEY DIODES

CAT#	amp	PIV	price	100	1000
1N5817	1	20	3/\$1.00	27.00	230.00
1N5819	1	40	3/\$1.00	27.00	230.00
1N5822	3	40	3/\$1.25	35.00	300.00
SR505	5	50	2/\$1.00	40.00	-

GERMANIUM DIODE

1N60A germanium diode. DO-7 case style. 40 V.
CAT# 1N60 2 for \$1.00

1 WATT ZENER DIODES

All 1 Watt Zeners listed are 4 OF ONE VALUE \$1.00
 100 OF ONE VALUE \$20.00

CAT#	VOLTAGE	CAT#	VOLTAGE	CAT#	VOLTAGE
1N4728	3.3	1N4740	10	1N4745	16
1N4730	3.9	1N4742	12	1N4748	22
1N4731	4.3	1N4744	15	1N4749	24
1N4733	5.1	20 volt 1 watt zener diode CAT# ZA20Z 10 for \$1.00 100 for \$7.00 • 1000 for \$50.00			
1N4734	5.6				
1N4735	6.2				
1N4737	7.5				
1N4739	9.1				

PHOTO-DIODES

Ledtech # LT4W55-2120-EA
 Black, side-looking photo diode.
CAT # PD-2 2 for \$ 1.30 • 50 for \$ 25.00

T 1 3/4 PHOTODIODE

Siemens # SFH2030F / SFH203FA.
 T 1 3/4 silicon PIN diode. Daylight filter
 (dark smoke) lens. Can be used as photodiode
 with reverse voltage or as photovoltaic cell.

CAT# PD-5 2 for \$1.30
 100 for 50¢ each • 1000 for 40¢ each

SWITCHING DIODES

CAT#	PRICE	100	1000
1N914	15 for \$1.00	\$5.00	\$35.00
1N916	15 for \$1.00	\$5.00	\$35.00
1N4148	15 for \$1.00	\$5.00	\$35.00

FULL WAVE BRIDGE RECTIFIERS

1 1/2 AMP 400 PIV

TO-5 case 3/8" dia. 3/16" high.
 Gl# WO4M or equiv.

CAT# FWB-15 2 for \$1.00

2 AMP 100 PIV

CAT# FWB-201 3 for \$1.00
 10 for \$3.00 100 for \$27.50

2 AMP 200 PIV

Leads on 0.15" centers.

CAT# FWB-202 65¢ ea. • 10 for \$6.00

2 AMP 600 PIV

Gl# 3N257.

Leads on 0.15" centers.

CAT# FWB-206 2 for \$1.00
 100 for \$35.00

8 AMP 400 VOLT

Liteon # PBU-804. Leads on 0.2" centers.
 Special Purchase. Limited quantity

CAT # FWB-804 2 for \$1.20
 100 for \$45.00

25 AMP BRIDGES

1 1/8" square.

50 P.I.V.	CAT# FWB-250	\$1.75 each
200 P.I.V.	CAT# FWB-252	\$2.50 each
400 P.I.V.	CAT# FWB-254	\$3.00 each
600 P.I.V.	CAT# FWB-256	\$3.50 each

35 AMP BRIDGES 1 1/8" square.

200 P.I.V. **CAT# FWB-352** \$2.50 each
 10 for \$22.50 • 100 for \$175.00

400 P.I.V.	CAT# FWB-354	\$4.00 each
600 P.I.V.	CAT# FWB-356	\$4.50 each
800 P.I.V.	CAT# FWB-358	\$4.75 each

OPTO SENSORS

Clarostat # S-2216.

Slotted optical switch, 0.125" gap
 between emitter and sensor. Mounting
 flange has slots that accept centers from
 0.30" to 0.75". Four 6" long wire leads
 terminate to 4 pin molex-type connector.

CAT# OSU-47 75¢ each

Telefunken # TCST 5123.

0.12" gap. 0.25" high.

CAT # OSU-37 2 for \$ 1.00
 Tube of 60 for \$ 21.00

Optek # K1796-EP 0.13" gap.
 0.75" mounting centers.

10" pigtail leads.

CAT # OSU-32 2 for \$1.00

Omron # EE-SX416

Surface-mount sensor
 assembly with 0.2" (5mm) gap.
 Mounted on a right-angle metal
 bracket, the sensor assembly, itself,
 is 0.79" x 1.18" x 0.62" high.

On-board three pin male header (0.1" centers).

CAT # OSU-40 \$1.00 each

OPTICAL SWITCH WITH INTERRUPT MECHANISM

Omron U-shaped opto-switch
 with a 0.2" gap. A spring-
 loaded plastic arm with a
 kind of flag at the end
 interrupts the switch beam. The
 arm slides back and forth through a teflon channel.
 Assembly mounted on a metal bracket, 2.32" x 1.1."

CAT # OSU-45 \$ 1.20 each

REFLECTIVE OPTO SENSOR

Vactec # 21L900. Reflective opto
 sensor. 0.79" x 0.58" x 0.21".

Four 7" leads with 4-pin connector

(0.1" centers). Removed from new equipment.


CAT# OSU-48 75¢ each • 100 for 55¢ each

SOLAR PANELS & PHOTOVOLTAICS

9 VDC, 60 MA SOLAR CELL

These 6" X 6" glass enclosed photo-voltaic panels produce 9 Vdc at 60 mA. Ideal for charging batteries and powering small devices. Put two or more together for more current and voltage. Includes metal connectors and instructions for soldering.

CAT# SPL-960 \$5.25 each



PHOTOVOLTAIC DETECTOR

Miniature silicon solar cell converts light impulses directly into electrical charges which can easily be amplified, using a transistor for example, to activate a control mechanism. Unlike a conventional photo diode or transistor, it generates its own power and does not require any external bias. Generates 0.4 vdc in moderate light. Silicon cell is mounted on a 0.31" x 0.23" x 0.07" thick plastic carrier and has pc leads on 0.2" centers. Large quantity available.

CAT # PVD-2 75¢ each

10 for \$6.50 • 100 for \$50.00



SOLAR CELL

Output: approximately 3 Volts @ 40 mA. 2.40" square x 0.13" thick epoxy-encapsulated silicon photovoltaic cell removed from solar lighting system. Solid, almost -unbreakable module with easy-to-solder spots on backside. Ideal for solar-powered battery chargers and other projects.

CAT # SPL-60 \$3.50 ea. • 100 for \$3.00 ea.




Silicon photovoltaic cells.

Approximate output:
0.45 Volts @ 100 mA.

0.79" x 0.79" (20mm x 20mm) square. 0.01" thick.

CAT # SPL-22 75¢ each • 10 for \$5.00



Approximate output: 0.45 Volts @ 50 mA
0.79" x 0.4" (20mm x 10mm). 0.01" thick.

CAT# SPL-12 3 for \$1.00



SOLAR PANELS


12 – 16 Volt solar arrays from Sun-Mate® Corporation. Use for charging rechargeable batteries. Weather-proof housing with silicone sealed edge. Built-in blocking diode to prevent reverse current flow at night. Alligator clip leads. Manufacturers guarantee. Two sizes available:

12 Volt 120 mA

6" x 11" x 1"

CAT# SM-685

\$59.95 each




12 Volt 500 mA

14.35" x

15.35" x 1"

CAT# SM-500


\$79.95 each



FLEXIBLE THIN FILM SOLAR PANELS

Very thin, extremely flexible polyester encapsulated photovoltaic modules suitable for indoor or protected outdoor use. Lightweight. Great for mounting on curved surfaces.

Ideal for charging nickel cadmium and nickel metal hydride batteries or running low current applications. Can be connected in series or parallel for higher voltage or current. Modules have copper strips at each end to make solder connections.



CAT # SPL-314 \$4.50 each

3 Volts @ 19 mA 4.5" x 1.44"

CAT # SPL-328 \$8.50 each

3 Volts @ 38 mA 4.5" x 2.88"

FLEXIBLE THIN FILM 6 AND 12 VOLT CHARGERS

Flexible thin film polyester encapsulated solar modules designed to charge 6 and 12 volt nickel cadmium, nickel metal hydride or gel cell packs.


Can be mounted on curved surfaces. Designed for limited outdoor use. For full time, all-weather conditions CAT # SPL-675 is Tefzel®/EVA encapsulated for added protection.

7.2 Volts @ 100 mA 9.92" x 2.9"

CAT # SPL-610 \$17.75 each

15.4 Volts @ 50 mA 9.92" x 2.9"

CAT # SPL-1250 \$21.95 each




ALL-WEATHER FLEXIBLE THIN FILM 6 VOLT CHARGER

Flexible thin film solar module designed to charge 6 Volt nickel cadmium, nickel metal hydride or gel cell packs. This is our CAT# SPL-610 module encapsulated in Tefzel®/EVA for weatherproofing. Flat copper leads extend outside of encapsulation to facilitate connection. Can be mounted on curved surfaces. 7.2 Volts @ 100 mA. 11.31" x 3.87".

CAT # SPL-675

\$29.95 each



PHOTOCONDUCTIVE CELLS

Cadmium sulfide photoconductive cells. Plastic encapsulated, moisture-resistant package.

LIGHT - 35 OHMS, DARK - 5K OHMS

0.29" X 0.25" X 0.08". 1.5" wire leads.

CAT# PRE-14 75¢ ea. • 10 / \$6.00 • 100 / \$50.00

LIGHT - 5 OHMS, DARK - 20K OHMS

Plastic encapsulated ceramic package.

0.44" x 0.40" x 0.04". 1.5" wire leads.

CAT # PRE-18 75¢ ea. • 10 / \$6.00 • 100 / \$50.00

JUMBO PHOTOCCELL

20 OHMS - LIGHT, 5K OHMS - DARK

1" x 0.85" x 0.07" thick plastic encapsulated ceramic package. 0.57" long leads on 0.75" centers.

CAT # PRE-19 75¢ ea. • 10 / \$6.00



PHOTOCELL IN TO-5 HERMETIC PACKAGE

100 OHMS - LIGHT, 3 MEG - DARK
0.2" dia. x 0.15" hermetically-sealed TO-5
metal package with clear lens. 1.5" leads.

CAT # PRE-20 75¢ ea. • 10 / \$6.00

40 OHMS - LIGHT, 20K - DARK

0.16" x 0.14" plastic encapsulated
ceramic package. 1.5" leads.

CAT # PRE-21 75¢ ea. • 10 / \$6.00

100 OHMS - LIGHT, 50K - DARK

0.16" x 0.14" plastic encapsulated
ceramic package. 1.5" leads.

CAT # PRE-23 75¢ ea. • 10 / \$6.00

100 OHMS - LIGHT, 50K - DARK

0.27" x 0.24" plastic encapsulated
ceramic package. 1.5" leads


CAT # PRE-22 75¢ ea. • 10 / \$6.00

BOOKS

ARRL HANDBOOK 2002 EDITION

The standard reference book for radio amateurs, electronics technicians and professional engineers. New material on digital signal processing (DSP) and wireless technology covering cell phones, pagers etc. A large variety of hands-on projects including a new versatile compensated wide-range modular RF voltmeter, easy-to-build VHF receiver, universal power supply, and solar charge controller. 1200+ pgs.

CAT # ARRL-2002 \$34.95 each



THREE BOOKS ON THE TESLA INVENTIONS

Nikola Tesla, at the turn of the century, invented the alternating current system still in use today. He also invented the Tesla coil which can boost wall voltage to millions of high frequency volts.

TESLA , The Lost Inventions

describes in detail some of his more amazing inventions. 34 pages, 42 illustrations. Softbound.

CAT # TESLA-1 \$5.95

TESLA COIL, a 26 page booklet with all the facts to build a Tesla coil on any scale. Softbound

CAT# TESLA-2 \$4.95

RADIO TESLA, The Secret of Tesla's Radio and Wireless Power

"Oscillations of low frequency are ever so much more effective in transmission," said Tesla in 1919. This, and other aspects of Tesla's radio theories are documented in RADIO TESLA. 38 pages, 66 illustrations. Softbound.

CAT # TESLA-3 \$6.50 each

FRONT SURFACE MIRRORS



Low-distortion front surface mirrors. Removed from equipment. Two sizes available:

12.5" x 2" x 0.4"

CAT # MIR-8 \$2.50 each

13.75" x 1" x 0.25"


CAT # MIR-9 \$2.00 each



LENSES & OPTICS

73 MM LENSES

73 mm (2.9") diameter plastic lenses, probably stock from an optician's supplies. They are clean and individually packaged. Some have small chips around the outer edge. Seven magnifications available. The positive numbers magnify, negative numbers make smaller. LNS-25 has dual characteristics.



CAT#	MAGNIFICATION	EACH
LNS-16	3.0	\$1.00
LNS-17	3.5	\$1.00
LNS-18	-3.50	\$1.00
LNS-19	-2.75	\$1.00
LNS-23	-3.75	\$1.00
LNS-24	-0.25	\$1.00
LNS-25	-4.25 and -1.00	\$1.00

20 mm DIAMETER GLASS MOUNTED POLARIZED FILTERS

Made by Polaroid for use in military binoculars, these filters are ideal for experimentation, education and optical projects. Optically ground glass, 20 mm diameter X 2 mm thick. Notched. 20% transmission.


CAT# PF-1 \$1.00 each Box of 40 - \$30.00



U.S. Precision Lens, Inc., Delta 67®

Assembly consists of one 2.9" dia. glass, convex-convex lens and two plastic lenses, 3.3" and 2.66" at front and rear. Outer housing is 4.58" dia. x 2.3" high. Focal length adjusts by way of a wingnut on the side of the lens.

CAT # LNS-67 \$ 5.50 each




1.5" CONVEX LENS

U.S. Precision # 7799-00-001
1.5" diameter x 0.4" thick (max) acrylic lens.

CAT # LNS-14 \$ 1.00 each



Voice Direct 364™ Speech Recognition Kit



This kit enables you to add voice recognition to toys, motors, appliances, lights and games. It can be trained to recognize up to 60 words or phrases lasting up to 2.5 seconds each. "Continuous Listening" technology allows it to be programmed to recognize three words or phrases within an ongoing monologue. The Voice Direct™ module is very selective, in that it responds only to the voice that programs it. Module size is 2" square. Operates on 4.5 - 5.2 Vdc Kit includes the Voice Direct module, a speaker, microphone, LED, resistors and pushbutton switches. Not included, but recommended: A 5 Vdc 100 mA power supply or 3 AA batteries and a battery holder, 3" x 3" proto or perf board, 0.1" male headers (17, 19 and 14 pins), hookup wire and some LEDs to monitor outputs.

CAT # SKR-364 \$49.95 each

KITS


A NOTE ABOUT KITS....

Kits cannot be returned or exchanged once assembly has begun. All parts supplied EXCEPT batteries. Some kits require permission of parties involved before use.

ADJUSTABLE LED FLASHER

Two potentiometers adjust the flash rate of two LEDs. 9V operation. Battery not included.


CAT #MK-1021 \$4.95 each



WATER ALARM

Buzzer sounds when water is detected. Water sensor can be placed at a distance by cutting the board and using wires to connect the sensor. 9V operation. Battery not included.


CAT # MK-108 \$ 7.95 each



L.E.D. FLASHER KIT

Two L.E.D.'s flash in unison when a 9 volt battery is attached. This kit includes a p.c. board, all the parts and instructions to make a simple flasher circuit. A quick and easy project for anyone with basic soldering skills.


CAT# LEDKIT \$1.75 per kit



LED CHASER KIT


Build this variable speed led chaser. 10 leds flash sequentially at whatever speed you set them for. Easy to build kit includes pc board, parts and instructions. Ideal for special lighting effects, costumes, etc. Operates on 3 to 9 volts. PC board is 5" X 2.25".

CAT# AEC \$6.50 each
10 for \$62.50 • 100 for \$600.00



STROBE KIT


Variable rate strobe kit, flashes between every 2 or 3 seconds. Our kit will operate on either 12 Vdc or 4.5 to 6 Vdc depending upon how you decide to wire the circuit. Comes complete with P.C. board and full instructions for easy assembly. **CAT# STROBE-1** \$7.50 each



DC TO PULSE WIDTH CONVERTER

Velleman # K8004. Ideal for the accurate control of DC motors, lighting levels and small heaters as well as other applications. The circuit converts DC voltage into a series of pulses, the duration of which is directly proportional to the voltage. Minimizes power loss in the control circuit. Overload and short circuit protection. Input Voltage: 2.5 - 35 VDC. Maximum output 8-35 Vdc, 6.5 Amps.

CAT # MK-804 \$22.95 each




UNIVERSAL BATTERY CHARGER / DISCHARGER KIT FOR NICKEL CAD AND NICKEL METAL HYDRIDE

Velleman # K7300.

Versatile kit allows charging of NiCad and NiMH batteries of different voltages and capacities. Settings for rapid and normal charge rates.

Also has a feature that discharges the batteries before charging to get maximum life out of the cells. Selectable charge current from 15 mA to 750 mA. Charges cells of 1.2, 2.8, 3.6, 4.8, 6, 7.2, 8.4 and 9 Volts. Requires a 15 vdc, 800 mA power supply/ wall adapter.

CAT # MK-173 \$ 24.95 each



INTERVAL TIMER KIT


Velleman # MK111. For intermittent operation of circuits and equipment. Use for blinking light control, slide projector control etc. Pulse time adjustable between 0.5 and 5 seconds. Pause time adjustable between 2.5 and 60 seconds. 3 Amp output relay. Power supply 12-15 Vdc @ 100 mA (not included).

CAT # MK-111 \$ 9.95 each

METAL DETECTOR

Ideal for locating metal pipes and objects in walls or ceilings. An LED indicates if a metal object is in the vicinity. If an audible signal is desired, space is provided for a buzzer. Operates on 9 Volt battery (not included).

CAT # MK-7102 \$12.99 each



I.R. RECEIVER MODULE (with timer)

When a signal is received from an infrared transmitter, this module will turn on a device (3-6 Vdc @ 0.5 amps) for 10 to 30 seconds. Can be activated with I.R. remote control from TV or VCR or make your own transmitter (see EM-111) below. Use with sound modules, toys and models. Requires 2 AA batteries. **CAT# EM-108** \$6.00 each

I.R. TRANSMITTER MODULE


Build this transmitter to use with the IR receiver module EM-108 above. Requires 2 AA batteries.

CAT# EM-111 \$3.50 each

DC MOTOR SPEED CONTROL KIT

Easy to build kit allows you to control the speed and direction of 6-12 vdc electric motors or control the intensity of 6-12v incandescent lamps. Includes pc board, parts, instructions and dc motor.

CAT# MSC-6 \$15.00 each




MOTOR SPEED CONTROL MODULE

For 3-6 Vdc motors @ 0.5 amps. Features a pulse width modulation design that can vary motor speed from 5% to 95% with little loss of power. Use with any 3-6 Vdc power source.

Does not include batteries or motor.

CAT# EM-114 \$3.50 each



STEREO PRE-AMP KIT

Low-noise stereo pre-amplifier. Boosts input signal in audio applications. 1K ohm input impedance. Frequency range 40Hz-30KHz(-3dB). Adjustable gain, 40 dB max. PCB dimensions: 1.7" x 2.6". Requires 10-30VDC/ 5 mA power supply (not-included).

CAT # MK-2572 \$ 17.50 each

TRAIN SOUNDS KIT

Produces 4 kinds of train sounds: approaching and departing station, diesel and steam train. With a size of only 0.78" X 0.78" X 2", it can be installed in various model trains. Includes speaker and battery holder. Requires 2 AA batteries


CAT# EM-105 \$6.95 each

FLASHING LEDS WITH MUSIC

When triggered, 7 leds flash randomly for a few seconds. When they stop a beeping sound is heard for a few seconds. If the leds stop on LED number seven, a piece of music is played for a few seconds.

Can be used as part of a game or a flashing badge. Operates on two AA batteries (not included).

CAT# EM-103 \$4.75 each



SOUND OPERATED CONTROL with TIMER


Clapping hands or other sharp noise is picked up by electret microphone and used to trigger a switch which can be used to turn on a light, motor or audio device. Shuts off automatically after 15 to 30 seconds. Operates on two AA batteries (not included).

CAT# EM-106 \$4.75 each

LIGHT RECEIVER with TIMER

Photodiode senses changes in ambient light and triggers a switch which can be used to control a light, buzzer or motor operating on up to 3 Vdc at 0.5 Amps. Resets itself automatically after 10 to 30 seconds. Operates on two AA batteries (not included).

CAT# EM-107 \$4.75 each




RUNNING MICROBUG

Velleman# MK-127 Bug-shaped miniature robot. Driven by two miniature motors, its photocell sensors seek light. Stops in total darkness. LED eyes

indicate driving direction. 3.93" x 2.36." Operates on two AAA cells (not included).

CAT # MK-127 \$14.95 each




CRAWLING MICROBUG

Velleman# MK-129

Two-speed miniature robot. Driven by two miniature motors, its photocell sensors seek light. Stops in total darkness. LED eyes indicate driving direction. 4.5" x 3.43."

Operates on two AAA cells (not included).

CAT # MK-129 \$19.95 each




SOLDERLESS KITS FOR KIDS...

WALKING DINOSAUR KIT

This dinosaur walks, wiggles its head and tail and blinks its LED eyes. May require adult supervision, since it has a lot of parts including a motor and gears. It's fun to watch and can be painted to suit your taste. Operates on 2 AA cells (not included).


CAT # MK-103 \$ 9.95 each



BIG WHEEL RACER KIT

Easy to build racer kit provides hours of enjoyment. The car is over 6" long and is designed to be assembled without soldering. The front and rear wheels have rubber tires. It can go straight or in circles. The small DC motor is powered by two AA batteries (not included).

CAT # MK-102 \$6.95 each



An excellent educational toy, the following radio kit makes a great gift for children ages 8 and older. Built on a plastic breadboard, they don't require soldering and are fun to listen to.


CRYSTAL RADIO KIT

How long has it been since you've seen a crystal radio?

Amaze your children and yourself with this easy to build kit, the first form of modern radio.


CAT# SK-103

\$5.95 each




BUILD YOUR OWN BATTERY OPERATED WOODEN MODEL

These complete kits come with pre-cut wooden parts, assembled gear unit, motor and complete illustrated instructions. Specially designed for children to build, these kits require the most basic electronic tools and two AA batteries (not included). Adult supervision recommended. Four kits available:



TRICERATOPS


CAT# SM-802 \$10.95 each



ROBOT

CAT# SM-803


\$10.95 each



ELEPHANT

CAT# SM-800

\$10.95 each



RACE CAR **CAT# SM-804** \$10.95 each

FERRITES

FERRITE BEADS

0.5" long x 0.5" o.d. x 0.31" i.d.

CAT # FB-35 \$1.00 each

1.13" long x 0.75" o.d. x 0.43" i.d.

CAT # FB-44 \$1.00 each

0.5" long x 1" o.d. x 0.47" i.d.

CAT # FB-45 \$ 1.00 each

0.54" long x 0.56" o.d. x 0.24" i.d.

CAT # FB-49 \$1.00 each


1.15" long x 0.74" o.d. x 0.4" i.d.

CAT # FB-50 \$1.00 each



FERRITE SPLIT BEADS WITH SNAP SLEEVES

Ferrite split beads are used to suppress RFI, EMI and unwanted spurious signals. Easy to install. Self-locking plastic snap sleeve holds ferrite form in place.



0.2" I.D. 0.50" o.d. x 1" long.

CAT # FB-28 \$ 1.25 each

0.25" I.D. Outer case size: 0.73" X 0.73" X 1.28"

CAT # FB-40 \$ 2.00 each

0.3" I.D.

Plastic snap-sleeve is 0.7" long x 0.92" wide.


CAT # FB-48 \$1.25 each

0.34" I.D. Ferrite snap-bead

prepped with several feet of wire looped through it. The wire is easily removed. Outer dimensions. 1.38" long x 0.79" O.D.

CAT # FB-37 \$1.50 each

10 for \$13.50 • 100 for \$100.00




0.36" I.D.

0.66" long x 0.87" O.D.

CAT # FB-46 \$1.75 each

10 for \$15.00 • 100 for \$120.00



0.4" I.D. 0.93" x 0.92" x 1.3" long.


CAT # FB-29 \$ 2.00 each

TOROIDS

O.D.	Ht.	I.D.	Color	CAT #	Price	100
0.375"	0.13"	0.19"	Beige	TOR-33	10 for \$1.00	.06
0.375"	0.13"	0.19"	Gray	TOR-29	10 for \$1.00	.06
0.5"	0.10"	0.30"	Charcoal	TOR-23	10 for \$1.00	.06
0.5"	0.18"	0.28"	Charcoal	TOR-4	10 for \$1.00	.06
0.5"	0.25"	0.31"	Charcoal	TOR-39	10 for \$1.00	.06
0.87"	0.25"	0.50"	Charcoal	TOR-28	3 for \$1.00	.20

FERRITE BOBBIN COILS

mh	CAT#	each
1	FBC-1	2.35
2	FBC-2	3.00
3.5	FBC-3.5	3.60
4.5	FBC-4.5	4.20
5.5	FBC-5.5	5.25
6.5	FBC-6.5	6.30
7.5	FBC-7.5	7.50
9	FBC-9	8.85



For speaker crossovers

Page 86

INDUCTORS

0.676 MICRO HENRY ADJUSTABLE

CHOKE 0.375" X 0.375" X 0.75" high coil with adjustable ferrite. PC leads on 0.38" (10mm) centers. **CAT# RC-676** 3 for \$1.00 100 for \$25.00



3.9 MICROHENRY COIL

J.W. Miller # 4608

3.9 uH, 1000 mA axial inductor.

0.21" diameter x 0.75" long with 1.5" leads.

CAT# CA-4608 \$ 1.00 each

10 for \$ 8.50 • 100 for \$ 75.00



46 MICROHENRY, 2 AMP

TDK# SF-T8-40SM. 46 uH, 2 amp toroidal inductor. 0.67" dia. X 0.35" thick. Coated exterior.

CAT# CC-462 75¢ each • 100 for \$50.00



220 MICROHENRY DRUM CHOKE

Coilcraft # TV1363-B. 220 uH 5% @ 100 KHz

0.1 V 0 ADC. 0.4 ohm DC resistance.

0.32" dia. x 0.59" high radial choke. Leads on 5 mm centers. Tape and reel packaging.

CAT # CR-220 4 for \$ 1.00

100 for \$ 20.00 • 1000 for \$ 100.00



CURRENT SENSING INDUCTORS

Encapsulated current sensing coil designed for use at 1KHz to 100 KHz. The conductor carrying the current to be measured is the "one turn primary" and passes through the center hole. The 200 turn, 80 mH secondary is the sensor and can read currents as high as 35 Amps with a sensitivity of 10mA to 1 Amp per volt depending on the resistance of the terminating resistor (200 ohms nom.). Sensitivity can be doubled by looping through the center hole twice. Applications include overload sensing, detecting load drop or shut-down, switching feedback control. Also useful in low frequency LC filters and tank circuits. PC pins on 0.5" centers. Spec. sheet included.

Falco # CS200 P/N TS50009

0.65" x 0.38" x 0.76" high.

CAT # VT-3

\$1.25 each • 100 for 75¢ each



Pulse# PE-51688

0.65" x 0.36" x 0.77" high.

CAT # VT-2 \$1.25 each • 100 for 75¢ each

Vitec# 57P1820

0.67" X 0.375" X 0.80" high.

CAT# VT-4 \$1.25 each • 100 for 75¢ each

CHOKES

ALL VALUES IN MICRO-HENRYS (uH)

NEW	Value	Cat#	Price
	1	CC-1	3 for \$1.00
	2.2	CC-202	3 for \$1.00
	10	CC-10	3 for \$1.00
	12	CC-12	3 for \$1.00
	15	CC-15	3 for \$1.00
	390	CC-390	3 for \$1.00
	1000	CC-1000	2 for \$1.00


4.0 mH HIGH CURRENT CHOKE

ACTUAL CURRENT RATING UNKNOWN

2.25" X 1.93" X 1.48"

CAT # CA-401

\$5.00 each



\$6.00 Shipping Charge Within the Continental USA

A.C POWER CORDS

2 CONDUCTOR

9' POWER CORD w/ "PIGGY-BACK" PLUG

Electricord. 3 conductor SPT-3, 18/3 black cord with 2 conductor plug. Right-angle piggy-back plug. 9' cord has a molded strain relief 6" from end. Tinned pigtail leads. **CAT# LCAC-98** \$1.00 ea. • 100 for 75¢ ea.


ROUND - 3 CONDUCTOR



3' BEIGE, 14/3 SJT, 14/3 power cord with stripped pigtail ends. 0.37" nom. O.D. UL, CSA. **CAT # LCAC-94** \$ 1.25 each
Case of 125 pcs 95¢ each

4' GRAY/ BEIGE, 14/3 SJT, 14/3 light-gray or beige jacket. 48" long. Hanked. UL, CSA. **CAT# LCAC-91** \$1.50 ea. • 100 for \$120.00

6' BLACK, 16/3

SJT, 16/3 cord w/ stripped pigtail ends.  Black, 0.32" nominal o.d., 105 deg C. UL, CSA. **CAT # LCAC-108** \$2.00 each
Case of 50 pieces for \$1.75 per piece

25' GRAY 18/3 Molded 3 prong grounded plug. 18/3, SJT, 105 deg.C insulation. **CAT# LCAC-25** \$4.50 each

DETACHABLE POWER CORDS



Standard IEC (SPH-386) power cord. IEC female connector one end, standard 3 prong grounded a.c. plug other end.

5' GRAY 18/3

SVT, shielded cable. 0.27" nominal o.d. UL, CSA. **CAT # LCAC-92** \$ 2.50 each

6' BLACK 18/3

SVT, 0.26" nominal o.d. UL, CSA. **CAT# LCAC-60** \$3.00 each
10 for \$25.00 • 100 for \$175.00


6' GRAY 18/3

SVT, 0.26" nominal O.D. UL CSA 10A **CAT# LCAC-71** \$ 3.00 each
10 for \$ 25.00 • 100 for \$ 175.00

10' GRAY 18/3

SJT, 0.33" nominal o.d. Shielded. UL, CSA. **CAT# LCAC-88** \$3.25 each
10 for \$27.50 • 100 for \$200.00

8' CORD WITH LOCKING END

Electricord. Black, 18/3 SVT power cord. Female end is a Sure-Lock™ connector with locking tabs. 0.25" dia. UL, CSA. **CAT# LCAC-109** \$3.00 each 

HEAVY-DUTY

6' 14/ 3 detachable power supply cord. Black SJT insulation. 0.37" diameter. UL, CSA. **CAT # LCAC-90** \$ 3.25 each


HOSPITAL GRADE CORDS



6' GRAY 18/3 SJT, 105 deg C. 0.31" o.d. Semi-clear molded plug and socket. UL, CSA. **CAT # LCAC-105** \$ 4.25 each

6' GRAY 18/3, SJT, 105 deg C. 0.31" o.d. Gray molded plug and right-angle socket. UL, CSA. **CAT # LCAC-107** \$ 4.25 each

DETACHABLE CORDS WITH STRAIGHT BLADE (IEC320) ENDS



Black 14/3 SJT power cords. Standard male 3 prong grounded plug on one end. 3 conductor straight blade, IEC 320, female connector molded on other end. 0.38" diameter. UL.

5 1/2 FOOT CORD


CAT # LCAC-102 \$3.75 each
10 for \$ 3.50 each • 100 for \$3.00 each

14 FOOT CORD

CAT # LCAC-101 \$ 5.75 each
10 for \$ 5.25 each • 100 for \$4.50 each

2 CONDUCTOR UNIVERSAL POWER CORD

Fits many laptop and video game power supplies. **CAT # LCAC-100** \$ 2.00 each



6' FLAT - 3 CONDUCTOR




Woods Electric # 464

6 foot 16/3, SPT-3 gray power cord. Molded 3 prong plug. Rated 13 Amps /125 volt. UL.

CAT# LCAC-84 \$1.50 ea. • 10 for \$1.25 ea.

STRAIN RELIEFS

Prevent power cords from pulling, pushing, or twisting in chassis hole. 

CAT#	WIRE TYPE	HEYCO# or equiv.	HOLE SIZE	PRICE
SR-40	flat 18/2 SPT-1	4P-4	.45"	10/ \$1.00
SR-60	flat 18/2 SPT-2	4N-4	.50"	10/ \$1.00
SR-50	18/2, 18/3, SV, SVT round	5L-1	.50"	10/ \$1.00
SR-18	round, 0.2" diameter cable	5P3-4	0.5"	10/ \$1.00
SR-19	round, 0.26" diameter cable	6W-1	0.5"	10/ \$1.00
SR-70	18/2, 18/3, 16/2, 6/3 SV, SVT, SJO round	6N-4	.65"	10/ \$1.50
SR-80	18/3, 16/3, SJ, SJT, SJO round	6N3-4	.625"	10/ \$1.50
SR-16	SJT 12/3 0.425" to 0.475" dia cable	31-2	0.875"	5/ \$1.00
SR-34	flat up to 0.29" X 0.65"	SR34-2	0.875"	2/ \$1.00

IN-LINE THUMBWHEEL SWITCH FOR SPT-2 CORD

S.P.S.T. on-off thumbwheel switch for two conductor SPT-2 power cords. Rated 6 Amps @ 125 Vac. To install, cut a small piece out of one side of a two conductor cord and screw together the two halves of the switch. Prongs puncture insulation and make the connection. UL, CSA.

CAT# SWT-1 \$1.25 each




AC PLUGS

3 PRONG AC PLUG

Leviton # 515PR. Black 15 Amp grounding 3-wire AC plug. Rubber body is dirt and moisture resistant. Tough elastomeric husk. Built-in cord grip adjusts to 0.245" to 0.655" cords, 18-3 to 12-3. UL, CSA.


CAT# ACP-8 \$2.50 each • 10 for \$1.85 each



AC PLUG ADAPTER

RATED: 125 Vac @ 15 amps. Turns 3-prong AC plugs into a 2-prong, polarized plug.


CAT# ACP-2 2 for \$1.00



15 AMP 3-WAY POWER TAP

Woods Electric # FF-148
Hard rubber, 3-way grounded power tap.
Rated 15 Amps @ 125 Vac.
UL, CSA.

CAT # TPA-1 \$1.50 each




A.C. SOCKETS

15 AMP GROUNDED OUTLET

Leviton # 1374-500.
Black 3 conductor grounded outlet.
Rated 15 Amps. Snap-mounts in 0.953" square chassis cutout.
Quick-connect / solder connectors with 6" green ground lead, AWG 16. UL, CSA.


CAT# ACS-28 \$1.20 ea. • 100 for 95¢ ea.



15 AMP GROUNDED OUTLET

Kulka Electric. Black, three-conductor outlet. Snap-mounts in 1" square cutout. Rated 15 Amps @ 125Vac. 6" pigtail leads, AWG 16 stranded wire. UL, CSA.


CAT# ACS-31 \$1.20 each • 100 for 95¢ ea.



3-PRONG GROUNDED SOCKET

Leviton # 114. Heavy-duty 3 prong socket for AC power cords. For 0.396" to 0.562" diameter cords. 18-14 AWG stranded conductors. Rubberized shell resists chemicals and remains flexible even in low temperatures. UL, CSA.


CAT # ACS-27 \$3.50 ea. • 10 for \$3.15 ea.



IEC (SPH-386) SOCKETS

Recessed power receptacle mates with any cord having the SPH-386 connector. Tough molded black plastic. 1 9/16" mounting centers.

CAT# ACS-3 65¢ each
10 for \$5.50 • 100 for \$35.00




RFI/EMI FILTERS

3 AMP EMI FILTER

Power Dynamics, Inc. #PB03F
Compatible with IEC power cords.
Mounting holes on 1.5" centers.
Extends 2" behind mounting panel.
0.25" qc or solder terminals. UL, CSA, VDE.


CAT# EMI-31 \$1.25 each • 100 for \$75.00



6 AMP RFI/EMI FILTER

CDE # APF600CET 1.18" x 0.8" x 1.63". Right angle terminals.

CAT # EMI-62 \$1.50 each
10 for \$12.00 • 100 for \$85.00



SURGE PROTECTORS

Protect computers, phone equipment, VCRs and other sensitive devices from electrical transients and glitches.


1290 JOULE SURGE SUPPRESSOR

Newpoint # 1002.


Six outlet strip with two spaced outlets to allow use of transformers without blocking other outlets.
Protects computers, audio/video equipment, fax machines, modems and other small devices from voltage surges caused by lightning or power fluctuations.

Also has EMI/ RFI noise reduction. Automatic shut-down when surge protection has reached capacity. Power switch with integrated circuit breaker. Protection indicator light. Modular phone jacks with surge and EMI/RFI protection as well. 6' power cord. Includes 6' modular phone cord.

CAT# PW-1290 \$12.00 each



6 OUTLET STRIP




CAT# PW-101
\$6.50 each

EXTENSION CORDS

7' EXTENSION CORD W/ FLAT PLUG

RCA # E1007W. 7' white, 16 gauge extension cord with right-angle plug to allow easy fit behind furniture. Two conductor, SPT-2 cord. Three tap outlet.

CAT# EXT-70 \$1.50 each




10' 16/2 EXTENSION CORD, 3 OUTLET END

Woods Electric # 5606.

10' gray, 2-conductor, 16 gauge extension cord. SPT-2 insulation.


UL listed. **CAT# EXT-10G** \$1.65 each



EXTENSION CORD WITH ROTATING PLUG


This 1 foot heavy-duty extension cord is great for gaining access to hard-to-reach outlets. The plug rotates 360 degrees, so the socket end of the cord can be reached from above or either side. Grounded, three-prong plug and socket. 14/3 gray SJT cable.

CAT# EXT-1 \$2.50 each




PHOTOCELL CONTROLLER

Hemco # SLC4CG. 150 Watts.
Automatically turns lights on
at dusk, off at dawn. For 115vac use,
incandescent lamps only. Blister
packaged with instructions. UL, CSA.
CAT# APC-4 \$2.50 each



TOUCH LAMP DIMMER

Turn lamps on and off, brighten and
dim with a touch of your finger.
Touch-controlled lamp dimmer screws
into most table and floor lamps and
instantly converts them to four-level
dimmers. Works on incandescent
lamps up to 150 Watts. Lamp must
have a metal base or pole connected to
the lamp socket. Outer metallic surface of
lamp socket must be exposed so dimmer can
make proper contact. UL.
CAT# DS-4 \$2.00 each




DC - DC CONVERTERS

9 VDC, 250 MA

PCA Electronics # EPC1053
Input: 7.5 - 16 Vdc
Output: 9 Vdc @ 250 mA (max)
1.27" x 0.6" x 0.48" high.


CAT # DC-18 \$1.75 each • 10 for \$15.00



DC-DC CONVERTER


TDK # CE-0381 Input: 5 Vdc
Outputs: -10 Vdc, -19 Vdc, -26 Vdc,
and 6 Vac w/ center tap. 1.23" x 0.9".
Includes hook-up diagram.

CAT # DC-32 2 for \$1.00 • 100 for \$25.00



5 VDC to 9 VDC (unregulated)

Valor # PM6045
1.3" x 0.8" x 0.45" high.
Provides 9 VDC @ 250 mA.
Requires about 100 mA load minimum.
CAT # DC-43 \$1.50 each



TUBE SOCKETS

PC mount socket for round base
7 pin relays and vacuum tubes.

WHITE **CAT# SOC-7PC**

2 for \$1.00 • 100 for \$40.00

BLACK **CAT# SOC-7PCB**

2 for \$1.00 • 100 for \$40.00



PC mount socket for round
base 8 pin relays and vacuum tubes.

CAT# OCT-PC 85¢ each


10 for \$8.00 • 100 for \$75.00



Solder style 9 pin tube socket.

CAT# SOC-9M

2 for \$1.00 • 100 for \$40.00



PC mount 9 pin tube socket.

CAT# SOC-9MPC

2 for \$1.00 • 100 for \$40.00



PARALLAX BASIC STAMP COMPUTERS

BASIC Stamps are general purpose I/O computers programmed in PBASIC, a variation of BASIC. Perfect for small control applications. Thousands are in use by hobbyists and professionals throughout the world. Each module has on board EPROM program memory, BASIC interpreter, 5 V regulator and a power reset circuit. Free technical support is available from Parallax by phone or internet <http://www.parallaxinc.com>

STARTER KIT

If you haven't used BASIC stamps before you should begin with one of these packages. They contain everything you need to utilize a BASIC stamp in your application. Included is the BS-1, BS-2 or BS-2SX module, carrier board and a Programming Kit (list price \$84.95) consisting of software disc, serial cable and a 454 page manual with examples, application notes and code conversion tips. The software requires DOS 2.0+ and a parallel port.

CAT#	DESCRIPTION	Each
27205	BS-1 Starter kit	\$ 109.00
27203	BS-2 Starter kit	\$ 149.00
27206	BS-2SX Starter kit	\$ 159.00

INDIVIDUAL BASIC STAMPS, CARRIER AND ACTIVITY BOARDS

BASIC stamps come in three configurations:


The BS1-IC has 8 I/O lines,

program storage for 80 BASIC instructions, 4 MHz operation and comes in a 14 pin SIP package. **CAT # BS-1** \$ 34.00 each




CARRIER BOARD FOR BS-1

CAT # 27110 \$ 15.00 each



The BS2-IC has 16 I/O lines, program storage for 600 BASIC instructions, 20 MHz operation and comes in a 24 pin DIP package.

CAT # BS-2 \$ 49.00 each



The BS2SX-IC

A more powerful version of BS2 with 2.5 x more speed (50 Mhz), 8x more code space and 63 more bytes of RAM. Pin and downward code compatible with the BS2 module with the exception of timing parameters. 24 pin DIP package.

CAT# BS-2SX \$59.00 each

CARRIER BOARD FOR BS-2 and BS2-SX


CAT # 27120 \$ 20.00 each

BOARD OF EDUCATION

Designed as part of an educational "Stamps in Class" program, the "Board of Education" is a useful development platform for the BS-2 and BS-2SX chips. 3" x 4" overall size. Features include: DB-9 connector for programming and serial communication during run time. P0-P15 I/O pins, Vdd and Vss connections adjacent to the breadboard. Includes 10 color-coded 22 gauge wires for wiring to bread board. Connector for optional AppMods (more breadboard space). On-board 9 Volt battery clips, or use with wall transformer. **CAT # 28150** \$ 59.00 each

2 X 16 SERIAL LCD

Scott Edwards Electronics
Useful if your BASIC stamp project needs to interact with a human user. Requires only one I/O line, +5 Volts DC and ground, and are controlled with simple SEROUT instructions from the BASIC stamp. **CAT # 27910** \$49.00 each



CELL PHONE ACCESSORIES

"HANDS-FREE" HEADSETS

Allows for hands-free operation while driving or walking. Earpiece fits in ear while microphone hangs next to your mouth. Makes your drive time safer and more comfortable.



Nokia 5100/6100 Models - Pushbutton
on microphone to answer and end calls.
CAT # NOK-2 \$6.95 each

Nokia 8200/3300
CAT# NOK-10 \$6.95 each

Motorola Star-Tac, Samsung 6100 and some other cell phones with a jack for a 2.5mm stereo phone plug. **CAT # MT-2** \$6.95 each


NOKIA 5100/6100 Padded Headset

If you find the in-the-ear type headset uncomfortable, this may be your salvation. The earpiece sits outside of your ear, held in place by a strap that goes over your ear.
CAT# NOK-9 \$7.95 each



"OVER-EAR" HANDS-FREE HEADSET W/ BOOM-MIKE

This "hands-free" headset puts the earpiece outside of your ear and has a boom-mike to get the mike closer to your mouth. Works with Motorola Star-Tac, Samsung and other cell phones as well as some cordless phones and computers. Beige headset and 5' cord with right-angle 2.5mm stereo mini phone plug.
CAT # PHN-21 \$ 4.95 each



BATTERY CHARGERS

NOKIA CHARGER FOR 5100/6100/8200/3300/8800

For most current model Nokia cell phones, models 5100 series, 6100 series, 8200, series, 8800 series, 3300 series. Allows you to power your cell phone and charge the batteries wherever an AC outlet is available.
CAT# NOK-11 \$7.95 each




CIGARETTE LIGHTER/ WALL CHARGER

Use your automobile cigarette lighter power cord to charge or operate cell phones, laptops, and audio equipment at home or in a hotel. If you don't have, your "in-home" charger, but still have the automobile charger, this wall transformer will work for most loads, up to one amp. Works with all car lighter cords that would normally work on 13.6 V automobile voltage.
CAT# DCTX-1286 \$9.95 each



CAR CHARGER

Plugs into car cigarette lighter or accessory socket. Charges most batteries in an hour or less.



Nokia 3300/5100/6100/8200 and 8260
CAT # NOK-1 \$ 4.95 each


Motorola Star-Tac
CAT # MT-1 \$ 4.95 each

Motorola V60, V6 6, I20 and
Nextel I85, I50, I80
CAT# MT-4 \$4.95 each

BATTERIES


LOW, LOW PRICE! NOKIA 5100/6100 CELL PHONE BATTERY

Standard battery for all Nokia 5100 and 6100 series cell phones. 3.6 Volt, 900 mAh nickel metal hydride pack good for 3-5 hours talk time, 60-270 hours standby time. These are new batteries with minor cosmetic blemishes, that do not impair the battery's usefulness in any way. Ideal replacement or spare battery.
CAT# NOK-8 \$6.95 each



NOKIA 5100/ 6100 LITHIUM-ION BATTERY WITH VIBRATOR

Provides 1000 mAh of storage capacity, twice that of the standard Ni-cad battery that comes with the phone. Also contains a mini-vibrator allowing you to shut-off the ringer and still be aware of incoming calls.
CAT # NOK-5 \$ 19.95 each



CLIPS AND CASES


NOKIA GENUINE LEATHER CASE

For 5100 and 6100 series. Protects phone and provides a belt clip. Also includes detachable wrist strap.
CAT# NOK-6 \$4.95 each




SWIVEL CLIP

Small knob attaches to back of phone which then slides into spring clip. Allows you to clip phone to belt or visor. Comes with two knobs; one fits Nokia 5100/ 6100 phones, the other has double-sided tape for attachment to any cell phone or other device.
CAT # SLP-1 \$ 2.50 each




MAGNETIC CELLPHONE HOLDER

A convenient cellphone holder for automobile dashboard. Compact magnet /clip attaches to any flat surface using extremely strong adhesive sticker. Provides a hanger for cellphone carrying case or swivel clip, or attach phone directly to magnet using adhesive-backed metal plates included with holder. Powerful 7500 gauss magnet securely holds phone in place.
CAT # MLP-1 \$ 3.75 each



PC BOARD W/ LEDS & NEONS

Unidentified assembly, possibly for telephone application, with two NE-2, neon lamps, a rectangular LED, a switch and a phone cord. **CAT # EX-70**
5 for \$1.00 • 100 for \$10.00



PRESSURE-LIMIT SAFETY VALVE


Take the guesswork out of inflating bicycle tires. Screws on to the tire valve stem, and stops filling tire when preset pressure limit has been reached. Eliminates need for tire gauge. Four tire pressures available:



For 40 psi tires **CAT# PLV-40** set of 2 for \$1.00
For 65 psi tires **CAT# PLV-65** set of 2 for \$1.00
For 90 psi tires **CAT# PLV-90** set of 2 for \$1.00
For 100 psi tires **CAT# PLV-100** set of 2 for \$1.00

MAGNETIC CARD READERS


Used credit card magnetic strip reader and telephone cradle mounted on a metal box. Originally part of a mobile pay phone system. Strip reader is 4" x 1.65" x 1.1." Box is 4.5" x 4" x 1.45." Phone not included.



CAT # MSR-2 \$ 3.00 each

Peripheral Dynamics
3807-20.

Card reader mechanism with 8 digit LED readout and related circuitry. Mounted in a 5.38" x 4.25" x 3" metal case. Used, removed from Bally gaming machines.




CAT# MCR-6
\$3.50 each

MEDIA STORAGE

MODULAR CD RACKS


Organize your CDs or CD ROMs with these high-impact, black plastic CD storage racks. Slots for 12 jewel cases. Each 12 CD module can interlock vertically and horizontally with other modules. Can be free standing or wall mounted.



CAT # CDR-3 \$2.00 each • 10 for \$17.50

MULTI-MEDIA RACK

Desktop flip rack keeps all of your important media in one place. CD's 3.5" floppies and ZIP discs all can be stored in the same rack. Outer rails hold 16 CD/CD ROMs. Inner rails hold 20 3.5" floppy discs, or 3 ZIP discs and two M.O. discs. Attractive retail packaging.




CAT# CDB-18M \$1.75 each • 10 for \$15.00

AUTO CADDY™ AUTOMATIC TEE MACHINE

For the golf enthusiast -- or anyone in need of a mechanical extension arm. An electrically controlled arm extends and drops a golf ball onto a tee when foot pedal is depressed.


Unbreakable plastic hopper, 18.75" x 10.5" x 9.5" high. Holds approximately 200 balls. Designed for use with "astroturf-style" mat to support standard rubber driving range tees. Dual motor mechanism may be useful for other applications. Arm with ball holding ring extends 8.5". When it reaches full extension it retracts a metal rod allowing the ball to drop. The arm then goes back inside the hopper. Operates on 120 Vac. 6 foot grounded power cord. Includes six rubber tees, height adjustment knob and hardware for foot pedal and mounting feet. Does not include driving mat.



CAT # CDY-1 \$ 20.00 each

NINTENDO GAME BOY™ AMPLIFIER


Nuby # GC-7. Turn up your "Game-Boy." Hear the game the way it's meant to be, in stereo, comfortable, but not too loud. Plugs directly into the audio jack. Designed to fit older "Game-Boys." Works with the new models, but is larger than the game and doesn't fit perfectly. Requires 9V battery or 9V wall transformer (not included).



CAT # NGA-7 \$1.85 each

COUNTDOWN CLOCK

This fully functional assembly from an unusual "LifeClock" countdown clock. Based on information you program into it, the "LifeClock" displays the estimated remainder of your life in hours, minutes, seconds and tenths of seconds.



The clock also flashes an inspirational message every minute and the actual time. Can be programmed to countdown shorter intervals by inputting a fictitious birthdate. Information is displayed on a backlight 2 x 16 LCD, 2.75" x 1.06". The whole assembly is on a triangular plastic base, 4.38" x 11.5" long and 2.7" high. Includes hook-up/ instruction sheet. Requires a 6 - 7.5 Vdc wall transformer (not included).

CAT # CDC-1 \$7.50 each


Recommended power supply:

CAT # DCTX-6570 \$ 3.00 each

Power supply requires removal and replacement of co-ax plug. Use **CAT# DCSID** 50¢ each

AUTO / MARINE RADIO NOISE FILTER

American International # S-10-ACL. Reduces and eliminates ignition and alternator interference (noise that increases or decreases with engine speed). For stereos, amps, equalizers and CB radios up to 10 Amps, 150 Watts. 4" x 2.27" x 1.9" high.




CAT# NF-10 \$2.50 each • 5 for \$2.00 each

MINIATURE WATER PUMP

Automobile windshield water pump shoots a forceful stream of water from a 1/8" diameter orifice. Intake is 0.5" diameter. Operates on 12 Vdc. Intermittent duty cycle. 2.9" long x 2.5" wide including connector.

CAT # PMP-2 \$ 3.75 each



HUMIDITY METER


Duracraft. Relative humidity scale calibrated from 20% to 100%, with 30% to 50% being designated the "Comfort Zone." 2" diameter meter in a wall-mount or table-top gray plastic case, 3.55" high x 2.66" wide x 1.18" deep.

CAT# HMR-1 \$2.50 each



100 WATT INVERTER


Car-tricity. Plugs into the cigarette lighter jack in your car and converts 12 Vdc to 115 Vac. Operate laptop computers, small televisions (14" or less), battery chargers and practically any device that is powered by a wall transformer. Two prong AC socket output. Includes detailed instructions. Will not operate larger devices that require more than 100 Watts. **CAT # INV-100** \$19.00 each



MULTI-PURPOSE CARRYING CASE

Two compartment, black leatherette case with webbed nylon shoulder strap. Main compartment is 11.5" high x 8" x 5.25" and has vented sides and top. Smaller, front compartment is 9.5" x 8" x 2" and has three Velcro-style straps inside to hold contents in place. Velcro-style straps on one side of case can be used to fasten 2-3" diameter items. Expandable 8.5" x 5.7" back pocket. Avstar logo on front and top.


CAT # CSE-24 \$7.95 each



PADDED CARRYING CASE

Belkin Media Drive Carrying Case # F8E161. Designed for a variety of media drives such as Zip(R), Jaz(R), & Discman. Ideal for cameras, audio equipment or any other small equipment. A durable black nylon case featuring three zippered, padded compartments. Also has zippered slots to bring cable in or out of case for in-the-case use of equipment. Overall size: 4" x 6.5" x 9." Removable shoulder strap that converts to waist pack.

CAT # CSE-25 \$ 6.50 each



INDEX

A.C./D.C. Adapters	59
A.C. Line Cords	87
A.C. Sockets	88
Adapters	48, 51 - 53
Alarms & Accessories	20, 21
Amplifier	91
Antennas	42
Audio Cables	53
Automotive	33, 54
Auto Power Cords	54
Barrier Strips	60
Basic Stamp	89
Batteries	37 - 39, 90
Battery Chargers	40, 90
Battery Holders	39, 40
Blacklight, (UV)	8, 61
Books	83
Breadboards	73
Bridge Rectifiers	81
Buzzers	20, 21
Cables	42, 44, 45, 50, 52 - 54, 87
Cable Ties	27
Cameras, Video	40, 41
Capacitors	66 - 68
Carrying Cases	92
Cases	72
Casters	65
CD Accessories	91
Cell-Phone Accessories	90
Ceramic Resonators	79
Chassis Boxes	72
Chemicals / Cleaners	78
Choke Coils	86
Circuit Breakers	21, 71
Coil Cords	45
Computer Accessories	50, 61
Connectors	43, 48 - 53
Crimp Terminals	26
Crossovers	71
DC-DC Converters	89
Diac	80
Diodes	80, 81
Displays, LED, LCD	2, 3, 5, 41, 89
Door Lock Actuator	31
Elapsed Time Indicator	25
Electrical Supplies	88
Electroluminescent Backlights	8
Enclosures	72
Encoders, Mech. Rotary	15
Extension Cords	88
Fans	16 - 18
Fasteners	26, 27
Ferrite Beads	86
F.E.T	80
Filter (RFI/EMI)	88
Flash Assemblies	5, 61
Fluorescent lamps	8
Fuse Holders	22, 23
Fuses	22, 23
Gear Motors	30 - 32
Gears and Pulleys	28
Hardware	26 - 28, 45, 64, 65
Headers	49
Headphones	23, 24
Heat Shrinkable Tubing	43
Heat Sinks	18, 19
Indicator Lights	6, 7
Inductors	86
Infrared Detectors	15
Infrared Remotes	15, 43

Integrated Circuits	78, 79
Inverters	8, 92
Jacks	48 - 53
Keypads	15
Kits	8, 83 - 85
Knobs	63, 64
Lamps	6 - 8
Lamp Holders	7
Lasers	2
LCD Displays	3, 41, 89
L.E.Ds	2, 4, 5
L.E.D. Holders	5
Lenses	83
Line Cords	87
Locks	64
Magnets	25, 76
Magnetic Card Reader	91
Meters, panel	50
Metal Detector	25, 84
Microphones	24
Mirrors	76, 83
MOSFETS	80
Motors	29 - 32
Motors, Gear	30, 31, 32
Motors, Stepper	32
Mounting Brackets	64
Optics, Lenses	83
Opto Electronics	4, 5, 80, 81
Panel Meters	50
P.C. Board Material	74
Peltier Devices	16
Perf Boards	73
Photocell Switches	89
Photoconductive Cells	82, 83
Photo Diodes and Transistors	80, 81
Photovoltaics	82
Piezo Elements	20
Plugs	48 - 53
Potentiometers	62, 63
Power Cords	87
Power Supplies	55 - 57, 72
Printed Circuit Supplies	74
Project Boxes	72
Rack Handles	65
Rechargeable Batteries	37 - 39
Relays	33 - 36
Relay Sockets	36
Remote Control, IR	43
Resistors	68
Resistors, Variable (Pots)	62, 63
RFI/EMI Filters	88
Ribbon Cable	45
Rotation Components	28
Rubber Feet	65
S.C.Rs.	80
Semiconductors	78 - 81
Shrink Tubing	43
Sirens	21
Sockets	
Lamp	7
I.C.	79
Relay	36
Transistor	80
Tube	89
Solar Cells (Photovoltaics)	82
Soldering Irons and Accessories	74, 75
Solderless Breadboards	73
Solid State Relays	35
Solenoids	36, 37
Spacers and Standoffs	27
Speakers	69 - 71
Split Loom Tubing	27
Spring Lever Terminals	71
Stepper Motors	32
Strain Reliefs	87
Strobe Lights	61, 84
Surge Suppressors	88
Switches	
Alarm Switch	14, 15
B.C.D.	14
Dip	10
Hall Effect	73
Heat Sensor	16
Key Switch	14
Lighted Rocker	10
Magnet	15
Push Button	12, 13
Reed	14
Rocker.	10
Rotary Switches	14
Slide	14
Snap-action	11, 12
Toggle	9
Thermal Switch	16
Tape, Electrical	76
Telephone Accessories	46, 47
Terminals, Crimp	26
Terminal Strips	60
Test Jumper	77
Test Equipment	76, 77
Thermal Fuse	16
Thermal Switch	16
Thermistors	16
Thermal Protectors	16
Thermoelectric Coolers	16
Tie Wraps	27
Timers	25
Tools	26, 43, 47, 73-77
Toroids	86
Transducers	21
Transformers	57 - 60, 71
Transistors	80
Transmitters	84
Triacs	80
Trim Capacitors	67
Tubing	27, 43, 45
T.V. Accessories	41, 42, 43
Tweeters	70
Ultraviolet Lamps	8
Unijunctions	80
Variacs	58
Varistors (M.O.V.'s)	79
Velcro™	64
Video Accessories	41, 42, 43
Video Cameras	40, 41
Video Tapes	41
Voltage Converters 220/110	71
Voltage Regulators	78
Wall Transformers	59
Wheels	65
Wire, cable	44, 45
Wire Nuts	27
Woofers	69, 70
Zener Diodes	81

ORDERING INFORMATION

NO MINIMUM ORDER

\$6.00 Shipping and Handling for most orders (see shipping instructions).

Phone Orders - You may use our **TOLL FREE NUMBER 1-800-826-5432** during our normal business hours, 6:30 AM to 5PM (Pacific Time) Monday - Friday and 9AM to 4 PM Saturday. Local callers may use 818-904-0524.

Mail Orders - and correspondence should be sent to **ALL ELECTRONICS CORP.,
P.O. Box 567, Van Nuys, CA 91408-0567.**

FAX - You may FAX us your order 24 hours a day, 7 days a week. Our FAX number is **1-818-781-2653**

Walk-In - Our Los Angeles and Van Nuys, California stores stock all of the items in this catalog as well as many which are not of sufficient quantity to be included. L.A. store, 213-380-8000. Van Nuys store, 818-997-1806.

Internet - E-mail us at allcorp@allcorp.com
Shop ON-LINE www.allelectronics.com

PAYMENT METHODS

U.S.A. - Check, money order or acceptable charge card information must accompany your order. We use Instacheck to verify checks. Returned checks are subject to a \$20.00 service charge.

Foreign - Only money orders or cashiers checks in U.S. funds payable thru the U.S. bank clearing systems (drawn on a U.S. bank) can be accepted. Canadian Postal Money Orders in U.S. funds are also acceptable.

Credit Cards - We accept Visa, Mastercard, American Express and Discover card. Please have your credit card information ready when calling. We will require your credit card number, expiration date and your name as it appears on the credit card. Your signature is required on Mail Orders.

Open Accounts - Government or State educational institutes and agencies can submit written formal purchase order forms (verbals are not accepted) for immediate acceptance. All others must submit proper credit information and await approval. Normal credit approval takes up to three weeks and credit terms are extended only to highly rated accounts. Our terms are NET 30 with a \$20.00 minimum. All open account orders are shipped F.O.B. Van Nuys, California (minimum shipping charge is \$6.00)

COD Orders - We do not accept COD orders.

California Customers - Orders delivered within the state of California require us to collect California State Sales Tax unless we have a resale card on file. Please add applicable state sales tax for your county in California (7.25% outside Los Angeles County, 8.25% in Los Angeles County).

SHIPPING INFORMATION

We will e-mail you when we ship your order if you enter your e-mail address on our order form.
Packages under 4 pounds may ship USPS.

Shipping Charges - U.S.A. -

Continental United States (not including Alaska or Hawaii) must include a \$6.00 shipping and handling fee. This will cover shipping via U.P.S. (GROUND) or U.S. mail (PARCEL POST).

Alaska, Hawaii, Puerto Rico, and the U.S. Territories must include full shipping with the order (a \$6.00 minimum shipping charge applies per order). Please check with your local post office regarding charges..

Shipping Charges - INTERNATIONAL

Customers outside the United States are responsible for all shipping and handling charges including but not limited to duties, import or export fees etc. Please check with your local agencies regarding rates. We will ship as per your instructions and will assist you in any way we can. If sufficient shipping is not included, your order will be returned.

Shipping Charges - RUSH ORDERS

We recommend UPS Next Day Air Service or UPS Second Day Service if express shipping is requested. We will also use Federal Express or other express freight companies if requested. We try to ship these orders the day they are placed. **We charge the normal U.P.S. Red, U.P.S. Blue, FED EX or specified express carrier fee plus a \$6.00 handling fee** for any order where special shipping or handling is requested.

Delivery - Except during busy holiday and rush periods, all orders are processed and shipped within two working days of receipt. If an item is out of stock, but expected within a few days, we will hold the order until the item arrives. If you do not want your order held for out of stock items, please let us know. Delivery via U.P.S. is usually made within 7 working days.

IF YOU HAVE A PROBLEM WITH YOUR ORDER

We try to be as accurate as possible but errors do happen. If you have a problem with your order please write promptly to:

Customer Service Department
ALL ELECTRONICS CORP
P.O. Box 567
Van Nuys, CA 91408-0567

No Return Authorization is necessary. Let us know what the problem is and please return any paperwork you receive with your order. Please include a phone number. We will rectify any problems promptly. Please make all claims within 30 days of receipt of your order.


YOUR SATISFACTION IS GUARANTEED

If you are not happy with a product, please return it to us following the above instructions **WITHIN 30 DAYS OF RECEIPT** in original condition (including paperwork etc.) and you will receive a refund or replacement, whichever you prefer.

PLEASE NOTE!

- We Are Not Responsible For Printing Errors
 - Quantities Are Limited
- Prices Are Subject To Change Without Notice
- Some Pictures May Vary From The Actual Item
 - Store Prices May Vary From Catalog Prices
- Quantity Pricing Is Subject To Freight Considerations

Order Toll Free 1-800-826-5432



ORDER FORM

ALL ELECTRONICS CORP.

P.O.Box 567

Van Nuys, CA 91408-0567

Local Phone Number 818-904-0524

ORDER TOLL FREE 1-800-826-5432

FAX YOUR ORDER 24 HOURS 818-781-2653

ORDER ONLINE 24/7 www.allelectronics.com

\$6.00 Shipping and Handling charge for most orders! (SEE SHIPPING INSTRUCTIONS)

Is This Your FIRST Order? Yes ☐ No ☐

If We Don't Have An Item?

Customer/Ref Number _____

(found on the address label)



SEND
REFUND
CHECK



SEND
CREDIT
SLIP



DO NOT
HOLD
ORDER

Any Special Instructions? _____

Name _____

()
Area Code and Daytime Phone Number

Address with Apt # (UPS can not deliver to P.O. Box Numbers)

City _____

State / Zip _____

E-mail Address (If you enter an e-mail address we will notify you when your order ships) _____

	Cat#	Qty.	Description	Pg#	Unit Price	Total Price
1						
2						
3						
4						
5						
6						
7						
8						
9						
10						
11						
12						
13						
14						
15						
16						
17						
18						
19						
20						

CREDIT CARD ORDERS

Visa, Mastercard,
Discover and American Express



Name of Cardholder _____

Charge Card Number _____

Exp. Date _____

Signature _____

PLEASE DO NOT SEND CASH! - NO C.O.D. ORDERS

SUB TOTAL

less
REFUND Slip

CALIFORNIA Only -
SALES TAX LA County 8.25%
ALL OTHER COUNTIES 7.25%

SHIPPING & HANDLING
48 Continental States \$6.00
OTHERS SEE INSTRUCTIONS

TOTAL

WEB 402

ALL ELECTRONICS


C O R P O R A T I O N

222 WATT POWER SUPPLY

Teapo Model # TP511B-4. Input: 100-240 Vac. Outputs: 5.1VDC @ 32A, 12VDC @ 6A, -5VDC @ 0.3A, -12 Vdc @ 0.3A, 3.3VDC @ 24A.

Enclosed, fan-cooled computer power supply. Push on/off power switch on 12" cord.

Has special power harness in addition to the common Molex-type power connectors. IEC power inlet. UL, CSA. 5.9" x 5.5" x 3.4." **CAT # PS-511**



\$16⁵⁰
each

Case of 8 for \$12.00 each


3VDC 100 mA WALL TRANSFORMER

Excellent for LEDs and low current applications.

3 Vdc, 100 mA wall transformer. 6' cord. 2.5mm mini-phone plug, tip positive. Large quantity available. UL.

CAT# DCTX-31

\$1³⁵
each



10 to 95 for \$1.25 each
96 to 575 \$1.00 each
576 to 1055 75¢ each
1056 or more 65¢ each

LIGHTWEIGHT STEREO HEADPHONES



Lightweight stereo headphones for audio and computer applications. Adjustable headband. 3.5mm phone plug with 4' shielded cord.

CAT# HP-100

10 for \$1.50 each
100 for \$1.20 each

\$1⁷⁵
each

INTERNET USERS!

Shop Online

www.allelectronics.com

E-Mail us at

allcorp@allcorp.com

California Store Locations

905 S. Vermont Avenue
Los Angeles, 90006
(213) 380-8000

14928 Oxnard Street
Van Nuys, 91411
(818) 997-1806

Presorted Standard
U.S. Postage

PAID

Ontario, CA
Permit No 1

OR CURRENT OCCUPANT